NAMA   : MUHAMMAD HIMMAWAN

NIM   : L200170161

KELAS   : D

MODUL   : 4

Kegitan 1:

1.

Desain Rangkaian Topologi

```
Switch#enable
Switch#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#vlan 10
Switch(config-vlan)#int fa 0/1
Switch(config-if)#switchport mode access
Switch(config-if)#switchportport access vlan 10
                            ^
% Invalid input detected at '^' marker.

Switch(config-if)#switchport access vlan 10
Switch(config-if)#int fa 0/4
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#exit
Switch(config)#vlan 20
Switch(config-vlan)#int fa 0/2
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 20
Switch(config-if)#int fa 0/5
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 20
Switch(config-if)#exit
Switch(config)#vlan 30
Switch(config-vlan)#int fa 0/3
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 30
```

2.
```
Switch(config-vlan)#int fa 0/1
Switch(config-if)#switchport mode access
Switch(config-if)#switchportport access vlan 10
                            ^
% Invalid input detected at '^' marker.

Switch(config-if)#switchport access vlan 10
Switch(config-if)#int fa 0/4
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#exit
Switch(config)#vlan 20
Switch(config-vlan)#int fa 0/2
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 20
Switch(config-if)#int fa 0/5
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 20
Switch(config-if)#exit
Switch(config)#vlan 30
Switch(config-vlan)#int fa 0/3
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 30
Switch(config-if)#int fa 0/6
Switch(config-if)#switchport mode access
Switch(config-if)#switch access vlan 30
Switch(config-if)#exit
Switch(config)#exit
```

3.

```
Switch#show vlan brief

VLAN Name                             Status    Ports
---- -------------------------------- ---------
--------------------------------
1    default                          active    Fa0/7, Fa0/8,
Fa0/9, Fa0/10
                                                Fa0/11, Fa0/12,
Fa0/13, Fa0/14
                                                Fa0/15, Fa0/16,
Fa0/17, Fa0/18
                                                Fa0/19, Fa0/20,
Fa0/21, Fa0/22
                                                Fa0/23, Fa0/24
10   zodiak1                          active    Fa0/1, Fa0/4
20   zodiak2                          active    Fa0/2, Fa0/5
30   zodiak3                          active    Fa0/3, Fa0/6
1002 fddi-default                     active
1003 token-ring-default               active
1004 fddinet-default                  active
1005 trnet-default                    active
Switch#show vlan id 10
```

4.

```
VLAN Name                             Status    Ports
---- -------------------------------- ---------
--------------------------------
10   zodiak1                          active    Fa0/1, Fa0/4

VLAN Type  SAID       MTU   Parent RingNo BridgeNo Stp  BrdgMode
Trans1 Trans2
---- ----- ---------- ----- ------ ------ -------- ---- --------
------ ------
10   enet  100010     1500  -      -      -        -    -
0      0
```

5.

```
Switch#show vlan 20
                 ^
% Invalid input detected at '^' marker.

Switch#show vlan id 20

VLAN Name                             Status    Ports
---- -------------------------------- ---------
--------------------------------
20   zodiak2                          active    Fa0/2, Fa0/5

VLAN Type  SAID       MTU   Parent RingNo BridgeNo Stp  BrdgMode
Trans1 Trans2
---- ----- ---------- ----- ------ ------ -------- ---- --------
------ ------
20   enet  100020     1500  -      -      -        -    -
0      0
```

6.

```
Switch#show vlan id 30

VLAN Name                             Status    Ports
---- -------------------------------- ---------
--------------------------------
30    zodiak3                         active    Fa0/3, Fa0/6

VLAN Type  SAID       MTU   Parent RingNo BridgeNo Stp  BrdgMode
Trans1 Trans2
---- ----- ---------- ----- ------ ------ -------- ---- --------
------ ------
30    enet  100030     1500  -      -      -        -    -
0      0

Switch#
```

7.

Kegiatan 2:

1.

IOS Command Line Interface

```
Switch>enable
Switch#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#vlan 10
Switch(config-vlan)#name zodiak1
Switch(config-vlan)#ex
Switch(config)#vlan 20
Switch(config-vlan)#name zodiak2
Switch(config-vlan)#ex
Switch(config)#vlan 30
Switch(config-vlan)#name zodiak3
Switch(config-vlan)#ex
Switch(config)#vlan 10
Switch(config-vlan)#switchport mode access
                         ^
% Invalid input detected at '^' marker.

Switch(config-vlan)#int fa 0/1
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#int fa 0/4
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 10
Switch(config-if)#ex
Switch(config)#vlan 20
```

Ctrl+F6 to exit CLI focus   Copy   Paste

Top

2.

3.

```
%SYS-5-CONFIG_I: Configured from console by console

Switch#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#int fa 0/7
Switch(config-if)#switchport mode trunk
Switch(config-if)#ex
Switch(config)#ex
Switch#
```

4.

PC LEO ke PC PISCES

5.

6.

7.

8.

PC LEO ke PC ARIES

9.

PC LEO ke PC AQUARIUS

PC LEO ke PC PISCES

```
Pinging 172.21.3.4 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.3.4:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>
```

☐ Top

PC LIBRA ke PC CANCER

PC LIBRA ke PC LEO

```
C:\>ping 172.21.1.1

Pinging 172.21.1.1 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 172.21.1.1:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

☐ Top

Kesimpulan :

Bahwa setiap kita ingin menyambungkan satu PC dengan PC yang harus sama dengan satu port VLAN yang sama agar dapat terhubng. Apabila beda VLAN maka akan terjadi Request Time Out.