Nama : Muhammad Himmawan

Nim : L200170161

Kelas : D – Prak.JarKom

Modul 11

1. Buat struktuk Topologi



2. Setting IP di tiap-tiap Router
   a) Lab JarKom



   b) Lab SI



c) Lab RPL



d) Gateaway



3. Konfigurasi routing table
   a) Lab JarKom

```
Jarkom#conf term
Enter configuration commands, one per line.  End with CNTL/Z.
Jarkom(config)#router rip
Jarkom(config-router)#network 172.15.0.0
Jarkom(config-router)#network 172.16.0.0
Jarkom(config-router)#network 172.17.0.0
Jarkom(config-router)#network 172.18.0.0
Jarkom(config-router)#network 172.19.0.0
Jarkom(config-router)#
Jarkom(config-router)#end
Jarkom#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Jarkom(config)#interface FastEthernet1/0
Jarkom(config-if)#
%SYS-5-CONFIG_I: Configured from console by console
```

   b) Lab SI

```
SistemInformasi(config-if)#ex
SistemInformasi(config)#router rip
SistemInformasi(config-router)#network 172.15.0.0
SistemInformasi(config-router)#network 172.16.0.0
SistemInformasi(config-router)#network 172.17.0.0
SistemInformasi(config-router)#network 172.18.0.0
SistemInformasi(config-router)#network 172.19.0.0
SistemInformasi(config-router)#ex
```

   c) Lab RPL

```
RPL(config-if)#ex
RPL(config)#router rip
RPL(config-router)#network 172.15.0.0
RPL(config-router)#network 172.16.0.0
RPL(config-router)#network 172.17.0.0
RPL(config-router)#network 172.18.0.0
RPL(config-router)#network 172.19.0.0
RPL(config-router)#ex
RPL(config)#
RPL#
%SYS-5-CONFIG_I: Configured from console by console
```

   d) Gateaway

```
UMS(config-if)#ex
UMS(config)#router rip
UMS(config-router)#network 172.15.0.0
UMS(config-router)#network 172.16.0.0
UMS(config-router)#network 172.17.0.0
UMS(config-router)#network 172.18.0.0
UMS(config-router)#network 172.19.0.0
UMS(config-router)#ex
UMS(config)#
UMS#
%SYS-5-CONFIG_I: Configured from console by console
```

4. Konfigurasi IP Address tiap-tiap PC

a) PC JarKom



b) PC SI



c) PC RPL



d) PC Admin



5. Test PING tiap-tiap PC dari PC Admin
   a) PC Adim ke PC JarKom

```
C:\>ping 172.16.0.2

Pinging 172.16.0.2 with 32 bytes of data:

Reply from 172.16.0.2: bytes=32 time=1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126
Reply from 172.16.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.16.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

   b) PC Admin ke PC SI

```
C:\>ping 172.17.0.2

Pinging 172.17.0.2 with 32 bytes of data:

Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126
Reply from 172.17.0.2: bytes=32 time=1ms TTL=126
Reply from 172.17.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.17.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

   c) PC Admin ke PC RPL

```
C:\>ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:

Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time=1ms TTL=126
Reply from 172.18.0.2: bytes=32 time<1ms TTL=126
Reply from 172.18.0.2: bytes=32 time<1ms TTL=126

Ping statistics for 172.18.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 1ms, Average = 0ms
```