

Q. What is Shared Preferences?
Write note on Shared preferences?

Shared preferences:

- Shared preferences is a method of data storing.
- used to store data that is very short.
- it is used to store singular data.
e.g. A user who has multiple attributes who is single.
- it stores data in the form of key and value pairs.
- it allows you to save and retrieve small amounts of data, such as user settings or preferences, across app restarts.
- it store data for a short period of time.

Drawback:

- For storing data of multiple users it is not suitable.

⇒ Shared preferences support the types Boolean, String, float, long, integers, making them an ideal to quickly store default values, instance variables, the current UI state, user preferences.

Uses:

- In Login form
- To store true or false value.
- To store data for next time to use
- They are commonly used to persist across user sessions and to share data between application components.

Methods:

Apply():

- To put values.
- make object of shared preferences
- if apply() or commit() is not used then the instructions will not be in execution.

Clear():

- Remove all values from the shared preferences.

○ clear all data.

remove (String key)

○ Delete value of particular (key, value)

putString (String key, String value)

○ To store String values.

putInt (String key, int value)

putLong (String key, long value):

putFloat (String key, float value):

Key points:

- Not secure.
- We can simply view the data stored within the shared preferences.
- Can be easily access data within that file.

To make secure:

- use encrypted shared preferences.
- That are more secure and

1: Creating Shared Preferences:

code:

⇒ `SharedPreferences sharedPreferences = getSharedPreferences("mypreferences", Context.MODE_PRIVATE);`

⇒ The first parameter is the name of the preferences file.

⇒ Second parameter is the mode, which determines the access level (e.g. `MODE_PRIVATE` means only the calling application can read and write the preferences).

2) Write to Shared preferences:

- Create a `SharedPreferences.Editor` by calling `edit()`.

- Pass the keys and values by using:

 - `putInt()`

 - `putString()`

- Then call `apply()` ~~or~~ `or`

 - `Commit()`

code:

SharedPreferences.Editor editor = SharedPreferences

editor.putString("key-username", "JohnDoe");
editor.apply(); // or editor.commit();

3: Read from SharedPreferences:

⇒ By using following methods:

- getInt()
- getString()

code:

String username = SharedPreferences.getString(
"key-username", "DefaultUsername");

↓
it will return
default value if the
key is not found.

Example:

To store and retrieve a username:

// writing data

SharedPreferences.Editor editor = SharedPreferences.
editor.putString("key-username", "JohnDoe");
editor.apply();