

Creating and using menus:-

Menu:

- Menus offer a way to expose application functions without sacrificing valuable screen space.
- Each Activity can specify its own Activity menu that is displayed when the device menu button is pressed.

Android option menus:

are the primary menus of android. They can be used for settings, search, delete item etc.

Process:

- Go to res.
- Click on new
- And click on Android resource directory.
- Choose resource type menu.
- Click ok.

⇒ Then create menu.

XML layout for menu.

```
<?xml version="1.0" encoding="utf-8"?>
<menu xmlns:android="http://schemas.android.com/apk/res/android"
      xmlns:app="http://schemas.android.com/apk/res-auto">
```

<item

android:id="@+id/item1"

android:icon="@drawable/ic_icon"

android:title="Item 1"

app:showAsAction="ifRoom"

/>

<item

android:id="@+id/item2"

android:title="Item 2"

app:showAsAction="never"

/>

<item

android:id="@+id/item3"

android:title="Item 3"

app:showAsAction="never"

/>

<menu>

<item

android: id = "@+id / subitem1"

android: title = "Sub Item 1"

/>

<item

android: id = "@+id / subitem2"

android: title = "Sub Item 2"

/>

</menu>

</item>

</menu>

Main Activity . java

public class MainActivity extends
AppCompatActivity

{ @Override

protected void onCreate (Bundle savedInstanceState)

super.onCreate (savedInstanceState);
setContentView (R.layout.activity_main);

}

@Override

public boolean onCreateOptionsMenu ()
(Menu menu)

{

MenuInflater inflater = getMenuInflater();
inflater.inflate (R.menu.example_menu,
menu);

return true;

}

@Override

public boolean onOptionsItemSelected (MenuItem
item)

{

switch (item.getItemId())

{

case R.id.item1:

Toast.makeText (this, "Item 1 selected",

Toast.LENGTH_SHORT).show();

return true;

case R.id.item2:

Toast.makeText (this, "Item 2 selected",

Toast.LENGTH_SHORT).show();

return true;

case R.id.item3:

Toast.makeText(this, "Item 3 selected",
Toast.LENGTH_SHORT).show(); return true;

case R.id.subitem1:

Toast.makeText(this, "Subitem 1 selected",
Toast.LENGTH_SHORT).show();
return true;

case R.id.subitem2:

Toast.makeText(this, "Subitem 2 selected",
Toast.LENGTH_SHORT).show();
return true;

default:

return super.onOptionsItemSelected(item);

}

}

}