

Q. How to implement map in android app?

```
public class MapsActivity extends  
    AppCompatActivity {  
    implements OnMapReadyCallback
```

```
private GoogleMap mMap;
```

```
protected void onCreate(Bundle  
    savedInstanceState)
```

```
{
```

```
    super.onCreate(savedInstanceState);
```

```
    setContentView(R.layout.activity_maps);
```

```
        MapSupportFragment mapFragment =  
            getSupportFragmentManager().
```

```
                findFragmentById(R.id.map);
```

```
        mapFragment.getMapAsync(this);
```

```
}
```

```
@Override
```

```
public void onMapReady(GoogleMap googleMap)  
{
```

```
    mMap = googleMap;
```



```

LatLong latLng = new LatLong (26.389, 73.129);
MarkerOptions markerOptions = new MarkerOptions()
    .position (latLng)
    .title ("Jodhpur");
mMap.addMarker (markerOptions);
mMap.moveCamera (CameraUpdate
    Factory.newLatLng
    (latLng));
// zoom in
mMap.animateCamera (CameraUpdateFactory
    .newLatLngZoom (latLng, 16f));

```

```

Log.d ("Map", "Yes");

```

```

}

```

```

}

```

```

}

```

Q. How to add Overlays in map?

Overlays means how to add overlays on our map layout.

We can add:

Circle

Polygone

Add Markers

Ground Overlays

// Circle

```
mMap.addCircle( new CircleOptions  
    .center ( latlng )  
    .radius ( 1000 )  
    .fillColor ( R.color.green )  
    .strokeColor ( Color.GRAY ) );
```

// Polygone

```
mMap.addPolygone( new PolygoneOptions ( )  
    .add( new Latlng ( _____ ) ,  
        new Latlng ( _____ ) ,  
        new Latlng ( _____ ) ,  
        new Latlng ( _____ ) ,  
        new Latlng ( _____ ) );
```


Geocodes: Getting data from Location

Geocodes - getting data from Location.

```
mMap.setOnMapClickListener(new GoogleMap.  
OnMapClickListener()
```

```
{  
    public void onMapClick (LatLng latlng)  
    {  
        mMap.addMarker(new MarkerOptions()  
            .position(latlng).title("clicker"));
```

```
Geocodes geocodes = new Geocodes(this);
```

```
geocodes.getFromLocation
```

```
ArrayList<Address> arrAdd = ArrayList<Address>
```

```
    geocodes.getFromLocation(latlng.latitude,  
        latlng.longitude, 2);
```

```
Log.d("Addrs", arrAdd.get(0).getAddressLine  
    (0));
```

```
}
```

```
catch (IOException e)
```

```
{
```

```
    e.printStackTrace();
```

```
}
```

```
}
```