



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

Name: Hirenkumar vyas

Roll no: 32

Branch: BE\_AI&DS

Experiment No. 3
Apply Stochastic Gradient Descent algorithm on a feed forward neural network for Iris Flower classification
Date of Performance:
Date of Submission:



# **Vidyavardhini's College of Engineering and Technology**

## **Department of Artificial Intelligence & Data Science**

**Aim:** Apply Stochastic Gradient Descent algorithm on a feed forward neural network for Iris Flower classification.

**Objective:** Ability to perform optimization technique on a feed forward neural network.

**Theory:**

Gradient Descent is an iterative optimization process that searches for an objective function's optimum value (Minimum/Maximum). It is one of the most used methods for changing a model's parameters in order to reduce a cost function in machine learning projects.

The primary goal of gradient descent is to identify the model parameters that provide the maximum accuracy on both training and test datasets. In gradient descent, the gradient is a vector pointing in the general direction of the function's steepest rise at a particular point. The algorithm might gradually drop towards lower values of the function by moving in the opposite direction of the gradient, until reaching the minimum of the function.

**Types of Gradient Descent:**

Typically, there are three types of Gradient Descent:

- Batch Gradient Descent
- Stochastic Gradient Descent
- Mini-batch Gradient Descent Stochastic Gradient Descent (SGD):

Stochastic Gradient Descent (SGD) is a variant of the Gradient Descent algorithm that is used for optimizing machine learning models. It addresses the computational inefficiency of traditional Gradient Descent methods when dealing with large datasets in machine learning projects.

In SGD, instead of using the entire dataset for each iteration, only a single random training example (or a small batch) is selected to calculate the gradient and update the model parameters. This random selection introduces randomness into the optimization process, hence the term "stochastic" in stochastic Gradient Descent.



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

The advantage of using SGD is its computational efficiency, especially when dealing with large datasets. By using a single example or a small batch, the computational cost per iteration is significantly reduced compared to traditional Gradient Descent methods that require processing the entire dataset.

### Stochastic Gradient Descent Algorithm

Initialization: Randomly initialize the parameters of the model.

Set Parameters: Determine the number of iterations and the learning rate ( $\alpha$ ) for updating the parameters.

Stochastic Gradient Descent Loop: Repeat the following steps until the model converges or reaches the maximum number of iterations:

- a. Shuffle the training dataset to introduce randomness.
- b. Iterate over each training example (or a small batch) in the shuffled order.
- c. Compute the gradient of the cost function with respect to the model parameters using the current training.
- d. Update the model parameters by taking a step in the direction of the negative gradient, scaled by the learning rate.
- e. Evaluate the convergence criteria, such as the difference in the cost function between iterations of the gradient.

Return Optimized Parameters: Once the convergence criteria are met or the maximum number of iterations is reached, return the optimized model parameters.

In SGD, since only one sample from the dataset is chosen at random for each iteration, the path taken by the algorithm to reach the minima is usually noisier than your typical Gradient Descent algorithm. But that doesn't matter all that much because the path taken by the algorithm does not matter, as long as we reach the minimum and with a significantly shorter training time.



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

Program:

```
import numpy as np from sklearn.datasets import  
load_iris from sklearn.model_selection import  
train_test_split from sklearn.preprocessing import  
StandardScaler from tensorflow.keras.models  
import Sequential from tensorflow.keras.layers  
import Dense from tensorflow.keras.utils import  
to_categorical from tensorflow.keras.optimizers  
import SGD  
  
iris = load_iris() X =  
iris.data  
  
y = iris.target scaler = StandardScaler() X =  
scaler.fit_transform(X) y = to_categorical(y) # Convert labels to  
one-hot encoding  
  
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42) model  
= Sequential([  
    Dense(16, activation='relu', input_shape=(X_train.shape[1],)),  
    Dense(8, activation='relu'),  
    Dense(3, activation='softmax') # 3 classes for Iris dataset
```



## Vidyavardhini's College of Engineering and Technology

### Department of Artificial Intelligence & Data Science

1)

```
model.compile(optimizer=SGD(learning_rate=0.01),  
loss='categorical_crossentropy',metrics=['accuracy']) batch_size = 32 num_epochs = 100  
model.fit(X_train, y_train, batch_size=batch_size, epochs=num_epochs, validation_split=0.1)  
test_loss, test_accuracy = model.evaluate(X_test, y_test) print(f"Test loss: {test_loss:.4f},  
Test accuracy: {test_accuracy:.4f}") Output:
```

```
Test loss: 0.3568, Test accuracy: 0.9000
```

#### Conclusion:

In this experiment, we applied the Stochastic Gradient Descent (SGD) algorithm to train a feed forward neural network for the classification of Iris flowers based on their features. By constructing a neural network architecture with input, hidden, and output layers, we were able to effectively capture complex patterns in the Iris dataset.