

## 1 Problem Setting and Preliminaries

### 1.1 Problem Setting

We consider optimization problems in which exact objective function values are unavailable, following the recent literature on error-aware optimization [2, 5, 6, 16, 35, 38]. When both objective values and gradients are heavily corrupted by noise, reliable optimization cannot be guaranteed. Thus, meaningful optimization requires that at least one source of information be sufficiently accurate. This work focuses on problems arising from finite-precision computations or inexact evaluations, where objective function evaluations are subject to non-negligible errors while gradient information can be computed with relatively high accuracy. Settings in which objective values are accurate but gradients are noisy, such as derivative-free optimization or stochastic approximation methods [3, 37], are beyond the scope of this paper.

In the following, we formalize the assumptions on function and gradient evaluations. We assume that only an error contaminated function  $\bar{f}(x)$  is accessible, satisfying the hybrid absolute-relative error model [20, 21]:

$$|f(x) - \bar{f}(x)| \leq \varepsilon_f \max(1, |f(x)|), \quad (1)$$

where  $0 \leq \varepsilon_f < 1$  is an error rate. This model captures the typical behavior of rounding errors in IEEE 754 floating-point arithmetic [20], and in our numerical experiments,  $\varepsilon_f$  is chosen to range from  $10^2$  to  $10^7$  times the machine epsilon. The error is predominantly relative when  $|f(x)|$  is large and effectively absolute when  $|f(x)|$  is small. Closely related models are also employed in practical stopping criteria [41].

We next state assumptions regarding gradient evaluations. In practice, termination is typically based on a gradient tolerance  $\varepsilon_{\text{gtol}}$ , and considers  $\|\nabla \bar{f}(x)\| \leq \varepsilon_{\text{gtol}}$  as a stopping criterion. In our numerical experiments, following common implementations [41], we use the infinity norm for the gradient, though other norms could equally be employed. If the gradient noise were comparable to or larger than  $\varepsilon_{\text{gtol}}$ , the stopping criterion could not be reliably satisfied, no matter how close  $x$  is to a stationary point. Therefore,  $\varepsilon_{\text{gtol}}$  must be chosen sufficiently large than the gradient noise level. Accordingly, it is natural to assume that the error in gradient evaluations is small compared to the prescribed tolerance:

$$\|\nabla f(x) - \nabla \bar{f}(x)\| \ll \varepsilon_{\text{gtol}}.$$

Since  $\|\nabla \bar{f}(x)\| > \varepsilon_{\text{gtol}}$  holds prior to termination, the gradient noise is also negligible compared to the gradient norm itself. Consequently, in our theoretical analysis, we assume exact gradients:

$$\|\nabla f(x) - \nabla \bar{f}(x)\| = 0. \quad (2)$$

The exactness of  $\bar{f}$  in eq. (2) serves as a theoretical modeling choice just for simplicity, rather than a claim about practical gradient accuracy. Our numerical experiments in section 5 also test the case where gradients are contaminated by noise, demonstrating the practical effectiveness of the proposed method even when eq. (2) is violated.

## 1.2 Regularized Quasi-Newton Methods

In classical Newton and quasi-Newton methods, line search techniques are commonly used in practice [41]. An alternative approach is to add regularization terms to the Hessian approximation. Recent years have seen renewed interest in regularized Newton-type methods, including cubic regularization schemes [30, 34, 42]. In this work, we focus on quadratic regularization [8, 22, 24, 36, 39, 40, 47].

Let  $g_k := \nabla f(x_k)$  and let  $B_k \in \mathbb{R}^{n \times n}$  denote an approximate Hessian. In line-search-based quasi-Newton methods, the update is given by

$$x_{k+1} = x_k + \alpha_k d_k, \quad d_k = -B_k^{-1} g_k,$$

where  $\alpha_k$  is determined by a line search. In contrast, regularized quasi-Newton methods compute the step as

$$x_{k+1} = x_k + d_k, \quad d_k = -(B_k + \mu_k I)^{-1} g_k,$$

with a regularization parameter  $\mu_k \geq 0$ . Combining regularization with line search is also possible and has been explored [39].

A fundamental strategy for choosing  $\mu_k$  in nonconvex optimization was proposed in earlier work on regularized Newton methods [36, 39, 40]. Their formulation sets

$$\mu_k = c_1 \max(0, -\lambda_{\min}(B_k)) + c_2 \|\nabla f(x_k)\|^\delta, \quad (3)$$

where  $c_1 > 1$ ,  $c_2 > 0$ ,  $\delta \geq 0$  and  $\lambda_{\min}(B_k)$  denotes the smallest eigenvalue of  $B_k$ .  $\|\cdot\|$  is the Euclidean norm. This choice guarantees that  $B_k + \mu_k I$  is positive definite, ensuring that  $d_k$  is a descent direction. The regularization strategy adopted in this paper is closely related in spirit, and we adapt it to noisy evaluation environments.

## 1.3 Objective-Function-Free Optimization

Objective-Function-Free Optimization (OFFO) refers to a class of methods that avoid explicit evaluations of the objective function and rely solely on gradient information [17, 18]. Such methods are particularly attractive when function values are unreliable due to noise. Similar adaptive trust-region approaches are also discussed [15].

Prominent examples of OFFO include adaptive gradient methods such as ADA-GRAD [10] and ADAGRAD-NORM [43]. Their update rules are

$$x_{k+1}^{(i)} = x_k^{(i)} - \frac{1}{\theta \sqrt{\varsigma + \sum_{j=0}^k (g_j^{(i)})^2}} g_k^{(i)}, \quad (i = 1, 2, \dots, n)$$

$$x_{k+1} = x_k - \frac{1}{\theta \sqrt{\varsigma + \sum_{j=0}^k \|g_j\|^2}} g_k,$$

respectively, where  $\varsigma > 0$  and  $\theta > 0$  are algorithmic parameters, and  $x^{(i)}$  denotes the  $i$ -th component of a vector  $x$ .

In this work, we draw inspiration from the OFFO framework to design robust regularization and scaling strategies. Unlike purely objective-function-free methods, our algorithm exploits function values whenever they are numerically reliable, while smoothly transitioning to gradient-based control when they are not. This hybrid behavior enables improved stability without sacrificing efficiency in practical optimization tasks.

## 2 Proposed Algorithm

In this section, we present the proposed algorithm for the problem setting stated in section 1.1. Its pseudo-code is given in Algorithm 1, where we note that the minimum of the empty set is defined as  $+\infty$  in Line 3. Algorithm 2 is an auxiliary line search algorithm called in Algorithm 1.

---

### Algorithm 1: Noise Tolerant Regularized Quasi-Newton Method

---

**Input:**  $x_0, 0 < k_{\max}, 0 \leq \varepsilon_f < 1, 0 < c < 1, 0 < \theta_{\min} \leq \theta_{\max}$  and  $0 < \varsigma < 1$

```

1  $k \leftarrow 0, g_0 \leftarrow \nabla \bar{f}(x_0), K^0 \leftarrow \emptyset, K^+ \leftarrow \emptyset$ 
2 for  $k = 0, 1, 2, \dots, k_{\max} - 1$  do
3   if  $\min_{j \in K^0} (\bar{f}(x_j) - \Delta_j) \geq \bar{f}(x_k)$  then
4      $K^0 \leftarrow K^0 \cup \{k\}$ 
5      $\mu_k \leftarrow 0$ 
6   else
7      $K^+ \leftarrow K^+ \cup \{k\}$ 
8      $\mu_k \leftarrow \theta_k \sqrt{\varsigma + \sum_{j \in K^+} \|g_j\|^2}$  with  $\theta_k \in [\theta_{\min}, \theta_{\max}]$  chosen adaptively
9      $d_k \leftarrow -(B_k + \mu_k I)^{-1} g_k$  with  $B_k$  chosen properly (section 4.1)
10    Find  $\alpha_k$  and  $\Delta_k$  satisfying eq. (4) by Algorithm 2
11     $x_{k+1} \leftarrow x_k + \alpha_k d_k, g_{k+1} \leftarrow \nabla \bar{f}(x_{k+1})$ 
12 end
```

---



---

### Algorithm 2: Backtracking Line Search with Relaxed Armijo Condition

---

**Input:**  $x_k \in \mathbb{R}^n, d_k \in \mathbb{R}^n, g_k \in \mathbb{R}^n, 0 < c < 1$  and  $0 < \beta_{\min} < \beta_{\max} < 1$

```

1  $\alpha_k \leftarrow 1$ 
2  $\Delta_k \leftarrow \frac{2\varepsilon_f}{1-\varepsilon_f} \max(1, \bar{f}(x_k), -\bar{f}(x_k + \alpha_k d_k))$ 
3 while  $\bar{f}(x_k) + c\alpha_k g_k^\top d_k + \Delta_k < \bar{f}(x_k + \alpha_k d_k)$  do
4    $\alpha_k \leftarrow \beta \alpha_k$  with  $\beta \in [\beta_{\min}, \beta_{\max}]$  chosen adaptively (section 4.2)
5    $\Delta_k \leftarrow \frac{2\varepsilon_f}{1-\varepsilon_f} \max(1, \bar{f}(x_k), -\bar{f}(x_k + \alpha_k d_k))$ 
6 end
7 return  $\alpha_k$ 
```

---




Fig. 1: An example of the sequence  $\{\bar{f}(x_k)\}$  generated by Algorithm 1. Each iteration index  $k$  is classified into  $K^0$  (blue) or  $K^+$  (red). The relaxed Armijo condition eq. (4) ensures a temporary increase of  $\bar{f}$  is at most  $\Delta_k$ , such as from  $k=2$  to  $k=3$ . We only set  $\mu_k=0$  when the sufficient decrease condition eq. (6) is satisfied over iterations in  $K^0$ , such as at  $k=5$ , preventing unbounded growth or oscillation of  $\bar{f}$ .

In the following, we explain the three main components of Algorithm 1.

*Computation of the Regularized Quasi-Newton Direction (Line 9)* The first component is the computation of the regularized quasi-Newton direction  $d_k$ . Given  $g_k = \nabla \bar{f}(x_k) = \nabla f(x_k)$ , an approximate Hessian  $B_k$ , and a regularization parameter  $\mu_k$ , we compute the search direction  $d_k = -(B_k + \mu_k I)^{-1} g_k$  as in section 1.2. For the theoretical analysis, any choice of  $B_k$  satisfying Assumption 3 stated in section 3.1 is admissible, which ensures  $B_k$  is positive definite. A practical choice of  $B_k$  is discussed in section 4.1.

*Relaxed Armijo Condition with an Error-Absorbing Term (Line 10)* The second component is the computation of the step size  $\alpha_k$  using a relaxed Armijo condition. We compute  $\alpha_k$  satisfying the relaxed Armijo condition

$$\begin{cases} \bar{f}(x_k) + c\alpha_k g_k^\top d_k + \Delta_k \geq \bar{f}(x_k + \alpha_k d_k), \\ \Delta_k = \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_k), -\bar{f}(x_k + \alpha_k d_k)) \end{cases} \quad (4)$$

where  $\Delta_k$  is the error-absorbing term that is recomputed for each  $\alpha_k$ . This relaxation guarantees the existence of  $\alpha_k \in (0, 1]$  even in the presence of numerical errors in  $\bar{f}$ . When  $d_k$  is a descent direction ( $g_k^\top d_k \leq 0$ ), eq. (4) ensures a temporary increase of  $\bar{f}$  is at most  $\Delta_k$ , as illustrated in Figure 1. Since  $\Delta_k$  depends on  $-\bar{f}(x_k + \alpha_k d_k)$  but not on  $\bar{f}(x_k + \alpha_k d_k)$ , the value of  $\Delta_k$  is independent of how much  $\bar{f}(x_k + \alpha_k d_k)$  increases, preventing unbounded growth of  $\Delta_k$ .

*Adaptive Update of the Regularization Parameter (Lines 3–8)* The third component is the adaptive update of the regularization parameter  $\mu_k$ . A larger  $\mu_k$  yields a more conservative step, while a smaller  $\mu_k$  allows a more aggressive quasi-Newton step, especially when  $\mu_k = 0$ . In practical settings, setting  $\mu_k = 0$  is preferred, since this allows us to fully exploit the quasi-Newton approximation and typically leads to practically faster convergence. Let us partition the iteration indices  $K := \{0, 1, 2, \dots, k_{\max} - 1\}$  into two sets:

$$K^0 := \{k \in K \mid \mu_k = 0\}, \quad K^+ := \{k \in K \mid \mu_k > 0\}. \quad (5)$$

We set  $\mu_k = 0$  if and only if the following condition holds:

$$\min_{j \in K^0, j < k} (\bar{f}(x_j) - \Delta_j) \geq \bar{f}(x_k), \quad (6)$$

where the minimum of the empty set is  $+\infty$ . This condition restricts  $\mu_k = 0$  to iterations for which a sufficient decrease in  $\bar{f}$  has been observed. Thereby, while  $\bar{f}$  can temporarily increase, this condition theoretically ensures that  $\bar{f}$  does not grow unboundedly or oscillate indefinitely. See Figure 1 for an illustrative example.

Otherwise, to ensure convergence to first-order stationary points, we apply an OFFO-based update

$$\mu_k = \theta_k \sqrt{\varsigma + \sum_{j \in K^+, j \leq k} \|g_j\|^2}, \quad (7)$$

as described in section 1.3. Since OFFO schemes do not rely on function values, this update is robust to numerical errors in  $\bar{f}$ .

### 3 Theoretical Analysis

In this section, we establish the global convergence properties of Algorithm 1 under the problem setting in section 1.1, namely, eqs. (1) and (2).

#### 3.1 Assumptions

Throughout this section, we make the following three assumptions. The first assumption guarantees that the objective function is bounded below.

**Assumption 1** *The function  $f$  is bounded below; that is, for all  $x \in \mathbb{R}^n$ ,*

$$f(x) \geq f^* := \inf_{x \in \mathbb{R}^n} f(x) > -\infty.$$

By the triangle inequality and eq. (1), we have  $\bar{f}(x) \geq f(x) - \varepsilon_f \max(1, |f(x)|)$ . Since the function  $g(t) = t - \varepsilon_f \max(1, |t|)$  is non-decreasing for  $0 \leq \varepsilon_f < 1$ , it follows that  $\inf_x g(f(x)) = g(f^*)$ . Consequently, we can also lower bound  $\bar{f}$  as

$$\bar{f}(x) \geq \bar{f}^* := \inf_{x \in \mathbb{R}^n} (f(x) - \varepsilon_f \max(1, |f(x)|)) = f^* - \varepsilon_f \max(1, |f^*|) > -\infty. \quad (8)$$

The second assumption ensures smoothness of the objective function.

**Assumption 2** The function  $f: \mathbb{R}^n \rightarrow \mathbb{R}$  is  $L$ -smooth, meaning that there exists a constant  $L > 0$  such that for all  $x, y \in \mathbb{R}^n$ ,

$$f(y) \leq f(x) + \nabla f(x)^\top (y - x) + \frac{L}{2} \|y - x\|^2.$$

The third assumption requires the sequence of matrices  $\{B_k\}$  to be uniformly bounded and uniformly positive definite.

**Assumption 3** There exist constants  $0 < m \leq 1 \leq M$  such that all  $B_k$  in Algorithm 1 satisfy

$$mI \preceq B_k \preceq MI.$$

As we will discuss in section 4, the standard BFGS update with a slight modification ensures that Assumption 3 holds in practice. By Assumption 3, we can derive two useful bounds involving  $g_k$  and  $d_k$ . Using  $d_k = -(B_k + \mu_k I)^{-1} g_k$  (Line 9) and Assumption 3 asserting  $(m + \mu_k)I \preceq B_k + \mu_k I \preceq (M + \mu_k)I$ , we obtain the following two bounds:

$$-g_k^\top d_k = g_k^\top (B_k + \mu_k I)^{-1} g_k \geq \frac{1}{M + \mu_k} \|g_k\|^2, \quad (9)$$

$$\|d_k\|^2 = \|(B_k + \mu_k I)^{-1} g_k\|^2 \leq \frac{1}{(m + \mu_k)^2} \|g_k\|^2. \quad (10)$$

### 3.2 Error Bound on Function Evaluations

In the following, we define the actual and observed function decreases as

$$\delta_k := f(x_k) - f(x_{k+1}), \quad (11)$$

$$\bar{\delta}_k := \bar{f}(x_k) - \bar{f}(x_{k+1}). \quad (12)$$

We first prove a useful property of  $\Delta_k$  defined in eq. (4). The following lemma asserts that the error between the actual values difference  $\delta_k$  and the observed values difference  $\bar{\delta}_k$  can be bounded by  $\Delta_k$ .

**Lemma 1** If  $x_k$  and  $x_{k+1}$  satisfies  $f(x_{k+1}) \leq f(x_k)$ , it holds that

$$\delta_k \leq \bar{\delta}_k + \Delta_k. \quad (13)$$

*Proof* By the definition of  $\bar{f}$  in eq. (1), for any  $x \in \mathbb{R}^n$  satisfying  $|f(x)| > 1$ , we have

$$|f(x) - \bar{f}(x)| \leq \varepsilon_f |f(x)|. \quad (14)$$

Since  $\varepsilon_f < 1$ , eq. (14) implies the signs of  $f(x)$  and  $\bar{f}(x)$  are the same. From the triangle inequality, eq. (14) also implies  $|f(x)| - |\bar{f}(x)| \leq \varepsilon_f |f(x)|$ . Since  $|f(x)| > 1$  means  $f(x) > 1$  or  $-f(x) > 1$ , we have

$$\begin{cases} f(x) \leq \frac{1}{1 - \varepsilon_f} \bar{f}(x) & \text{if } f(x) > 1, \\ -f(x) \leq \frac{1}{1 - \varepsilon_f} (-\bar{f}(x)) & \text{if } -f(x) > 1. \end{cases} \quad (15)$$

In general, for all  $k \in K$ , we have

$$\begin{aligned}
|\delta_k - \bar{\delta}_k| &= |(f(x_k) - \bar{f}(x_k)) - (f(x_{k+1}) - \bar{f}(x_{k+1}))| && \text{(rearrangement)} \\
&\leq \varepsilon_f \max(1, |f(x_k)|) + \varepsilon_f \max(1, |f(x_{k+1})|) && \text{(definition in eq. (1))} \\
&\leq 2\varepsilon_f \max(1, |f(x_k)|, |f(x_{k+1})|) && \text{(max property)} \quad (16)
\end{aligned}$$

From the condition of this lemma ( $f(x_{k+1}) \leq f(x_k)$ ), this can be further bounded as

$$\begin{aligned}
2\varepsilon_f \max(1, |f(x_k)|, |f(x_{k+1})|) &= 2\varepsilon_f \max(1, f(x_k), -f(x_{k+1})) && (f(x_{k+1}) \leq f(x_k)) \\
&\leq \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_k), -\bar{f}(x_{k+1})) && \text{(eq. (15))} \\
&= \Delta_k, && \text{(eq. (4))}
\end{aligned}$$

which yields the desired inequality by the triangle inequality.  $\square$

We also derive the following lemma for later use.

**Lemma 2** *If  $x_k$  and  $x_{k+1}$  satisfies the relaxed Armijo condition (eq. (4)) with a descent direction  $d_k$  ( $g_k^\top d_k \leq 0$ ), it holds that*

$$\bar{\delta}_k \leq \delta_k + \frac{1 + \varepsilon_f}{1 - \varepsilon_f} \Delta_k.$$

*Proof* By condition of this lemma and eq. (4), we have

$$\bar{f}(x_k) - \bar{f}(x_{k+1}) \geq -c\alpha_k g_k^\top d_k - \Delta_k \geq -\Delta_k. \quad (17)$$

Using eqs. (15) and (17), the right-hand side of eq. (16) can be further bounded as

$$\begin{aligned}
2\varepsilon_f \max(1, |f(x_k)|, |f(x_{k+1})|) &\leq \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_k), -\bar{f}(x_k), \bar{f}(x_{k+1}), -\bar{f}(x_{k+1})) \\
&\leq \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_k) + \Delta_k, -\bar{f}(x_{k+1}) + \Delta_k) \\
&\leq \frac{2\varepsilon_f}{1 - \varepsilon_f} (\max(1, \bar{f}(x_k), -\bar{f}(x_{k+1})) + \Delta_k).
\end{aligned}$$

Combining this with eq. (16) and the definition of  $\Delta_k$  in eq. (4) yields

$$|\delta_k - \bar{\delta}_k| \leq \frac{2\varepsilon_f}{1 - \varepsilon_f} (\max(1, \bar{f}(x_k), -\bar{f}(x_{k+1})) + \Delta_k) = \left(1 + \frac{2\varepsilon_f}{1 - \varepsilon_f}\right) \Delta_k = \frac{1 + \varepsilon_f}{1 - \varepsilon_f} \Delta_k.$$

Applying the triangle inequality completes the proof.  $\square$

### 3.3 Backtracking Stage

We next analyze the line search in Algorithm 2. Recall that we assume parameters in Algorithm 2 satisfies  $0 < c < 1$  and  $0 < \beta_{\min} < \beta_{\max} < 1$ .

**Proposition 1** *Under the assumptions, the backtracking procedure in Algorithm 2 terminates whenever the step size  $\alpha_k$  satisfies*

$$\alpha_k \leq \frac{2(1-c)m}{L}. \quad (18)$$

*Proof* Under the  $L$ -smoothness of  $f$  (Assumption 2), we always have

$$\begin{aligned} f(x_k) - f(x_k + \alpha_k d_k) &\geq -\alpha_k g_k^\top d_k - \frac{L}{2} \alpha_k^2 \|d_k\|^2 \\ &= -c \alpha_k g_k^\top d_k + \alpha_k \left( -(1-c) g_k^\top d_k - \frac{L \alpha_k}{2} \|d_k\|^2 \right). \end{aligned} \quad (19)$$

From Line 9 of Algorithm 1, it follows that  $g_k = -(B_k + \mu_k I) d_k$ . Then, from Assumption 3 and  $\mu_k \geq 0$ , we have

$$-g_k^\top d_k = d_k^\top (B_k + \mu_k I) d_k \geq (m + \mu_k) \|d_k\|^2 \geq 0. \quad (20)$$

Thus, when  $\alpha_k$  satisfies the bound in eq. (18), we have

$$-(1-c) g_k^\top d_k - \frac{L \alpha_k}{2} \|d_k\|^2 \geq \left( (1-c)m - \frac{L \alpha_k}{2} \right) \|d_k\|^2 \geq 0. \quad (21)$$

Combining eqs. (19) and (21) yields

$$f(x_k) - f(x_k + \alpha_k d_k) \geq -c \alpha_k g_k^\top d_k \geq 0.$$

Hence, the condition of Lemma 1 is satisfied with  $x_{k+1} = x_k + \alpha_k d_k$  and thus we obtain  $\delta_k \leq \bar{\delta}_k + \Delta_k$ , i.e.,

$$-c \alpha_k g_k^\top d_k \leq f(x_k) - f(x_k + \alpha_k d_k) \leq \bar{f}(x_k) - \bar{f}(x_k + \alpha_k d_k) + \Delta_k.$$

This inequality means that the relaxed Armijo condition (eq. (4)) is satisfied and thus the backtracking procedure terminates. This completes the proof.  $\square$

Now, let us analyze the behavior of Algorithm 2 using Proposition 1. Define

$$\bar{\alpha} := \beta_{\min} \min \left( \frac{2(1-c)m}{L}, 1 \right) > 0. \quad (22)$$

The following corollary summarizes two immediate consequences: the backtracking procedure terminates after finitely many rejections, and the resulting step size is uniformly bounded by  $\bar{\alpha}$ .

**Corollary 1** *Under the assumptions, the backtracking line search in Algorithm 2 terminates after finitely many rejections, and the step size  $\alpha_k$  satisfies*

$$\alpha_k \geq \bar{\alpha}.$$

*Proof* Let  $r$  denote the number of backtracking rejections. Initially,  $\alpha_k = 1$ , and each rejection multiplies  $\alpha_k$  by  $\beta \leq \beta_{\max} < 1$ . Hence, after  $r$  rejections,  $\alpha_k \leq \beta_{\max}^r$  holds. By Proposition 1, if

$$\alpha_k \leq \beta_{\max}^r \leq \frac{2(1-c)m}{L}, \quad (23)$$

the backtracking procedure must terminate. Since  $0 < c < 1$  and  $0 < m$ , the right-hand side is positive, and thus  $r$  is finite. We next establish the lower bound of  $\alpha_k$ . For the case  $r = 0$ ,  $\alpha_k = 1 \geq \bar{\alpha}$  by  $\beta_{\min} < 1$ . Otherwise, let  $\alpha'_k$  denote the last rejected step size. By Proposition 1, we have

$$\alpha'_k > \frac{2(1-c)m}{L} \geq \min\left(\frac{2(1-c)m}{L}, 1\right). \quad (24)$$

The accepted step size  $\alpha_k$  is chosen from the interval  $[\beta_{\min}\alpha'_k, \beta_{\max}\alpha'_k]$ , and thus

$$\alpha_k \geq \beta_{\min}\alpha'_k > \beta_{\min} \min\left(\frac{2(1-c)m}{L}, 1\right) = \bar{\alpha}. \quad (25)$$

This completes the proof.  $\square$

### 3.4 Bound for the case $\mu_k = 0$

In this subsection, we bound the sum of  $\|g_k\|^2$  over  $k \in K^0$ . Recall that  $K^0$  be a set of iteration indices  $k$  such that  $\mu_k = 0$  in Algorithm 1 as defined in eq. (5).

To this end, we first establish that the sum of  $\Delta_k$  over  $k \in K^0$  is bounded, which means that the total possible increase of  $\bar{f}$  over  $k \in K^0$  is bounded. To this purpose, we introduce the following constant:

$$\Delta_{\max} := \frac{2\varepsilon_f}{1-\varepsilon_f} \max(1, \bar{f}(x_0), -\bar{f}^*). \quad (26)$$

**Lemma 3** *Under the assumptions, the sum of  $\Delta_k$  over  $k \in K^0$  in Algorithm 1 satisfies*

$$\sum_{k \in K^0} \Delta_k \leq \bar{f}(x_0) - \bar{f}^* + \Delta_{\max}.$$

*Proof* Recall that Line 3 asserts that the following eq. (6) holds for  $k \in K^0$ :

$$\min_{j \in K^0, j < k} (\bar{f}(x_j) - \Delta_j) \geq \bar{f}(x_k).$$

Note that  $\mu_0 = 0$  and  $0 \in K^0$ , meaning that  $|K^0| \geq 1$ , and that the empty sum is zero.

Let us enumerate the elements of  $K^0$  in increasing order as  $K^0 = (k_i)_{i=0}^{|K^0|-1}$ . For all  $i < |K^0| - 1$ , using eq. (6) with  $j = k_i$  and  $k = k_{i+1}$ , we obtain

$$\Delta_{k_i} \leq \bar{f}(x_{k_i}) - \bar{f}(x_{k_{i+1}}). \quad (27)$$

Summing up eq. (27) over  $i < |K^0| - 1$  and adding the case  $k_{\text{last}} := k_{|K^0|-1}$  yields

$$\sum_{k \in K^0} \Delta_k \leq \sum_{i=0}^{|K^0|-2} (\bar{f}(x_{k_i}) - \bar{f}(x_{k_{i+1}})) + \Delta_{k_{\text{last}}} = \bar{f}(x_0) - \bar{f}(x_{k_{\text{last}}}) + \Delta_{k_{\text{last}}}. \quad (28)$$

It also holds that  $\bar{f}(x_0) \geq \bar{f}(x_{k_{\text{last}}}) \geq \bar{f}^*$  from eq. (6) with  $j = 0$  and  $k = k_{\text{last}}$ , and Assumption 1 and eq. (8). Thus, eq. (28) can be further bounded as

$$\sum_{k \in K^0} \Delta_k \leq \bar{f}(x_0) - \bar{f}(x_{k_{\text{last}}}) + \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_{k_{\text{last}}}), -\bar{f}(x_{k_{\text{last}}+1})) \quad (\text{eq. (4)})$$

$$\leq \bar{f}(x_0) - \bar{f}^* + \frac{2\varepsilon_f}{1 - \varepsilon_f} \max(1, \bar{f}(x_0), -\bar{f}^*) \quad (\text{eq. (8)})$$

$$= \bar{f}(x_0) - \bar{f}^* + \Delta_{\max}. \quad (\text{eq. (26)})$$

This completes the proof.  $\square$

Using this lemma, we can bound the sum of  $\|g_k\|^2$  over  $k \in K^0$  using  $\delta_k = f(x_k) - f(x_{k+1})$  in eq. (11) as follows.

**Lemma 4** *Under the assumptions, the sum of  $\delta_k$  over  $k \in K^0$  satisfies*

$$\sum_{k \in K^0} \delta_k \geq \frac{c\bar{\alpha}}{M} \sum_{k \in K^0} \|g_k\|^2 - \frac{2}{1 - \varepsilon_f} (\bar{f}(x_0) - \bar{f}^* + \Delta_{\max}).$$

*Proof* The relaxed Armijo condition (eq. (4)) at iteration  $k \in K^0$  yields

$$\begin{aligned} \bar{\delta}_k + \Delta_k &= \bar{f}(x_k) - \bar{f}(x_{k+1}) + \Delta_k & (\text{eq. (12)}) \\ &\geq -c\alpha_k g_k^\top d_k & (\text{eq. (4)}) \\ &\geq \frac{c\bar{\alpha}}{M + \mu_k} \|g_k\|^2 & (\text{Corollary 1 and eq. (9)}) \\ &= \frac{c\bar{\alpha}}{M} \|g_k\|^2. & (\mu_k = 0 \text{ since } k \in K^0) \end{aligned} \quad (29)$$

Since the conditions of Lemma 2 are always satisfied, we also have

$$\bar{\delta}_k + \Delta_k \leq \delta_k + \frac{1 + \varepsilon_f}{1 - \varepsilon_f} \Delta_k + \Delta_k = \delta_k + \frac{2}{1 - \varepsilon_f} \Delta_k. \quad (30)$$

Then, combining eqs. (29) and (30) and summing up over  $k \in K^0$  gives

$$\sum_{k \in K^0} \frac{c\bar{\alpha}}{M} \|g_k\|^2 \leq \sum_{k \in K^0} \delta_k + \frac{2}{1 - \varepsilon_f} \sum_{k \in K^0} \Delta_k \leq \sum_{k \in K^0} \delta_k + \frac{2}{1 - \varepsilon_f} (\bar{f}(x_0) - \bar{f}^* + \Delta_{\max}),$$

where the last inequality follows from Lemma 3. This completes the proof.  $\square$

### 3.5 Bound for the case $\mu_k > 0$

Next, we show that the sum of  $\|g_k\|^2$  over  $k \in K^+$  is bounded. Recall that  $K^+$  be a set of iteration indices  $k$  such that  $\mu_k > 0$  as defined in eq. (5), and that  $\mu_k$  is defined as  $\theta_k \sqrt{\varsigma + \sum_{j \in K^+, j < k} \|g_j\|^2}$  with  $\theta_k \in [\theta_{\min}, \theta_{\max}]$  in Line 8 of Algorithm 1.

Before proceeding to the main proof, we present standard inequalities in the ADAGRAD-NORM algorithm analysis [43, Lemma 3.2], [18, Lemma 3.1]. Its proof is deferred to ??.

**Lemma 5** *In Algorithm 1, we have*

$$\begin{aligned} \sum_{k \in K^+} \frac{\|g_k\|^2}{\mu_k^2} &\leq \frac{1}{\theta_{\min}^2} \left( \ln \left( \varsigma + \sum_{k \in K^+} \|g_k\|^2 \right) - \ln(\varsigma) \right), \\ \sum_{k \in K^+} \frac{\|g_k\|^2}{\mu_k} &\geq \frac{1}{\theta_{\max}} \left( \sqrt{\varsigma + \sum_{k \in K^+} \|g_k\|^2} - \sqrt{\varsigma} \right). \end{aligned}$$

We bound the sum of  $\|g_k\|^2$  over  $k \in K^+$  using  $\delta_k$  defined in eq. (11). Now, we define the following constants for later use:

$$C_1 := \frac{\bar{\alpha}}{\theta_{\max}} \quad C_2 := \frac{M\bar{\alpha} + L/2}{\theta_{\min}^2} \quad (31)$$

Note that  $0 < C_1 \leq C_2$  holds since  $1 \leq M$  and  $\theta_{\min} \leq \theta_{\max}$ .

**Lemma 6** *Under the assumptions, the sum of  $\delta_k$  over  $k \in K^+$  satisfies*

$$\sum_{k \in K^+} \delta_k \geq C_1 \left( \sqrt{\varsigma + \sum_{k \in K^+} \|g_k\|^2} - \sqrt{\varsigma} \right) - C_2 \left( \ln \left( \varsigma + \sum_{k \in K^+} \|g_k\|^2 \right) - \ln(\varsigma) \right)$$

*Proof* From the  $L$ -smoothness (Assumption 2), for  $k \in K^+$  we have

$$\begin{aligned} \delta_k &= f(x_k) - f(x_k + \alpha_k d_k) && \text{(eq. (11) and } x_{k+1} = x_k + \alpha_k d_k) \\ &\geq -\alpha_k g_k^\top d_k - \frac{\alpha_k^2 L}{2} \|d_k\|^2 && \text{(Assumption 2)} \\ &\geq \left( \frac{\alpha_k}{M + \mu_k} - \frac{\alpha_k^2 L}{2(m + \mu_k)^2} \right) \|g_k\|^2 && \text{(eqs. (9) and (10))} \\ &\geq \left( \frac{\bar{\alpha}}{M + \mu_k} - \frac{L}{2(m + \mu_k)^2} \right) \|g_k\|^2. && \text{(Corollary 1 and } \alpha_k \leq 1) \end{aligned} \quad (32)$$

We can further bound the terms in eq. (32) as

$$\frac{\bar{\alpha}}{M + \mu_k} = \frac{\bar{\alpha}}{\mu_k} \frac{1}{1 + \frac{M}{\mu_k}} \geq \frac{\bar{\alpha}}{\mu_k} \left( 1 - \frac{M}{\mu_k} \right) = \frac{\bar{\alpha}}{\mu_k} - \frac{M\bar{\alpha}}{\mu_k^2}, \quad \frac{L}{2(m + \mu_k)^2} \leq \frac{L}{2\mu_k^2}. \quad (33)$$

Thus, applying eq. (33) to eq. (32) yields

$$\delta_k \geq \left( \frac{\bar{\alpha}}{\mu_k} - \frac{M\bar{\alpha} + L/2}{\mu_k^2} \right) \|g_k\|^2. \quad (34)$$

Summing up eq. (34) over  $k \in K^+$  and applying Lemma 5 yield

$$\begin{aligned}
& \sum_{k \in K^+} \delta_k \\
& \geq \sum_{k \in K^+} \left( \frac{\bar{\alpha}}{\mu_k} - \frac{M\bar{\alpha} + L/2}{\mu_k^2} \right) \|g_k\|^2 \\
& \geq \frac{\bar{\alpha}}{\theta_{\max}} \left( \sqrt{\varsigma + \sum_{k \in K^+} \|g_k\|^2} - \sqrt{\varsigma} \right) - \frac{M\bar{\alpha} + L/2}{\theta_{\min}^2} \left( \ln \left( \varsigma + \sum_{k \in K^+} \|g_k\|^2 \right) - \ln(\varsigma) \right),
\end{aligned}$$

which yields the desired result.  $\square$

### 3.6 Global Convergence Result

Finally, we combine the results for  $k \in K^0$  (Lemma 4) and  $k \in K^+$  (Lemma 6) to derive a bound on the total sum of  $\|g_k\|^2$ . We define the constant  $F$  as follows:

$$F = f(x_0) - f^* + \frac{2}{1 - \varepsilon_f} \left( \bar{f}(x_0) - \bar{f}^* + \Delta_{\max} \right) + C_1 \sqrt{\varsigma} - C_2 \ln(\varsigma). \quad (35)$$

Then, we can obtain the following unified bound of the sum of  $\|g_k\|^2$ .

**Proposition 2** *Under the assumptions, the sum of  $\|g_k\|^2$  over  $k \in K^0, K^+$  satisfies*

$$F \geq \frac{c\bar{\alpha}}{M} \sum_{k \in K^0} \|g_k\|^2 + C_1 \sqrt{\varsigma + \sum_{k \in K^+} \|g_k\|^2} - C_2 \ln \left( \varsigma + \sum_{k \in K^+} \|g_k\|^2 \right),$$

*Proof* By  $f(x_{k_{\max}}) \geq f^*$  by Assumption 1 and  $K = K^0 \cup K^+$ , we have

$$f(x_0) - f^* \geq f(x_0) - f(x_{k_{\max}}) = \sum_{k \in K} \delta_k = \sum_{k \in K^0} \delta_k + \sum_{k \in K^+} \delta_k.$$

From Lemmas 4 and 6, we can further bound as

$$\begin{aligned}
f(x_0) - f^* & \geq \frac{c\bar{\alpha}}{M} \sum_{k \in K^0} \|g_k\|^2 + C_1 \sqrt{\varsigma + \sum_{k \in K^+} \|g_k\|^2} - C_2 \ln \left( \varsigma + \sum_{k \in K^+} \|g_k\|^2 \right) \\
& \quad - \frac{2}{1 - \varepsilon_f} \left( \bar{f}(x_0) - \bar{f}^* + \Delta_{\max} \right) - C_1 \sqrt{\varsigma} + C_2 \ln(\varsigma).
\end{aligned}$$

Rearranging and substituting eq. (35) yields the desired bound, concluding the proof.  $\square$

This proposition is key to proving the global convergence of Algorithm 1, since we can derive upper-bounds for the sums of  $\|g_k\|^2$  over  $k \in K^0$  and  $k \in K^+$  separately. Let us first bound the sum of  $\|g_k\|^2$  over  $k \in K^0$ . In the following, let  $G$  denote

$$G := \varsigma + \sum_{k \in K^+} \|g_k\|^2$$

for simplicity.

**Corollary 2** *Under the assumptions, the sum of  $\|g_k\|^2$  over  $k \in K^0$  satisfies*

$$\sum_{k \in K^0} \|g_k\|^2 \leq \frac{M}{c\bar{\alpha}} \left( F - 2C_2 + 2C_2 \ln \frac{2C_2}{C_1} \right).$$

*Proof* By simple calculus, we can verify that

$$C_1 \sqrt{G} - C_2 \ln(G) \geq C_1 \sqrt{G^*} - C_2 \ln(G^*) = 2C_2 - 2C_2 \ln \frac{2C_2}{C_1},$$

where  $G^* := (2C_2/C_1)^2$ . Thus, Proposition 2 yields

$$F \geq \frac{c\bar{\alpha}}{M} \sum_{k \in K^0} \|g_k\|^2 + C_1 \sqrt{G^*} - C_2 \ln(G^*) = \frac{c\bar{\alpha}}{M} \sum_{k \in K^0} \|g_k\|^2 + 2C_2 - 2C_2 \ln \frac{2C_2}{C_1}.$$

□

Then, we focus on the sum over  $k \in K^+$ . From Proposition 2, we obtain

$$F \geq C_1 \sqrt{G} - C_2 \ln(G). \quad (36)$$

Since  $\sqrt{G}$  grows faster than  $\ln(G)$  as  $G \rightarrow \infty$ , the  $G$  satisfying eq. (36) must be bounded above. This inequality is closely related to the Lambert  $W$  function [7, 18]. Let  $e$  be the base of the natural logarithm. The only fact we use in this paper is that, if  $x \in [-1/e, 0)$ ,  $ye^y = x$  has two real and negative solutions, and the smaller solution is given by the second branch of Lambert  $W$  function  $W_{-1}(x) < 0$  and thus  $ye^y > x$  for all  $y < W_{-1}(x)$ . Using this fact, we can derive the following upper bound on the sum of  $\|g_k\|^2$  over  $k \in K^+$ .

**Corollary 3** *Under the assumptions, the sum of  $\|g_k\|^2$  over  $k \in K^+$  satisfies*

$$\sum_{k \in K^+} \|g_k\|^2 \leq \max \left( \left( \frac{2F}{C_1} \right)^2, G_0 \right) - \varsigma,$$

where  $G_0$  is

$$G_0 = \left( -\frac{4C_2}{C_1} W_{-1} \left( -\frac{C_1}{4C_2} \right) \right)^2.$$

*Proof* From Proposition 2, it suffices to show that any  $G > G_0$  satisfying eq. (36) also satisfies  $G \leq \left( \frac{2F}{C_1} \right)^2$ . We assume  $G > G_0$  in the following. The definition of  $G_0$  implies

$$-\frac{C_1 \sqrt{G}}{4C_2} < W_{-1} \left( -\frac{C_1}{4C_2} \right) < 0. \quad (37)$$

Since  $-\frac{1}{e} \leq -\frac{C_1}{4C_2} < 0$  from  $0 < C_1 \leq C_2$ , the definition of  $W_{-1}$  and eq. (37) yield

$$-\frac{C_1 \sqrt{G}}{4C_2} e^{-\frac{C_1 \sqrt{G}}{4C_2}} > -\frac{C_1}{4C_2}.$$

This is equivalent to  $\sqrt{G} < e^{\frac{C_1\sqrt{G}}{4C_2}}$ , and taking logarithms and multiplying by  $2C_2$  gives

$$2C_2 \ln(\sqrt{G}) = C_2 \ln(G) < \frac{C_1}{2} \sqrt{G}. \quad (38)$$

Combining eqs. (36) and (38) yields

$$F \geq C_1 \sqrt{G} - C_2 \ln(G) > C_1 \sqrt{G} - \frac{C_1}{2} \sqrt{G} = \frac{C_1}{2} \sqrt{G}.$$

Thus, we have  $G \leq \left(\frac{2F}{C_1}\right)^2$  for all  $G > G_0$ . This completes the proof.  $\square$

Combining Corollaries 2 and 3, we can establish the following global convergence result for Algorithm 1.

**Theorem 1 (Global Convergence)** *Under the assumptions, the average of squared gradient norms generated by Algorithm 1 satisfies:*

$$\frac{1}{k_{\max}} \sum_{k=0}^{k_{\max}-1} \|g_k\|^2 = \mathcal{O}\left(\frac{1}{k_{\max}}\right),$$

which means that the iteration complexity to achieve  $\|\nabla f(x_k)\| \leq \varepsilon_{\text{gtol}}$  is

$$\min \{k \mid \|\nabla f(x_k)\| \leq \varepsilon_{\text{gtol}}\} = \mathcal{O}(1/\varepsilon_{\text{gtol}}^2).$$

*Proof* Using Corollaries 2 and 3, we have

$$\frac{1}{k_{\max}} \sum_{k=0}^{k_{\max}-1} \|g_k\|^2 = \frac{1}{k_{\max}} \left( \sum_{k \in K^0} \|g_k\|^2 + \sum_{k \in K^+} \|g_k\|^2 \right) \leq \frac{C}{k_{\max}} \quad (39)$$

where  $C$  is a constant defined as

$$C := \left( \frac{2M(F - 2C_2 + 2C_2 \ln \frac{2C_2}{C_1})}{c\bar{\alpha}} + \max \left( \left( \frac{2F}{C_1} \right)^2, G_0 \right) - \varsigma \right).$$

If  $k_{\max} > C/\varepsilon_{\text{gtol}}^2$  and  $\|g_k\| > \varepsilon_{\text{gtol}}$  for all  $k \in K$ , we have

$$\frac{1}{k_{\max}} \sum_{k=0}^{k_{\max}-1} \|g_k\|^2 > \varepsilon_{\text{gtol}}^2 > \frac{C}{k_{\max}},$$

which contradicts eq. (39). Hence, there exists an index  $k < k_{\max}$  such that  $\|g_k\| \leq \varepsilon_{\text{gtol}}$ , and thus we obtain the desired iteration complexity.  $\square$

Theorem 1 is a standard convergence guarantee for first-order optimization algorithms applied to  $L$ -smooth nonconvex functions, and it matches the optimal convergence rate for such problems. We interpret these results in light of classical optimization results.

- As for  $K^0$  and Corollary 2, this is an analogue of the classical gradient descent bound for an error-contaminated function  $\bar{f}$ . Indeed, for gradient descent with fixed step size  $\alpha = 1/L$ , the sum of squared gradients is bounded as

$$\sum_{j=0}^k \|g_j\|^2 \leq 2L(f(x_0) - f^*) = \frac{2(f(x_0) - f^*)}{\alpha}.$$

- As for  $K^+$  and Corollary 3, this is analogous to the convergence property of ADAGRAD-NORM [43], which scales as  $(f(x_0) - f^*)^2$ . This follows from the fact that  $F$  contains the initial optimality gaps  $f(x_0) - f^*$  and  $\bar{f}(x_0) - \bar{f}^*$  (as the definition in eq. (35)), and the term in Corollary 3 is quadratic in  $F$ .

#### 4 Practical Choices of Algorithmic Variables

In sections 2 and 3, we introduced Algorithm 1 and established its convergence properties. In this section, we discuss practical choices of algorithmic variables and parameters that lead to fast and stable performance in practice. The quantities to be discussed here are the matrices  $B_k$ , the step sizes  $\alpha_k$ , and the regularization parameters  $\mu_k$ .

##### 4.1 Approximate Hessian $B_k$

We first discuss the construction of the matrices  $B_k$  used in Line 9 of Algorithm 1. As mentioned in ??, we employ an L-BFGS method to form  $B_k$ . The purpose of this subsection is to show that  $B_k$  can satisfy Assumption 3, the uniform spectral bound, with the modification and selection of curvature pairs.

*Construction of  $B_k$*  Before stating concrete construction of  $B_k$ , we recall the L-BFGS method and the curvature pair notation [4, 25, 31]. For an iteration  $k$ , we define

$$s_k := x_{k+1} - x_k, \quad y_k := g_{k+1} - g_k \quad (40)$$

where  $g_k$  and  $g_{k+1}$  are the gradients at  $x_k$  and  $x_{k+1}$ , respectively. Starting from an initial matrix, an approximate Hessian is obtained by successively applying BFGS updates to a sequence of curvature pairs. Let  $\{(s_{k_i}, y_{k_i})\}_{i=0}^{p-1}$  be a collection of curvature pairs, where  $k_i$  denotes the iteration index at which the  $i$ -th pair was generated. Starting from the initial matrix  $\gamma I$  with  $\gamma = \|y_{k_0}\|^2 / y_{k_0}^\top s_{k_0}$ , we define  $\text{BFGS}(\{(s_{k_i}, y_{k_i})\}_{i=0}^{p-1})$  as the matrix obtained by sequentially applying the BFGS update using these pairs in the given order. Here,  $p$  denotes the maximum number of stored curvature pairs and is a fixed small integer in the L-BFGS method. When fewer than  $p$  curvature pairs are available, the BFGS update is applied using all currently available pairs.

Now, we provide a sufficient condition for Assumption 3 by the following proposition, which is a variant of existing work [12, Theorem 5.5] [14, Lemma 1]. Its proof is deferred to ??.

**Proposition 3** Let  $\{(s_{k_i}, y_{k_i})\}_{i=0}^{p-1}$  be a fixed number of curvature pairs with  $s_{k_i} \neq 0$ . Assume that there exist constants  $0 < \lambda \leq \Lambda$  such that for all  $(s, y) \in \{(s_{k_i}, y_{k_i})\}_{i=0}^{p-1}$ ,

$$y^\top s \geq \frac{1}{\Lambda} \|y\|^2, \quad (41)$$

$$y^\top s \geq \lambda \|s\|^2. \quad (42)$$

Define the condition number  $\kappa := \Lambda/\lambda$ . Then there exist  $0 < m < M$  such that

$$mI \preceq \text{BFGS}(\{(s_{k_i}, y_{k_i})\}_{i=0}^{p-1}) \preceq MI, \quad (43)$$

where

$$M := \gamma + p\Lambda, \quad m := \left( (1 + \sqrt{\kappa})^{2p} \left( \gamma + \frac{1}{\lambda(2\sqrt{\kappa} + \kappa)} \right) \right)^{-1}.$$

Proposition 3 shows that, whenever eqs. (41) and (42) hold for the stored pairs, the resulting BFGS matrix satisfies Assumption 3 as expressed in eq. (43).

Based on Proposition 3, we basically adopt the following rule for forming  $B_k$ :

$$B_k = \text{BFGS}(\{(s_{k_i}, \bar{y}_{k_i} := \theta_i^{\text{damp}} y_{k_i} + (1 - \theta_i^{\text{damp}}) B_{k-1} s_{k_i})\}), \quad (44)$$

where  $\theta_i^{\text{damp}} \in [0, 1]$  is determined using damped BFGS update [26, 33] and the indices  $\{k_i\}_{i=0}^{p-1}$  are selected so that the modified pairs  $(s_{k_i}, \bar{y}_{k_i})$  satisfy eqs. (41) and (42) for some constants  $\lambda, \Lambda$ . The damped BFGS is a classical technique to ensure  $\bar{y}_{k_i}^\top s_{k_i} > 0$ .

Since we do not employ the Wolfe conditions in the line search, this damping technique plays a central role in ensuring the positive definiteness of  $B_k$ . The selection of curvature pairs shares the same spirit as the cautious update [23, 27, 28], which only uses pairs satisfying certain curvature conditions. By Proposition 3,  $B_k$  satisfies the uniform spectral bound in Assumption 3. This confirms that the practical construction of  $B_k$  is consistent with the theoretical requirements.

*Remarks for Practical Implementation* Having established that the proposed construction of  $B_k$  satisfies Assumption 3, we now present several remarks on its practical implementation. We begin by describing how to compute the search direction

$$d_k = -(B_k + \mu_k I)^{-1} g_k \quad (45)$$

with  $B_k$  in eq. (44). When  $\mu_k = 0$ , the direction can be computed efficiently by the standard L-BFGS two-loop recursion [25, 31]. For the case  $\mu_k > 0$ , regularized limited-memory schemes may in principle be employed [22]. Alternatively, one may adopt the simple and robust approximation mentioned in the same reference. Specifically, we approximate  $B_k$  in eq. (44) by

$$B_k \approx \text{BFGS}(\{(s_{k_i}, \bar{y}_{k_i} + \mu_k s_{k_i})\}_{i=0}^{p-1}) - \mu_k I, \quad (46)$$

so that  $B_k + \mu_k I \approx \text{BFGS}(\{(s_{k_i}, \bar{y}_{k_i} + \mu_k s_{k_i})\}_{i=0}^{p-1})$ . Its inverse can then be computed using the standard two-loop recursion. Although this approximation is inexact, it has

been reported to yield nearly identical practical performance while remaining comparatively simple to implement [22]. We adopt this approximation in the this work.

Separately, there exist function-based modified secant conditions [1, 19, 45, 48] that adjust the secant equation using available function values and gradients when those quantities are deemed reliable. Such adjustments aim to improve practical convergence behavior. We partially adopt these function-based modifications following prior work [46, 49]. The suffix -MS in section 5 indicates the use of this technique. Because these modifications are well established, we omit low-level implementation details here. Further specifics are available in the cited references and in our open-source implementation<sup>??</sup>.

#### 4.2 Step Size $\alpha_k$

We next discuss the adjustment of the step size  $\alpha_k$  in Line 4 of Algorithm 2.

As indicated in the pseudo-code, we choose  $\alpha_k$  using interpolation of the objective function. Moré–Thuente line searches [29] are widely used in quasi-Newton methods [41], and they typically employ cubic or quadratic interpolation to select trial step sizes. In our implementation, we use essentially the same procedure with a slight modification, namely, clipping the trial step size to the interval  $[\beta_{\min}\alpha_k, \beta_{\max}\alpha_k]$ . For all numerical experiments, we set the Armijo parameter to  $c = 10^{-4}$  and choose the interpolation bounds as  $\beta_{\min} = 1/16$  and  $\beta_{\max} = 15/16$ .

Furthermore, when  $\mu_k > 0$  and  $\alpha_k = 1$ , we introduce a one-time adjustment of the trial step size using gradient information. Let  $d_k$  be the search direction and  $g_k$  and  $g_{\text{try}}$  the gradients at the current and trial points. If the directional derivative along  $d_k$  changes sign,  $d_k^\top g_k < 0$  and  $d_k^\top g_{\text{try}} > 0$ , and the trial gradient is sufficiently aligned with  $d_k$ , namely  $d_k^\top g_{\text{try}} > 0.5\|d_k\|\|g_{\text{try}}\|$ , we rescale  $\alpha_k$  once by a secant-like factor,

$$\alpha_k \leftarrow \text{clip}\left(\alpha_k \frac{-d_k^\top g_k}{d_k^\top g_{\text{try}} - d_k^\top g_k}, \beta_{\min}\alpha_k, \beta_{\max}\alpha_k\right),$$

where clip means clipping to the specified interval. When objective values are unreliable and backtracking and interpolation do not occur, this correction effectively refines the step size. Since this adjustment is at most once per iteration, the theoretical results in section 3 remain valid.

#### 4.3 Regularization Parameter $\mu_k$

We finally discuss the adjustment of the regularization parameter  $\mu_k$  in Line 8 of Algorithm 1.

In our implementation, we choose the regularization parameter as

$$\mu_k = \text{clip}\left(\frac{1}{10}\|g_k\|, \frac{1}{100}G_k, G_k\right) \text{ where } G_k := \sqrt{\varsigma + \sum_{j \in K, j \leq k} \|g_j\|^2},$$

which is consistent with the general form (eq. (7)) with an adaptive factor  $\theta_k \in [10^{-2}, 1]$ . In practice, we may set  $\varsigma = 0$  as long as the initial gradient is nonzero since  $\varsigma$  is mainly introduced for avoiding zero division, but to make it consistent with the theory, we set  $\varsigma = 10^{-10}$  in all experiments.

When  $B_k$  is a good approximation of the Hessian, the regularization parameter  $\mu_k$  should be small for fast convergence. Since the quantity  $G_k$  is strictly increasing with  $k$ , it is natural in practice to decrease the effective regularization when sufficient progress in the objective function is achieved. When the difference between the two sides of eq. (6) is larger than 1, we restart the accumulation by resetting  $K^+$  to the empty set and  $G_k$  to  $\varsigma$ . As long as the number of such restarts is finite, the overall convergence analysis in section 3 remains valid. Since these choices are heuristic, there may be room for further improvement. Especially, further increasing  $\mu_k$  stabilizes the method when the objective function values are highly noisy, and decreasing  $\mu_k$  more aggressively may accelerate convergence when the objective function is accurate.

## 5 Numerical Experiments

### 5.1 Methods

We compared the following optimization algorithms:

- (Ours): Our proposed regularized quasi-Newton method
  - We used Algorithm Algorithms 1 and 2 with the details in section 4.
- (Line): Line-search L-BFGS method
  - Our Python implementation ported from LBFGSpp [32].
  - The step size was determined using the Moré–Thuente line search, closely resembling SciPy’s implementation.
- (SciPy): SciPy’s L-BFGS-B method [41]
  - An established L-BFGS method implemented in C and called from Python.
  - We used the default parameters, with the exception that `ftol` was set to 0 to avoid premature termination.
- (Reg): Regularized L-BFGS method [22]
  - A quadratic regularizationbased quasi-Newton method that does not rely on line search and is conceptually closer to trust-region methods.
  - We wrapped the function `regLBFGS` using `solveNonmonotone`.
- (NTQN): Noise-tolerant quasi-Newton method [37, 44]
  - A method designed to accommodate inexact gradient information, as mentioned in section 1.1.
  - We mainly used the default parameter settings, and slightly modified the stopping criteria to terminate at the desired gradient norm tolerance.

In the following, each method is referred to by the name given in parentheses. For (Ours) and (Line), we additionally tested variants incorporating the modified secant condition described in section 4.1, which are denoted by (Ours-MS) and (Line-MS), respectively. All these methods are L-BFGS-based, and we set the number of stored curvature pairs to 10, the default value in SciPy’s L-BFGS-B implementation.

| explanation             | min abs value           | relative error                         | $\epsilon_f$          |
|-------------------------|-------------------------|----------------------------------------|-----------------------|
| 64-bit double precision | $2.23 \times 10^{-308}$ | $2^{-52} \approx 2.22 \times 10^{-16}$ | $2.22 \times 10^{-9}$ |
| 32-bit single precision | $1.18 \times 10^{-38}$  | $2^{-23} \approx 1.19 \times 10^{-7}$  | $1.19 \times 10^{-3}$ |
| 16-bit half precision   | $6.10 \times 10^{-5}$   | $2^{-10} \approx 9.77 \times 10^{-4}$  | $9.77 \times 10^{-2}$ |

Table 1: The “min abs value” is the smallest positive normalized number, the “relative error” is the maximum relative rounding error, and  $\epsilon_f$  is the parameter in (1) used in our experiments.

All experiments were conducted on a Microsoft Windows 11 Home system (version 10.0, build 26100) equipped with a 13th Gen Intel® Core™ i7-1360P CPU, featuring 12 physical cores and 16 logical processors. All computations were performed using the CPU only.

## 5.2 Experimental Results

### 5.2.1 Test Problems and Settings

We evaluated all algorithms on unconstrained problems from the CUTEst collection [13], implemented in Python using the PyCUTEst interface [11]. All problems were initialized with the default starting points provided by the library. Following the previous work [22], we excluded 17 problems where either the initial point is already stationary or all algorithms are known to fail. This left 220 test problems. To simulate different numerical environments, we tested the following four settings:

- Artificial noise with absolute noise level of  $10^{-3}$  at 64-bit precision (220 problems,  $\epsilon_f = 10^{-2}$ )
- 64-bit floating-point precision (220 problems,  $\epsilon_f = 2.22 \times 10^{-9}$ )
- 32-bit floating-point precision (220 problems,  $\epsilon_f = 1.19 \times 10^{-2}$ )
- 16-bit floating-point precision (152 problems,  $\epsilon_f = 9.77 \times 10^{-1}$ )

Each setting uses a different error rate  $\epsilon_f$  in the relative error model (eq. (1)), as summarized in Table 1. The table relates the machine epsilon (maximum relative rounding error) for each floating-point precision to the  $\epsilon_f$  value used in our experiments. We set  $\epsilon_f$  equal to or larger than the machine epsilon to account for additional uncertainties in function and gradient evaluations. We also set the maximum number of iterations to  $k_{\max} = 15,000$  and timed out runs exceeding 10 minutes per problem.

In the reduced precision settings, to simulate lower numerical precision, we first casted the input vector  $x$  to the target lower precision, then computed  $\bar{f}(x)$  and  $\nabla \bar{f}(x)$  using the lower-precision input. Although the internal computations of CUTEst remain in 64-bit precision, the casting of the input vector effectively simulated the impact of reduced precision on function and gradient evaluations. In the 16-bit precision setting, we excluded problems where the initial gradient norm contains NaN or INF values after casting, resulting in a total of 152 problems.

In the artificial noise setting, we added uniform random noise sampled from  $[-10^{-3}, 10^{-3}]$  to both the objective function values and each component of the gradient vectors independently, i.e.,

$$\bar{f}(x) = f(x) + \text{unif}(-10^{-3}, 10^{-3}), \quad \nabla \bar{f}(x) = \nabla f(x) + \text{unif}(-10^{-3}, 10^{-3}) \mathbb{1},$$

where  $\text{unif}(a, b)$  denotes a uniform random variable in the interval  $[a, b]$  and  $\mathbb{1}$  is the vector of all ones. This setting is the same as the one in [37].

### 5.2.2 Performance Profiles

We used performance profiles [9] to compare the algorithms. Let  $P$  denote the set of test problems and  $S$  the set of solvers. For each problem  $p \in P$  and solver  $s \in S$ , let  $t_{p,s} > 0$  denote the number of function and gradient evaluations required to reach a specified gradient norm tolerance  $\epsilon_{\text{gtol}}$ . Note that  $t_{p,s}$  is not time in this experiment but the number of evaluations. When a solver fails to converge within the gradient tolerance or exceeds a maximum number of evaluations, we set  $t_{p,s} = +\infty$ . Then, the performance ratio  $r_{p,s}$  is defined as

$$r_{p,s} = \frac{t_{p,s}}{\min_{s' \in S} t_{p,s'}}.$$

For a given threshold  $\tau \geq 1$ , the performance profile plots the proportion of problems for which  $r_{p,s} \leq \tau$ , which means that the  $y$ -coordinate for solver  $s$  at  $x$ -coordinate  $\tau$  is given by

$$\rho_s(\tau) = \frac{1}{|P|} |\{p \in P \mid r_{p,s} \leq \tau\}|.$$

A curve that lies above others indicates better overall performance.

### 5.2.3 Results with Artificial Noise

We first present the results in the artificial noise setting described in section 5.2.1. Figure 2 presents the performance profile with  $\epsilon_f = 10^{-2}$ . In this regime, the proposed method shows superior robustness compared to other quasi-Newton methods. Notably, (Ours) and (Ours-MS) outperform (NTQN), which is specifically designed to handle noisy gradients.

### 5.2.4 Results at Different Precision Levels

We next present performance profiles for each floating-point precision (64-bit, 32-bit, and 16-bit). We evaluated each method at three gradient norm tolerance levels ( $10^{-3}$ ,  $10^{-4}$ , and  $10^{-5}$ ), i.e.,  $\epsilon_{\text{gtol}} \in \{10^{-3}, 10^{-4}, 10^{-5}\}$ . These tolerance levels represent different optimization regimes, from moderate accuracy to high precision requirements. Figure 3 shows the comprehensive performance profiles across all three precision levels. Our method (Ours) demonstrates competitive or superior performance compared to existing methods in the standard 64-bit setting. The modified secant equation variant (Ours-MS) further improves performance. As numerical precision degrades from




Fig. 2: Performance profile for artificial noise setting (level of  $10^{-3}$ ) and  $\epsilon_{\text{gtol}} = 10^{-2}$ .

64-bit to 32-bit and further to 16-bit, our regularizationbased approach demonstrates improved relative performance. The proposed method maintains stability even when traditional line-search methods encounter difficulties with reduced precision arithmetic.

### 5.3 Computational Time

In this subsection, we present an experiment to compare the per-iteration computational cost of each method. Since the previous experiments focused on the number of function and gradient evaluations, they did not directly reflect the computational overhead of each algorithm. Here, we measured the total execution time required to perform a fixed number of iterations on a simple problem. We conducted experiments on the ill-conditioned quadratic problem

$$\underset{x \in \mathbb{R}^n}{\text{minimize}} \quad \frac{1}{2} \sum_{i=1}^n ix_i^2$$

with  $n = 10,000$ , and measured the total execution time. Timing data were collected after three warm-up runs, followed by 100 recorded trials. The initial point  $x_0$  was




Fig. 3: Performance profiles across different floating-point precisions (64, 32, and 16-bit) and tolerance levels. Each row corresponds to a different precision level, demonstrating the robustness of the proposed method as numerical precision degrades.

chosen as the all-ones vector. We used memory size  $m = 10$  and maximum iterations  $k_{\max} = 100$ , and we did not set any stopping criteria other than reaching  $k_{\max}$ . The simplicity of the optimization problem and the small value of  $k_{\max}$  are well suited to the purpose of this experiment, as they ensure that the total runtime is dominated by algorithmic overhead rather than function or gradient computation.

The results are summarized in Table 2 and Figure 4. In Table 2, we report the total number of oracle calls (calls of  $\bar{f}$  and  $\nabla \bar{f}$ ) and final objective values  $f(x_{k_{\max}})$ . We only report the unique values per method since both quantities were identical across runs for each method. The comparable values in the table indicate that the comparison of execution times is fair and not affected by differences in convergence behavior. In Figure 4, we report the execution time statistics, and we can observe that our proposed methods (Ours) and (Ours-MS) exhibit competitive performance compared to other methods. Although the (SciPy) calls optimized C routines, it incurs associated




Fig. 4: Mean execution times for the experiment in section 5.3. This plot roughly indicates the extra computational overhead of each method. Error bars represent one standard deviation over 100 runs.

dispatch overhead, producing a larger mean time. The (Reg) method explicitly computes  $-(B_k + \mu_k I)^{-1} g_k$ , which is numerically attractive but entails extra per-iteration cost. In contrast, our proposed methods employ the simplified strategy described in section 4, which reduces per-iteration overhead while preserving performance. This design accounts for their competitive mean execution times.

|                         | Ours | Line | Line-MS | Ours-MS | NTQN | SciPy | Reg  |
|-------------------------|------|------|---------|---------|------|-------|------|
| # Calls                 | 202  | 212  | 212     | 202     | 219  | 212   | 206  |
| $\bar{f}(x_{k_{\max}})$ | 1.34 | 1.24 | 1.24    | 1.34    | 1.43 | 1.24  | 1.47 |

Table 2: The number of oracle calls and final observed objective values for the experiment in section 5.3.

## 6 Conclusion

In this work, we proposed a regularized quasi-Newton method for noisy nonconvex optimization and established its global convergence properties. We also demonstrated the method’s effectiveness through numerical experiments on standard benchmark problems under various noise and precision settings. The results indicate that our method is robust and practically efficient, particularly in noisy or low-precision environments where traditional line-search methods may struggle.

Future work includes the investigation of local convergence properties, the extension to constrained optimization, and the application to practical problems in machine learning and scientific computing. Additionally, exploring adaptive strategies for selecting algorithmic parameters based on problem characteristics could further enhance the method's performance.

Explicitly analyzing the impact of inexact gradient evaluations can also provide valuable insights into the method's robustness and guide further enhancements.

## References

1. Babaie-Kafaki S, Ghanbari R, Mahdavi-Amiri N (2010) Two new conjugate gradient methods based on modified secant equations. *Journal of Computational and Applied Mathematics* 234(5):1374–1386, DOI 10.1016/j.cam.2010.01.052
2. Bellavia S, Gurioli G, Morini B, Toint PL (2021) The Impact of Noise on Evaluation Complexity: The Deterministic Trust-Region Case. DOI 10.48550/arXiv.2104.02519, [2104.02519](#)
3. Berahas AS, Cao L, Choromanski K, Scheinberg K (2021) A Theoretical and Empirical Comparison of Gradient Approximations in Derivative-Free Optimization. DOI 10.48550/arXiv.1905.01332, [1905.01332](#)
4. Berahas AS, Curtis FE, Zhou B (2022) Limited-memory BFGS with displacement aggregation. *Mathematical Programming* 194(1):121–157, DOI 10.1007/s10107-021-01621-6
5. Carter RG (1993) Numerical Experience with a Class of Algorithms for Non-linear Optimization Using Inexact Function and Gradient Information. *SIAM Journal on Scientific Computing* 14(2):368–388, DOI 10.1137/0914023
6. Clancy RJ, Menickelly M, Hückelheim J, Hovland P, Nalluri P, Gjini R (2022) TROPHY: Trust Region Optimization Using a Precision Hierarchy. In: *Computational Science – ICCS 2022*, Springer, Cham, pp 445–459, DOI 10.1007/978-3-031-08751-6\_32
7. Corless RM, Gonnet GH, Hare DEG, Jeffrey DJ, Knuth DE (1996) On the LambertW function. *Advances in Computational Mathematics* 5(1):329–359, DOI 10.1007/BF02124750
8. Doikov N, Mishchenko K, Nesterov Y (2024) Super-Universal Regularized Newton Method. *SIAM Journal on Optimization* 34(1):27–56, DOI 10.1137/22M1519444
9. Dolan ED, Moré JJ (2002) Benchmarking optimization software with performance profiles. *Mathematical Programming* 91(2):201–213, DOI 10.1007/s101070100263
10. Duchi J, Hazan E, Singer Y (2011) Adaptive Subgradient Methods for Online Learning and Stochastic Optimization. *Journal of Machine Learning Research* 12(61):2121–2159
11. Fowkes J, Roberts L, Bűrmen Á (2022) PyCUTEst: An open source Python package of optimization test problems. *Journal of Open Source Software* 7(78):4377, DOI 10.21105/joss.04377

12. Gao W, Goldfarb D (2018) Quasi-Newton Methods: Superlinear Convergence Without Line Searches for Self-Concordant Functions. DOI 10.48550/arXiv.1612.06965, [1612.06965](#)
13. Gould NI, Orban D, Toint PL (2015) CUTEst: A Constrained and Unconstrained Testing Environment with safe threads for mathematical optimization. *Comput Optim Appl* 60(3):545–557, DOI 10.1007/s10589-014-9687-3
14. Gower RM, Goldfarb D, Richtárik P (2016) Stochastic Block BFGS: Squeezing More Curvature out of Data. DOI 10.48550/arXiv.1603.09649, [1603.09649](#)
15. Grapiglia GN, Stella GFD (2022) An adaptive trust-region method without function evaluations. *Computational Optimization and Applications* 82(1):31–60, DOI 10.1007/s10589-022-00356-0
16. Gratton S, Toint PL (2020) A note on solving nonlinear optimization problems in variable precision. *Computational Optimization and Applications* 76(3):917–933, DOI 10.1007/s10589-020-00190-2
17. Gratton S, Toint PL (2023) OFFO minimization algorithms for second-order optimality and their complexity. *Computational Optimization and Applications* 84(2):573–607, DOI 10.1007/s10589-022-00435-2
18. Gratton S, Jerad S, Toint PhL (2024) Complexity of a class of first-order objective-function-free optimization algorithms. *Optimization Methods and Software* 0(0):1–31, DOI 10.1080/10556788.2023.2296431
19. Hassan BA, Moghrabi IAR (2023) A modified secant equation quasi-Newton method for unconstrained optimization. *Journal of Applied Mathematics and Computing* 69(1):451–464, DOI 10.1007/s12190-022-01750-x
20. Higham NJ (2002) Accuracy and Stability of Numerical Algorithms. Society for Industrial and Applied Mathematics, DOI 10.1137/1.9780898718027
21. Izycheva A, Darulova E (2017) On sound relative error bounds for floating-point arithmetic. In: *Proceedings of the 17th Conference on Formal Methods in Computer-Aided Design, FMCAD Inc, Austin, Texas*
22. Kanzow C, Steck D (2023) Regularization of limited memory quasi-Newton methods for large-scale nonconvex minimization. *Mathematical Programming Computation* 15(3):417–444, DOI 10.1007/s12532-023-00238-4
23. Li DH, Fukushima M (2001) On the Global Convergence of the BFGS Method for Nonconvex Unconstrained Optimization Problems. *SIAM Journal on Optimization* 11(4):1054–1064, DOI 10.1137/S1052623499354242
24. Li YJ, Li DH (2009) Truncated regularized Newton method for convex minimizations. *Computational Optimization and Applications* 43(1):119–131, DOI 10.1007/s10589-007-9128-7
25. Liu DC, Nocedal J (1989) On the limited memory BFGS method for large scale optimization. *Mathematical Programming* 45(1):503–528, DOI 10.1007/BF01589116
26. Lotfi S, de Ruisselet TB, Orban D, Lodi A (2020) Stochastic Damped L-BFGS with Controlled Norm of the Hessian Approximation. DOI 10.13140/RG.2.2.27851.41765/1, [2012.05783](#)
27. Mannel F (2025) A Globalization of L-BFGS and the Barzilai–Borwein Method for Nonconvex Unconstrained Optimization. *Journal of Optimization Theory and Applications* 204(3):1–34, DOI 10.1007/s10957-024-02565-5

28. Mannel F, Om Aggrawal H, Modersitzki J (2024) A structured L-BFGS method and its application to inverse problems. *Inverse Problems* 40(4):045022, DOI 10.1088/1361-6420/ad2c31
29. Moré JJ, Thuente DJ (1994) Line search algorithms with guaranteed sufficient decrease. *ACM Trans Math Softw* 20(3):286–307, DOI 10.1145/192115.192132
30. Nesterov Y, Polyak B (2006) Cubic regularization of Newton method and its global performance. *Mathematical Programming* 108(1):177–205, DOI 10.1007/s10107-006-0706-8
31. Nocedal J, Wright SJ (1999) *Numerical Optimization*. Springer, DOI 10.1007/978-0-387-40065-5
32. Okazaki N (2007) libLBFGS: A library of limited-memory broyden-fletcher-goldfarb-shanno (l-BFGS)
33. Powell MJ (1978) Algorithms for nonlinear constraints that use lagrangian functions. *Math Program* 14(1):224–248, DOI 10.1007/BF01588967
34. Ranganath A, Singhal M, Marcia R (2025) Symmetric Rank-One Quasi-Newton Methods for Deep Learning Using Cubic Regularization. DOI 10.48550/arXiv.2502.12298, [2502.12298](#)
35. Ruan H, Yang W (2024) Adaptive Regularized Quasi-Newton Method Using Inexact First-Order Information. *Journal of Computational Mathematics* 42(6):1656–1687, DOI 10.4208/jcm.2306-m2022-0279
36. Sheng Z, Yuan G, Cui Z (2018) A new adaptive trust region algorithm for optimization problems. *Acta Mathematica Scientia* 38(2):479–496, DOI 10.1016/S0252-9602(18)30762-8
37. Shi HJM, Xie Y, Byrd R, Nocedal J (2022) A Noise-Tolerant Quasi-Newton Algorithm for Unconstrained Optimization. *SIAM Journal on Optimization* 32(1):29–55, DOI 10.1137/20M1373190
38. Sun S, Nocedal J (2023) A trust region method for noisy unconstrained optimization. *Mathematical Programming* 202(1):445–472, DOI 10.1007/s10107-023-01941-9
39. Ueda K, Yamashita N (2010) Convergence Properties of the Regularized Newton Method for the Unconstrained Nonconvex Optimization. *Applied Mathematics and Optimization* 62(1):27–46, DOI 10.1007/s00245-009-9094-9
40. Ueda K, Yamashita N (2014) A regularized Newton method without line search for unconstrained optimization. *Computational Optimization and Applications* 59(1):321–351, DOI 10.1007/s10589-014-9656-x
41. Virtanen P, Gommers R, Oliphant TE, Haberland M, Reddy T, Cournapeau D, Burovski E, Peterson P, Weckesser W, Bright J, van der Walt SJ, Brett M, Wilson J, Millman KJ, Mayorov N, Nelson ARJ, Jones E, Kern R, Larson E, Carey CJ, Polat I, Feng Y, Moore EW, VanderPlas J, Laxalde D, Perktold J, Cimrman R, Henriksen I, Quintero EA, Harris CR, Archibald AM, Ribeiro AH, Pedregosa F, van Mulbregt P, SciPy 10 Contributors (2020) SciPy 1.0: Fundamental algorithms for scientific computing in python. *Nature Methods* 17:261–272, DOI 10.1038/s41592-019-0686-2
42. Wang S, Fadili J, Ochs P (2025) Convergence rates of regularized quasi-Newton methods without strong convexity. DOI 10.48550/arXiv.2506.00521, [2506.00521](#)

- 
43. Ward R, Wu X, Bottou L (2020) AdaGrad stepsizes: Sharp convergence over nonconvex landscapes. *J Mach Learn Res* 21(1):219:9047–219:9076
  44. Xie Y, Byrd RH, Nocedal J (2020) Analysis of the BFGS method with errors. *SIAM Journal on Optimization* 30(1):182–209
  45. Yabe H, Ogasawara H, Yoshino M (2007) Local and superlinear convergence of quasi-Newton methods based on modified secant conditions. *Journal of Computational and Applied Mathematics* 205(1):617–632, DOI 10.1016/j.cam.2006.05.018
  46. Yuan G, Wei Z (2010) Convergence analysis of a modified BFGS method on convex minimizations. *Computational Optimization and Applications* 47(2):237–255, DOI 10.1007/s10589-008-9219-0
  47. Zhang H, Ni Q (2018) A new regularized quasi-Newton method for unconstrained optimization. *Optimization Letters* 12(7):1639–1658, DOI 10.1007/s11590-018-1236-z
  48. Zhang J, Xu C (2001) Properties and numerical performance of quasi-Newton methods with modified quasi-Newton equations. *Journal of Computational and Applied Mathematics* 137(2):269–278, DOI 10.1016/S0377-0427(00)00713-5
  49. Zhang JZ, Deng NY, Chen LH (1999) New Quasi-Newton Equation and Related Methods for Unconstrained Optimization. *Journal of Optimization Theory and Applications* 102(1):147–167, DOI 10.1023/A:1021898630001