



# Introduction to Data Mining

## Lecture7 Mining Frequent Patterns, Association and Correlations

Jun Huang

Anhui University of Technology

Spring 2018

[huangjun\\_cs@163.com](mailto:huangjun_cs@163.com)




# KDD Process

Data Mining-Core of Knowledge discovery process

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns





# Mining Frequent Patterns, Association and Correlations

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Basic Concepts
- Mining single-dimensional Boolean association rules
- Mining multilevel association rules
- Mining multidimensional association rules
- Summary



# Basic Concepts

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **What are patterns?**

- **Patterns:** A set of items, subsequences, or substructures that occur frequently together (or strongly correlated) in a data set
- **Patterns** represent intrinsic and important properties of datasets

- **Pattern discovery:** Uncovering patterns from massive data sets

- **Motivation examples:**

- What products were often purchased together?
- What are the subsequent purchases after buying an iPad?
- What code segments likely contain copy-and-paste bugs?
- What word sequences likely form phrases in this corpus?



# Pattern Discovery: Why Is It Important?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Finding **inherent regularities** in a data set
- **Foundation** for many essential data mining tasks
  - Association, correlation, and causality analysis
  - Mining sequential, structural (e.g., sub-graph) patterns
  - Pattern analysis in spatiotemporal, multimedia, time-series, and stream data
  - Classification: Discriminative pattern-based analysis
  - Cluster analysis: Pattern-based subspace clustering
- **Broad applications**
  - Basket data analysis
  - Cross-marketing
  - Catalog design
  - Sale campaign analysis
  - Web log (click stream) analysis
  - DNA sequence analysis



# Market Basket Analysis

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# What Is Association Rules Mining?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Association rules mining**

- Finding frequent patterns, associations among sets of items or objects in transaction databases, relational databases, and other information repositories

- **Examples**

- What products were often purchased together? —Beer and diapers?
- What DNA segments often occur together in DNA sequences?

- **Where does the data come from?**

- Supermarket transactions, membership cards, discount coupons, customer complaint calls



# Basic Concepts

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

Transaction-ID	Items bought
10	A,B,D
20	A,C,D
30	A,D,E
40	B,E,F
50	B,C,D,E,F

- **Item collection**  $X = \{x_1, \dots, x_m\}$ , e.g.,  $\{A, B, \dots, F\}$
- **Itemset**: a set of items,  $k$ -itemset
- **Transaction**  $T \subseteq X$ , each  $T$  associates a unique Tid and items bought by a customer
- **Rule** form  $\alpha \geq \beta, \alpha \subset X, \beta \subset X, \alpha \cap \beta = \emptyset$





# Basic Concepts

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Support**,  $s$ , probability that a transaction contains  $\alpha$  and  $\beta$ 
  - $\text{support}(\alpha \Rightarrow \beta) = P(\alpha \cap \beta)$
- Frequent itemset, occurrence greater than a **min\_support**
- Frequent itemset mining, find all the rules  $\alpha \geq \beta$  satisfying min\_support
- Let  $\text{supmin} = 50\%$ ,
- frequent Itemsets A:3, B:3, D:4, E:3, AD:3
- $\text{support}(A) = 3/5 = 60\%$ ,  $\text{support}(AD) = 3/5 = 60\%$





# Basic Concepts

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Support**,  $s$ , conditional probability that a transaction having  $\alpha$  also contains  $\beta$
- **Confidence**  $(\alpha \Rightarrow \beta) = P(\beta|\alpha) = \frac{P(\alpha \cap \beta)}{P(\alpha)}$
- Measure of rule interestingness
- Rules satisfy **min\_support** and **min\_confidence** are strong
- Let  $\text{supmin} = 50\%$ ,  $\text{confmin} = 50\%$ ,
- frequent itemsets  $A:3, B:3, D:4, E:3, AD:3$
- Association rules:  $\alpha \Rightarrow \beta$  (support, confidence)
  - $A \Rightarrow D$  (60%, 100%)
  - $D \Rightarrow A$  (60%, 75%)



# There Are Too Many Frequent Patterns

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- A long pattern contains a **combinatorial number of sub-patterns**
- How many frequent itemsets does the following TDB1 contain?
  - **TDB1**:  $T_1 : \{a_1, \dots, a_{50}\}; T_2 : \{a_1, \dots, a_{100}\}$
  - Assuming (absolute) minsup = 1
  - Let's have a try
  - **1-itemsets**:  
 $\{a_1\} : 2, \{a_2\} : 2, \dots, \{a_{50}\} : 2, \{a_{51}\} : 1, \dots, \{a_{100}\} : 1,$
  - **2-itemsets**:  $\{a_1, a_2\} : 2, \dots, \{a_1, a_{50}\} : 2, \{a_1, a_{51}\} : 1, \dots, \{a_{99}, a_{100}\} : 1,$
  - $\dots, \dots, \dots$
  - **99-itemsets**:  $\{a_1, a_2, \dots, a_{99}\} : 1, \dots, \{a_2, a_3, \dots, a_{100}\} : 1$
  - **100-itemset**:  $\{a_1, a_2, \dots, a_{100}\} : 1$
- The total number of frequent itemsets:  $2^{100} - 1$



# Expressing Patterns in Compressed Form

## Closed Patterns

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- How to handle such a challenge?
- Solution 1: **Closed patterns**: A pattern (itemset)  $X$  is closed if  $X$  is frequent, and there exists no super-pattern  $Y \supset X$ , with the same support as  $X$ 
  - Let Transaction DB TDB1:  
 $T_1 : \{a_1, \dots, a_{50}\}; T_2 : \{a_1, \dots, a_{100}\}$
  - Suppose minsup = 1. How many closed patterns does TDB1 contain?
    - Two:  $P_1 : "\{a_1, \dots, a_{50}\} : 2"; P_2 : "\{a_1, \dots, a_{100}\} : 1"$
- **Closed pattern** is a **lossless** compression of frequent patterns
  - Reduces the # of patterns but does not lose the support information!
  - You will still be able to say:  $"\{a_2, \dots, a_{40}\} : 2",$   
 $"\{a_5, a_{51}\} : 1"$



# Expressing Patterns in Compressed Form

## Max Patterns

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Solution 2: **Max-patterns**: A pattern  $X$  is a max-pattern if  $X$  is frequent and there exists no frequent super-pattern  $Y \supset X$
- Difference from close-patterns?
  - Do not care the real support of the sub-patterns of a max-pattern
  - Let Transaction DB TDB1:  
 $T_1 : \{a_1, \dots, a_{50}\}; T_2 : \{a_1, \dots, a_{100}\}$
  - Suppose minsup = 1. How many max-patterns does TDB1 contain?
    - One:  $P : \{\{a_1, \dots, a_{100}\} : 1\}$
- **Max-pattern is a lossy compression!**
  - We only know one pattern is frequent, e.g.,  $\{a_1, \dots, a_{40}\}$
  - But we do not know the real support of  $\{a_1, \dots, a_{40}\}, \dots$ , any more!
- Thus in many applications, **mining close-patterns is more desirable than mining max-patterns**



# Association Rule Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Boolean** vs. **quantitative** associations (based on the types of values handled)
  - **Boolean association rules**, only concern presence or absence of items,  $\text{buys}(x, \text{"SQLServer"})$  and  $\text{buys}(x, \text{"DMBook"}) \Rightarrow \text{buys}(x, \text{"DBMiner"}) [0.2\%, 60\%]$
  - **Quantitative association rules**, concern quantitative attributes,  $\text{age}(x, \text{"30...39"})$  and  $\text{income}(x, \text{"42...48K"}) \Rightarrow \text{buys}(x, \text{"HD TV"}) [1\%, 75\%]$
- **Single level** vs. **multiple-level** analysis (based on the levels of abstraction involved)
  - $\text{age}(x, \text{"30...39"}) \Rightarrow \text{buys}(x, \text{"laptop computer"})$
  - $\text{age}(x, \text{"30...39"}) \Rightarrow \text{buys}(x, \text{"computer"})$
- **Single dimension** vs. **multiple dimensional** associations (based on dimensions involved)
  - $\text{buys}(X, \text{"milk"}) \Rightarrow \text{buys}(X, \text{"bread"})$
  - $\text{age}(X, \text{"19-25"})$  and  $\text{occupation}(X, \text{"student"}) \Rightarrow \text{buys}(X, \text{"coke"})$



# Mining Frequent Patterns, Association and Correlations

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Basic Concepts
- Mining single-dimensional Boolean association rules
- Mining multilevel association rules
- Mining multidimensional association rules
- Summary



# Handling Exponential Complexity

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Given  $n$  transactions and  $m$  different items:
  - Number of possible association rules:  $O(2^m)$
  - Computation complexity:  $O(nm2^m)$
- Apriori Principle
  - Collect single item counts, find large items
  - Find candidate pairs, count them  $\Rightarrow$  large pairs of items
  - Find candidate triplets, count them  $\Rightarrow$  large triplets of items, And so on...
  - **Guiding Principle:** Every subset of a frequent itemset has to be frequent
    - Used for pruning many candidates





# Apriori: A Candidate Generation and Test Approach

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Apriori uses prior knowledge of frequent itemsets
- Iterative approach, level-wise search
- The Apriori property (downward closure property, anti-monotone) of frequent patterns
  - **Any subset of a frequent itemset must be frequent**
  - **If any itemset is infrequent, its superset should not be generated/tested**
  - If  $\{\text{beer, diaper, nuts}\}$  is frequent, so is  $\{\text{beer, diaper}\}$ , every transaction having beer, diaper, nuts also contains beer, diaper
  - If  $\{\text{beer, diaper}\}$  is infrequent,  $\{\text{beer, diaper, nut}\}$  cannot be frequent at all



# Apriori: A Candidate Generation and Test Approach

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Apriori Method:**

- ➊ Initially, scan DB once to get frequent 1-itemset
- ➋ Generate length  $(k + 1)$  candidate itemsets from length  $k$  frequent itemsets
- ➌ Test the candidates against DB
- ➍ Terminate when no frequent or candidate set can be generated



# Example of Apriori Algorithm

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Example of Apriori Algorithm

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Example of Apriori Algorithm

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Example of Apriori Algorithm

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Apriori Algorithm

## Pseudo-code

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- ❶  $C_k$ : Candidate itemset of size  $k$
- ❷  $L_k$ : frequent itemset of size  $k$
- ❸ **Input**: Database  $D$ , **min\_support**
- ❹ **Output**: frequent itemsets  $L$
- ❺  $L_1 = \{\text{frequent single items from } D\};$
- ❻ **for** ( $k = 2; L_{k-1} \neq \emptyset; k++$ ) **do**
- ❼  $C_k = \text{candidates generated from } L_{k-1};$
- ❽ **for each** transaction  $t \in D$  **do**
- ❾     increment the count of all candidates in  $C_k$  which are contained in  $t$
- ❿ **end**
- ⓫  $L_k = \text{candidates in } C_k \text{ with } \text{min\_support}$
- ⓬ **end**
- ⓭ **return**  $L = \cup_k L_k;$



# How to Generate Candidates?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- How to generate candidates?

- Step 1:** self-joining  $L_k$
- Step 2:** pruning

- Example

- $L_3 = \{abc, abd, acd, ace, bcd\}$
- Self-joining:**  $L_3 \bowtie L_3$ 
  - $abc$  and  $abd \rightarrow abcd$ ,  $acd$  and  $ace \rightarrow acde$
- Pruning:**
  - $acde$  is pruned because  $ade$  is not in  $L_3$
- $C_4 = \{abcd\}$





# How to Generate Candidates?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- ① Suppose the items in  $L_{k-1}$  are listed in order
- ② **Step 1: self-joining**  $L_{k-1}$
- ③ **for** each itemset  $l_1 \in L_{k-1}$
- ④   **for** each itemset  $l_2 \in L_{k-1}$
- ⑤     **if** ( $l_1[1] = l_2[1]$ ) and ( $l_1[2] = l_2[2]$ ) and  $\dots$  and
- ⑥       ( $l_1[k-2] = l_2[k-2]$ ) **then**
- ⑦        $c = l_1 \text{ join } l_2$
- ⑧       pruning ( $c$ )
- ⑨   **end**
- ⑩ **end**
- ⑪ **Step 2: pruning**
- ⑫ **forall** ( $k-1$ )-subsets  $s$  of  $c$  **do**
- ⑬   **if** ( $s$  is not in  $L_{k-1}$ ) then delete  $c$



# How to Count Supports of Candidates?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Why counting supports of candidates a problem?**
- The total number of candidates can be very huge
- One transaction may contain many candidates
- **Method:**
- Candidate itemsets are stored in a hash-tree
- Leaf node of hash-tree contains a list of itemsets and counts
- Interior node contains a hash table



# Exercise

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- A database has 9 transactions. Let  $\text{min\_sup} = 20\%$ . Please present all the candidates and frequent itemsets at each iteration and frequent itemsets at each iteration.

TID	List of items_IDs
T100	I1,I2,I5
T200	I2,I4
T300	I2,I3
T400	I1,I2,I4
T500	I1,I3
T600	I2,I3
T700	I1,I3
T800	I1,I2,I3,I5
T900	I1,I2,I3



# Challenges of Frequent Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Challenges**
  - Multiple scans of transaction database
  - Huge number of candidates
  - Tedious workload of support counting for candidates
- **Improving Apriori**
  - Reduce passes of transaction database scans
  - Shrink number of candidates
  - Facilitate support counting of candidates



# Apriori: Improvements and Alternatives

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Reduce passes of transaction database scans**
  - Partitioning (e.g., Savasere, et al., 1995)
  - Dynamic itemset counting (Brin, et al., 1997)
- **Shrink the number of candidates**
  - Hashing (e.g., DHP: Park, et al., 1995)
  - Pruning by support lower bounding (e.g., Bayardo 1998)
  - Sampling (e.g., Toivonen, 1996)
- **Exploring special data structures**
  - Tree projection (Agarwal, et al., 2001)
  - H-miner (Pei, et al., 2001)
  - Hypercube decomposition (e.g., LCM: Uno, et al., 2004)



# Partition: Scan Database Only Twice

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- A. Savasere, E. Omiecinski, and S. Navathe. **An efficient algorithm for mining association in large databases.** In VLDB' 95.
- Partitioning technique
  - Partition the data into  $N$  small partitions
  - **Phase 1:** find local frequent itemsets on each data partition. Record all local frequent itemsets.
  - **Phase 2:** Integrate all local frequent itemsets, scan database, find global frequent itemsets.
- **Correctness:** Any itemset that is potentially frequent in DB must be frequent in at least one of the partitions



# Partition: Scan Database Only Twice

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Each partition can be fit into memory
- Scan database only **twice**! Reduce I/O cost!
- Execution time scales linearly
- Good for very large-scale database
- Applicable to **parallel/distributed** computing systems
  - Each processor performs FIM on its local data
  - Central server aggregates local frequent itemsets, broadcast potential global itemsets
  - Each processor scans local data to count the frequency
  - Central server aggregates the counts, find the global itemsets



# Reduce the Number of Candidates

## DHP: Direct Hashing and Pruning

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- J. Park, M. Chen, and P. Yu. **An effective hash-based algorithm for mining association rules.** In SIGMOD' 95
- Hash-based technique
  - When scanning transactions to generate frequent  $k$ -itemsets,  $L_k$ , generate all  $(k+1)$ -itemsets for each transaction
  - Hash all  $(k+1)$ -itemsets into buckets, increase bucket count
  - If a  $(k+1)$ -itemset bucket count is below **min\_sup**, it must be removed from  $(k+1)$  candidate itemsets,  $C_{k+1}$
- **Correctness:** A  $k$ -itemset whose corresponding hashing bucket count is below the threshold cannot be frequent





# Reduce the Number of Candidates

DHP: Direct Hashing and Pruning

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Example: At the 1st scan of TDB, count 1-itemset, and Hash 2-itemsets in the transaction to its bucket
  - $\{ab, ad, ce\}$
  - $\{bd, be, de\}$
  - ...
- At the end of the first scan,
- if  $\text{minsup} = 80$ , remove  $ab, ad, ce$ , since  $\text{count}\{ab, ad, ce\} < 80$

Itemsets	Count
$\{ab, ad, ce\}$	35
$\{bd, be, de\}$	298
.....	...
$\{yz, qs, wt\}$	58

**Hash Table**



# Bottleneck of Frequent-pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Multiple database scans are costly
- Mining long patterns needs many passes of scanning and generates lots of candidates
- To find frequent itemset  $i_1, i_2, \dots, i_{100}$ 
  - # of scans: 100
  - # of Candidates:  
 $(100^1) + (100^2) + \dots + (100^{100}) = 2^{100} - 1 \approx 1.27 * 10^{30}$
- Bottleneck: candidate generation and test
- Can we avoid candidate generation?



# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- ➊ **Scan DB once**, find frequent 1-itemset (single item pattern)
- ➋ Sort frequent items in frequency descending order  $L$
- ➌ Create the root of the tree, labeled with “null”
- ➍ **Scan DB again**, sort each transaction in  $L$  order, a branch is created for each transaction
  - Increment the count of each node along a common prefix by 1
  - Create nodes for the items following the prefix
- ➎ Build a header table, connect each item point in the tree



# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

TID	Items in the Transaction	Ordered, frequent itemlist
100	$\{f, a, c, d, g, i, m, p\}$	$f, c, a, m, p$
200	$\{a, b, c, f, l, m, o\}$	$f, c, a, b, m$
300	$\{b, f, h, j, o, w\}$	$f, b$
400	$\{b, c, k, s, p\}$	$c, b, p$
500	$\{a, f, c, e, l, p, m, n\}$	$f, c, a, m, p$

- Let  $\text{min\_support} = 3$
- 1-itemset:  $f : 4, a : 3, c : 4, b : 3, m : 3, p : 3$
- $L = f \rightarrow c \rightarrow a \rightarrow b \rightarrow m \rightarrow p$



# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

After inserting the 1<sup>st</sup> frequent  
Itemlist: "*f, c, a, m, p*"





# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts  
Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

After inserting the 2<sup>nd</sup> frequent  
itemlist “*f, c, a, b, m*”





# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

After inserting all the  
frequent itemlists





# Construct FP-Tree from a Transaction Database

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules


Mining  
multidimensional  
association rules

Sequential Patterns

Summary

**min\_support = 3**

Item	Frequency	Header
f	4	
c	4	
a	3	
b	3	
m	3	
p	3	



**Conditional database of each pattern**

<u>Item</u>	<u>Conditional database</u>
<i>c</i>	<i>f:3</i>
<i>a</i>	<i>fc:3</i>
<i>b</i>	<i>fca:1, f:1, c:1</i>
<i>m</i>	<i>fca:2, fcab:1</i>
<i>p</i>	<i>fcam:2, cb:1</i>





# Benefits of the FP-tree Structure

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Completeness**

- Preserve complete information for frequent pattern mining
- Never break a long pattern of any transaction

- **Compactness**

- Reduce irrelevant info—infrequent items are gone
- Items in frequency descending order: the more frequently occurring, the more likely to be shared
- Never be larger than the original database



# Mining Frequent Patterns With FP-trees

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- ① procedure **FP\_growth**(Tree,  $\alpha$ )
- ② **if** Tree contains a single path  $P$  then
- ③   **for each** combination (denoted as  $\beta$ ) of the nodes in the path  $P$
- ④     generate pattern  $\beta \cup \alpha$  with support\_count = minimum support count of nodes in  $\beta$
- ⑤ **else**
- ⑥   **for each**  $\alpha_i$  in the header of Tree {
- ⑦     generate pattern  $\beta = \alpha_i \cup \alpha$  with support\_count =  $\alpha_i$ .support\_count
- ⑧     construct  $\beta$ 's conditional pattern base and then  $\beta$ 's conditional FP\_tree Tree $_{\beta}$
- ⑨     **if** Tree $_{\beta}$  **then**
- ⑩       call **FP\_growth**(Tree $_{\beta}$ ,  $\beta$ )}



# Exercise

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- A database has 9 transactions. Let  $\text{min\_sup} = 20\%$ . Please present all the candidates and frequent itemsets at each iteration and frequent itemsets at each iteration.

TID	List of items_IDs
T100	I1,I2,I5
T200	I2,I4
T300	I2,I3
T400	I1,I2,I4
T500	I1,I3
T600	I2,I3
T700	I1,I3
T800	I1,I2,I3,I5
T900	I1,I2,I3



# Solution

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

TID	List of items_IDs
T100	I1,I2,I5
T200	I2,I4
T300	I2,I3
T400	I1,I2,I4
T500	I1,I3
T600	I2,I3
T700	I1,I3
T800	I1,I2,I3,I5
T900	I1,I2,I3





# Solution

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

item	conditional pattern base	conditional FP-tree	frequent patterns generated
I5	$\{\{I2, I1: 1\}, \{I2, I1, I3: 1\}\}$	$\langle I2: 2, I1: 2 \rangle$	$\{I2, I5: 2\}, \{I1, I5: 2\}, \{I2, I1, I5: 2\}$
I4	$\{\{I2, I1: 1\}, \{I2: 1\}\}$	$\langle I2: 2 \rangle$	$\{I2, I4: 2\}$
I3	$\{\{I2, I1: 2\}, \{I2: 2\}, \{I1: 2\}\}$	$\langle I2: 4, I1: 2 \rangle, \langle I1: 2 \rangle$	$\{I2, I3: 4\}, \{I1, I3: 4\}, \{I2, I1, I3: 2\}$
I1	$\{\{I2: 4\}\}$	$\langle I2: 4 \rangle$	$\{I2, I1: 4\}$





# FP Tree vs. Apriori: Scalability With the Support Threshold

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Why Is FP-Growth the Winner?

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Divide-and-conquer:**

- Decompose both the mining task and DB according to the frequent patterns obtained so far
- Focus searching on smaller databases

- **Other factors**

- No candidate generation, no candidate test
- Compressed database: FP-tree structure
- Two scans of entire database
- Basic ops—counting local freq items and building sub FP-tree, no pattern search and matching



# Scaling FP-growth by Item-Based Data Projection

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- What if FP-tree cannot fit in memory? —Do not construct FP-tree
  - “Project” the database based on frequent single items
  - Construct & mine FP-tree for each projected DB
- **Parallel projection** vs. **partition projection**
  - Parallel projection: Project the DB on each frequent item
    - Space costly, all partitions can be processed in parallel
  - Partition projection: Partition the DB in order
    - Passing the unprocessed parts to subsequent partitions





# Scaling FP-growth by Item-Based Data Projection

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Parallel projection:** Project the DB on each frequent item
  - Space costly, all partitions can be processed in parallel





# Scaling FP-growth by Item-Based Data Projection

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree


Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Partition projection**: Partition the DB in order
  - Passing the unprocessed parts to subsequent partitions





# Exploring Vertical Data Format: ECLAT

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

**A transaction DB in Horizontal  
Data Format**

Tid	Itemset
10	a, c, d, e
20	a, b, e
30	b, c, e

**The transaction DB in Vertical  
Data Format**

Item	TidList
a	10, 20
b	20, 30
c	10, 30
d	10
e	10, 20, 30



# Exploring Vertical Data Format: ECLAT

## ECLAT (Equivalence Class Transformation)

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- ECLAT: A depth-first search algorithm using set intersection [Zaki et al. KDD' 97]
- **Tid-List**: List of transaction-ids containing an itemset
- **Vertical format**:  $t(e) = \{T_{10}, T_{20}, T_{30}\};$   
 $t(a) = \{T_{10}, T_{20}\}; t(ae) = \{T_{10}, T_{20}\}$
- **Properties of Tid-Lists**
  - $t(X) = t(Y)$ :  $X$  and  $Y$  always happen together (e.g.,  $t(ac) = t(d)$ )
  - $t(X) \subset t(Y)$ : transaction having  $X$  always has  $Y$  (e.g.,  $t(ac) \subset t(ce)$ )
- Deriving frequent patterns based on vertical intersections
- Using **diffset** to accelerate mining
  - Only keep track of differences of tids
  - $t(e) = \{T_{10}, T_{20}, T_{30}\}, t(ce) = \{T_{10}, T_{30}\} \rightarrow$   
 $Diffset(ce, e) = \{T_{20}\}$



# Mining Frequent Patterns, Association and Correlations

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Basic Concepts
- Mining single-dimensional Boolean association rules
- Mining multilevel association rules
- Mining multidimensional association rules
- Summary



# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Association rules at high concept levels may represent common sense knowledge
- Hard to find association rules at low concept level
- Items at the lower level usually have lower support, less than  $\text{min\_support}$  threshold
- Mining association rules at multiple levels of abstraction
- Example: sales in AllElectronics store computer sector



# Example

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary


## • Uniform support

- Top-down, level-wise
- Use uniform minimum support for each level
- Perform Apriori at each level
- Optimization: if an ancestor is infrequent, the search on the descendants can be avoided

## uniform support

Level 1  
 $\text{min\_sup} = 5\%$

Level 2  
 $\text{min\_sup} = 5\%$







# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules


Mining  
multidimensional  
association rules

Sequential Patterns


Summary

uniform support

Level 1  
 $\text{min\_sup} = 5\%$



Level 2  
 $\text{min\_sup} = 5\%$



## Drawbacks

- Miss interesting associations with too high threshold
- Generate too many uninteresting rules with too low threshold



# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules


Sequential Patterns

Summary

- **Reduced support**

- Top-down, level-wise
- Each concept level has its own minimum support threshold
- The lower level, the smaller threshold
- Perform Apriori at each level

reduced support





# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules


Sequential Patterns

Summary

## Reduced support

- Optimization – level-cross filtering by single item
- An item at the  $i$ th concept level is examined iff its parent concept at the  $(i - 1)$ th level is frequent
- If a concept is infrequent, its descendents are pruned from the database
- Drawbacks
  - Miss associations at low level items which are frequent based on a reduced  $\text{min\_support}$ , but whose ancestors do not satisfy  $\text{min\_support}$

reduced support





# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules


Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Reduced support**

- Optimization – level-cross filtering by k-itemset
  - Only the children of frequent k-itemsets are examined
  - Drawback: many valuable patterns may be filtered out





# Mining multilevel association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Reduced support**

- Optimization – Controlled level-cross filtering by single item

- next level min sup < level passage threshold < min sup
- Allow the children of items that do not satisfy the min\_sup to be examined if they satisfy the level passage threshold

**Level 1**

**min\_sup = 12%**

**Level\_passage\_sup = 8%**

**Milk**  
**[support = 10 %]**

**Level 2**

**min\_sup = 3%**

**2% Milk**  
**[support = 6 %]**

**Skim Milk**  
**[support = 4 %]**



# Multi-level Association: Redundancy Filtering

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Some rules may be redundant due to "ancestor" relationships between items
- Example
  - $\text{buys}(X, \text{"Laptop computer"}) \Rightarrow \text{buys}(X, \text{"HP printer"})$   
[support = 8%, confidence = 70%]
  - $\text{buys}(X, \text{"IBM laptop computer"}) \Rightarrow \text{buys}(X, \text{"HP printer"})$   
[support = 2%, confidence = 72%]
- We say the first rule is an ancestor of the second rule
- A rule is redundant if its support is close to the "expected" value, based on the rule's ancestor



# Mining Frequent Patterns, Association and Correlations

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Basic Concepts
- Mining single-dimensional Boolean association rules
- Mining multilevel association rules
- Mining multidimensional association rules
- Summary



# Mining multidimensional association rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Single-dimensional rules:  
 $\text{buys}(X, \text{"milk"}) \Rightarrow \text{buys}(X, \text{"bread"})$
- Multi-dimensional rules:  $\geq 2$  dimensions or predicates
  - Inter-dimension assoc. rules (no repeated predicates)  
 $\text{age}(X, \text{"19-25"}) \text{ and } \text{occupation}(X, \text{"student"}) \Rightarrow \text{buys}(X, \text{"coke"})$
  - hybrid-dimension assoc. rules (repeated predicates)  
 $\text{age}(X, \text{"19-25"}) \text{ and } \text{buys}(X, \text{"popcorn"}) \Rightarrow \text{buys}(X, \text{"coke"})$
- **Categorical Attributes**: finite number of possible values, no ordering among values
- **Quantitative Attributes**: numeric, implicit ordering among values —discretization, clustering approaches





# Mining Quantitative Associations

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

Techniques can be used to **categorize numerical attributes**

- **Static discretization** based on predefined concept hierarchies
- **Dynamic discretization** based on data distribution
- **Clustering**: Distance-based association
  - one dimensional clustering then association



# Multidimensional Association Rules and Static Discretization of Quantitative Attributes

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Discretized prior to mining using **concept hierarchy**
- Numeric values are **replaced by ranges**
- In relational database, finding all frequent  $k$ -predicate sets will require  $k$  or  $k + 1$  table scans
- **Data cube** is well suited for mining
  - The cells of a  $n$ -dimensional: cuboid correspond to the dimensions
  - Mining from data cubes can be much faster



# Multidimensional Association Rules and Static Discretization of Quantitative Attributes

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules


FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary





# Quantitative Association Rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Numeric attributes are dynamically discretized
  - Such that the confidence or compactness of the rules mined is maximized
- 2-D quantitative association rules:  
 $A_{quan1} \text{ and } A_{quan2} \Rightarrow A_{cat}$
- Association rule clustering system (ARCS)
  - Binning: 2-D grid, manageable size
  - Finding frequent predicate sets: scan the database, count the support for each grid cell
  - Clustering the rules: cluster adjacent cells to form a rule



# Quantitative Association Rules

Example: age and income  $\Rightarrow$  buy HD TV

Introduction  
to Data  
Mining

Jun Huang


Mining  
Frequent  
Patterns

Basic Concepts  
Boolean Association  
Rules

FP-Tree  
Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns  
Summary





# Quantitative Association Rules

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- **Example:**

- $\text{age}(X, "34") \text{ and } \text{income}(X, "31-40K") \Rightarrow \text{buys}(X, "HD \text{ TV} ")$
- $\text{age}(X, "35") \text{ and } \text{income}(X, "31-40K") \Rightarrow \text{buys}(X, "HD \text{ TV} ")$
- $\text{age}(X, "34") \text{ and } \text{income}(X, "41-50K") \Rightarrow \text{buys}(X, "HD \text{ TV} ")$
- $\text{age}(X, "35") \text{ and } \text{income}(X, "41-50K") \Rightarrow \text{buys}(X, "HD \text{ TV} ")$
- $\Rightarrow \text{age}(X, "34-35") \text{ and } \text{income}(X, "31-50K") \Rightarrow \text{buys}(X, "HD \text{ TV} ")$



# Interestingness Measure: Correlations (Lift)

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- $\text{play basketball} \Rightarrow \text{eat cereal [40\%, 66.7\%]}$  is misleading
- The overall percentage of students eating cereal is 75% > 66.7%.
- Measure of dependent/correlated events:

$$\text{lift}(A, B) = \frac{P(A \cap B)}{P(A)P(B)}$$

- $\text{lift}(A, B) = 1$ :  $A$  and  $B$  are independent
- $\text{lift}(A, B) > 1$ :  $A$  and  $B$  are positive correlated
- $\text{lift}(A, B) < 1$ :  $A$  and  $B$  are negative correlated



# Interestingness Measure: Correlations (Lift)

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

	Basketball	Not basketball	Sum (row)
Cereal	2000	1750	3750
Not Cereal	1000	250	1250
Sum (col.)	3000	2000	5000

- $lift(A, B) = \frac{2000/5000}{(3000/5000)*(3750/5000)} = 0.89$
- $lift(A, \bar{B}) = \frac{1000/5000}{(3000/5000)*(1250/5000)} = 1.33$
- $A \Rightarrow B$  [support, confidence, correlation]





# Sequence Databases & Sequential Patterns

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Sequential pattern mining has broad applications
  - Customer shopping sequences
  - Purchase a laptop first, then a digital camera, and then a smartphone, within 6 months
  - Medical treatments, natural disasters (e.g., earthquakes), science & engineering processes, stocks and markets, ...
  - Weblog click streams, calling patterns, ...
  - Software engineering: Program execution sequences, ...
  - Biological sequences: DNA, protein, ...
- Transaction DB, sequence DB vs. time-series DB
- Gapped vs. non-gapped sequential patterns
  - Shopping sequences, clicking streams vs. biological sequences



# Sequential Pattern and Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Sequential pattern mining: Given a set of sequences, find the complete set of frequent subsequences (i.e., satisfying the  $\text{min\_sup}$  threshold)

A sequence database

SID	Sequence
10	$\langle a(\underline{ab}c)(\underline{ac})d(cf) \rangle$
20	$\langle (ad)c(bc)(ae) \rangle$
30	$\langle (ef)(\underline{ab})(df)\underline{cb} \rangle$
40	$\langle eg(af)cbc \rangle$

- A sequence:  $\langle (ef)(ab)(df)cb \rangle$
- An element may contain a set of items (also called events)
- Items within an element are unordered and we list them alphabetically
- $\langle a(bc)dc \rangle$  is a subsequence of  $\langle a(abc)(ac)d(cf) \rangle$
- Given support threshold  $\text{min\_sup} = 2$ ,  $\langle (ab)c \rangle$  is a sequential pattern



# Sequential Pattern and Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Algorithm requirement: Efficient, scalable, finding complete set, incorporating various kinds of user-specific constraints
- The Apriori property still holds: If a subsequence  $s_1$  is infrequent, none of  $s_1$ 's super-sequences can be frequent
- Representative algorithms
  - GSP (Generalized Sequential Patterns): Srikant & Agrawal @ EDBT' 96)
  - Vertical format-based mining: SPADE (Zaki@Machine Learning' 00)
  - Pattern-growth methods: PrefixSpan (Pei, et al. @TKDE' 04)
- Mining closed sequential patterns: CloSpan (Yan, et al. @SDM' 03)
- Constraint-based sequential pattern mining (to be covered in the constraint mining section)



# GSP: Apriori-Based Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Initial candidates: All 8-singleton sequences
- $\langle a \rangle, \langle b \rangle, \langle c \rangle, \langle d \rangle, \langle e \rangle, \langle f \rangle, \langle g \rangle, \langle h \rangle$
- Scan DB once, count support for each candidate
- Generate length-2 candidate sequences
- Repeat (for each level (i.e., length- $k$ ))
  - Scan DB to find length- $k$  frequent sequences
  - Generate length- $(k+1)$  candidate sequences from length- $k$  frequent sequences using Apriori
  - set  $k = k + 1$
- Until no frequent sequence or no candidate can be found



# GSP: Apriori-Based Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

## Algorithm GSP( $\mathcal{S}$ )

```
1  $C_1 \leftarrow \text{init-pass}(\mathcal{S})$ 
2  $F_1 \leftarrow \{ \langle \{f\} \rangle \mid f \in C_1, f.\text{count}/n \geq \text{min\_sup} \}$ 
3 for ( $k = 2$ ;  $F_{k-1} \neq \emptyset$ ;  $k++$ ) do
4    $C_k \leftarrow \text{candidate-gen-SPM}(F_{k-1})$ 
5   for each data sequence  $s \in \mathcal{S}$  do
6     for each candidate  $c \in C_k$  do
7       if  $c$  is contained in  $s$  then
8          $c.\text{count}++$ ;
9       end
10    end
11     $F_k \leftarrow \{ c \in C_k \mid c.\text{count}/n \geq \text{min\_sup} \}$ 
12  end
13  return  $F \leftarrow \cup_k F_k$ 
14 end
```



# GSP: Apriori-Based Sequential Pattern Mining

## Function candidate-gen-SPM( $F_{k-1}$ )

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- 1 **Joint step.** Candidate sequences are generated by joining  $F_{k-1}$  with  $F_{k-1}$ . A sequence  $s_1$  joins with  $s_2$  if the subsequence obtained by dropping the first item of  $s_1$  is the same as the subsequence obtained by dropping the last item of  $s_2$ . The candidate sequence generated by joining  $s_1$  with  $s_2$  is the sequence  $s_1$  extended with the last item in  $s_2$ . There are two cases:

- the added item forms a separate element if it was a separate element in  $s_2$ , and is appended at the end of  $s_1$  in the merged sequence
- the added item is part of the last element of  $s_1$  in the merged sequence

When joining  $F_1$  with  $F_1$ , we need to add the item in  $s_2$  both as part of an itemset and as a separate element. That is, joining  $\langle \{x\} \rangle$  with  $\langle \{y\} \rangle$  gives us both  $\langle \{x, y\} \rangle$  and  $\langle \{x\}, \{y\} \rangle$ . Note that  $x$  and  $y$  in  $\{x, y\}$  are ordered.

- 2 **Prune step.** A candidate sequence is pruned if any one of its  $(k-1)$ -subsequences is infrequent (without minimum support)



# GSP: Apriori-Based Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

$\min\_sup = 2$

Cand.	sup
<a>	3
<b>	5
<c>	4
<d>	3
<e>	3
<f>	2
<del>&lt;g&gt;</del>	1
<del>&lt;h&gt;</del>	1

	<a>	<b>	<c>	<d>	<e>	<f>
<a>	<aa>	<ab>	<ac>	<ad>	<ae>	<af>
<b>	<ba>	<bb>	<bc>	<bd>	<be>	<bf>
<c>	<ca>	<cb>	<cc>	<cd>	<ce>	<cf>
<d>	<da>	<db>	<dc>	<dd>	<de>	<df>
<e>	<ea>	<eb>	<ec>	<ed>	<ee>	<ef>
<f>	<fa>	<fb>	<fc>	<fd>	<fe>	<ff>

	<a>	<b>	<c>	<d>	<e>	<f>
<a>		<(ab)>	<(ac)>	<(ad)>	<(ae)>	<(af)>
<b>			<(bc)>	<(bd)>	<(be)>	<(bf)>
<c>				<(cd)>	<(ce)>	<(cf)>
<d>					<(de)>	<(df)>
<e>						<(ef)>
<f>						



# GSP: Apriori-Based Sequential Pattern Mining

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

SID	Sequence
10	<(bd)cb(ac)>
20	<(bf)(ce)b(fg)>
30	<(ah)(bf)abf>
40	<(be)(ce)d>
50	<a(bd)bc(bade)>


5<sup>th</sup> scan: 1 cand. 1 length-5 seq. pat.

4<sup>th</sup> scan: 8 cand. 7 length-4 seq. pat.

3<sup>rd</sup> scan: 46 cand. 20 length-3 seq. pat. 20  
cand. not in DB at all

2<sup>nd</sup> scan: 51 cand. 19 length-2 seq. pat.  
10 cand. not in DB at all

1<sup>st</sup> scan: 8 cand. 6 length-1 seq. pat.







# Summary

Introduction  
to Data  
Mining

Jun Huang

Mining  
Frequent  
Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- Frequent pattern mining —an important task in data mining
- Scalable frequent pattern mining methods
  - Apriori (Candidate generation & test)
  - Partition, DIC, DHP, etc.
  - Projection-based (FP-growth)
- Mining a variety of rules and interesting pattern



# Readings

## Introduction to Data Mining

Jun Huang

## Mining Frequent Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- R. Agrawal, T. Imielinski, and A. Swami, “Mining association rules between sets of items in large databases” , in Proc. of SIGMOD’93
- R. J. Bayardo, “Efficiently mining long patterns from databases” , in Proc. of SIGMOD’98
- N. Pasquier, Y. Bastide, R. Taouil, and L. Lakhal, “Discovering frequent closed itemsets for association rules” , in Proc. of ICDT’99
- J. Han, H. Cheng, D. Xin, and X. Yan, “Frequent Pattern Mining: Current Status and Future Directions” , Data Mining and Knowledge Discovery, 15(1): 55-86, 2007
- R. Agrawal and R. Srikant, “Fast algorithms for mining association rules” , VLDB’94
- A. Savasere, E. Omiecinski, and S. Navathe, “An efficient algorithm for mining association rules in large databases” , VLDB’95
- J. S. Park, M. S. Chen, and P. S. Yu, “An effective hash-based algorithm for mining association rules” , SIGMOD’95



# Readings

## Introduction to Data Mining

Jun Huang

## Mining Frequent Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- S. Sarawagi, S. Thomas, and R. Agrawal, “Integrating association rule mining with relational database systems: Alternatives and implications” , SIGMOD’98
- M. J. Zaki, S. Parthasarathy, M. Ogihara, and W. Li, “Parallel algorithm for discovery of association rules” , Data Mining and Knowledge Discovery, 1997
- J. Han, J. Pei, and Y. Yin, “Mining frequent patterns without candidate generation” , SIGMOD’ 00
- M. J. Zaki and Hsiao, “CHARM: An Efficient Algorithm for Closed Itemset Mining” , SDM’02
- J. Wang, J. Han, and J. Pei, “CLOSET+: Searching for the Best Strategies for Mining Frequent Closed Itemsets” , KDD’03
- C. C. Aggarwal, M.A., Bhuiyan, M. A. Hasan, “Frequent Pattern Mining Algorithms: A Survey” , in Aggarwal and Han (eds.): Frequent Pattern Mining, Springer, 2014



# Readings

## Introduction to Data Mining

Jun Huang

## Mining Frequent Patterns

Basic Concepts

Boolean Association  
Rules

FP-Tree

Mining multilevel  
association rules

Mining  
multidimensional  
association rules

Sequential Patterns

Summary

- C. C. Aggarwal and P. S. Yu. A New Framework for Itemset Generation. PODS' 98
- S. Brin, R. Motwani, and C. Silverstein. Beyond market basket: Generalizing association rules to correlations. SIGMOD'97
- M. Klemettinen, H. Mannila, P. Ronkainen, H. Toivonen, and A. I. Verkamo. Finding interesting rules from large sets of discovered association rules. CIKM'94
- E. Omiecinski. Alternative Interest Measures for Mining Associations. TKDE' 03
- P.-N. Tan, V. Kumar, and J. Srivastava. Selecting the Right Interestingness Measure for Association Patterns. KDD'02
- T. Wu, Y. Chen and J. Han, Re-Examination of Interestingness Measures in Pattern Mining: A Unified Framework, Data Mining and Knowledge Discovery, 21(3):371-397, 2010