

Macrolop Specification

Temirkhan Myrzamadi (a.k.a. Hirrolot)

November 17, 2020

Contents

1	EBNF Grammar	2
2	Reduction Semantics	2

1 EBNF Grammar

```
<eval> ::= "MACROLOP_EVAL(" { <term> }* ")" ;

<term> ::= "call(" <op> "," { <term> }* ")"
        | "v(" <preprocessor-token-list> ")" ;

<op>    ::= <ident> | { <term> }+ ;
```

Figure 1: Grammar rules

A metaprogram in Macrolop consists of a (possibly empty) sequence of terms, each of which is either a macro call or just a value.

Notes:

- The grammar above describes metaprograms already expanded by the C preprocessor, except for `MACROLOP_EVAL`, `call`, and `v`.
- `call` accepts `op` either as an identifier or as a non-empty sequence of terms that reduces to an identifier.
- `call` accepts arguments without a separator.

2 Reduction Semantics

We define reduction semantics for Macrolop. First of all, take into consideration the following notation for sequences:

Notation 1 (Sequences). *A sequence has the form (x_1, \dots, x_n) . $()$ denotes the empty sequence. An element can be appended by comma: if $a = (1, 2, 3)$ and $b = 4$, then $a, b = (1, 2, 3, 4)$. *seq-extract* extracts elements from a sequence without a separator: $\text{seq-extract}((a, b, c)) = a \ b \ c$. *seq-comma-sep* extracts elements from a sequence separated by comma: $\text{seq-comma-sep}((a, b, c)) = a, b, c$.*

The abstract machine executes configurations of the form $\langle k; acc; control \rangle$:

- k is a continuation of the form $\langle k; acc; control \rangle$, where *control* include the `?` sign, which will be substituted with a result after a continuation is called. For example: let $k = \langle k'; (1, 2, 3); v(abc) ? \rangle$, then $k(v(ghi))$ is $\langle k'; (1, 2, 3); v(abc) \ v(ghi) \rangle$. A special continuation *halt* terminates the abstract machine with provided result.
- *acc* is an accumulator, a sequence of already computed results.
- *control* is a concrete sequence of terms upon which the abstract machine is operating right now. For example: `call(F00, v(123) v(456)) v(w 8) v(blah)`.

$(v) : \langle k; acc; v(\overline{tok}) \text{ term } \overline{term'} \rangle$	$\rightarrow_1 \langle k; acc, \overline{tok}; \text{term } \overline{term'} \rangle$
$(v\text{-end}) : \langle k; acc; v(\overline{tok}) \rangle$	$\rightarrow_1 k(\text{seq-extract}(acc, \overline{tok}))$
$(op) : \langle k; acc; call(\overline{term}, \overline{a}) \overline{term'} \rangle$	$\rightarrow_1 \langle \langle k; acc; call(?, \overline{a}) \overline{term'} \rangle; () ; \overline{term} \rangle$
$(args) : \langle k; acc; call(ident, \overline{a}) \overline{term} \rangle$	$\rightarrow_1 \langle \langle k; acc; ident(\text{seq-comma-sep}(?)) \overline{term} \rangle; () ; \overline{a} \rangle$
$(start) : MACROLOP_EVAL(\overline{term})$	$\rightarrow_1 \langle \text{halt}; () ; \overline{term} \rangle$

Figure 2: Computational rules

Notes:

- A body of a macro called using `call` must follow the grammar of Macrolop, otherwise it might result in a compilation error.