EXP NO: 4

CREATE UDF IN PIG

\$start-all.sh

```
hadoop@kali--

File Actions Edit View Help

(hadoop@kali)-[~]
$ start-all.sh

WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds.

WARNING: This is not a recommended production deployment configuration.

WARNING: Use CTRL-C to abort.

Starting namenodes on [localhost]

Starting natanodes

Starting secondary namenodes [kali]

Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true

2024-09-11 04:59:16,429 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable

Starting resourcemanager

Starting nodemanagers
```


\$ jps

```
(hadoop® kali)-[~]

$ jps
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true
14436 NodeManager
16772 Jps
13830 SecondaryNameNode
14311 ResourceManager
13597 DataNode
13471 NameNode
```

\$wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz \$

tar xvzf pig-0.16.0.tar.gz




\$nano ~/.bashrc

```
#PIG settings
export PIG_HOME=/home/hadoop/pig
export PATH=SPATH:SPIG_HOME/bin
export PIG_CLASSPATH=SPIG_HOME/conf:SHADOOP_HOME/etc/hadoop/
export PIG_CONF_DIR=SPIG_HOME/conf
#export JAVA_HOME=/usr/lib/jvm/java-8-openjdk-amd64
export PIG_CLASSPATH=SPIG_CONF_DIR:SPATH
#PIG setting ends
```

\$mv pig-0.16.0 pig

\$pig



\$cd DA-Lab \$mkdir exp4 \$cd exp4

\$nano sample.txt




\$nano demo_pig.pig



\$hdfs dfs -mkdir /exp4

\$hdfs dfs -copyFromLocal ~/DA-Lab/exp4/sample.txt /exp4

\$pig demo_pig.pig



\$nano uppercase udf.py

\$hdfs dfs -copyFromLocal ~/DA-Lab/exp4/uppercase udf.py /exp4

\$nano udf example.pig

```
File Actions Edit View Help

GNU nano 7.2

— Register the Python UDF script

REGISTER 'hdfs:///exp4/uppercase_udf.py' USING jython AS udf;

— Load some data
data = LOAD 'hdfs:///exp4/sample.txt' AS (text:chararray);


— Use the Python UDF


uppercased_data = FOREACH data GENERATE udf.uppercase(text) AS uppercase_text;

— Store the result

STORE uppercased_data INTO 'hdfs:///exp4/output';
```

\$pig -f udf_example.pig





\$hdfs dfs -cat /exp4/output/*

```
(hadoop® kali)-[~/hadoop/bin]
$ ./hdfs dfs -cat /exp4/output/*
Picked up _JAVA_OPTIONS: -Dawt.useSystemAAFontSettings=on -Dswing.aatext=true
2024-09-21 00:33:32,731 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform ...
1,JOHN
2,JANE
3,JOE
4,EMMA
```