AN AI-ENABLED INTELLIGENT STUDY ASSISTANT (AURALEARN) TO ENHANCE STUDENT LEARNING OUTCOMES

Project Group ID: R26-SE-022

A dissertation submitted in partial fulfillment of the requirements for the

B.Sc. (Hons) Degree in Information Technology

Specializing in Software Engineering

Research Group Components & Student Investigators:

I.H. Sonal Dilmith (IT22120120) — Hallucination-Controlled LLM-Based Tutor

T.G.K.G. Vijithapala (IT22187178) — Learning Objective-Aware Lecture Summarization & Flashcards

K.K.G.Y. Mihiraj (IT22224552) — Affect and Attention-Aware Emotion Detection Module

W.H.H. Thathsara (IT22371690) — Emotion- and Progress-Aware Adaptive Study Reminder System

Supervised by: Mrs. Suriya Kumari

Co-Supervised by: Mr. Ravi Supunya

Department of Software Engineering
Faculty of Computing
Sri Lanka Institute of Information Technology (SLIIT)
Sri Lanka

October 2026


DECLARATION

We hereby declare that this dissertation titled 'An AI-Enabled Intelligent Study Assistant (AuraLearn) to Enhance Student Learning Outcomes' represents our own original research work, carried out in collaborative group capacity as well as individual specialized components under the academic supervision of Mrs. Suriya Kumari and co-supervision of Mr. Ravi Supunya at the Sri Lanka Institute of Information Technology (SLIIT).

This document has not been submitted in whole or in part for any degree, diploma, or qualification at this or any other educational institution. All scholarly citations, theoretical frameworks, datasets, open-source libraries, and academic resources utilized throughout this research have been explicitly acknowledged according to standard IEEE academic citation standards.


Furthermore, we hereby grant to Sri Lanka Institute of Information Technology the non-exclusive right to reproduce, archive, and distribute this dissertation in whole or in part across digital and physical media for educational and institutional research purposes.

Table D.1: Candidate Authors and Component Undertakings

Student Name	Student Registration No	Individual Research Component	Signature
I.H. Sonal Dilmith	IT22120120	Hallucination-Controlled LLM Tutor	
T.G.K.G. Vijithapala	IT22187178	Objective-Aware Summarization & Flashcards	
K.K.G.Y. Mihiraj	IT22224552	Affect & Attention Emotion Detection	
W.H.H. Thathsara	IT22371690	Adaptive Spaced Reminder System	

SUPERVISOR ATTESTATION

The undersigned academic supervisors certify that the candidate students named above have carried out this research project under our guidance, and that this dissertation is worthy of submission in partial fulfillment of the requirements for the B.Sc. (Hons) Degree in Information Technology Specialized in Software Engineering.



Signature of Supervisor: _____

Date: 2026.10.11

ABSTRACT

Higher education students increasingly face unprecedented cognitive overload, academic stress, and revision fragmentation during self-directed study and examination preparation. Although Artificial Intelligence (AI) and Large Language Models (LLMs) offer promising avenues for automated academic support, existing educational technologies suffer from four fundamental, debilitating limitations: (1) commercial conversational tutors frequently generate plausible but factually hallucinated explanations when answering ungrounded curricular queries; (2) automated summarization tools produce generic concept condensations divorced from official syllabus learning objectives and Bloom's taxonomy assessment criteria; (3) emotion-aware learning systems rely on invasive video streaming or persistent biometric storage that violates student privacy and imposes high computational bottlenecks; and (4) modern study planners utilize rigid, fatigue-blind spaced repetition schedules (such as classic SuperMemo SM-2) that ignore real-time cognitive burnout, leading to procrastination and steep drop-off in study adherence.

To overcome these interconnected challenges, this dissertation presents AuraLearn, an integrated, intelligent, and privacy-preserving Smart Study Assistant engineered through a multi-tier microservice architecture. AuraLearn harmonizes four novel AI modules into a closed-loop personalized learning ecosystem: (1) a Hallucination-Controlled LLM Tutoring Module that couples Retrieval-Augmented Generation (RAG) with token log-probability uncertainty estimation, reducing hallucination rates to 3.8% and routing replies through dynamic Socratic scaffolding; (2) a Learning Objective-Aware Summarization and Flashcard Generation Module leveraging fine-tuned transformer architectures (BART/T5) that aligns lecture notes and transcripts directly to syllabus outcomes, attaining superior ROUGE-1 (52.8%) and 94% curriculum coverage; (3) an Affect and Attention-Aware Emotion Detection Module utilizing MediaPipe 468-point 3D facial mesh kinematics, Eye Aspect Ratio (EAR), and MobileNetV2 hybrid geometric fusion operating under a zero-storage volatile RAM privacy protocol (87.2% overall accuracy across five affective states, 18.4 ms inference latency); and (4) an Emotion- and Progress-Aware Adaptive Study Reminder System powered by Contextual Bandit Reinforcement Learning that dynamically calibrates review intervals and break alerts using an Affective Readiness Index (ARI), achieving an 86.4% study plan adherence rate and an 88% retention rate over a 30-day evaluation.

Rigorous experimental validation across benchmark datasets (FER-2013, curated course syllabi) and an empirical trial of 32 undergraduate engineering students confirms that AuraLearn maintains end-to-end response latencies under 3.5 seconds on commodity student hardware

while scoring 87.8 on the System Usability Scale (SUS). By uniting cognitive grounding, pedagogical alignment, ethical affective sensing, and adaptive behavioral reinforcement, AuraLearn establishes a robust foundation for next-generation, human-centered educational technologies.

Keywords *— Intelligent Tutoring Systems, Retrieval-Augmented Generation (RAG), Hallucination Control, Learning Objective Alignment, Affective Computing, MediaPipe Face Mesh, Privacy-Preserving AI, Spaced Repetition, Contextual Bandits, Educational Technology.*

ACKNOWLEDGEMENT

First and foremost, we express our profound gratitude to our research supervisor, Mrs. Suriya Kumari, Senior Lecturer in the Department of Software Engineering, for her exceptional guidance, intellectual mentorship, and unwavering encouragement throughout this research journey. Her profound insights into intelligent systems, software architecture, and academic rigor have been indispensable in steering both our collective project and our individual research modules.

We extend our sincere appreciation to our co-supervisor, Mr. Ravi Supunya, for his constructive recommendations, thorough reviews, and technical advice during the design and evaluation phases of this dissertation.

We are deeply grateful to the Department of Software Engineering and the Faculty of Computing at the Sri Lanka Institute of Information Technology (SLIIT) for providing state-of-the-art laboratory facilities, high-performance computing resources, and an intellectually vibrant environment.

Our sincere thanks go to the 32 undergraduate student participants who generously volunteered their time to test the AuraLearn prototype, contribute to our empirical datasets, and complete rigorous evaluation surveys under strict ethical protocols.

Finally, we express our deepest appreciation to our parents, families, and friends for their enduring patience, moral support, and belief in our aspirations throughout our undergraduate studies.

TABLE OF CONTENTS

DECLARATION ..... **ii**
ABSTRACT ..... **iv**
ACKNOWLEDGEMENT ..... **vi**
LIST OF FIGURES ..... **ix**
LIST OF TABLES ..... **x**
LIST OF ABBREVIATIONS ..... **xi**
1. INTRODUCTION **1**
1.1 Background and Literature Survey 2
1.1.1 Hallucination-Controlled LLM-Based Tutoring (C1: Dilmith) 2
1.1.2 Learning Objective-Aware Summarization & Flashcards (C2: Vijithapala) 3
1.1.3 Affect and Attention-Aware Emotion Detection (C3: Mihiraj) 4
1.1.4 Emotion- and Progress-Aware Adaptive Study Reminders (C4: Thathsara) 4
1.2 Research Gap 5
1.2.1 Research Gaps in Academic AI Tutoring Systems 5
1.2.2 Research Gaps in Pedagogical Summarization and Active Recall 5
1.2.3 Research Gaps in Educational Affective Sensing & Biometric Privacy 6
1.2.4 Research Gaps in Affect-Aware Adaptive Study Scheduling 6
1.2.5 Cross-Cutting System Gaps in Integrated EdTech Platforms 6
1.3 Research Problem 7
1.3.1 Hallucination and Overconfidence in Conversational Academic AI 7
1.3.2 Fragmented and Objective-Blind Course Material Summarization 7
1.3.3 Intrusive and Computationally Heavy Facial Monitoring 7
1.3.4 Rigid, Fatigue-Blind Spaced Repetition Causing Dropout 8
1.3.5 Unified Research Problem Statement 8
1.4 Research Objectives 8
1.4.1 Main Objective 8
1.4.2 Specific Objectives for Hallucination-Controlled Tutoring (C1) 9
1.4.3 Specific Objectives for Objective-Aware Summarization (C2) 9
1.4.4 Specific Objectives for Emotion Detection Module (C3) 9
1.4.5 Specific Objectives for Adaptive Reminder System (C4) 10
2. METHODOLOGY **11**
2.1 Component 1: Hallucination-Controlled LLM Tutoring Module 11
2.2 Component 2: Learning Objective-Aware Summarization & Flashcard Generation 13
2.3 Component 3: Affect and Attention-Aware Emotion Detection Module 14
2.4 Component 4: Emotion- and Progress-Aware Adaptive Study Reminder System 17
2.5 Unified 7-Layer System Architecture & Microservice Integration 18

2.6 Feasibility Study (Technical, Operational, Economic) 21
2.7 Project Requirements Specification 21
2.8 Ethical, Privacy, and Security Governance 23
2.9 Commercialization & Educational Market Viability 23
2.10 Comprehensive Testing & Validation Strategy 24
3. RESULTS AND DISCUSSION 25
3.1 Component 1 Results: Hallucination Suppression & RAG Grounding 25
3.2 Component 2 Results: Summarization ROUGE Benchmarks & Objective Alignment 26
3.3 Component 3 Results: Emotion Accuracy, Ablation & Privacy Benchmarks 27
3.4 Component 4 Results: Spaced Retention, Adherence & Fatigue Prevention 28
3.5 Integrated System Evaluation & Cross-Microservice Benchmarks 29
3.6 Synthesis and In-Depth Research Discussion 30
4. CONCLUSION 32
4.1 Component-Specific Conclusions (C1 to C4) 32
4.2 Holistic System Contributions 33
4.3 Research Limitations 33
4.4 Future Research Horizons 33
REFERENCES 35
GLOSSARY 37
APPENDICES 38

LIST OF FIGURES

Figure 2.1: AuraLearn: Unified 7-Layer Holistic System Architecture 18
Figure 2.2: Component 1: Confidence-Aware RAG Tutoring Pipeline & Uncertainty Gate..... 11
Figure 2.3: Component 2: Learning Objective-Aware Summarization & Flashcard Pipeline 13
Figure 2.4: Component 3: Affect & Attention-Aware Facial Mesh Perception Pipeline 15
Figure 2.5: Component 4: Emotion & Progress-Aware Spaced Repetition Workflow..... 17
Figure 2.6: Unified End-to-End Student Study Session Flowchart 21
Figure 3.1: Component 1: Hallucination Suppression & Factual Accuracy Benchmarks 25
Figure 3.2: Component 2: Summarization ROUGE Scores & Pedagogical Alignment 26
Figure 3.3: Component 3: Emotion Model Convergence & Ablation Comparisons..... 27
Figure 3.4: Component 4: Retention Decay Curves & Study Adherence Metrics 28
Figure 3.5: Integrated AuraLearn Cross-Microservice Latencies & Usability Scores..... 29

LIST OF TABLES

Table 1.1: Comparison of existing AI tutoring systems with Component 1 5
Table 1.2: Comparison of text summarization methods against Component 2 5
Table 1.3: Comparison of educational affective sensing approaches vs Component 3 6
Table 1.4: Comparison of spaced repetition schedulers against Component 4 6
Table 2.1: Component 1 Prompt Engineering and Uncertainty Routing Rules 12
Table 2.2: Component 2 Bloom's Taxonomy Cognitive Mapping Specifications 13
Table 2.3: Component 3 Biomechanical Feature Engineering Formulae 15
Table 2.4: Component 4 Modified SM-2 Variable Definitions and Formulations 17
Table 2.5: Unified REST API Microservice Specification for AuraLearn 20
Table 2.6: Overall Hardware and Cloud Infrastructure Specifications 21
Table 2.7: System Stakeholders and User Functional Requirements Matrix 22
Table 2.8: Non-Functional Operational and Security Requirements 22
Table 2.9: End-to-End System Test Cases and Functional Validation Suite 24
Table 3.1: Component 1 Factual Accuracy and Latency Benchmarks 25
Table 3.2: Component 2 ROUGE Evaluation and Concept Alignment Metrics 26
Table 3.3: Component 3 Confusion Matrix and Empirical Classification Metrics (N=1,920) 27
Table 3.4: Component 4 Adherence, Retention, and Fatigue Metrics vs Static Baselines 28
Table 3.5: AuraLearn End-to-End Microservice Performance and Latency SLA 29
Table 3.6: System Usability Scale (SUS) Survey Breakdown across 32 Students 30

LIST OF ABBREVIATIONS

Table A.1: List of Domain Abbreviations

Abbreviation	Expanded Academic Term
AI	Artificial Intelligence
API	Application Programming Interface
ARI	Affective Readiness Index
AUC	Area Under the Receiver Operating Characteristic Curve
BART	Bidirectional and Auto-Regressive Transformers
BFR	Brow Furrow Ratio
CLAHE	Contrast Limited Adaptive Histogram Equalization
CNN	Convolutional Neural Network
DSR	Design Science Research
EAR	Eye Aspect Ratio
FAISS	Facebook AI Similarity Search
FER	Facial Expression Recognition
GDPR	General Data Protection Regulation
HGF	Hybrid Geometric Fusion
IQR	Interquartile Range
LMS	Learning Management System (Moodle, Canvas)
LLM	Large Language Model
MAR	Mouth Aspect Ratio
NLP	Natural Language Processing
OCR	Optical Character Recognition
RAG	Retrieval-Augmented Generation
RL	Reinforcement Learning
ROC	Receiver Operating Characteristic
ROUGE	Recall-Oriented Understudy for Gisting Evaluation
SaaS	Software as a Service

Abbreviation	Expanded Academic Term
SLIIT	Sri Lanka Institute of Information Technology
SM-2	SuperMemo 2 Spaced Repetition Algorithm
SUS	System Usability Scale
SVM	Support Vector Machine
T5	Text-to-Text Transfer Transformer

1. INTRODUCTION

The rapid evolution of higher education technology has profoundly altered how undergraduate students interact with academic curricula. Traditional classroom lectures are now supplemented with expansive digital repositories, including multi-hour lecture video recordings, digital slide decks, instructional PDFs, programming lab manuals, and supplementary reading assignments. While these digital platforms democratize access to vast educational resources, they have inadvertently introduced severe cognitive overload for university students. Navigating expansive, unstructured course materials during high-stakes examination preparation requires learners to extract salient concepts, reconcile conceptual ambiguities, retain complex multi-layered technical principles, and maintain disciplined revision cadences over prolonged periods.

Educational psychology and self-regulated learning theories establish that successful academic outcomes depend on three fundamental pillars: (1) cognitive comprehension and conceptual grounding; (2) active recall and structured memory consolidation; and (3) affective self-regulation and cognitive well-being. In self-directed study environments, learners routinely falter across all three pillars. When students attempt to study independently outside formal lecture hours, they lack access to continuous instructional guidance. Although generic commercial generative AI chatbots have emerged as pervasive study aids, their lack of grounding in institutional course syllabi frequently leads to plausible but factually hallucinated assertions, instilling dangerous misconceptions during exam preparation.

Simultaneously, learners struggle with revision fragmentation. Summarizing lengthy lecture transcripts and visual slide presentations using generic summarization software results in superficial, unstructured summaries that ignore formal syllabus learning outcomes and Bloom's taxonomy assessment criteria. Furthermore, passive review of static summaries produces weak long-term retention compared to active recall through spaced flashcard repetition.

Compounding these cognitive hurdles is the complete neglect of students' emotional and mental states. Rigorous study sessions are characterized by continuous fluctuations in cognitive engagement, analytical confusion, acute frustration, and mental fatigue. Prolonged study under conditions of extreme exhaustion induces burnout, task avoidance, and revision abandonment. Existing automated study schedulers operate under static, rigid spaced repetition formulas (such as classic SuperMemo SM-2) that schedule flashcard reviews completely blind to real-time cognitive exhaustion. Conversely, prior attempts to introduce facial emotion recognition into educational systems have relied on intrusive video surveillance architectures that transmit raw student video streams across cloud networks, violating basic student privacy rights under GDPR and sparking widespread student refusal.

To resolve this nexus of cognitive, pedagogical, affective, and behavioral bottlenecks, this dissertation introduces AuraLearn (Group R26-SE-022), an AI-enabled, intelligent, and privacy-preserving Smart Study Assistant engineered specifically to enhance university student learning outcomes. AuraLearn brings together four dedicated, specialized research modules into a unified, synergistic microservice architecture:

1. A Hallucination-Controlled LLM Tutoring Module (I.H. Sonal Dilmith — IT22120120) that enforces factual grounding in verified course materials and modulates explanations based on calibrated model uncertainty;
2. A Learning Objective-Aware Summarization and Flashcard Generation Module (T.G.K.G. Vijithapala — IT22187178) that condenses complex lecture slides and transcripts aligned strictly with syllabus learning outcomes and Bloom's taxonomy;
3. An Affect and Attention-Aware Emotion Detection Module (K.K.G.Y. Mihiraj — IT22224552) that senses facial affective states and visual attention via in-memory geometric facial mesh kinematics under a strict zero-storage privacy protocol; and
4. An Emotion- and Progress-Aware Adaptive Study Reminder System (W.H.H. Thathsara — IT22371690) that dynamically balances spaced repetition intervals with real-time affective readiness scores using reinforcement learning.

1.1 Background and Literature Survey

The intersection of Natural Language Processing (NLP), Computer Vision, Affective Computing, and Reinforcement Learning offers unprecedented opportunities to transform computer-assisted learning into an adaptive, human-centered science. Below, we review the scientific background and contemporary literature across each of the four specialized domains.

1.1.1 Hallucination-Controlled LLM-Based Tutoring (Component 1: Dilmith)

Large Language Models (LLMs) parameterized with hundreds of billions of weights have demonstrated remarkable generative prowess across natural language understanding, code synthesis, and multi-turn dialogue. In educational environments, LLM tutors possess the potential to democratize personalized Socratic tutoring, providing instant clarifications and customized conceptual analogies to students around the clock.

Despite these capabilities, commercial foundation models suffer from a fundamental failure mode known as artificial hallucination: the generation of syntactically fluent, persuasive, yet factually incorrect or unverified assertions. In higher-education STEM curricula, where technical precision is paramount (e.g., algorithmic complexity proofs, mathematical derivations, or software architecture patterns), hallucinated explanations can severely distort a learner's

foundational knowledge. Standard retrieval-augmented generation (RAG) frameworks mitigate ungrounded responses by supplying external text chunks retrieved from a vector database into the prompt context. However, existing RAG solutions still exhibit critical deficiencies: they typically apply static, uncalibrated prompting strategies, fail to quantify model uncertainty over retrieved passages, and possess no mechanism to verify whether an answer is fully supported by the institutional course textbook.

Recent advances in uncertainty estimation suggest that token-level log-probabilities and semantic entropy across model output distributions can serve as reliable proxies for epistemic confidence. By calibrating this uncertainty against retrieval cosine similarities, an intelligent tutoring agent can dynamically adapt its pedagogical strategy: providing direct, highly cited answers when certainty is high, offering Socratic hints and guided questions when uncertainty is moderate, and gracefully abstaining or seeking instructor clarification when certainty is low.

1.1.2 Learning Objective-Aware Lecture Summarization and Flashcards (Component 2: Vijithapala)

Effective learning requires active processing, synthesis, and periodic retrieval practice. Students routinely attempt to extract high-yield concepts from lengthy lecture transcripts and visual slide presentations. Modern automated text summarization techniques are categorized into extractive methods (selecting salient sentences from source text) and abstractive methods (reformulating concepts using seq2seq transformer architectures such as BART and T5).

However, conventional text summarizers operate under generalized statistical salience principles, optimizing for surface-level sentence centrality rather than pedagogical relevance. They treat all document segments with equal educational importance, frequently summarizing anecdotal introductory remarks or tangential examples while omitting core analytical concepts required for examination mastery. Educational research grounded in Bloom's Revised Taxonomy confirms that effective study tools must structure concepts hierarchically, emphasizing higher-order cognitive dimensions (e.g., Application, Analysis, Evaluation).

Furthermore, cognitive psychology has established that passive reading of summaries produces fragile retention compared to active recall through flashcards. Existing flashcard generation tools rely on simplistic cloze-deletion heuristics or naive LLM prompt queries that generate superficial factual trivia rather than deep conceptual questions. A significant literature gap exists in developing domain-adapted transformer architectures that ingest lecture slides and spoken transcripts simultaneously, align extracted content with formal syllabus learning objectives, and synthesize exam-calibrated question-answer flashcard decks.

1.1.3 Affect and Attention-Aware Emotion Detection (Component 3: Mihiraj)

Affective computing in educational technology examines the bidirectional interaction between learners' emotional states and cognitive processing efficiency. Foundational studies by Kort, Reilly, and Picard established that learning is an inherently affective spiral: states such as curiosity and engagement foster flow and cognitive consolidation, whereas persistent frustration, boredom, and confusion signal impending task abandonment and cognitive fatigue.

Historically, student engagement monitoring relied on specialized physical hardware, such as galvanic skin response sensors, EEG headsets, or infrared gaze trackers. While accurate, these laboratory instruments are prohibitively expensive and impractical for everyday home study on student laptops. Consequently, computer vision-based Facial Expression Recognition (FER) has emerged as the dominant non-invasive paradigm. Deep Convolutional Neural Networks (CNNs) trained on generic datasets (such as FER-2013) classify basic universal emotions. However, direct application of generic FER models to student study environments fails due to domain mismatch: academic affective states (e.g., subtle brow furrowing during analytical concentration) differ drastically from exaggerated prototypical emotions (such as screaming anger or joyous laughter).

Moreover, traditional facial analysis pipelines suffer from two major barriers: computational inefficiency and severe privacy infringement. Continuous video capture at 30 frames per second over multi-hour study sessions causes severe thermal throttling on low-spec student hardware. Crucially, streaming video to external servers or saving facial frames locally creates catastrophic biometric surveillance vulnerabilities. Addressing this challenge requires an edge-optimized framework combining 3D facial landmark geometry (MediaPipe 468 mesh), periodic sampling (20-30 frames per minute), hybrid geometric fusion, and a strict in-memory zero-storage protocol.

1.1.4 Emotion- and Progress-Aware Adaptive Study Reminders (Component 4: Thathsara)

Long-term retention of academic knowledge requires systematically scheduled revision to counteract Ebbinghaus's forgetting curve. Pioneered in the 1980s, the SuperMemo SM-2 algorithm remains the standard baseline for algorithmic spaced repetition. SM-2 computes expanding review intervals based purely on historical recall grades (0 to 5) provided by the user.

Despite its mathematical elegance, SM-2 and its modern variations operate in an emotional and behavioral vacuum. They assume the learner is an idealized machine capable of executing review tasks at any scheduled timestamp, regardless of their prevailing mental fatigue, acute stress levels, or recent study volume. Empirical learning analytics reveal that when rigid algorithms

demand intense revision sessions during periods of student exhaustion, students experience frustration, develop negative task associations, and frequently abandon the study system entirely.

A critical frontier in educational data science is the integration of real-time affective readiness signals into spaced repetition modeling. Reinforcement Learning (RL), specifically Contextual Bandit frameworks, provides a natural paradigm for optimizing multi-objective scheduling: balancing long-term memory retention against acute cognitive load and student well-being. By observing both mastery history and real-time affective embeddings, an intelligent scheduler can adaptively prescribe review flashcards, recommend micro-breaks, or adjust topic difficulty.

1.2 Research Gap

While substantial progress has been achieved in individual sub-fields, existing EdTech platforms remain highly fragmented and disjointed. Below, we delineate the specific research gaps addressed by each of the four components, supported by structured comparative matrices.

1.2.1 Research Gaps in Academic AI Tutoring Systems

As summarized in Table 1.1, existing commercial and open-source tutoring platforms exhibit critical shortcomings in factual grounding, pedagogical scaffolding, and uncertainty transparency.

Table 1.1: Comparison of existing AI tutoring systems with Component 1

System / Paradigm	Factual Grounding Mechanism	Uncertainty Estimation	Pedagogical Scaffolding	Hallucination Risk
Generic Commercial LLMs (ChatGPT)	Implicit pre-training weights only	None (high overconfidence)	Direct text generation	High (frequent hallucinations)
Standard RAG Systems (LangChain)	Cosine top-k vector retrieval	Basic retrieval score	Static prompt concatenation	Moderate (unverified synthesis)
Khanmigo (Khan Academy)	Curated system prompts	Heuristic refusal filters	Socratic questioning prompts	Low-Moderate (model dependent)
AuraLearn Component 1 (Proposed)	Course vector DB + re-ranking	Token log-probability calibration	Dynamic 3-tier routing	Very Low (< 3.8% measured)

1.2.2 Research Gaps in Pedagogical Summarization and Active Recall

Table 1.2 highlights the gap between existing generic summarization algorithms and the curriculum-aligned needs of university learners.

Table 1.2: Comparison of text summarization methods against Component 2

Summarization Method	Target Input Material	Curriculum Alignment	Bloom's Cognitive Hierarchy	Flashcard Integration
Standard Extractive (TextRank)	Plain text documents	None (frequency based)	None (flat ranking)	Not supported
Standard Abstractive (BART/T5)	General articles, news	Implicit attention weights	None (general summary)	Separate prompt
Commercial Tools (QuillBot)	User paste text	None (user dependent)	None	Keyword matching
AuraLearn Component 2 (Proposed)	Lecture slides + transcripts	Explicit syllabus matching	Hierarchical Bloom's ranking	Integrated active flashcards

1.2.3 Research Gaps in Educational Affective Sensing and Biometric Privacy

Table 1.3 contrasts traditional affective monitoring pipelines against Component 3's edge-native, privacy-preserving paradigm.

Table 1.3: Comparison of educational affective sensing approaches vs Component 3

Affective Sensing Approach	Hardware / Sensor Modality	Edge Compute Overhead	Biometric Privacy & Storage	Academic State Domain Tuning
Physiological Wearables (EEG, GSR)	Headsets, wristbands	Low compute / High cost	Persistent biometric storage	Laboratory calibrated only
Continuous Video FER (Cloud CNN)	Webcam (30 fps video stream)	Extreme CPU/Network load	Cloud storage of raw images (High Risk)	Generic 7 basic emotions
Client Edge Face Mesh (MediaPipe)	Webcam (video stream)	Moderate CPU load	Local coordinates without policy	Raw landmark coordinates only
AuraLearn Component 3 (Proposed)	Webcam (20-30 fpm periodic)	Ultralight (< 15% CPU load)	Strict RAM-only zero-storage policy	5 Study-specific states + Attention

1.2.4 Research Gaps in Affect-Aware Adaptive Study Scheduling

Table 1.4 illustrates the limitations of traditional spaced repetition models and the advances achieved by Component 4.

Table 1.4: Comparison of spaced repetition schedulers against Component 4

Scheduling Algorithm	Primary Optimization Metric	Affective State Integration	Burnout & Fatigue Prevention	Adherence in High-Stress Prep
Classic SuperMemo SM-2 (Anki)	Historical grade score (0-5)	Completely ignored	None (rigid card buildup)	Low (steep review abandonment)
Modern FSRS (Free Spaced Repetition)	Statistical memory stability	Ignored (performance-only)	None (fixed review scheduling)	Moderate
Pomodoro & Fixed Timer Apps	Arbitrary 25-minute intervals	Ignored	Rule-based fixed breaks	Low (rigid, context-blind)
AuraLearn Component 4 (Proposed)	Memory stability + Real-time ARI	Continuous affect embedding fusion	Dynamic micro-breaks & pacing	High (86.4% verified adherence)

1.2.5 Cross-Cutting System Gaps in Integrated EdTech Platforms

The overarching research gap in educational technology lies in the total absence of a unified, closed-loop platform that interconnects grounded conceptual tutoring, curriculum-mapped revision materials, real-time cognitive-affective sensing, and intelligent behavioral scheduling. Existing students are forced to toggle between disjointed tools (e.g., ChatGPT for explanations, QuillBot for summaries, Anki for flashcards, and static calendar reminders), resulting in fragmented learning analytics, high context-switching friction, and zero awareness of the student's holistic mental well-being.

1.3 Research Problem

Based on the established academic literature and empirical gaps, the research problem is formalized into four interrelated dimensions and a unified central thesis question.

1.3.1 Hallucination and Overconfidence in Conversational Academic AI

University students attempting to comprehend complex STEM concepts through conversational LLMs are exposed to ungrounded assertions that mimic factual truth. Because generative models lack self-awareness regarding the boundaries of their domain training, they respond with equal linguistic confidence to valid questions and out-of-distribution queries. In the absence of calibrated uncertainty thresholds and course-grounded verification, students adopt incorrect principles, leading to flawed problem-solving and poor academic performance.

1.3.2 Fragmented and Objective-Blind Course Material Summarization

Undergraduate courses generate hundreds of pages of textual and auditory instructional content per semester. When students attempt to summarize this material using standard tools, the resulting notes fail to prioritize high-yield concepts designated in the formal syllabus learning outcomes. Consequently, learners waste disproportionate revision time on tangential descriptions while remaining under-prepared for assessment-critical analytical challenges.

1.3.3 Intrusive and Computationally Heavy Facial Monitoring

While tracking student attention and emotional state is vital for affective tutoring, existing video-based monitoring tools impose intolerable computational loads on commodity laptops and violate basic student privacy rights. Capturing, transmitting, or persistently storing facial biometric images creates profound ethical and legal liabilities under GDPR. Without an in-memory, privacy-preserving, and computationally lightweight architecture, affective computing cannot be ethically or practically deployed in higher education.

1.3.4 Rigid, Fatigue-Blind Spaced Repetition Causing Dropout

Algorithmic spaced repetition tools enforce uncompromising study queues based strictly on chronological recall history. When students experience intense academic burnout, exhaustion, or severe frustration, these algorithms continue to demand heavy flashcard reviews. This disconnect induces acute cognitive fatigue, increases study avoidance, and drives learners to abandon structured revision precisely when they need adaptive support most.

1.3.5 Unified Research Problem Statement

How can an integrated, intelligent, and privacy-preserving Smart Study Assistant be engineered to enhance university student learning outcomes by uniting course-grounded hallucination-controlled LLM tutoring, syllabus objective-aligned summarization, in-memory zero-storage affective sensing, and emotion-aware adaptive study scheduling into a cohesive, closed-loop educational ecosystem?

1.4 Research Objectives

1.4.1 Main Objective

The primary objective of this research is to design, develop, and empirically evaluate AuraLearn, an integrated, intelligent, privacy-preserving Smart Study Assistant that enhances university students' learning effectiveness and well-being by uniting grounded AI tutoring, learning-objective-aware summarization, edge-based emotion detection, and emotion-aware adaptive study reminders.

1.4.2 Specific Objectives for Hallucination-Controlled Tutoring (C1: Dilmith)

1. To construct an automated course-material ingestion and indexing pipeline using document parsing and vector databases (FAISS/ChromaDB);
2. To implement a confidence-aware Retrieval-Augmented Generation (RAG) framework incorporating token log-probability uncertainty estimation;
3. To develop a dynamic three-tier pedagogical response dispatch system (Direct Verified Answer, Socratic Scaffolding Hint, Safe Clarification Request);
4. To empirically evaluate factual accuracy, hallucination suppression rates (< 5%), and retrieval precision against course benchmarks.

1.4.3 Specific Objectives for Objective-Aware Summarization (C2: Vijithapala)

1. To build a multi-modal parser capable of extracting structured text and concepts from lecture slide decks and spoken audio transcripts;
2. To engineer a semantic alignment algorithm that correlates lecture segments with formal course syllabus learning objectives;
3. To fine-tune seq2seq transformer models (BART/T5) for hierarchical, Bloom's-taxonomy-aligned abstractive summarization;
4. To generate exam-oriented active recall flashcard decks and validate summary fidelity via ROUGE metrics and student comprehension testing.

1.4.4 Specific Objectives for Emotion Detection Module (C3: Mihiraj)

1. To design a lightweight client-side computer vision perception pipeline leveraging MediaPipe 468-point 3D facial mesh;
2. To formulate biomechanical kinematic feature extraction algorithms (Eye Aspect Ratio, Mouth Aspect Ratio, Brow Furrow, Head Pose);
3. To train a MobileNetV2 deep learning classifier augmented with Hybrid Geometric Fusion (HGF) to classify five learning-centered affective states and compute a continuous Attention Score (0 to 100);
4. To implement and formally audit a strict zero-storage, RAM-only processing protocol ensuring 100% GDPR biometric compliance on low-spec hardware.

1.4.5 Specific Objectives for Adaptive Reminder System (C4: Thathsara)

1. To mathematically formulate an Affective Readiness Index (ARI) that synthesizes real-time emotion embeddings with cognitive attention metrics;
2. To extend the SuperMemo SM-2 spaced repetition algorithm by integrating dynamic memory decay parameters with affective readiness inputs;
3. To implement a Contextual Bandit Reinforcement Learning policy that dynamically

recommends review flashcard intervals and cognitive micro-breaks; 4. To evaluate long-term memory retention gains and verify that study plan adherence exceeds 85% in empirical student cohorts.

2. METHODOLOGY

This chapter presents the comprehensive research methodology, technical design, mathematical formulations, and engineering architecture governing the four specialized modules of AuraLearn and their holistic integration. The research follows the Design Science Research (DSR) methodology, iterating through problem identification, artifact design, empirical implementation, and rigorous evaluation.

2.1 Component 1: Hallucination-Controlled LLM Tutoring Module (Dilmith)

The Hallucination-Controlled Tutoring Module is engineered to provide academically reliable, course-specific conceptual assistance to university students while eliminating artificial hallucinations.




Figure 2.2: Component 1: Confidence-Aware RAG Tutoring Pipeline & Uncertainty Gate

2.1.1 Confidence-Aware RAG Pipeline Architecture

The pipeline operates across four discrete stages: (1) Document Ingestion and Chunking, (2) Semantic Indexing and Retrieval, (3) Confidence Calibration and Uncertainty Gating, and (4) Socratic Response Generation. Course materials (textbooks, lecture presentations, professor notes) are parsed and segmented using recursive character-based chunking with an optimal

chunk size of 512 tokens and an overlap of 64 tokens to preserve semantic continuity across section boundaries.

2.1.2 Vector Database and Course Material Indexing

Extracted text chunks are passed through a dense text embedding model (e.g., text-embedding-ada-002 / BGE-Large) to generate 1,536-dimensional semantic representations. The resulting embeddings are stored in a FAISS (Facebook AI Similarity Search) vector database utilizing an IndexFlatIP (inner product) indexing scheme normalized for cosine similarity. When a student submits a natural language question Q, Q is embedded into query vector v_Q, and FAISS executes top-k nearest neighbor retrieval to extract the top 5 most relevant document chunks {d_1, d_2, ..., d_5}.

2.1.3 Token Log-Probability Uncertainty Estimation and Calibration

To eliminate hallucinations, the module computes a composite confidence metric C(Q, A) based on the retrieved context similarity and the LLM's autoregressive token log-probabilities. Let A = (y_1, y_2, ..., y_T) represent the sequence of T generated output tokens. The sequence log-probability is formulated as:

log P(A|Q, D) = (1 / T) * sum_{t=1}^T log P(y_t | y_{<t}, Q, D)

The final confidence score C is calibrated by combining normalized sequence probability with maximum cosine retrieval similarity Sim(v_Q, v_D):

C = alpha * exp((1 / T) * sum_{t=1}^T log P(y_t | y_{<t}, Q, D)) + (1 - alpha) * max_{i} Sim(v_Q, v_{d_i})

where alpha is an empirical weighting parameter tuned to 0.65.

2.1.4 Dynamic Socratic Response Routing

Based on the calculated confidence score C, the inference engine dynamically dispatches one of three pedagogical strategies, detailed in Table 2.1.

Table 2.1: Component 1 Prompt Engineering and Uncertainty Routing Rules

Confidence Tier	Score Range (C)	Prompt Scaffolding Strategy	System Output Action
High Confidence	C >= 0.82	Factual Direct Synthesis with Mandatory Citations	Provides direct answer, highlighting exact textbook slide and chapter citations.
Moderate Confidence	0.60 <= C < 0.82	Socratic Guided Prompting & Conceptual Hints	Refrains from complete answer; prompts student with guiding questions and key definitions.

Confidence Tier	Score Range (C)	Prompt Scaffolding Strategy	System Output Action
Low Confidence	C < 0.60	Safe Epistemic Refusal & Escalation	Politely states insufficient course context; offers to log query for lecturer review.

2.2 Component 2: Learning Objective-Aware Summarization & Flashcards (Vijithapala)

Component 2 bridges the gap between raw instructional media and exam-oriented active recall by parsing multi-modal lecture assets and aligning extracted concepts with formal course learning objectives.




Figure 2.3: Component 2: Learning Objective-Aware Summarization & Flashcard Pipeline

2.2.1 Multi-Modal Document & Transcript Ingestion Pipeline

The ingestion engine accepts multi-modal course assets: PDF slide presentations, DOCX lecture notes, and automated audio transcripts (Whisper ASR). Optical Character Recognition (Tesseract OCR) extracts slide titles, bullet hierarchies, diagrams, and code snippets, while transcript timestamps are aligned with visual slide transitions.

2.2.2 Pedagogical Alignment & Bloom's Taxonomy Mapping

Course syllabi specify formal Learning Outcomes (e.g., 'Analyze memory management algorithms in operating systems'). The alignment engine utilizes a semantic similarity matrix to

map every lecture paragraph against syllabus outcome vectors. Content is categorized across Bloom's Taxonomy cognitive levels using action verb classifiers, as defined in Table 2.2.

Table 2.2: Component 2 Bloom's Taxonomy Cognitive Mapping Specifications

Bloom's Taxonomy Level	Characteristic Action Verbs	Extracted Educational Focus	Flashcard Question Archetype
Remember / Understand	Define, Describe, Identify, Explain	Core terminology, foundational concepts	'What is the primary role of virtual memory paging?'
Apply / Analyze	Calculate, Compare, Differentiate, Solve	Mechanisms, architectural trade-offs	'Compare segmentation vs paging in terms of external fragmentation.'
Evaluate / Create	Assess, Design, Optimize, Formulate	System design decisions, optimizations	'How does the TLB reach rate influence effective memory access time?'

2.2.3 Fine-Tuned Transformer Summarization (BART / T5)

A seq2seq transformer model (BART-Large / T5-Base) is fine-tuned on educational discourse corpora. The input to the transformer is conditioned on the target learning outcome prefix: '<summarize_for_objective: LO_2> [Context Text]'. This prompt conditioning forces the model to ignore conversational digressions and concentrate abstractive generation exclusively on syllabus-critical material.

2.2.4 Exam-Oriented Flashcard Synthesis

From the verified objective summaries, an active recall synthesis engine generates question-answer flashcard pairs. Heuristic quality filters prune trivial questions, ensure clear answers, and attach difficulty ratings (1 to 5) based on the associated Bloom's taxonomy depth. These flashcard decks are exported directly to Component 4 for scheduled spaced repetition.

2.3 Component 3: Affect and Attention-Aware Emotion Detection Module (Mihiraj)

Component 3 provides non-invasive, edge-native affective computing capabilities designed to recognize student engagement, confusion, frustration, boredom, and fatigue in real time while guaranteeing 100% biometric privacy.




Figure 2.4: Component 3: Affect & Attention-Aware Facial Mesh Perception Pipeline

2.3.1 MediaPipe 468-Point 3D Facial Mesh Perception Pipeline

Rather than analyzing high-resolution video streams, Component 3 deploys Google's MediaPipe Face Mesh on periodic webcam frames captured at 20 to 30 frames per minute (fpm). MediaPipe predicts the 3D coordinates (x, y, z) of 468 standardized facial landmarks in real time. The landmark pipeline operates entirely on the client or local edge microservice, eliminating video streaming overhead.

2.3.2 Biomechanical Kinematic Feature Formulation

From the 468 landmark coordinates, four scale-invariant geometric ratios are formulated to capture subtle facial muscle deformations corresponding to cognitive states, as summarized in Table 2.3.

Table 2.3: Component 3 Biomechanical Feature Engineering Formulae

Biomechanical Feature	Mathematical Formulation	Landmark Indices Used	Cognitive / Affective Interpretation
Eye Aspect Ratio (EAR)	EAR = (‖p2 - p6‖ + ‖p3 - p5‖) / (2 * ‖p1 - p4‖)	Left: 33,160,158,133,153,144 Right: 362,385,387,263,373,380	Measures eyelid separation; values < 0.21 signal blinks and ocular drowsiness.
Mouth Aspect Ratio (MAR)	MAR = (‖p13 - p14‖ + ‖p17 - p18‖) / (2 * ‖p11 - p12‖)	Lips: 78, 308, 13, 14, 82, 312	Detects yawning, jaw tension, and verbal frustration.

Biomechanical Feature	Mathematical Formulation	Landmark Indices Used	Cognitive / Affective Interpretation
Brow Furrow Ratio (BFR)	BFR = ‖p_inner_left - p_inner_right‖ / Face_Width	Eyebrows: 70, 107, 300, 336	Contraction of corrugator muscle indicates analytical confusion and stress.
Head Pose (Yaw, Pitch, Roll)	PnP Algorithm via 6 3D reference points	Nose 1, Chin 199, Eyes 33,263, Mouth 61,291	Estimates gaze alignment; excessive pitch/yaw denotes off-screen distraction.

2.3.3 Hybrid Geometric Fusion with MobileNetV2 Deep Architecture

The classification pipeline combines deep spatial features with the biomechanical kinematic ratios through Hybrid Geometric Fusion (HGF). A lightweight MobileNetV2 backbone extracts spatial texture embeddings from cropped, CLAHE-enhanced facial patches, outputting a 128-dimensional latent vector. This vector is concatenated with the 12-dimensional kinematic feature vector (EAR, MAR, BFR, Head Pose angles, and temporal deltas) and passed through a dense fusion layer to classify the student's affective state across five classes: Neutral, Engaged, Confused, Frustrated, and Bored/Fatigued.

Simultaneously, a continuous Attention Score (0 to 100) is synthesized via weighted linear regression:

Attention Score = w_1 * (EAR / EAR_baseline) + w_2 * (1 - BFR_strain) + w_3 * cos(Pitch) * cos(Yaw) - w_4 * (MAR_yawn)

where weights w_1=40, w_2=25, w_3=25, w_4=10 are calibrated to maximize correlation with student focus.

2.3.4 In-Memory Ephemeral Processing & Zero-Storage Privacy Protocol

To address severe student privacy concerns and comply with GDPR Article 9 (biometric data protection), Component 3 enforces a strict zero-storage policy: webcam frames are processed exclusively in volatile RAM. No image is ever written to hard drives, SSDs, or external cloud buckets. Once the 16-dimensional numerical embedding is computed (typically within 18.4 milliseconds), the raw image array is dereferenced and immediately expunged via Python's garbage collector.

2.4 Component 4: Adaptive Study Reminder System (Thathsara)

Component 4 transforms traditional, rigid spaced repetition into a human-centered, affective-aware scheduling policy powered by Contextual Bandit Reinforcement Learning.




Figure 2.5: Component 4: Emotion & Progress-Aware Spaced Repetition Workflow

2.4.1 Modified SuperMemo SM-2 Mathematical Formulation

The classic SuperMemo SM-2 algorithm calculates the interval I(n) between reviews based on repetition number n and an Easiness Factor EF:

$I(1) = 1$ day, $I(2) = 6$ days, $I(n) = I(n-1) * EF$ (for $n > 2$)

$EF' = EF + (0.1 - (5 - q) * (0.08 + (5 - q) * 0.02))$, $EF >= 1.3$

where q in {0, 1, 2, 3, 4, 5} is the student's subjective recall grade. To inject affective intelligence, Component 4 introduces the Modified SM-2 formulation, detailed in Table 2.4.

Table 2.4: Component 4 Modified SM-2 Variable Definitions and Formulations

Variable / Parameter	Mathematical Symbol	Formulation / Default Value	Educational Function
Easiness Factor	EF_t	EF_{t-1} + Delta_q	Baseline knowledge complexity of the flashcard.
Affective Readiness Index	ARI_t	0.5 * (Attention / 100) + 0.3 * (1 - Fatigue) + 0.2 * Mood	Real-time cognitive availability derived from Component 3.

Variable / Parameter	Mathematical Symbol	Formulation / Default Value	Educational Function
Fatigue Penalty	gamma_f	exp(-lambda * Consecutive_Study_Hours)	Damps review volume during prolonged continuous study.
Adaptive Interval	I_adaptive	I_SM2 * (0.7 + 0.6 * ARI_t) * gamma_f	Dynamically expands intervals when alert; shortens intervals for consolidation.

2.4.2 Contextual Bandit Reinforcement Learning Policy

The scheduling agent operates as a Contextual Bandit. At each decision step t, the agent observes context vector x_t = [ARI_t, Mastery_Score, Session_Duration, Historical_Adherence, Time_of_Day]. The agent selects action a_t from a discrete action space A = {Immediate Review, Micro-Break (5 min), Cognitive Reset Break (15 min), Difficulty Downgrade, Schedule Tomorrow}. The reward function R(x_t, a_t) rewards high adherence and memory retention while heavily penalizing study abandonment and extreme fatigue.

2.5 Unified System Architecture & Microservice Integration

AuraLearn coordinates all four specialized research components within a 7-layer microservice architecture, illustrated in Figure 2.1.




Figure 2.1: AuraLearn: Unified 7-Layer Holistic System Architecture

The seven architectural layers function as follows:

Layer 1 (User Interaction): Next.js web application providing student dashboard, chat tutor UI, and active recall interfaces;
Layer 2 (Data Acquisition): Ingestion endpoints capturing course slides, student queries, webcam frames, and study logs;
Layer 3 (Preprocessing & Perception): Document OCR parsers, text embedding generators, and MediaPipe face mesh extractors;
Layer 4 (Core AI Research Modules): The 4 specialized microservices (C1 Tutoring, C2 Summarization, C3 Emotion, C4 Reminder);
Layer 5 (Shared Context & Knowledge): FAISS vector store, syllabus graph, ephemeral affect cache (Redis), and mastery DB;
Layer 6 (Decision & Personalization): Uncertainty response router, affective readiness engine, and RL scheduling policy;

Layer 7 (Multi-Modal Output): Grounded answers with citations, curriculum summaries, cognitive break alerts, and calendar notifications.

The inter-service REST API specification is detailed in Table 2.5.

Table 2.5: Unified REST API Microservice Specification for AuraLearn

Microservice	Endpoint Route	HTTP Method	Input Payload	Response Payload
C1: RAG Tutor	/api/v1/tutor/query	POST	{"query": str, "course_id": str}	{"response": str, "confidence": float, "citations": list}
C2: Summarizer	/api/v1/summary/generate	POST	{"doc_id": str, "bloom_level": str}	{"summary": str, "flashcards": list, "lo_coverage": float}
C3: Emotion Detector	/api/v1/affect/frame-mesh	POST	{"frame_b64": str, "session_id": str}	{"state": str, "attention_score": float, "ari": float}
C4: Adaptive Scheduler	/api/v1/schedule/next-action	POST	{"student_id": str, "ari": float, "due_cards": int}	{"action": str, "interval_hours": float, "break_alert": bool}




Figure 2.6: Unified End-to-End Student Study Session Flowchart

2.6 Feasibility Study

A comprehensive three-dimensional feasibility study was executed prior to implementation:

Technical Feasibility: All required machine learning models (MobileNetV2, MediaPipe, FAISS, BART/T5, LinUCB Bandits) execute efficiently on consumer-grade student hardware with multi-core CPUs and 8 GB RAM. Microservices operate within Docker containers communicating over asynchronous REST and WebSockets.

Operational Feasibility: The user interface is designed for minimal cognitive friction. Student webcam monitoring requires explicit, revocable opt-in consent and displays a visual indicator when active. Flashcards synchronize seamlessly with mobile web browsers.

Economic Feasibility: The system relies primarily on open-source frameworks (FastAPI, PyTorch, LangChain, Next.js). Cloud inference costs for the RAG embedding tier average less than $0.002 per student inquiry, demonstrating exceptional economic viability for university-wide deployment.

2.7 Project Requirements Specification

Table 2.6 delineates the operational hardware and infrastructure requirements.

Table 2.6: Overall Hardware and Cloud Infrastructure Specifications

Component Layer	Minimum Hardware Specification	Recommended Production Infrastructure	Software / Framework Stack
Client Machine (Student)	Intel Core i3 / Ryzen 3, 4GB RAM, 720p Webcam	Intel Core i5 / Apple M1, 8GB RAM, 1080p Webcam	Modern Web Browser (Chrome / Edge / Firefox)
Edge / Backend Server	4 vCPU, 8GB RAM, 50GB SSD	8 vCPU, 16GB RAM, NVIDIA T4 GPU (16GB)	Ubuntu 22.04 LTS, Docker, Python 3.12, Node.js 20
Database & Vector Stores	2 vCPU, 4GB RAM, 20GB Storage	4 vCPU, 8GB RAM, PostgreSQL + Redis + FAISS	PostgreSQL 16, Redis 7.2, ChromaDB / FAISS

Table 2.7 outlines the stakeholder user requirements across the platform.

Table 2.7: System Stakeholders and User Functional Requirements Matrix

Stakeholder Group	Requirement ID	Functional Requirement Description	Associated Module
Undergraduate Students	FR-01	Submit natural language questions and receive cited, verified textbook answers.	Component 1 (Tutor)
Undergraduate Students	FR-02	Upload lecture slides and obtain syllabus-aligned summaries and active flashcards.	Component 2 (Summarizer)
Undergraduate Students	FR-03	View real-time cognitive attention metrics without risk of biometric storage.	Component 3 (Emotion)
Undergraduate Students	FR-04	Receive adaptive study reminders and micro-break recommendations matched to mental fatigue.	Component 4 (Scheduler)
Academic Instructors	FR-05	Upload official syllabus learning outcomes and monitor anonymized cohort confusion trends.	Platform Admin

Table 2.8 specifies the non-functional operational and security requirements.

Table 2.8: Non-Functional Operational and Security Requirements

Category	Requirement ID	Target Specification Metric	Validation Method
Latency / Performance	NFR-01	End-to-end RAG response generation latency < 5.0 seconds	Automated load testing with Locust (50 concurrent users)
Inference Latency	NFR-02	Facial mesh extraction and emotion inference < 50 milliseconds	Profiled Python time benchmarks across 1,000 frames
Privacy & Security	NFR-03	Zero persistence of facial imagery to disk (100% GDPR compliant)	Memory dump audit and filesystem file integrity monitoring
Usability	NFR-04	System Usability Scale (SUS) score > 80.0 across student trial cohort	Standard 10-item post-study SUS questionnaire (N=32)
Availability	NFR-05	Microservice uptime > 99.5% during examination testing periods	Health-check daemon with automated Docker container restarts

2.8 Ethical, Privacy, and Security Governance

Ethical compliance constitutes the cornerstone of AuraLearn's architectural philosophy. Research involving student behavioral data and facial imagery demands rigorous governance:

Informed Consent Protocol: Every student user must review and digitally sign an informed consent agreement explaining the webcam sampling process, the ephemeral nature of the features, and their right to revoke consent at any instant without academic penalty. Zero-Storage Ephemeral Pipeline: The facial analysis engine strictly operates in volatile RAM. No facial video streams or still frames are written to local disk, transmitted across networks, or cached in persistent databases. Garbage collection runs synchronously after feature extraction. Anonymized Learning Analytics: Student IDs are hashed using SHA-256 with cryptographic salting. Aggregated reports delivered to course instructors display only anonymized cohort-level concept confusion heatmaps, preventing surveillance or punitive evaluations.

2.9 Commercialization and Educational Market Viability

AuraLearn possesses immense commercialization potential across global EdTech markets. The platform addresses a multi-billion dollar market spanning university LMS integrations and individual student subscriptions:

B2B Institutional SaaS Model: AuraLearn can be licensed to higher education universities as an official institutional study portal, seamlessly integrating with LMS platforms such as Canvas, Moodle, and Blackboard via LTI 1.3 standards. Institutional licensing fees provide predictable annual recurring revenue.

B2C Freemium Student Model: Individual students can access standard RAG tutoring and basic flashcard generation free of charge, with premium tiers unlocking personalized emotion-aware scheduling, deep syllabus analysis, and cross-course analytics.

Patent Opportunities: The proprietary integration of Contextual Bandit RL with real-time biometric Affective Readiness Indexes represents patentable intellectual property in adaptive educational computing.

2.10 Comprehensive Testing & Validation Strategy

The verification suite incorporates unit tests, microservice integration tests, stress tests, and end-to-end student trials, summarized in Table 2.9.

Table 2.9: End-to-End System Test Cases and Functional Validation Suite

Test Case ID	Target System Component	Test Objective & Execution Procedure	Expected Verification Outcome	Status
TC-01	C1 RAG Vector Retrieval	Query vector store with 100 domain questions; verify top-3 recall.	Top-3 document chunks contain correct syllabus answer (> 90%).	PASSED
TC-02	C1 Uncertainty Gating	Submit 50 out-of-distribution queries; verify safe refusal action.	System refuses or seeks clarification for all 50 ungrounded queries.	PASSED
TC-03	C2 Objective Alignment	Upload 10 lecture slide decks; measure syllabus objective mapping.	Extracted concepts map to official syllabus outcomes (> 92%).	PASSED
TC-04	C3 Ephemeral RAM Audit	Monitor OS disk I/O write operations during 1-hour webcam session.	Zero image files written to disk; memory usage stable (< 250 MB).	PASSED
TC-05	C4 Adaptive Scheduling	Simulate student fatigue signal (ARI < 0.35); trigger review query.	System defers heavy review queue and issues micro-break alert.	PASSED
TC-06	E2E Platform Pipeline	Simulate 32 concurrent student study workflows over 2 hours.	Zero service crashes; average end-to-end latency < 3.5 seconds.	PASSED

3. RESULTS AND DISCUSSION

This chapter presents the empirical findings, quantitative performance benchmarks, ablation analyses, and qualitative student feedback obtained during comprehensive evaluation of AuraLearn across both curated academic datasets and live student trials.

3.1 Component 1 Results: Hallucination Suppression & RAG Grounding

Component 1 was evaluated on a benchmark of 500 domain-specific computer science examination questions categorized into Grounded (covered in course notes) and Out-of-Distribution (uncovered) questions.




Figure 3.1: Component 1: Hallucination Suppression & Factual Accuracy Benchmarks

As illustrated in Figure 3.1 and detailed in Table 3.1, standard ungrounded LLMs exhibited a severe hallucination rate of 38.5% when answering nuanced engineering questions. Introducing standard RAG reduced hallucinations to 14.2%. Crucially, AuraLearn's confidence-aware uncertainty gating suppressed hallucinations to an unprecedented 3.8%, achieving 93.4% factual accuracy while keeping average inference latency to 1.82 seconds.

Table 3.1: Component 1 Factual Accuracy and Latency Benchmarks

Tutoring Architecture	Factual Accuracy (%)	Hallucination Rate (%)	Citation Precision (%)	Average Latency (s)
Baseline Ungrounded LLM (Llama-3-8B)	61.4%	38.5%	N/A (no citations)	1.24 s
Standard Vanilla RAG	78.9%	14.2%	74.6%	1.65 s

Tutoring Architecture	Factual Accuracy (%)	Hallucination Rate (%)	Citation Precision (%)	Average Latency (s)
AuraLearn Confidence-Aware RAG (Ours)	93.4%	3.8%	96.2%	1.82 s

3.2 Component 2 Results: Summarization ROUGE Benchmarks & Objective Alignment

Component 2 was evaluated on 20 undergraduate lecture units using standard ROUGE metrics (comparing against professor reference notes) and expert pedagogical syllabus alignment ratings.




Figure 3.2: Component 2: Summarization ROUGE Scores & Pedagogical Alignment

The quantitative benchmarks in Table 3.2 confirm that AuraLearn's objective-conditioned T5 model significantly outperforms general-purpose summarizers, achieving a ROUGE-1 score of 52.8%, ROUGE-2 of 31.4%, and ROUGE-L of 48.9%. More importantly, syllabus concept coverage reached 94.0% compared to only 54.0% for generic LLM summaries.

Table 3.2: Component 2 ROUGE Evaluation and Concept Alignment Metrics

Summarization Model	ROUGE-1 (%)	ROUGE-2 (%)	ROUGE-L (%)	Syllabus Coverage (%)	Exam Relevance (%)
Generic LLM Zero-Shot Summary	38.2%	18.4%	34.6%	54.0%	58.0%
Standard Fine-Tuned BART	44.1%	23.5%	40.8%	71.5%	76.0%

Summarization Model	ROUGE-1 (%)	ROUGE-2 (%)	ROUGE-L (%)	Syllabus Coverage (%)	Exam Relevance (%)
AuraLearn Objective-Aligned Model (Ours)	52.8%	31.4%	48.9%	94.0%	91.0%

3.3 Component 3 Results: Emotion Accuracy, Ablation & Privacy Benchmarks

Component 3 was rigorously evaluated on both the FER-2013 benchmark (35,887 images remapped to 5 learning states) and an empirical primary dataset of 1,920 video frames captured from 32 consented university students during active study sessions.




Figure 3.3: Component 3: Emotion Model Convergence & Ablation Comparisons

The confusion matrix and class-wise performance metrics on the 32-student empirical cohort are presented in Table 3.3. The Hybrid Geometric Fusion model achieved an overall accuracy of 87.2% and a macro F1-score of 87.3%. Engaged and Neutral states attained superior classification accuracies (> 90%), while subtle Frustration and Confusion states achieved 81.3% and 83.5% recall, dramatically outperforming raw CNN baselines.

Table 3.3: Component 3 Confusion Matrix and Empirical Classification Metrics (N=1,920)

Affective Class	Support (Frames)	Precision (%)	Recall (%)	F1-Score (%)	Key Kinematic Discriminator
Neutral	480	88.4%	91.2%	89.8%	Baseline EAR ~0.28, minimal brow strain
Engaged	420	89.6%	90.5%	90.0%	Stable head pitch, consistent ocular fixation

Affective Class	Support (Frames)	Precision (%)	Recall (%)	F1-Score (%)	Key Kinematic Discriminator
Confused	360	84.2%	83.5%	83.8%	Elevated brow furrow ratio (BFR > 0.42)
Frustrated	320	82.1%	81.3%	81.7%	Lip compression (MAR drop), corrugator tension
Bored / Fatigued	340	91.5%	89.1%	90.3%	Depressed EAR (< 0.20), frequent yawning
Overall / Macro Avg	1,920	87.2%	87.1%	87.3%	Inference Latency: 18.4 ms (54.3 fps)

3.4 Component 4 Results: Spaced Retention, Adherence & Fatigue Prevention

Component 4 underwent a 30-day longitudinal study with 32 undergraduate students randomly partitioned into two groups: Group A utilized traditional static SuperMemo SM-2, while Group B utilized AuraLearn's Adaptive RL scheduler.




Figure 3.4: Component 4: Retention Decay Curves & Study Adherence Metrics

As documented in Figure 3.4 and Table 3.4, students utilizing AuraLearn achieved an 86.4% review queue adherence rate (compared to 58.0% for static SM-2), an 88.0% 30-day knowledge retention rate (compared to 68.0%), and reported an 84.0% burnout prevention satisfaction rating.

Table 3.4: Component 4 Adherence, Retention, and Fatigue Metrics vs Static Baselines

Evaluation Metric	Static SM-2 Baseline (Group A)	AuraLearn RL Scheduler (Group B)	Statistical Improvement
Study Queue Adherence Rate	58.0%	86.4%	+28.4% ($p < 0.001$)
30-Day Knowledge Retention	68.0%	88.0%	+20.0% ($p < 0.01$)
Session Completion Rate	62.0%	89.0%	+27.0% ($p < 0.001$)
Prompt Review Execution (< 15 min)	64.0%	88.0%	+24.0% ($p < 0.01$)
Burnout Prevention Rating	51.0%	84.0%	+33.0% ($p < 0.001$)

3.5 Integrated System Evaluation & Cross-Microservice Benchmarks

The complete AuraLearn microservice pipeline was benchmarked under real-world multi-user loads. Figure 3.5 and Table 3.5 illustrate processing latencies across all four microservices.




Figure 3.5: Integrated AuraLearn Cross-Microservice Latencies & Usability Scores

Table 3.5: AuraLearn End-to-End Microservice Performance and Latency SLA

Microservice Component	Measured P50 Latency (s)	Measured P95 Latency (s)	Target SLA Limit (s)	Compliance Status
C1: Hallucination-Controlled Tutor	1.82 s	2.65 s	< 5.0 s	COMPLIANT
C2: Objective-Aware Summarizer	2.45 s	3.80 s	< 5.0 s	COMPLIANT
C3: Emotion & Mesh Processing	0.018 s	0.028 s	< 0.050 s	COMPLIANT
C4: Adaptive RL Reminder Scheduler	0.120 s	0.210 s	< 1.0 s	COMPLIANT

Microservice Component	Measured P50 Latency (s)	Measured P95 Latency (s)	Target SLA Limit (s)	Compliance Status
End-to-End Pipeline Execution	3.42 s	4.65 s	< 6.0 s	COMPLIANT

Table 3.6 presents the System Usability Scale (SUS) survey breakdown across the 32 participating students, yielding an overall SUS score of 87.8 (Grade A+), significantly higher than the industry standard benchmark of 68.0.

Table 3.6: System Usability Scale (SUS) Survey Breakdown across 32 Students

Usability Dimension	Mean Score (out of 5.0)	Normalized Percent (%)	Qualitative Feedback Summary
System Simplicity & Navigation	4.45 / 5.0	89.0%	Students praised the unified single-window study dashboard.
Tutoring Reliability & Trust	4.55 / 5.0	91.0%	Textbook citations eliminated anxiety over AI hallucinations.
Flashcard Utility for Exams	4.60 / 5.0	92.0%	Bloom's taxonomy alignment matched actual past-paper questions.
Privacy Comfort & In-Memory Policy	4.80 / 5.0	96.0%	Zero image storage removed webcam intimidation completely.
Break Timing & Schedule Adherence	4.40 / 5.0	88.0%	Affective breaks effectively preempted study burnout.
Overall System Usability Scale (SUS)	87.8 / 100	Grade A+	Exceptional user satisfaction and high adoption willingness.

3.6 Synthesis and In-Depth Research Discussion

The empirical results validate the core hypothesis of this research: that intelligent academic support requires a closed-loop coupling of cognitive grounding, pedagogical structure, affective awareness, and behavioral adaptation. Operating these four modules in isolation yields fragmented benefits; however, their holistic integration inside AuraLearn produces synergistic reinforcement. Real-time affective monitoring (C3) prevents cognitive fatigue during adaptive review (C4), while grounded tutoring (C1) and objective summaries (C2) provide reliable instructional scaffolding. Furthermore, the verified zero-storage privacy protocol resolves the historic barrier that previously prevented the adoption of affective computing in academic institutions.

4. CONCLUSION

This concluding chapter synthesizes the core contributions across each of the four individual research components, summarizes the holistic accomplishments of the integrated AuraLearn system, acknowledges research limitations, and outlines compelling horizons for future exploration.

4.1 Component-Specific Conclusions

4.1.1 Component 1: Hallucination-Controlled LLM Tutor (Dilmith — IT22120120)

Component 1 successfully developed and validated a confidence-aware Retrieval-Augmented Generation tutoring system grounded in verified university course materials. By calibrating token log-probabilities against retrieval similarities, the module effectively suppressed artificial hallucination rates from 38.5% down to 3.8% while elevating factual accuracy to 93.4%. The dynamic Socratic scaffolding mechanism ensures students receive guided pedagogical hints when uncertainty is moderate, establishing a dependable, non-hallucinating AI tutor for rigorous higher education.

4.1.2 Component 2: Objective-Aware Summarization & Flashcards (Vijithapala — IT22187178)

Component 2 resolved the challenge of revision fragmentation by engineering an automated multi-modal parsing and transformer summarization pipeline that aligns lecture slides and transcripts directly with formal syllabus learning outcomes. Achieving a ROUGE-1 score of 52.8% and 94% syllabus concept coverage, the module guarantees that students focus revision on high-yield, assessment-critical concepts structured according to Bloom's Revised Taxonomy.

4.1.3 Component 3: Affect and Attention-Aware Emotion Detection (Mihiraj — IT22224552)

Component 3 demonstrated that non-invasive, ethically sound affective computing can be achieved on commodity student laptops without expensive sensors or invasive video surveillance. Leveraging MediaPipe 468 3D facial mesh kinematics and MobileNetV2 hybrid geometric fusion, the module achieved 87.2% classification accuracy across five learning states and computed continuous attention scores in 18.4 milliseconds. The audited zero-storage RAM-only privacy protocol guarantees 100% GDPR compliance, establishing a gold standard for privacy-preserving educational vision.

4.1.4 Component 4: Adaptive Study Reminder System (Thathsara — IT22371690)

Component 4 fundamentally transformed spaced repetition by replacing rigid chronological intervals with an affective-aware Contextual Bandit scheduling policy. By integrating real-time Affective Readiness Indexes with modified SuperMemo SM-2 formulations, the module achieved an 86.4% review adherence rate and an 88% 30-day retention rate while significantly reducing student burnout, proving that adaptive learning schedules must account for learners' mental readiness.

4.2 Holistic System Contributions

AuraLearn represents an end-to-end milestone in human-centered educational technology. Its overarching contributions include:

1. A Unified 7-Layer Architecture that successfully synchronizes natural language processing, computer vision, affective sensing, and reinforcement learning into a seamless multi-tier microservice platform;
2. An Audited Privacy-First Paradigm proving that continuous emotional and attention sensing can be deployed safely without persistent biometric storage;
3. Measurable Educational Efficacy, demonstrated through statistically significant gains in study plan adherence (+28.4%), factual accuracy (+32.0%), and a System Usability Scale score of 87.8/100.

4.3 Research Limitations

Notwithstanding its validated successes, several research limitations must be acknowledged:

1. Cohort Sample Size: While the empirical trial of 32 students provided robust statistical evidence, larger longitudinal cohorts across diverse university disciplines (e.g., Medicine, Humanities) are required to verify generalizability;
2. Extreme Ambient Lighting: In environments with severe backlighting or near-total darkness, webcam landmark detection confidence decreases, temporarily degrading emotion classification accuracy;
3. Multi-Speaker Audio Overlap: In lecture recordings where multiple instructors or students speak simultaneously, automated audio transcript alignment occasionally introduces noise into summarization inputs.

4.4 Future Research Horizons

Future extensions of AuraLearn will explore several promising research directions:

1. Multi-Modal Affective Fusion: Integrating keystroke dynamics and mouse jitter as passive secondary behavioral signals to complement facial mesh kinematics in low-light conditions; 2. Institutional LMS Plugins: Releasing production LTI 1.3 certified plugins for Canvas and Moodle to enable one-click course enrollment and automated syllabus synchronization; 3. Voice-Interactive Socratic Dialogue: Equipping Component 1 with ultra-low-latency speech-to-speech conversational agents to enable real-time spoken Socratic tutoring debates.

REFERENCES

[1] P. Lewis et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in Advances in Neural Information Processing Systems (NeurIPS), vol. 33, pp. 9459-9474, 2020.

[2] S. Lin, J. Hilton, and O. Evans, "TruthfulQA: Measuring how models mimic human falsehoods," in Proc. 60th Annual Meeting of the Association for Computational Linguistics (ACL), 2022, pp. 3214-3252.

[3] M. Lewis et al., "BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension," in Proc. 58th Annual Meeting of the Association for Computational Linguistics (ACL), 2020, pp. 7871-7880.

[4] C. Raffel et al., "Exploring the limits of transfer learning with a unified text-to-text transformer," Journal of Machine Learning Research, vol. 21, no. 140, pp. 1-67, 2020.

[5] B. S. Bloom, Taxonomy of Educational Objectives: The Classification of Educational Goals. New York: Longmans, Green, 1956.

[6] C. Lugaresi et al., "MediaPipe: A Framework for Building Perception Pipelines," arXiv preprint arXiv:1906.08172, 2019.

[7] T. Soukupova and J. Cech, "Real-Time Eye Blink Detection using Facial Landmarks," in Proc. 21st Computer Vision Winter Workshop (CVWW), 2016, pp. 1-8.

[8] M. Sandler, A. Howard, M. Zhu, A. Zhmoginov, and L. C. Chen, "MobileNetV2: Inverted Residuals and Linear Bottlenecks," in Proc. IEEE/CVF Conf. on Computer Vision and Pattern Recognition (CVPR), 2018, pp. 4510-4520.

[9] B. Kort, R. Reilly, and R. W. Picard, "An affective model of interplay between emotions and learning: Re-engineering educational pedagogy," in Proc. IEEE Int. Conf. on Advanced Learning Technologies (ICALT), 2001, pp. 43-46.

[10] P. A. Wozniak, "Optimization of repetition," Master's thesis, University of Technology in Poznan, Poland, 1990.

[11] H. Ebbinghaus, Memory: A Contribution to Experimental Psychology. New York: Teachers College, Columbia University, 1885.

[12] L. Li, W. Chu, J. Langford, and R. E. Schapire, "A contextual-bandit approach to personalized news article recommendation," in Proc. 19th Int. Conf. on World Wide Web (WWW), 2010, pp. 661-670.

[13] J. Sweller, "Cognitive load during problem solving: Effects on learning," Cognitive Science, vol. 12, no. 2, pp. 257-285, 1988.

[14] B. J. Zimmerman, "Becoming a self-regulated learner: An overview," Theory Into Practice, vol. 41, no. 2, pp. 64-70, 2002.

[15] I. J. Goodfellow et al., "Challenges in representation learning: A report on three machine learning contests," in Proc. Int. Conf. on Neural Information Processing (ICONIP), Springer, 2013, pp. 117-124.

[16] A. R. Hevner, S. T. March, J. Park, and S. Ram, "Design science in information systems research," MIS Quarterly, vol. 28, no. 1, pp. 75-105, 2004.

[17] J. Brooke, "SUS: A quick and dirty usability scale," Usability Evaluation in Industry, vol. 189, no. 194, pp. 4-7, 1996.

[18] European Parliament, "Regulation (EU) 2016/679 of the European Parliament and of the Council (General Data Protection Regulation)," Official Journal of the European Union, 2016.

[19] H. Qarbal et al., "Deep learning for real-time student engagement and posture analysis in virtual classrooms," Computers & Education: Artificial Intelligence, vol. 6, p. 100214, 2025.

[20] S. Vishnumolakala, R. S. Rao, and A. K. Singh, "Eye-tracking based student engagement detection in online learning environments," IEEE Access, vol. 11, pp. 56421-56434, 2023.

[21] Y. Wang, H. Li, and J. Zhang, "Federated learning for privacy-preserving emotion recognition systems," IEEE Access, vol. 10, pp. 113456-113468, 2022.

[22] C. Thomas and D. B. Jayagopi, "Predicting student engagement in classrooms using facial behavioral cues," in Proc. 1st ACM SIGCHI Int. Workshop on Multimodal Interaction for Education, 2017, pp. 33-40.

[23] M. A. A. Dewan, M. Murshed, and F. Lin, "Engagement detection in online learning: A review," Smart Learning Environments, vol. 6, no. 1, pp. 1-20, 2019.

[24] F. Pedregosa et al., "Scikit-learn: Machine Learning in Python," Journal of Machine Learning Research, vol. 12, pp. 2825-2830, 2011.

[25] J. Johnson, M. Douze, and H. Jégou, "Billion-scale similarity search with GPUs," IEEE Transactions on Big Data, vol. 7, no. 3, pp. 535-547, 2019.

[26] C. Y. Lin, "ROUGE: A package for automatic evaluation of summaries," in Text Summarization Branches Out, 2004, pp. 74-81.

[27] T. Mikolov, K. Chen, G. Corrado, and J. Dean, "Efficient estimation of word representations in vector space," arXiv preprint arXiv:1301.3781, 2013.

[28] A. Vaswani et al., "Attention is all you need," in Advances in Neural Information Processing Systems (NeurIPS), vol. 30, 2017.

[29] J. Devlin, M. W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of deep bidirectional transformers for language understanding," in Proc. NAACL-HLT, 2019, pp. 4171-4186.

[30] R. S. J. D. Baker and K. Yacef, "The state of educational data mining in 2009: A review and future visions," Journal of Educational Data Mining, vol. 1, no. 1, pp. 3-17, 2009.

GLOSSARY

Affective Computing: The study and development of computational systems that can recognize, interpret, and adapt to human emotional and psychological states.

Affective Readiness Index (ARI): A normalized composite metric (0 to 1.0) synthesizing real-time alertness, valence, and focus to quantify a student's cognitive availability for learning.

Bloom's Revised Taxonomy: A pedagogical hierarchical framework categorizing educational objectives into six cognitive levels: Remembering, Understanding, Applying, Analyzing, Evaluating, and Creating.

Contextual Bandit: A reinforcement learning algorithm that selects actions based on dynamic environmental context vectors to optimize cumulative scalar rewards without full state transitions.

Eye Aspect Ratio (EAR): A scalar geometric ratio measuring vertical eyelid aperture relative to horizontal eye width, utilized for blink frequency and ocular fatigue detection.

Hallucination (in LLMs): The generation of factually incorrect, unverified, or fabricated assertions by generative language models presented with high linguistic confidence.

Hybrid Geometric Fusion (HGF): An educational vision architecture cross-validating deep convolutional representations with physical facial muscle kinematic ratios.

MediaPipe Face Mesh: A machine learning pipeline estimating 468 3D facial landmark coordinates in real time from a single camera frame without persistent biometric storage.

Retrieval-Augmented Generation (RAG): An AI framework combining dense vector information retrieval with generative language models to ground answers in verified external documents.

SuperMemo SM-2: A foundational spaced repetition algorithm calculating expanding review intervals based on historical recall performance grades.

Zero-Storage Privacy Protocol: A security architecture ensuring that biometric sensory data is processed exclusively in volatile RAM and purged immediately via garbage collection without writing to persistent storage.

APPENDICES

Appendix A: Research Instruments and Verification Protocols

The research instruments utilized throughout this study encompass: (1) The FER-2013 benchmark dataset re-mapped to educational affective states; (2) The curated primary dataset of 1,920 video frames captured across 32 undergraduate engineering students under institutional ethical clearance; (3) Standardized 10-item System Usability Scale (SUS) survey questionnaires; and (4) The 500-question computer science examination validation benchmark. All functional testing procedures and microservice verification scripts are maintained within the project's institutional repository.

Appendix B: Academic Integrity and Generative AI Disclosure

In accordance with SLIIT academic integrity policies, generative AI and natural language processing tools were utilized strictly for code scaffolding, document formatting, grammatical refinement, and typographical styling. The primary research designs, machine learning models, training pipelines, empirical data collection, statistical analyses, and scientific conclusions were conceived, executed, and validated independently by the candidate authors.