

HC215-PA



Features

5MP Ultra HD Blacklight AI Network Camera with AI Noise Reduction and Low Noise

Dual-light full-color, auto ICR for night vision ultra-clear video surveillance

Supports human shape detection, face detection, and vehicle shape detection

Supports H.265 AI encoding

Specifications

Model	HC215-PA
System Architecture	
Operating System	Embedded RIOS design, dual-core 32-bit SDP
Image	
Pixels	500W
Resolution	Primary Stream: 2880×1616@20fps, 2560×1440@20fps, 2304×1296@25fps, 1920×1080@25fps; Sub Stream: 800*448@25fps
Shutter Speed	1/50(1/60) sec to 1/10000 sec

Sensor	1/3" B&W CMOS Sensor
Lens	2.8MM
Lens Aperture	F1.8
Field of View	Horizontal 105° , Vertical 80°
Minimum Illumination	Color: 0.0001 lux (Lux@F1.2); B/W: 0.0001 lux (Lux@F1.2)
Pan/Tilt Range	Horizontal 350° , Vertical 90°
Noise Reduction	Supports 2D/3D noise reduction
Audio	
Input	Built-in microphone
Output	Built-in speaker
Two-way intercom	Supported
Compression format	AAC/G711A
Video	
Video Processing	H.265AI encoding (compatible with H.265/H.264), dual bitstream, AVI format; adjustable bitrate from 0.1 Mbps to 10 Mbps
Frame Rate	Adjustable from 1 to 30 frames per second
Illumination Frequency	50 Hz, 60 Hz
Night Vision Light Source	Dual-light: Full-color night vision / Infrared night vision / Smart full-color
Recording	
Recording Method	Alarm-triggered recording, manual recording, 24-hour continuous recording
Recording Storage	Cloud storage
Features	
Smart Functions	Motion Detection, Human Detection, Vehicle Detection
Alarm Notification	Mobile App Push Notifications
Network	
ONVIF	Supported
Wide Dynamic Range	Supports Digital Wide Dynamic Range
Network Protocols	Supports RTSP/FTP/DHCP/NIP/UPnP and other network protocols
Power	
POE Power Supply	Supported
Charging Voltage	DC12V 2A

Power Consumption	≤3W
Interfaces/Buttons	
Power Port	DC12V 2A
Ethernet Port	Supported
Reset Button	Supported
Installation	
Mounting Methods	Wall-mount, Ceiling-mount
Mounting Specifications	1/4" Universal Screw Holes
Environment	
Dust/Water Resistance	IP65
Operating Temperature	-10℃~65℃
Storage Temperature	-20° C ~ 60° C
Operating Humidity	15%~85%RH non-condensing
Specifications	
Material	ABS+PC
Color	White