

HD118-PZ



Features

Supports face detection, human figure detection, and vehicle type detection;

8.0MP resolution, low-light performance, delivering clear and detailed images;

Features 2D/3D noise reduction and digital wide dynamic range;

Advanced H.265AI video compression (compatible with H.265/H.264) delivers ultra-low bitrate with high-definition quality;

Lightning protection compliant with national standard GB/T17626.5 and international standard IEC61000-4-5;

Supports ONVIF protocol for integration with third-party backends/platforms; enables mobile monitoring (iOS, Android);

Supports web interface, CMS, and MYEYE central management platform software; provides SDK for development;

Supports multiple cloud technologies to achieve network penetration, front-end/back-end integration, and alarm notifications to mobile devices.

Specifications

Model	HD118-PZ
System Architecture	
Operating System	Embedded RIOS design, dual-core 32-bit SDP
Image	
Pixels	800W
Resolution	Main stream: 3480×2160@15fps Sub stream: 800×448@25fps
Shutter Speed	1/50(1/60) sec to 1/10000 sec
Sensor	1/2.8" IMX415 backlight CMOS Sensor
Lens	4.7-94MM
Minimum Illumination	Color: 0.0001 lux (Lux@F1.2); B/W: 0.0001 lux (Lux@F1.2)
Pan/Tilt Range	Horizontal 350° , Vertical 90°
Noise Reduction	Supports 2D/3D noise reduction
Audio	
Input	Built-in microphone
Output	Built-in speaker
Two-way intercom	Supported
Compression format	AAC/G711A
Video	
Video Processing	H.265AI encoding (compatible with H.265/H.264), dual bitstream, AVI format; adjustable bitrate from 0.1 Mbps to 10 Mbps
Frame Rate	Adjustable from 1 to 30 frames per second
Illumination Frequency	50 Hz, 60 Hz
Night Vision Light Source	Dual-light: Full-color night vision / Infrared night vision / Smart full-color
Recording	
Recording Method	Alarm-triggered recording, manual recording, 24-hour continuous recording
Recording Storage	Micro supports SD card storage (up to 256GB) and cloud storage
Features	
Smart Functions	Motion Detection, Human Detection, Vehicle Detection
Alarm Notification	Mobile App Push Notifications

Network	
ONVIF	Supported
Wide Dynamic Range	Supports Digital Wide Dynamic Range
Network Protocols	Supports RTSP/FTP/DHCP/NIP/UPnP and other network protocols
Power	
POE Power Supply	Supported
Charging Voltage	DC12V 2A
Power Consumption	≤3W
Interfaces/Buttons	
Power Port	DC12V 2A
Network Interface	Supports 1*RJ45 network interface
Installation	
Mounting Methods	Wall-mount
Mounting Specifications	1/4" Universal Screw Holes
Environment	
Dust/Water Resistance	IP65
Operating Temperature	-10℃~65℃
Storage Temperature	-20° C ~ 60° C
Operating Humidity	15%~85%RH non-condensing
Specifications	
Material	ABS+PC
Color	White