

# 12MP HD Fixed Bullet POE Camera

YHB812-PA



12MP



Dual-light



Ultra motion detection



Built-in Mic



Speaker



Edge storage



IP67



PoE

## Features

High quality image with 12 MP, 1/2.7" CMOS sensor

12 MP (3840 × 2880)@20 fps; 5 MP (3072 × 1728)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 1080P (1920 × 1080)@30/25 fps

Supports ultra motion detection

Smart dual-light ensures high quality image

Ultra 265, H.265, H.264

Built-in mic and speaker

2D/3D DNR (digital noise reduction)

ROI (region of interest) ensures image quality in areas of interest with low bandwidth

Up to 30 m (98.4 ft.) IR and warm light distance

MicroSD, up to 512 GB

IP67 protection

DC 12 V, PoE power supply

3-axis

## Specifications

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| Model                              | YHB812-PA                                            |
| Camera                             |                                                      |
| Max Resolution                     | 12 MP                                                |
| Sensor                             | 1/2.7" CMOS                                          |
| Min. Illumination                  | Color: 0.05 Lux (F1.6, AGC ON), 0 Lux with IR        |
| Day/Night                          | IR- cut filter with auto switch (ICR)                |
| Shutter                            | Auto/Manual, 1 ~ 1/100000s                           |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360° |
| S/N                                | >52 dB                                               |
| WDR                                | DWDR                                                 |
| Lens                               |                                                      |
| Focal Length                       | 2.8 mm                                               |
| Iris Type                          | Fixed                                                |
| Iris                               | F1.6                                                 |
| Field of View (H)                  | 106.5°                                               |
| Field of View (V)                  | 59.1°                                                |
| Field of View (D)                  | 121.7°                                               |
| Lens Type                          | Fixed                                                |
| DORI                               |                                                      |
| DORI Distance (Lens)               | 2.8 mm                                               |
| DORI Distance (Detect)             | 84.0 m (275.6 ft.)                                   |
| DORI Distance (Observe)            | 33.6 m (110.2 ft.)                                   |
| DORI Distance (Recognize)          | 16.8 m (55.1 ft.)                                    |
| DORI Distance (Identify)           | 8.4 m (27.6 ft.)                                     |
| Illuminator                        |                                                      |
| Supplemental Light                 | Dual light                                           |
| Illumination Distance (IR)         | 30 m (98.4 ft.)                                      |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)                                      |
| Wavelength                         | 850 nm                                               |
| Video                              |                                                      |
| Video Compression                  | Ultra 265, H.265, H.264                              |

|                         |                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H.264 Code Profile      | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                      |
| Frame Rate              | Main Stream: 12MP (3840 × 2880), max. 20 fps; 5 MP (3072 × 1728), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps<br>Sub Stream: 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |
| Video Bit Rate          | 128 Kbps to 16 Mbps                                                                                                                                                                                                                                                                                                                               |
| U-code                  | Support                                                                                                                                                                                                                                                                                                                                           |
| OSD                     | Up to 4 OSDs                                                                                                                                                                                                                                                                                                                                      |
| Privacy Mask            | Up to 4 areas                                                                                                                                                                                                                                                                                                                                     |
| ROI                     | Support                                                                                                                                                                                                                                                                                                                                           |
| Video Stream            | Dual streams                                                                                                                                                                                                                                                                                                                                      |
| Image                   |                                                                                                                                                                                                                                                                                                                                                   |
| White Balance           | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance                                                                                                                                                                                                                                                                          |
| Digital Noise Reduction | 2D/3D DNR                                                                                                                                                                                                                                                                                                                                         |
| Smart IR                | Support                                                                                                                                                                                                                                                                                                                                           |
| Flip                    | Normal, Flip vertical, Flip horizontal, 180°                                                                                                                                                                                                                                                                                                      |
| Dewarping               | N/A                                                                                                                                                                                                                                                                                                                                               |
| HLC                     | Support                                                                                                                                                                                                                                                                                                                                           |
| BLC                     | Support                                                                                                                                                                                                                                                                                                                                           |
| Defog                   | Digital defog                                                                                                                                                                                                                                                                                                                                     |
| Image Stabilization     | N/A                                                                                                                                                                                                                                                                                                                                               |
| Events                  |                                                                                                                                                                                                                                                                                                                                                   |
| Basic Detection         | Motion detection, Ultra motion detection (based on human body and vehicle detection), Tampering alarm, Audio detection                                                                                                                                                                                                                            |
| General Function        | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                                                                                                                                                                     |
| Audio                   |                                                                                                                                                                                                                                                                                                                                                   |
| Audio Compression       | G.711U, G.711A                                                                                                                                                                                                                                                                                                                                    |
| Audio Bitrate           | 64 Kbps                                                                                                                                                                                                                                                                                                                                           |
| Two-way Audio           | Support                                                                                                                                                                                                                                                                                                                                           |
| Suppression             | Support                                                                                                                                                                                                                                                                                                                                           |
| Sampling Rate           | 8 kHz                                                                                                                                                                                                                                                                                                                                             |
| Storage                 |                                                                                                                                                                                                                                                                                                                                                   |
| Edge Storage            | Micro SD, up to 512 GB                                                                                                                                                                                                                                                                                                                            |
| Network Storage         | ANR, NAS (NFS)                                                                                                                                                                                                                                                                                                                                    |

| Network                |                                                                                                                                                                                                            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocols              | IPv4, IPv6, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, IGMP, SMTP, QoS, SSL/TLS, SNMP                                                                            |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API, SDK                                                                                                                                                          |
| User/Host              | Up to 32 users. 3 user levels: administrator, common user and operator                                                                                                                                     |
| Security               | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Web Browser            | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| Interface              |                                                                                                                                                                                                            |
| Built-in Mic           | Yes                                                                                                                                                                                                        |
| Built-in Speaker       | Yes                                                                                                                                                                                                        |
| Network                | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                                                                                       |
| General                |                                                                                                                                                                                                            |
| Protection             | IP67                                                                                                                                                                                                       |
| Power Consumption      | Max. 4.7 W                                                                                                                                                                                                 |
| Power                  | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                                                                            |
| Power Interface        | Ø5.5 mm coaxial power plug                                                                                                                                                                                 |
| Dimensions             | 206.1 mm × 75.7 mm × 73.8 mm (8.1" × 3.0" × 2.9") (L × W × H)                                                                                                                                              |
| Weight                 | 0.54 kg (1.19 lb.)                                                                                                                                                                                         |
| Material               | Graphene + Metal                                                                                                                                                                                           |
| Working Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                    |
| Storage Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                                                                                    |
| Surge Protection       | 4 KV                                                                                                                                                                                                       |
| Reset Button           | N/A                                                                                                                                                                                                        |
| Web Client Language    | 4 Languages: English, Russian, Spanish, Vietnamese                                                                                                                                                         |

## Dimensions

