

## 16CH Network Video Recorder

YNVR-P-8



### Key Features

- Support Ultra 265/H.265/H.264 video formats
- 8/16-channel input
- Plug & Play with 8 independent PoE network interfaces
- Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T ) and RTSP protocols
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDD up to 6TB
- Support cloud upgrade

### Specifications

| Model             | YNVR-P-8 |
|-------------------|----------|
| Video/Audio Input |          |
| IP Video Input    | 16-ch    |
| Network           |          |

|                                            |                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Incoming Bandwidth                         | 64Mbps                                                                                                                                                                                                                            |
| Outgoing Bandwidth                         | 48Mbps                                                                                                                                                                                                                            |
| Remote Users                               | 128                                                                                                                                                                                                                               |
| Protocols                                  | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP                                                                                                                                                                 |
| <b>Video/Audio Output</b>                  |                                                                                                                                                                                                                                   |
| HDMI/VGA Output                            | HDMI:<br>4K(3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz<br>VGA:<br>1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| Recording Resolution                       | 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF                                                                                                                                                                                        |
| Audio Output                               | 1-ch, RCA                                                                                                                                                                                                                         |
| Audio Compression                          | G.711A, G.711U                                                                                                                                                                                                                    |
| Synchronous Playback                       | 16-ch                                                                                                                                                                                                                             |
| Liveview display                           | 1/4/6/8/9/16                                                                                                                                                                                                                      |
| Corridor Mode Screen                       | 3/4/5/7/9/10/12/16                                                                                                                                                                                                                |
| <b>Snapshot</b>                            |                                                                                                                                                                                                                                   |
| FTP/Schedule/Event Snapshot                | 1-ch snapshot, up to D1 resolution                                                                                                                                                                                                |
| <b>Decoding</b>                            |                                                                                                                                                                                                                                   |
| Decoding format                            | Ultra 265/H.265/H.264                                                                                                                                                                                                             |
| Liveview/Playback                          | 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF                                                                                                                                                                                        |
| Capability                                 | 1 x 4K@30, 4 x 5MP@25, 4 x 4MP@25, 4 x 3MP@25, 4 x 1080p@30, 8 x 720p@30, 16 x D1@25                                                                                                                                              |
| <b>Hard Disk</b>                           |                                                                                                                                                                                                                                   |
| SATA                                       | 1 SATA interface                                                                                                                                                                                                                  |
| Capacity                                   | up to 6TB for each disk                                                                                                                                                                                                           |
| <b>Smart</b>                               |                                                                                                                                                                                                                                   |
| VCA Detection by Camera                    | Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Audio Detection                                                                                                                                                |
| VCA Search                                 | Behavior Search                                                                                                                                                                                                                   |
| Smart Intrusion Prevention (SIP) by Camera | 4-ch(supports channel 1-4; Alarm only, no image)                                                                                                                                                                                  |
| <b>General Alarm</b>                       |                                                                                                                                                                                                                                   |
| General Alarm                              | Motion, Tampering, Human Body Detection, Video Loss, Alarm Input                                                                                                                                                                  |
| Alert Alarm                                | IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal                                                                                  |
| <b>External Interface</b>                  |                                                                                                                                                                                                                                   |
| Network Interface                          | 1 RJ45 10M/100M self-adaptive Ethernet Interface                                                                                                                                                                                  |

|                      |                                                                     |
|----------------------|---------------------------------------------------------------------|
| USB Interface        | Rear panel: 2 x USB2.0                                              |
| RS232                | NA                                                                  |
| RS485                | NA                                                                  |
| Alarm In             | NA                                                                  |
| Alarm Out            | NA                                                                  |
| PoE                  |                                                                     |
| Interface            | 8 RJ45 10M/100M self-adaptive Ethernet Interface                    |
| Max Power            | Max 30W for single port<br>Max 75W in total                         |
| Supported Standard   | IEEE 802.3at, IEEE 802.3af                                          |
| General              |                                                                     |
| Power Supply         | 52V DC<br>Power Consumption: ≤9 W (without HDD)                     |
| Working Environment  | -10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing) |
| Dimensions (W×D×H)   | 270mm × 205mm × 46mm (10.6"×8.1"×1.8")                              |
| Weight (without HDD) | ≤0.8 kg (1.76 lb)                                                   |