



## Lab 10.2: Launching an S3 Bucket

**Step1:** To start the lab session, choose **Start Lab** in the upper-right corner of the page.




**Step2:** Choose the **Services** menu, locate the **Storage services**, and select **S3**.




## Lab 10.2: Launching an S3 Bucket

Step3: Select **Create bucket** on the right side of the page.




Step4: For **Bucket name**, enter a unique Domain Name System (DNS)-compliant name for your new bucket.




## Lab 10.2: Launching an S3 Bucket

**Step5:** For **Region**, choose the AWS Region where you want the bucket to reside. Choose a Region close to you to minimize latency and costs, or to address regulatory requirements. Objects stored in a Region never leave that Region unless you explicitly transfer them to another Region.




**Step6:** Uncheck the **Block all public access** box because you want to be able to test if the website is working.




## Lab 10.2: Launching an S3 Bucket

Step7: Below the warning, check the box next to **I acknowledge that....**




Step8: Scroll to the bottom of the page, and select **Create bucket**.




## Lab 10.2: Launching an S3 Bucket

### Step9: Successfully created Bucket.



### Step10: Choose the link for your bucket's name, and then select the permission tab.







## Lab 10.2: Launching an S3 Bucket

Step11: In the **Bucket policy** section, choose **Edit**.

To grant public read access for your website, copy the following bucket policy, and paste it in the policy editor.




Step12: In the policy, replace **example-bucket** with the name of your bucket.  
Select **Save changes**.




## Lab 10.2: Launching an S3 Bucket

Step13: Open the context menu (right-click) for the following link, and then choose **Save link as:** [index.html](#)




Step14: Save the index.html file to your local computer.



## Lab 10.2: Launching an S3 Bucket

Step15: In the console, choose the **Objects** tab.




Step16: Upload the index.html file to your bucket.

Choose **Upload**.


Drag and drop the index.html file onto the upload page.

As an alternative, choose **Add files**, navigate to the file, and choose **Open**.






### Step17: Expand the **Permissions** section.




### Step18: Under **Predefined ACLs**, select **Grant public-read access**. A warning message similar to **Granting public-read access is not recommended** appears below the setting you selected.




## Lab 10.2: Launching an S3 Bucket

**Step19:** Expand the **Properties** section. Ensure that the **Standard** storage class is selected.




**Step20:** At the bottom of the page, choose **Upload**.




## Lab 10.2: Launching an S3 Bucket

Step21: Choose **Close**. The index.html file appears in the **Objects** list.




Step22: Select the **Properties** tab, and scroll down to the **Static website hosting** section. Choose Edit, Select Enable




## Lab 10.2: Launching an S3 Bucket

**Step23:** In the **Index document** text box, enter bucket-name.html Select **Save changes**.



**Step24:** Scroll down to the **Static website hosting** section again, and copy the **Bucket website endpoint URL** to your clipboard.



## Lab 10.2: Launching an S3 Bucket

Step24: Static hosted website with EBS storage.

