

# Experiment NO. 9

## Kernel SVM

### Importing the libraries

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

### Importing the dataset

```
In [2]: dataset = pd.read_csv('Social_Network_Ads.csv')
X = dataset.iloc[:, [2, 3]].values
y = dataset.iloc[:, -1].values
```

### Splitting the dataset into the Training set and Test set

```
In [3]: from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_
```

### Feature Scaling

```
In [4]: from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

### Training the Kernel SVM model on the Training set

```
In [5]: from sklearn.svm import SVC
classifier = SVC(kernel = 'rbf', random_state = 0)
classifier.fit(X_train, y_train)
```

```
Out[5]: SVC(random_state=0)
```

### Predicting the Test set results

```
In [6]: y_pred = classifier.predict(X_test)
```

### Making the Confusion Matrix

```
In [7]: from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
print(cm)
```


```
[[3 0]
 [0 5]]
```

## Visualising the Training set results

```
In [8]: from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('Kernel SVM (Training set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()
```

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.



## Visualising the Test set results

```
In [9]: from matplotlib.colors import ListedColormap
X_set, y_set = X_test, y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                     np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
```

```

        alpha = 0.75, cmap = ListedColormap(['red', 'green']))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(['red', 'green'])(i), label = j)
plt.title('Kernel SVM (Test set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.

\*c\* argument looks like a single numeric RGB or RGBA sequence, which should be avoided as value-mapping will have precedence in case its length matches with \*x\* & \*y\*. Please use the \*color\* keyword-argument or provide a 2-D array with a single row if you intend to specify the same RGB or RGBA value for all points.

