1. Connect the scanner

Read pages 1-4 first. Setup barcodes are on pages 5-6.

How the three pieces work together
The NETUM sends a barcode number to your phone/tablet. Tech Command links that number to an asset record. NIIMBOT prints labels from its own app. Both devices use the same phone/tablet.

Item	Connect it here	Purpose
NETUM C750	Phone/tablet Bluetooth settings	Enter scanned barcode text
NIIMBOT M2_H	Inside the NIIMBOT app	Print PM and asset labels
IntelliScanner tags	No connection or printing needed	Preprinted permanent asset ID

1. **Charge and wake it.** Charge the scanner and tablet. Press the scanner trigger. Unplug its USB data cable/receiver while setting up Bluetooth.
2. **Scan A, B and C on page 5.** A selects Bluetooth; B clears the old pairing; C selects HID keyboard mode. These codes configure a C750 only. Confirm C750 on the scanner before using them.
3. **Pair in phone/tablet Settings.** Open Bluetooth settings and select the scanner name shown, commonly **NETUM Bluetooth** or **barcode scanner**. If an old entry exists, forget it and pair again. Choose the scanner, not the printer.
4. **Scan D, E and F.** D sends scans immediately; E leaves automatic Enter off; F selects trigger scanning. Start with these settings so a scan does not unexpectedly submit a form.
5. **Scan one real tag into Notes.** Open a blank note, tap the text area and scan an IntelliScanner tag. Every digit must match the label, including starting zeros. A scanner app is not needed for HID input.
6. **Keep this scanner with that tablet.** Reconnection should use the same paired device. Use B only when changing tablets or repairing a failed pairing. If needed, code G on page 6 selects US English.

Ready for the next step
If the complete tag number appears correctly in Notes, scanner input is working. Next, set up NIIMBOT on page 2; then link one asset on page 3.

2. Connect the printer

Your photos identify the printer as NIIMBOT M2_H. It uses labels plus a thermal-transfer ribbon.

1. **Load the consumables.** Remove shipping tape as directed. Use M2_H-compatible labels and ribbon. Seat and lock the ribbon cartridge. Load labels with the print side facing down; adjust the guides, pull the end through the outlet and close the lid.
2. **Turn it on.** Charge from its Type-C port using a suitable 5V/2A supply. Hold Power/Menu until the screen lights. Use Paper Feed/Select to advance a label when outside the menu.
3. **Install NIIMBOT.** Use the commercial **NIIMBOT** app from the App Store or Google Play. Allow Bluetooth access and any requested Android Nearby Devices/location permission.



Your M2_H. Match the device ID on its screen when connecting.

4. **Connect inside the NIIMBOT app.** Use its device-connect control and select the M2_H whose ID matches the printer screen. Enable phone Bluetooth. If the app requests a printer PIN, the manufacturer lists **0000** or **1234**.
5. **Match the label roll.** Confirm the exact width/height and paper type in the editor. The M2_H accepts 20-50 mm wide media. Use white labels and a black ribbon for dependable barcodes. If feed alignment is wrong, use the printer menu: Power/Menu to select Paper Calibration, then Paper Feed/Select to confirm.
6. **Save these two templates.** Create simple text labels in the editing canvas. Replace bracketed fields for each asset. Start by printing just one label.

Template 1: TechFlex PM	Template 2: Service required
TECHFLEX | PM Asset: [permanent tag number] PM: [actual completed date] Due: [approved due date] Tech: [name] | Result: [result]	**TECHFLEX | SERVICE REQUIRED** Asset: [permanent tag number] Date: [date] WO: [work order] Contact: 877-231-8324

To scan into a label: tap its editable text/barcode-value field and scan the permanent tag. If that field will not accept scanner input, scan into Notes, copy the number and paste it. A printed sticker does not update Tech Command; save the service result there separately.

Your preprinted IntelliScanner tags do not go through this printer. Keep them as the primary asset tags; use the M2_H mainly for PM/service stickers and approved replacements. Due dates come from the approved maintenance schedule.

3. Link a tag to Tech Command

Do this once per asset. The printed tag number is the lookup key, not the manufacturer serial number.

Software step to confirm during setup
These instructions describe field purposes; live Tech Command screens have not been inspected or changed for this guide. Use its existing asset registry and barcode/tag field. If that field or lookup is missing, software support must be added before this workflow can run.

1. **Open the correct facility and unit.** Go to **app.techcommandhq.com**. Search the existing inventory by manufacturer serial number before creating an asset. If the unit already has a TechFlex tag, keep it.
2. **Choose one unused tag.** Scan it into the asset search first to check it is not already assigned. Do not use a tag that brings up another unit. IntelliScanner supplies the number; do not replace it with an invented sequence.
3. **Add the number to the asset.** Open the existing record, or create one only if the unit is genuinely new. Tap the asset barcode/tag/label-alias field and scan. Store the exact text. Keep the internal record ID and OEM serial number separate.
4. **Identify the physical unit.** Enter or verify manufacturer, model, OEM serial, facility and room/location. Do not assume a scanned manufacturer barcode is a unique unit serial number; it may identify only a product/model.
5. **Apply the permanent tag and save.** Use an approved, clean, dry, flat, accessible surface. Avoid removable parts, vents, controls and manufacturer labels. Photograph the tag and unit nameplate, then save the asset record.
6. **Check the link.** Return to asset search, tap the barcode search input and scan that tag. Tap Search if needed. It must find the same unit at the right facility. Open it and match the model/serial before using the workflow.

Keep these values separate

Value	Where it belongs
00123456 (example only)	External tag/barcode value; save as text to preserve the zeros
Manufacturer serial number	OEM serial field; read from the equipment nameplate
Internal asset record ID	Keep the existing system ID; link the tag as its barcode/alias
PM date, result and notes	Service history for that same asset; the permanent ID stays the same

A barcode can contain the same ID in Code 39 or Code 128. The lookup uses the decoded value. A camera feature that reads QR codes is separate from NETUM keyboard input; NETUM needs a focused text field.

4. Useful functions and final check

Use the manual phone/tablet workflow first. Hardware compatibility does not confirm a live software integration.

Function	Simple method
Find an existing asset	Tap Tech Command barcode search, scan and confirm the unit. Requires saved tag mapping and working lookup.
Print PM/service stickers	Use the saved NIIMBOT template and the same permanent asset number; save results in Tech Command too.
Replace a damaged asset label	In NIIMBOT, add a barcode (Code 128 if offered) with the existing tag value and readable text. Check the printed scan. Keep that ID on the same unit.
Batch-print labels	NIIMBOT supports table/Excel import. Use that option when available; keep the ID column as text and verify one print before a batch.
Use the scanner on a computer	For NETUM, use USB HID with a data cable or its 2.4 GHz HID receiver. For M2_H, use NIIMBOT desktop software with a data-capable USB cable.
Add a QR shortcut	Put a verified, stable Tech Command asset link in a NIIMBOT QR label. Check it on a phone. A scanned URL does not automatically open itself.
Collect barcode numbers offline	Storage mode saves barcode numbers only. Upload into a blank list for office review; it does not log asset details or completed PM work.

Before handing this to technicians

- [ ] Scan a real IntelliScanner tag into Notes; the full value matches.
- [ ] Save that value on the correct asset; scan again and find the same record.
- [ ] Sign in as a technician and confirm access to that facility/job and its workflow.
- [ ] Print one PM/service sticker. If it has a barcode, scan it and verify the value.
- [ ] Confirm the saved record survives closing and reopening the page.

If lookup or direct printing is missing
Tech Command needs exact barcode text, duplicate protection, facility lookup and service history linked to the asset. Direct M2_H printing requires a separate integration checked on the actual tablet/printer. Pairing alone does not add these functions.

Manufacturer references

NETUM C750 official manual and product resources

NIIMBOT M2_H manufacturer product information

NIIMBOT M2_H manufacturer manual (hosted copy)

NIIMBOT app, PDF import and desktop download

IntelliScanner: Code 39 tags and scanner compatibility

Checked 05 Oct 2026. Hardware instructions use manufacturer material and your photos/manual. Asset procedures are TechFlex recommendations. Physical scanning, printing and live Tech Command behavior remain to be confirmed by the first-time user.

5. Scanner setup barcodes

Scan the bars with the NETUM. Do not type these commands. Print on plain Letter paper at 100%.

First-time setup or a new tablet: scan A, B and C in order. Aim at only one code at a time; cover adjacent codes if needed. These are original codes from your supplied C750 manual.

A **Bluetooth transmission**

Send the scans by Bluetooth.



Original C750 manual, page 17

B **Clear old pairing**

Disconnects the previous device. First setup/re-pairing only.



Original C750 manual, page 18

C **HID keyboard mode**

Lets the scanner type into normal text fields.



Original C750 manual, page 17

Pause here and pair the tablet
Open phone/tablet Settings > Bluetooth. Select the NETUM scanner. Once connected, scan D, E and F below.

D **Normal mode**

Send each scan immediately; use for daily work.



Original C750 manual, page 5

E **No automatic Enter**

Leaves Enter off. Tap Search yourself after scanning.



Original C750 manual, page 44

F **Trigger scanning**

Press the trigger for each scan.



Original C750 manual, page 46

Now return to page 1, step 5: scan one real IntelliScanner tag into Notes and compare all digits. Keep this sheet with the office kit; configuration codes are not asset tags.

6. Help and optional settings

Use only the setting needed. Daily work uses Normal mode, HID and no automatic Enter.

G US English keyboard

Use with a US English tablet/computer keyboard layout.



Original C750 manual, page 29

H Enable Code 39

Use if your IntelliScanner tags are not being read.



Original C750 manual, page 76

I Show/hide iOS keyboard

Use when the iPhone/iPad onscreen keyboard is hidden.



Original C750 manual, page 18

J Optional automatic Enter

Office only: enable after checking that Enter runs asset search safely.



Original C750 manual, page 44

If J submits a form, creates extra lines or opens the wrong action, scan E on page 5 to return to manual Search. Terminator settings do not remove other custom suffixes; if output is still wrong, inspect those settings in the C750 manual.

Fix the problem at the right place

What you see	Next step
No scanner entry in Bluetooth	Wake/charge it; scan A. Forget the old scanner entry, then use B and C before pairing again. Turn Bluetooth off on the old tablet if it reconnects there.
Beep, but no input	Tap Notes and scan. Check connection and Normal mode D. If only the app fails, check its input/lookup or report it to the office.
Wrong/truncated tag number	Use G with US English input. Check for custom prefix/suffix, hidden characters, Code 39 check-digit or start/stop settings. Restore exact tag output before use.
Printer connects but labels are blank/misaligned	Check compatible labels, locked ribbon and closed cover. Match the roll size/type; use Paper Calibration for feed issues.
Tech Command shows white screen/login error	A scanner setting will not fix the app. Report the device, browser and error; keep barcode/serial notes for later entry.

One permanent ID per unit. Confirm the tag and record after troubleshooting. Save the service record separately from printing the PM sticker.