Scenario 1: Using Frida to Test Your Android App - Full Guide

Step 1: Requirements

- PC with Windows/macOS/Linux

- Rooted Android device or rooted emulator

- Frida CLI (frida, frida-trace, etc.)

- Frida Server (same version as Frida CLI)

- ADB for device communication

- Optional: MobSF, Objection

Step 2: Install Frida on PC

$ pip install frida-tools

Check version with: frida --version

Step 3: Install Frida Server on Android

1. Get Android architecture:

$ adb shell getprop ro.product.cpu.abi

2. Download frida-server from: https://github.com/frida/frida/releases

3. Push and run:

$ adb push frida-server /data/local/tmp/

$ adb shell "chmod 755 /data/local/tmp/frida-server"

$ adb shell "/data/local/tmp/frida-server &"

Step 4: Identify Your App

```
$ frida-ps -Uai
```

Step 5: Inject JavaScript into App

Example hook:

```
Java.perform(function () {
    var LoginClass = Java.use("com.example.myapp.LoginManager");
    LoginClass.authenticate.implementation = function (username, password) {
        console.log("Hooked Login - Username: " + username + " Password: " + password);
        return true;
    };
});
```

Run it:

```
$ frida -U -n com.example.myapp -l login_hook.js
```

Use Cases for Frida Testing

- Bypass login
- Dump credentials
- Intercept API traffic
- Disable SSL pinning
- Modify in-app logic
- Extract sensitive data

Pro Tip: Use frida-trace

```
$ frida-trace -U -n com.example.myapp -m "com.example.myapp.LoginManager.authenticate"
```

Resources

- Frida Docs: https://frida.re/docs/home/

- Frida CodeShare: https://codeshare.frida.re/

- Objection: https://github.com/sensepost/objection

- MobSF: https://github.com/MobSF/Mobile-Security-Framework-MobSF