RV College of Engineering®

Artificial Intelligence and Machine learning

IS353IA

UNIT 5

Mekhala V Purohit

Assistant Professor

Department of Computer Science and Engineering

RVCE

All material presented in this PowerPoint is credited to the respective authors of standard textbooks, reference presentations shared by senior faculty at **RVCE**, and authentic internet sources.

Note to Students:

This presentation is meant **only for classroom reference and conceptual understanding**.

For exam and detailed preparation, please refer to the **textbook extracts and materials shared in Google Classroom**, as the content here is a **summary version** and not exhaustive.

Go, change the world®

CONTENTS

Unsupervised Learning: Overview, What Is Cluster Analysis, Different Types of Clustering's, Different Types of Clusters.

K-means: The Basic K-means Algorithm, Additional Issues, Bisecting K-means, K-means and Different Types of Clusters, Strengths and Weaknesses, K-means as an Optimization Problem.

Cluster Evaluation: Overview, Unsupervised Cluster Evaluation Using Cohesion and Separation, Unsupervised Cluster Evaluation Using the Proximity Matrix, Determining the Correct Number of Clusters, Supervised Measures of Cluster Validity, Assessing the Significance of Cluster Validity Measures, Choosing a Cluster Validity Measure.

RV College of Engineering®

What is Cluster Analysis?

- Cluster: A collection of data objects
  - similar (or related) to one another within the same group
  - dissimilar (or unrelated) to the objects in other groups
- Cluster analysis (or *clustering*, *data segmentation*, …)
  - Finding similarities between data according to the characteristics found in the data and grouping similar data objects into clusters
- Unsupervised learning: no predefined classes (i.e., *learning by observations* vs. learning by examples: supervised)
- Typical applications
  - As a stand-alone tool to get insight into data distribution
  - As a preprocessing step for other algorithms

Clustering for Data Understanding and Applications

- Biology: taxonomy of living things: kingdom, phylum, class, order, family, genus and species
- Information retrieval: document clustering
- Land use: Identification of areas of similar land use in an earth observation database
- Marketing: Help marketers discover distinct groups in their customer bases, and then use this knowledge to develop targeted marketing programs
- City-planning: Identifying groups of houses according to their house type, value, and geographical location
- Earth-quake studies: Observed earth quake epicenters should be clustered along continent faults
- Climate: understanding earth climate, find patterns of atmospheric and ocean
- Economic Science: market resarch

Clustering as a Preprocessing Tool (Utility)

- Summarization:
  - Preprocessing for regression, PCA, classification, and association analysis
- Compression:
  - Image processing: vector quantization
- Finding K-nearest Neighbors
  - Localizing search to one or a small number of clusters
- Outlier detection
  - Outliers are often viewed as those “far away” from any cluster

What is Cluster Analysis?

- Finding groups of objects such that the objects in a group will be similar (or related) to one another and different from (or unrelated to) the objects in other groups



Quality: What Is Good Clustering?

- A good clustering method will produce high quality clusters with
  - high intra-class similarity
  - low inter-class similarity
- The quality of a clustering result depends on both the similarity measure used by the method and its implementation
- The quality of a clustering method is also measured by its ability to discover some or all of the hidden patterns

Measure the Quality of Clustering

- Dissimilarity/Similarity metric: Similarity is expressed in terms of a distance function, typically metric: $d(i, j)$
- There is a separate "quality" function that measures the "goodness" of a cluster.
- The definitions of distance functions are usually very different for interval-scaled, boolean, categorical, ordinal ratio, and vector variables.
- Weights should be associated with different variables based on applications and data semantics.
- It is hard to define "similar enough" or "good enough"
  - the answer is typically highly subjective.

Data Type	Distance / Similarity Measure
Interval-scaled (numeric)	Euclidean, Manhattan
Boolean	Hamming distance
Categorical	Simple matching, Jaccard
Ordinal	Rank-based distance
Ratio	Normalized distance
Vector (text, images)	Cosine similarity

Notion of a Cluster can be Ambiguous

How many clusters?

Six Clusters

Two Clusters



Four Clusters

RV College of Engineering®

TYPES OF DATA IN CLUSTER ANALYSIS

Data Structures

Data matrix(two modes)

A **data matrix** represents the **original dataset**.

Meaning of symbols

- **Rows (n)** → Objects / data points
- **Columns (p)** → Features / attributes
- xij → value of **j^th^ feature** of **i^th^ object**

Example:

- Rows → Students
- Columns → Marks in Math, Physics, CS

$$\begin{bmatrix} x_{11} & \cdots & x_{1f} & \cdots & x_{1p} \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ x_{i1} & \cdots & x_{if} & \cdots & x_{ip} \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ x_{n1} & \cdots & x_{nf} & \cdots & x_{np} \end{bmatrix}$$

Dissimilarity matrix(one mode)

A **dissimilarity matrix** stores **pairwise distances** between objects.

Key points

- Matrix size → **n × n**
- Diagonal elements → **0** (distance of an object to itself)
- d(i,j)→ distance between object *i* and object *j*

$$\begin{bmatrix} 0 & & & & \\ d(2,1) & 0 & & & \\ d(3,1) & d(3,2) & 0 & & \\ \vdots & \vdots & \vdots & & \\ d(n,1) & d(n,2) & \cdots & \cdots & 0 \end{bmatrix}$$

RV College of Engineering®

Type of data in clustering analysis

- Interval-scaled variables
- Binary variables
- Nominal, ordinal, and ratio variables
- Variables of mixed types

RV College of Engineering®

Inter Values

What are interval-valued variables?

•Numeric variables where **differences matter**

•Example: height, weight, temperature, marks

Why standardize data?

Different features may have **different scales**.

•Height → 150–180

•Weight → 40–90

Without standardization, **large-scale features dominate distance**.

Interval-valued variables

- Standardize data
  - Calculate the mean absolute deviation:

$$s_f = \frac{1}{n}(|x_{1f} - m_f| + |x_{2f} - m_f| + \ldots + |x_{nf} - m_f|)$$

$$m_f = \frac{1}{n}(x_{1f} + x_{2f} + \ldots + x_{nf}).$$

where
- mf = mean of feature f
- Measures **average spread** from mean

  - Calculate the standardized measurement (*z-score*)

$$z_{if} = \frac{x_{if} - m_f}{s_f}$$

- Converts all values to **same scale**
- Mean ≈ 0, spread ≈ 1

- Using mean absolute deviation is more robust than using standard deviation

Less affected by outliers

More **robust** for real data

Similarity and Dissimilarity Between Objects

- Distances are normally used to measure the similarity or dissimilarity between two data objects
- Some popular ones include: *Minkowski distance*

$$d(i,j)=\sqrt[q]{(|x_{i_1}-x_{j_1}|^q+|x_{i_2}-x_{j_2}|^q+\ldots+|x_{i_p}-x_{j_p}|^q)}$$

where $i = (x_{i1}, x_{i2}, \ldots, x_{ip})$ and $j = (x_{j1}, x_{j2}, \ldots, x_{jp})$ are two p-dimensional data objects, and q is a positive integer (distance parameter)

- If $q = 1$, d is Manhattan distance

$$d(i,j)=|x_{i_1}-x_{j_1}|+|x_{i_2}-x_{j_2}|+\ldots+|x_{i_p}-x_{j_p}|$$

Similarity and Dissimilarity Between Objects

RV College of Engineering®

- *If q = 2, d* is Euclidean distance

$$d(i,j)=\sqrt{(|x_{i_1}-x_{j_1}|^2+|x_{i_2}-x_{j_2}|^2+\ldots+|x_{i_p}-x_{j_p}|^2)}$$

  - Properties
    - $d(i,j) \geq 0$
    - $d(i,i) = 0$
    - $d(i,j) = d(j,i)$
    - $d(i,j) \leq d(i,k) + d(k,j)$
- Also, one can use weighted distance, parametric Pearson product moment correlation, or other dissimilarity measures

Binary Variables

RV College of Engineering®

A contingency table for binary data(A **contingency table** is a **2 × 2 table** used to **summarize how two binary objects/variables match or differ)**

		Object j 1	0	sum
Object i	1	a	b	$a+b$
	0	c	d	$c+d$
	sum	$a+c$	$b+d$	p

- Distance measure for symmetric binary variables: (0 and 1 are equally important, e.g., gender):

$$d(i,j)=\frac{b+c}{a+b+c+d}$$

- Distance measure for asymmetric binary variables((1 is more important than 0, e.g., disease present , (ignores **d**, joint absence)):

$$d(i,j)=\frac{b+c}{a+b+c}$$

- Jaccard coefficient (measures shared 1s, Common in text, medical, web data).

$$sim_{Jaccard}(i,j)=\frac{a}{a+b+c}$$

Dissimilarity between Binary Variables

RV College of Engineering®

- Example

Name	Gender	Fever	Cough	Test-1	Test-2	Test-3	Test-4
Jack	M	Y	N	P	N	N	N
Mary	F	Y	N	P	N	P	N
Jim	M	Y	P	N	N	N	N

  - gender is a symmetric attribute
  - the remaining attributes are asymmetric binary
  - let the values Y and P be set to 1, and the value N be set to 0

$$d(jack, mary) = \frac{0+1}{2+0+1} = 0.33$$

$$d(jack, jim) = \frac{1+1}{1+1+1} = 0.67$$

$$d(jim, mary) = \frac{1+2}{1+1+2} = 0.75$$

RV College of Engineering®

Identify variable types

- **Gender** → *symmetric binary*
  (M/F are equally important → NOT used here)
- **Fever, Cough, Test-1 to Test-4** → *asymmetric binary*
  (presence matters more than absence)

So we **ignore Gender** for distance calculation.

Convert values to binary

Rule given:

- **Y, P → 1**
- **N → 0**

Converted table (excluding Gender)

Name	Fever	Cough	T1	T2	T3	T4
Jack	1	0	1	0	0	0
Mary	1	0	1	0	1	0
Jim	1	1	0	0	0	0

RV College of Engineering®

- **Distance between Jack and Mary**

Compare feature-wise:

Feature	Jack	Mary
Fever	1	1 → a
Cough	0	0 → ignored
T1	1	1 → a
T2	0	0 → ignored
T3	0	1 → c
T4	0	0 → ignored

Counts:

- a = 2
- b = 0
- c = 1

$$d(\text{Jack, Mary}) = \frac{0+1}{2+0+1} = \frac{1}{3} = 0.33$$

RV College of Engineering®

Distance between **Jack and Jim**

Feature	Jack	Jim
Fever	1	1 → a
Cough	0	1 → c
T1	1	0 → b
T2	0	0 → ignored
T3	0	0 → ignored
T4	0	0 → ignored

Counts:

- a = 1
- b = 1
- c = 1

$$d(\text{Jack, Jim}) = \frac{1+1}{1+1+1} = \frac{2}{3} = 0.67$$

RV College of Engineering®

Distance between **Jim and Mary**

Feature	Jim	Mary
Fever	1	1 → a
Cough	1	0 → b
T1	0	1 → c
T2	0	0 → ignored
T3	0	1 → c
T4	0	0 → ignored

Counts:

- a = 1
- b = 1
- c = 2

$$d(\text{Jim, Mary}) = \frac{1+2}{1+1+2} = \frac{3}{4} = 0.75$$

RV College of Engineering®

Pair	Distance
Jack – Mary	**0.33** (most similar)
Jack – Jim	**0.67**
Jim – Mary	**0.75** (least similar)

This problem demonstrates that choosing the correct binary distance measure based on data semantics is crucial, and asymmetric binary dissimilarity effectively captures similarity when the presence of attributes is more important than absence.

Nominal Variables

What are nominal variables?
•Categorical, **no order**
•Example: red, blue, green

- A generalization of the binary variable in that it can take more than 2 states, e.g., red, yellow, blue, green
- Method 1: Simple matching
  - *m*: # of matches, *p*: total # of variables

$$d(i,j) = \frac{p-m}{p}$$

- Method 2: use a large number of binary variables
- creating a new binary variable for each of the *M* nominal states (**Binary encoding**
- Convert each category into binary variables
- Then apply binary distance measures)

Ordinal Variables

What are ordinal variables?

•Order matters, differences don't

•Example: rank, grades (low/medium/high)

- An ordinal variable can be discrete or continuous
- Order is important, e.g., rank
- Can be treated like interval-scaled
  - replace x_{if} by their rank $r_{if} \in \{1, \ldots, M_f\}$
  - map the range of each variable onto [0, 1] by replacing *i*-th object in the *f*-th variable by

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

  - compute the dissimilarity using methods for interval-scaled variables

Ratio-Scaled Variables

- Ratio-scaled variable: a positive measurement on a nonlinear scale.

Although they are numeric, **ratio-scaled variables often follow a nonlinear or exponential scale**, such as: Ae^{Bt} or Ae^{-Bt}

- Methods:
  - treat them like interval-scaled variables—*not a good choice!* (why?—the scale can be distorted)
  - apply logarithmic transformation

$$y_{if} = log(x_{if})$$

  - treat them as continuous ordinal data treat their rank as interval-scaled

Variables of Mixed Types

- A database may contain all the six types of variables
  - symmetric binary, asymmetric binary, nominal, ordinal, interval and ratio, A **single distance formula cannot be used directly** for all of them.
- One may use a weighted formula to combine their effects $$d(i,j) = \frac{\sum_{f=1}^{p} \delta_{ij}^{(f)} d_{ij}^{(f)}}{\sum_{f=1}^{p} \delta_{ij}^{(f)}}$$
  - f is binary or nominal: $$d_f(i,j) = \begin{cases} 0 & \text{if } x_{if} = x_{jf} \\ 1 & \text{otherwise} \end{cases}$$
  - f is interval-based: use the normalized distance $$d_f(i,j) = \frac{|x_{if} - x_{jf}|}{\text{range}_f}$$
  - f is ordinal or ratio-scaled
    - compute ranks r_{if} and
    - and treat z_{if} as interval-scaled $$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

Meaning of each term

- f → feature index
- w_f → weight of feature f (importance)
- δ_f → 0 if missing, 1 otherwise
- $d_f(i,j)$ → distance computed **according to variable type**

This formula:

- Combines **different distance rules**
- Handles **missing values**
- Allows **feature importance**

RV College of Engineering®

Types of clusters

Types of Clusters

- Well-separated clusters
- Center-based clusters (Prototype clusters)
- Contiguous clusters (Graph based)
- Density-based clusters
- Shared Property or Conceptual
- Described by an Objective Function

Types of Clusters: Well-Separated

- Well-Separated Clusters:
  - A cluster is a set of points such that any point in a cluster is closer (or more similar) to every other point in the cluster than to any point not in the cluster.



3 well-separated clusters

RV College of Engineering®

Well-Separated Clusters

Definition: A **well-separated cluster** is a set of objects such that:

- Every object in the cluster is **closer to all other objects in the same cluster** than to **any object outside the cluster**

Key characteristics

- Clusters are **far apart**
- Very little or **no overlap**
- This is an **idealistic definition**
- Exists only when **natural clusters are clearly separated**

Shape

- Can be **any shape**, not necessarily circular

Limitation

- Rare in real-world data
- Noise and overlap usually violate this condition

RV College of Engineering®

Prototype-Based (Center-Based) Clusters

Definition: A **prototype-based cluster** is a set of objects where:

- Each object is **closer to its own cluster's prototype**
- Than to the prototype of any other cluster

What is a prototype?

- **Centroid** → mean of all points (for numerical data)
- **Medoid** → most representative actual object (for categorical data)

Key characteristics

- Clusters are usually **globular (spherical)**
- Each cluster has a **central representative**

Examples

- **K-means clustering**
- **K-medoids**

Types of Clusters: Center-Based

- Center-based
  - A cluster is a set of objects such that an object in a cluster is closer (more similar) to the “center” of a cluster, than to the center of any other cluster
  - The center of a cluster is often a centroid, the average of all the points in the cluster, or a medoid, the most “representative” point of a cluster

4 center-based clusters

RV College of Engineering®

Graph-Based Clusters

Definition

If data is represented as a **graph**:

- Nodes → objects
- Edges → connections (similarity or proximity)

A **cluster** is defined as a **connected component**:

- Objects are connected to each other
- No connections to objects outside the cluster

RV College of Engineering®

Contiguity-Based Clusters (Important type)

- Two objects are connected **only if they are within a given distance**
- A cluster forms by chaining nearby points

Advantage

- Can detect **irregular or intertwined clusters**

Major problem

- **Noise** can create small bridges
- These bridges may **incorrectly merge separate clusters**

RV College of Engineering®

- Contiguous Cluster (Nearest neighbor or Transitive)
  - A cluster is a set of points such that a point in a cluster is closer (or more similar) to one or more other points in the cluster than to any point not in the cluster.

8 contiguous clusters

RV College of Engineering®

Clique-Based Graph Clusters

- A cluster is a **clique** (every node connected to every other)
- Formed by gradually adding edges based on distance
- Tend to be **globular**, similar to center-based clusters

Types of Clusters: Density-Based

- Density-based
  - A cluster is a dense region of points, which is separated by low-density regions, from other regions of high density.
  - Used when the clusters are irregular or intertwined, and when noise and outliers are present.



6 density-based clusters

RV College of Engineering®

Definition

A **density-based cluster** is:

- A region of **high density of points** Surrounded by regions of **low density**

Key idea

- Clusters grow where data is dense
- Sparse regions separate clusters

Comparison with contiguity-based

- Contiguity-based → fails with noise
- Density-based → robust to noise

Types of Clusters: Conceptual Clusters

- Shared Property or Conceptual Clusters
  - Finds clusters that share some common property or represent a particular concept.



2 Overlapping Circles

RV College of Engineering®

Shared-Property (Conceptual) Clusters

Definition

A cluster is defined as:

A set of objects that share a **common property or concept**

This is a **very general definition**.

Conceptual Clustering

•Clusters are defined using **domain knowledge**

•Requires a **specific concept of what a cluster is**

Limitation

•Too complex for standard clustering

•Moves toward **pattern recognition**

•Hence, usually not considered in basic clustering texts

Types of Clusters: Objective Function

- In this approach, **clusters are formed by optimizing (minimizing or maximizing) a mathematical function**, called an **objective function**.
- The objective function measures how *good* a clustering is.
- Clusters Defined by an Objective Function
  - Finds clusters that minimize or maximize an objective function.
  - The algorithm tries to:

Minimize something undesirable
(e.g., distance between points inside a cluster)
OR **maximize** something desirable
(e.g., separation between different clusters)

Enumerate all possible ways of dividing the points into clusters"

•Ideally, the algorithm would:

- •Try **every possible clustering**
- •Compute the objective function value for each
- •Pick the best one

But this is **not practical** for large datasets.

"Evaluate the goodness of each potential set of clusters"

•"Goodness" means:

- •How compact the clusters are
- •How well separated they are

•This is **quantified numerically** using the objective function.

RV College of Engineering®

"Can have global or local objectives"

There are **two types of optimization goals**:

(a) Global Objective

•One single function for the **entire clustering**

•Tries to optimize clustering as a whole

Example:

•Minimize total within-cluster variance for all clusters together

(b) Local Objective

•Decisions are made **step by step**

•Each step optimizes only a **part of the clustering**

"Hierarchical clustering algorithms typically have local objectives"

•Hierarchical clustering:

- •Merges or splits clusters **one step at a time**
- •Each step makes the **best local decision**

•Does **not reconsider earlier decisions**

Hence, **local objective optimization**

"Partitional algorithms typically have global objectives"

•Partitional clustering (e.g., K-means):

- •Optimizes a **single global objective function**
- •Iteratively improves the entire clustering

Hence, **global objective optimization**

Types of Clusters: Objective Function …

- Map the clustering problem to a different domain and solve a related problem in that domain

➢ Instead of solving clustering **directly in data space**, we:
➢ Convert the problem into **another well-studied problem**
➢ Solve it there
➢ Interpret the solution back as clusters
➢ Here, clustering is mapped to a **graph problem**.

- Proximity matrix defines a weighted graph, where the nodes are the points being clustered, and the weighted edges represent the proximities between points
- Clustering is equivalent to breaking the graph into connected components, one for each cluster
- Want to minimize the edge weight between clusters and maximize the edge weight within clusters

RV College of Engineering®

Considerations for Cluster Analysis

- Partitioning criteria
  - Single level vs. hierarchical partitioning(Clusters inside clusters) (often, multi-level hierarchical partitioning is desirable)
- Separation of clusters
  - Exclusive (e.g., one customer belongs to only one region) vs. non-exclusive (e.g., one document may belong to more than one class)
- Similarity measure
  - Distance-based (Uses physical or mathematical distance)(e.g., Euclidian, road network, vector) vs. connectivity-based(Based on links, density, or neighborhood (e.g., density or contiguity)
- Clustering space
  - Full space(Uses **all features)** (often when low dimensional) vs. subspaces(Uses **only selected features)** (often in high-dimensional clustering)

Requirements and Challenges

RV College of Engineering®

- Scalability
  - Clustering all the data instead of only on samples
- Ability to deal with different types of attributes
  - Numerical, binary, categorical, ordinal, linked, and mixture of these
- Constraint-based clustering
  - User may give inputs on constraints
  - Use domain knowledge to determine input parameters
- Interpretability and usability
- Others
  - Discovery of clusters with arbitrary shape
  - Ability to deal with noisy data
  - Incremental clustering and insensitivity to input order
  - High dimensionality

Major Clustering Approaches (I)

- Partitioning approach:
  - Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
  - Typical methods: k-means, k-medoids, CLARANS
- Hierarchical approach:
  - Create a hierarchical decomposition of the set of data (or objects) using some criterion
  - Typical methods: Diana, Agnes, BIRCH, CAMELEON
- Density-based approach:
  - Based on connectivity and density functions
  - Typical methods: DBSACN, OPTICS, DenClue
- Grid-based approach:
  - based on a multiple-level granularity structure
  - Typical methods: STING, WaveCluster, CLIQUE

Major Clustering Approaches (II)

- Model-based:
  - A model is hypothesized for each of the clusters and tries to find the best fit of that model to each other
    - •Assume **each cluster follows a model**
      - Data → Try Model → Adjust → Best Fit → Cluster
    - •Fit the data to the **best model**
  - Typical methods: EM, SOM, COBWEB
- Frequent pattern-based:
  - Based on the analysis of frequent patterns
  - Typical methods: p-Cluster
- User-guided or constraint-based:
  - Clustering by considering user-specified or application-specific constraints
  - Typical methods: COD (obstacles), constrained clustering
- Link-based clustering:
  - Objects are often linked together in various ways
  - Massive links can be used to cluster objects: SimRank, LinkClus

Partitional Clustering



Original Points



A Partitional Clustering

Hierarchical Clustering



Traditional Hierarchical Clustering



Traditional Dendrogram



Non-traditional Hierarchical Clustering



Non-traditional Dendrogram

Density based Clustering

Original Points



Clusters

RV College of Engineering®

Partitional Clustering

Partitional Clustering

RV College of Engineering®

- Given
  - A data set of **n objects**
  - **K the number of clusters to form**
- Organize the objects into k partitions **(k<=n) where each partition** represents a cluster
- The clusters are formed to optimize an objective partitioning criterion
  - Objects within a cluster are **similar**
  - Objects of different clusters are **dissimilar**

K-means Clustering

- The basic algorithm is very simple
- Number of clusters, K, must be specified
- Each cluster is associated with a centroid (mean or center point)
- Each point is assigned to the cluster with the closest centroid

```
Select K points as the initial centroids.
repeat
    Form K clusters by assigning all points to the closest centroid.
    Recompute the centroid of each cluster.
until The centroids don't change
```

K-means Clustering – Details

RV College of Engineering®

- Initial centroids are often chosen randomly.
  - Clusters produced vary from one run to another.
- The centroid is (typically) the mean of the points in the cluster.
- 'Closeness' is measured by Euclidean distance, cosine similarity, correlation, etc.
- K-means will converge for common similarity measures mentioned above.
- Most of the convergence happens in the first few iterations.
  - Often the stopping condition is changed to 'Until relatively few points change clusters' or some measure of clustering doesn't change.
- Complexity is O(n * K * I * d)
  - n = number of points, K = number of clusters, I = number of iterations, d = number of attributes

Evaluating K-means Clusters

RV College of Engineering®

- Most common measure is Sum of Squared Error (SSE)
  - For each point, the error is the distance to the nearest cluster
  - To get SSE, we square these errors and sum them.(Error = **distance from the point to its nearest cluster center)**

$$SSE = \sum_{i=1}^{K} \sum_{x \in C_i} dist^2(m_i, x)$$

  - x is a data point in cluster C_i and m_i is the representative point for cluster C_i
    - It can be shown that the **value of mi that minimizes SSE corresponds to the mean (centroid)** of the cluster.
  - Given two clusters, we can choose the one with the smallest error

- **Effect of Number of Clusters (K)**

One easy way to reduce SSE is to **increase the number of clusters (K)**.

However, **a good clustering with smaller K can have lower SSE than a poor clustering with a larger K**.

Two different K-means Clusterings

RV Colle
Engineering®

Optimal Clustering

•Clusters are **compact and well separated**

•Each point is assigned to the **nearest cluster mean**

•The **Sum of Squared Error (SSE) is minimum**

•This represents a **good local minimum**

•This is the **desired result** of K-means.



Original Points



Optimal Clustering



Sub-optimal Clustering

Sub-optimal Clustering

•Some points are assigned to **less appropriate clusters**

•Cluster centers are **not ideally placed**

•**SSE is higher** than in optimal clustering

•This happens due to **different initial centroids**

K-means **can converge to a sub-optimal solution**.

Importance of Choosing Initial Centroids

•The **final clustering depends on the initial choice of cluster centroids**.

•Different initial centroids can lead to:

- Different cluster assignments
- Different SSE values

•As a result, K-means **does not guarantee a globally optimal solution**.

•It is possible for K-means to converge to a **suboptimal clustering**, even when the data has a clear natural grouping.

•Because of this sensitivity, it is common to:

- Run K-means **multiple times with different initial centroids**
- Choose the clustering with the **lowest SSE**

Importance of Choosing Initial Centroids (Case i)



Importance of Choosing Initial Centroids (Case i)

Good Initialization

- Initial centroids are well chosen
- Clusters converge correctly
- SSE is relatively low
- Represents a **good local minimum**



Importance of Choosing Initial Centroids (Case ii)



Importance of Choosing Initial Centroids (Case ii)

Poor Initialization

- Initial centroids are poorly chosen
- Algorithm converges to incorrect clusters
- SSE is higher
- Represents a **suboptimal local minimum**



Problems with Selecting Initial Points

Why selecting good initial centroids in K-means is difficult

Suppose there are **K "real" clusters** in the data.
K-means starts by **randomly selecting K initial centroids**.
The probability that **each initial centroid comes from a different real cluster** is **very small**, especially when:
•The number of clusters **K is large**
•The clusters are of **equal size**

- For example, if K = 10, then probability = $10!/10^{10} = 0.00036$
- Sometimes the initial centroids will readjust themselves in 'right' way, and sometimes they don't

$$P = \frac{\text{number of ways to select one centroid from each cluster}}{\text{number of ways to select } K \text{ centroids}} = \frac{K!n^K}{(Kn)^K} = \frac{K!}{K^K}$$

•There are **K clusters**
•Each cluster has **n points**

This shows that the probability **decreases rapidly as K increases.**

10 Clusters Example (Good Clusters)



Starting with two initial centroids in one cluster of each pair of clusters

10 Clusters Example (Good Clusters)



Starting with two initial centroids in one cluster of each pair of clusters

10 Clusters Example (Bad Clusters)



Starting with some pairs of clusters having three initial centroids, while other have only one.

10 Clusters Example (Bad Clusters)



Starting with some pairs of clusters having three initial centroids, while other have only one.

Solutions to Initial Centroids Problem

RV College of Engineering®

- Multiple Runs
  Run K-means multiple times with different random initial centroids
  Select the clustering with the smallest SSE
  This approach helps, but when K is large the probability of selecting good initial centroids is still small
- Sample and Use Hierarchical Clustering
  Apply hierarchical clustering to a sample of the data
  Use the resulting clusters to determine initial centroids for K-means
  This improves the quality of initialization compared to random selection
- Select More Than K Initial Centroids
  Select more than K candidate initial centroids
  Choose the most widely separated points among them
  Use these selected points as the initial centroids
- Post-processing
  Apply post-processing techniques after K-means has converged
  Improve cluster quality when the initial clustering is poor
- Bisecting K-means
  A variant of the K-means algorithm
  Works by repeatedly splitting clusters

Pre-processing and Post-processing

RV College of Engineering®

- Pre-processing
  - Normalize the data
  - Eliminate outliers
- Post-processing
  - Eliminate small clusters that may represent outliers
  - Split ‘loose’ clusters, i.e., clusters with relatively high SSE
  - Merge clusters that are ‘close’ and that have relatively low SSE
  - Can use these steps during the clustering process
    - ISODATA

Bisecting K-means

The bisecting K-means algorithm is a straightforward extension of the basic K-means algorithm that is based on a simple idea: to obtain K clusters, split the set of all points into two clusters, select one of these clusters to split, and so on, until K clusters have been produced.

Bisecting K-means creates clusters by **repeatedly splitting data into two parts**.

Instead of forming K clusters at once, it starts with all points in one cluster and keeps dividing one cluster into two until K clusters are formed.

Basic Idea

- Start with **all data points in one cluster**.
- Split the cluster into **two sub-clusters** using K-means (K = 2).
- Select one of the clusters (usually with highest variance or SSE).
- Repeat the splitting process until **K clusters** are formed.

Bisecting K-means

```
Initialize the list of clusters to contain the cluster containing all points.
repeat
    Select a cluster from the list of clusters
    for i = 1 to number_of_iterations do
        Bisect the selected cluster using basic K-means
    end for
    Add the two clusters from the bisection with the lowest SSE to the list of clusters.
until Until the list of clusters contains K clusters
```

Bisecting K-means Example



K-means and Different Types of Clusters

- K-means and its variations have a number of limitations with respect to finding different types of clusters.
- In particular, K-means has difficulty detecting the “natural” clusters, when clusters have non-spherical shapes or widely different sizes or densities.

Limitations of K-means

- K-means has problems when clusters are of differing
  - Sizes
  - Densities
  - Non-globular shapes

Limitations of K-means: Differing Sizes



Original Points



K-means (3 Clusters)

In Figure, one cluster is much larger than the other two.
Because of this size difference, K-means splits the large cluster and incorrectly merges part of it with a smaller cluster instead of finding the three natural clusters.

Limitations of K-means: Differing Density



Original Points



K-means (3 Clusters)

In Figure, two clusters are much denser than the third cluster.
Because of this density difference, K-means cannot correctly separate the three natural clusters.

Limitations of K-means: Non-globular Shapes



Original Points



K-means (2 Clusters)

In Figure , the natural clusters do not have a globular shape.
Because of this, K-means mixes parts of the natural clusters and forms incorrect clusters.

The problem in these cases is that the K-means objective function does not match the type of clusters present in the data.

K-means works best for
globular clusters with similar size and density or
for well-separated clusters,

However, these limitations can be overcome, in some sense, if the user is willing to accept a clustering that breaks the natural clusters into a number of subclusters.

Overcoming K-means Limitations

- Instead of finding two or three clusters, **n clusters are formed**
- Each natural cluster is broken into **smaller subclusters**
- Each subcluster is **pure**, meaning it contains points from only one natural cluster
- Although natural clusters are split, their structure is still captured in parts





- One solution is to use many clusters.
  - Find parts of clusters, but need to put together.

Overcoming K-means Limitations



Original Points



K-means

Clusters

- One solution is to use many clusters.
  - Find parts of clusters, but need to put together.

Overcoming K-means Limitations





Original Points

K-means

Clusters

- One solution is to use many clusters.
  - Find parts of clusters, but need to put together.

Limitations of K-means: Outlier Problem

- The k-means algorithm is sensitive to outliers !
  - Since an object with an extremely large value may substantially distort the distribution of the data.
- Solution: Instead of taking the **mean** value of the object in a cluster as a reference point, **medoids** can be used, which is the **most centrally located** object in a cluster.
- A **medoid** is an **actual data point** that lies near the center of a cluster.
- Unlike the **mean**, it is **not an average** — it is one of the real objects in the data.



RV College of Engineering®

Strengths and Weaknesses of K means

Advantages of K-means

- Simple and easy to implement
- Efficient for large datasets
- Variants such as bisecting K-means improve efficiency and initialization

Limitations of K-means

- Cannot handle non-globular clusters
- Performs poorly with clusters of different sizes and densities
- Sensitive to outliers

Handling Limitations

- Increasing the number of clusters produces pure subclusters
- Outlier detection and removal improve clustering resul

K-means as an Optimization Problem

K-means as an Optimization Problem

- Clustering can be treated as an optimization problem
- The objective function is usually to minimize SSE

Global vs Practical Solution

- Enumerating all possible clustering finds the global optimum
- This approach is computationally infeasible

Optimization Approach Used

- Start with an initial clustering solution
- Repeatedly update the solution to reduce SSE
- This approach is similar to gradient descent

Simplifying Assumption

- Data is assumed to be one-dimensional
- Distance is defined as $(x - y)^2$
- This simplifies the mathematical analysis

Unit 5

Cluster Evaluation-Overview, Unsupervised Cluster Evaluation Using Cohesion and Separation, Unsupervised Cluster Evaluation Using the Proximity Matrix, Determining the Correct Number of Clusters, Supervised Measures of Cluster Validity, Assessing the Significance of Cluster Validity Measures, Choosing a Cluster Validity Measure

Cluster Evaluation: hard problem

Why cluster evaluation is hard

Clustering is unsupervised, so:

- We **do not know the true/correct clusters** beforehand.
- There is **no ground truth** to directly compare results against.

- Different algorithms (K-means, Hierarchical, DBSCAN) may give **different valid clusterings** for the same data.
- Hence, **quality assessment is subjective and difficult.**

RV College of Engineering®

Methods used to evaluate clustering

1. User Inspection

- A human manually examines the clustering result.
- Common in:
  - Exploratory data analysis
  - Small datasets
- Limitation: **subjective and not scalable**

2. Study centroids and spreads

- Analyze:
  - **Centroids** → represent the center of each cluster
  - **Spread (variance / radius)** → how tightly data points are grouped
- Good clustering:
  - Small intra-cluster distance
  - Large inter-cluster separation

3. Rules from a decision tree

- Build a **decision tree** using cluster labels as target classes.
- If:
  - Simple rules separate clusters well → clustering is good
  - Complex/deep tree needed → clusters overlap heavily
- This gives an **indirect interpretability check**

4. Reading documents (for text clustering)

- For document clustering:
  - Manually read a few documents from each cluster
  - Check if documents in the same cluster discuss **similar topics**
- Common in:
  - Information retrieval
  - Topic modeling

Cluster evaluation: ground truth

RV College of Engineering®

- Some **labeled data** is available
- Labels are used **only for evaluation**, not for clustering
- Evaluation becomes similar to **classification assessment**

Basic Assumption

- **Each class is treated as one cluster**
- True class labels represent **ground truth**
- Enables direct comparison with generated clusters

Confusion Matrix

- Construct a **confusion matrix** after clustering
- Rows → **True classes**
- Columns → **Clusters produced by algorithm**
- Each cell → number of data points assigned

RV College of Engineering®

Evaluation Measures

Computed from confusion matrix:

- **Purity** – dominant class proportion in a cluster
- **Entropy** – class mixing inside a cluster
- **Precision** – correctness of cluster assignments
- **Recall** – completeness of class capture
- **F-score** – balance between precision and recall

Dataset: **D**

True classes:

$C = \{c_1, c_2, ..., c_k\}$

Generated clusters:

$D_1, D_2, ..., D_k$

Properties:

- Clusters are **disjoint**
- $D = \bigcup_{i=1}^{k} D_i$

Key Points

•Ground truth enables **objective cluster evaluation**

•Not always available in real-world datasets

•Used mainly for **benchmarking and research**

Evaluation measures: Entropy

Entropy: For each cluster, we can measure its entropy as follows:

$$entropy(D_i) = -\sum_{j=1}^{k} \Pr_i(c_j) \log_2 \Pr_i(c_j), \tag{29}$$

where $\Pr_i(c_j)$ is the proportion of class c_j data points in cluster i or D_i. The total entropy of the whole clustering (which considers all clusters) is

$$entropy_{total}(D) = \sum_{i=1}^{k} \frac{|D_i|}{|D|} \times entropy(D_i) \tag{30}$$

Evaluation measures: purity

RV College of Engineering®

- Simple and intuitive metric
- Purity measures how much a cluster contains **a single class**
- Higher purity → **better clustering**

Purity: This again measures the extent that a cluster contains only one class of data. The purity of each cluster is computed with

$$purity(D_i) = \max_j(\Pr_i(c_j)) \tag{31}$$

Chooses the **dominant class** in the cluster

The total purity of the whole clustering (considering all clusters) is

$$purity_{total}(D) = \sum_{i=1}^{k} \frac{|D_i|}{|D|} \times purity(D_i) \tag{32}$$

An example

RV College of Engineering®

Example 14: Assume we have a text collection D of 900 documents from three topics (or three classes), Science, Sports, and Politics. Each class has 300 documents. Each document in D is labeled with one of the topics (classes). We use this collection to perform clustering to find three clusters. Note that class/topic labels are not used in clustering. After clustering, we want to measure the effectiveness of the clustering algorithm.

Cluster	Science	Sports	Politics		Entropy	Purity
1	250	20	10		0.589	0.893
2	20	180	80		1.198	0.643
3	30	100	210		1.257	0.617
Total	300	300	300		1.031	0.711

Entropy & Purity Evaluation

- Dataset **D = 900 documents**
- **3 classes**: Science, Sports, Politics (300 each)
- Clustering produces **3 clusters**
- True labels used **only for evaluation**

Cluster 1

- Proportions:
  - Science = 250/280
  - Sports = 20/280
  - Politics = 10/280
- Dominant class = **Science**

$$purity(D_1) = \frac{250}{280} = 0.893$$

Cluster Distribution

- C1: Science=250, Sports=20, Politics=10 → Purity = **0.893**, Entropy = **0.589**
- C2: Science=20, Sports=180, Politics=80 → Purity = **0.643**, Entropy = **1.198**
- C3: Science=30, Sports=100, Politics=210 → Purity = **0.617**, Entropy = **1.257**

Overall Results

- **Total Purity = 0.711**
- **Total Entropy = 1.031**

Conclusion

- Good cluster → **High purity, Low entropy**

A remark about ground truth evaluation

- Commonly used to compare different clustering algorithms.
- A real-life data set for clustering has no class labels.
  - Thus although an algorithm may perform very well on some labeled data sets, no guarantee that it will perform well on the actual application data at hand.
- The fact that it performs well on some label data sets does give us some confidence of the quality of the algorithm.
- This evaluation method is said to be based on **external data** or information.

Evaluation based on internal information

Unsupervised Cluster Evaluation Using Cohesion and Separation

(Unsupervised Cluster Evaluation: Cohesion & Separation)

- Used when **no ground truth labels** are available
- Evaluation is based **only on the data itself**

Intra-cluster cohesion (compactness):

- Measures how **close data points** in a cluster are to the **cluster centroid**
- **Sum of Squared Error (SSE)** is a commonly used measure
- Lower cohesion value → **better clustering**

Inter-cluster separation (isolation):

- Measures how **far apart different cluster centroids** are
- Larger separation → **better clustering**
- In most applications, **expert judgment is still the key**



(a) Cohesion. (b) Separation.

Indirect evaluation

Indirect Evaluation

- In some applications, **clustering is not the primary task**
- Clustering is used to **support another main task**
- Clustering methods are compared using **performance of the primary task**

Example: Recommendation System

- Primary task: **recommend books** to online shoppers
- Books are clustered based on **their features**
- Better clustering → **better recommendations**
- Different clustering algorithms are evaluated by:
  - How well they improve the recommendation task
- Assumption: **recommendation quality can be reliably evaluated**

Assessing Clustering Tendency

RV College of Engineering®

Assessing Clustering Tendency

- Used to assess whether **non-random structure** exists in the data
- Measures the probability that data is generated by a **uniform distribution**
- Spatial randomness is tested using **Hopkins Statistic**
- Test spatial randomness by statistic test: Hopkins Static

Symbol	Meaning
(x_i)	Sampled **actual data point** from dataset
(q_i)	**Random point** generated uniformly
(v)	Nearest **dataset point**

Hopkins Statistic Procedure

- Given dataset **D** as a sample of a random variable
- Sample p points $x_1, x_2, \ldots, x_p$ from **D**
  - For each x_i, find nearest neighbor in **D**
  - $x_i = \min(dist(x_i, v))$
- Sample p points $q_1, q_2, \ldots, q_p$ uniformly from **D**
  - For each q_i, find nearest neighbor in **D**
  - $y_i = \min(dist(q_i, v)),\ v \neq q_i$

Hopkins Statistic

$$H = \frac{\sum_{i=1}^{p} y_i}{\sum_{i=1}^{p} x_i + \sum_{i=1}^{p} y_i}$$

- Uniform data → $H \approx 0.5$
- Highly clustered data → $H \approx 0$

Determine the Number of Clusters

- Number of clusters ≈ $\sqrt{n/2}$ for a dataset of n points

- Empirical method
  - # of clusters ≈√n/2 for a dataset of n points
- Elbow method
  - Use the turning point in the curve of sum of within cluster variance w.r.t the # of clusters
- Cross validation method

➢ Divide dataset into **m parts**
➢ Use **m−1 parts** to build clustering model
➢ Use remaining part to test clustering quality
➢ For each test point:
  ➢ Find closest centroid
  ➢ Compute **sum of squared distance**
➢ Repeat for different values of k
➢ Select the **number of clusters that gives best quality**



Line plot between K and inertia

Measuring Clustering Quality

- Two methods: extrinsic vs. intrinsic
- Extrinsic: supervised, i.e., the ground truth is available
  - Compare a clustering against the ground truth using certain clustering quality measure
  - Ex. precision and recall metrics
- Intrinsic: unsupervised, i.e., the ground truth is unavailable
  - Evaluate the goodness of a clustering by considering how well the clusters are separated, and how compact the clusters are
  - Ex. Silhouette coefficient

Measuring Clustering Quality: Extrinsic Methods

- Clustering quality measure: $Q(C, C_g)$, for a clustering C given the ground truth C_g.
- Q is good if it satisfies the following **4** essential criteria

1. Cluster Homogeneity

- Clusters should be **pure**
- Higher purity → better clustering

2. Cluster Completeness

- Objects belonging to the same ground truth category should be assigned to the **same cluster**

3. Rag Bag Criterion

- Assigning a heterogeneous object to a **pure cluster** should be penalized more than assigning it to a **rag bag**
- Rag bag = *miscellaneous / other category*

4. Small Cluster Preservation

- Splitting a **small category** into many clusters is more harmful than splitting a **large category**

Different Aspects of Cluster Validation

RV College of Engineering®

1. Determining the clustering tendency of a set of data, i.e., distinguishing whether non-random structure actually exists in the data.
2. Comparing the results of a cluster analysis to externally known results, e.g., to externally given class labels.
3. Evaluating how well the results of a cluster analysis fit the data *without* reference to external information.
   - Use only the data
4. Comparing the results of two different sets of cluster analyses to determine which is better.
5. Determining the 'correct' number of clusters.

For 2, 3, and 4, we can further distinguish whether we want to evaluate the entire clustering or just individual clusters.

Measures of Cluster Validity

RV College of Engineering®

Numerical measures that are applied to judge various aspects of cluster validity, are classified into the following three types.

1. External Index

- Measures the extent to which cluster labels match **externally supplied class labels**
- Requires **ground truth**
- Example:
  - **Entropy**

2. Internal Index

- Measures the **goodness of clustering structure** without using external information
- Based only on the data itself
- Example:
  - **Sum of Squared Error (SSE)**

3. Relative Index

- Used to **compare two different clusterings** or clustering results
- Often uses an **external or internal index**
- Examples:
  - **Entropy**
  - **SSE**

Measuring Cluster Validity Via Correlation

RV College of Engineering®

Uses **two matrices** for evaluation

1. Proximity Matrix

- Captures similarity or distance between data points

2. Incidence Matrix

- One row and one column for **each data point**
- Entry = **1** → pair of points belong to the **same cluster**
- Entry = **0** → pair of points belong to **different clusters**

Correlation Computation

- Compute the **correlation between the two matrices**
- Since matrices are **symmetric**:
  - Only $\frac{n(n-1)}{2}$ unique entries are considered

Interpretation

- **High correlation** →
  - Points that belong to the same cluster are **close to each other**
- Indicates **good clustering quality**

Measuring Cluster Validity Via Correlation

RV College of Engineering®

- Correlation of incidence and proximity matrices for the K-means clusterings of the following two data sets.



Corr = -0.9235



Corr = -0.5810

Using Similarity Matrix for Cluster Validation

RV College of Engineering®

- Order the similarity matrix with respect to cluster labels and inspect visually.





Visual Insight

•Points in the same cluster appear as **bright/dense blocks**

•Weak clustering results in **scattered or unclear blocks**

Using Similarity Matrix for Cluster Validation

- Clusters in random data are not so crisp





Observation

•Compared to structured data, random data:

- Produces **blurred blocks**
- Shows **overlapping similarities**

Example

•DBSCAN applied to random data

•Resulting clusters are **less distinct**

•Confirms poor clustering tendency

Using Similarity Matrix for Cluster Validation

RV College of Engineering®

- Clusters in random data are not so crisp





K-means

Using Similarity Matrix for Cluster Validation

- Clusters in random data are not so crisp





Observation (Complete Link Clustering)

•Complete link clustering applied to random data

•Resulting clusters show:

- **Overlapping boundaries**
- **Weak separation**

•Similarity blocks are **blurred and irregular**

Using Similarity Matrix for Cluster Validation





DBSCAN

Internal Measures: SSE

- Clusters in more complicated figures aren't well separated
- Internal Index: Used to measure the goodness of a clustering structure without respect to external information
  - SSE
- SSE is good for comparing two clusterings or two clusters (average SSE).
- Can also be used to estimate the number of clusters





Framework for Cluster Validity

RV College of Engineering®

A framework is needed to **interpret any validity measure**

Example: If an evaluation measure = **10**, is it **good, fair, or poor**?

- **Statistical Framework for Cluster Validity**
- Statistics help **interpret cluster validity measures**
- **Unusual (atypical) clustering results** are more likely to show **real structure**
- Index values can be compared with:
  - Results from **random data**
  - Results from **random clusterings**
- If an index value is **unlikely due to randomness**, the clustering is **valid**
- These methods are **complex and difficult to understand**

Comparing Two Clusterings

- When comparing **two clustering results**,
  a full statistical framework is **not always needed**
- However, we must check whether the **difference in index values is significant**

Statistical Framework for SSE

- Example
  - Compare SSE of 0.005 against three clusters in random data
  - Histogram shows SSE of three clusters in 500 sets of random data points of size 100 distributed over the range 0.2 – 0.8 for x and y values





Statistical Framework for Correlation

RV College of Engineering®

- Correlation of incidence and proximity matrices for the K-means clusterings of the following two data sets.



Corr = -0.9235



Corr = -0.5810



RV College of Engineering®

Internal Measures: Cohesion and Separation

- Cluster Cohesion: Measures how closely related are objects in a cluster
  - Example: SSE
- Cluster Separation: Measure how distinct or well-separated a cluster is from other clusters
- Example: Squared Error
  - Cohesion is measured by the **Within cluster sum of squares (SSE)**

$$WSS = \sum_i \sum_{x \in C_i} (x - m_i)^2$$

  - Separation is measured by the **Between cluster sum of squares**

    - Where $|C_i|$ is the size of cluster i

$$BSS = \sum_i |C_i| (m - m_i)^2$$

Internal Measures: Cohesion and Separation

- Example: SSE
  - BSS + WSS = constant



K=1 cluster:

$$WSS = (1-3)^2 + (2-3)^2 + (4-3)^2 + (5-3)^2 = 10$$

$$BSS = 4 \times (3-3)^2 = 0$$

$$Total = 10 + 0 = 10$$

K=2 clusters:

$$WSS = (1-1.5)^2 + (2-1.5)^2 + (4-4.5)^2 + (5-4.5)^2 = 1$$

$$BSS = 2 \times (3-1.5)^2 + 2 \times (4.5-3)^2 = 9$$

$$Total = 1 + 9 = 10$$

RV College of Engineering®

Case 1: K = 1 cluster

- All points belong to **one cluster**
- Cluster mean = overall mean = **3**

WSS (within-cluster error):

$$(1-3)^2 + (2-3)^2 + (4-3)^2 + (5-3)^2 = 10$$

BSS (between-cluster error):

$$4 \times (3-3)^2 = 0$$

Total:

$$WSS + BSS = 10 + 0 = 10$$

Case 2: K = 2 clusters

- Cluster 1: $\{1, 2\}$, mean $m_1 = 1.5$
- Cluster 2: $\{4, 5\}$, mean $m_2 = 4.5$

WSS (within clusters):

$$(1-1.5)^2 + (2-1.5)^2 + (4-4.5)^2 + (5-4.5)^2 = 1$$

BSS (between clusters):

$$2(3-1.5)^2 + 2(4.5-3)^2 = 9$$

Total:

$$WSS + BSS = 1 + 9 = 10$$

Internal Measures: Cohesion and Separation

- A proximity graph based approach can also be used for cohesion and separation.
  - Cluster cohesion is the sum of the weight of all links within a cluster.
  - Cluster separation is the sum of the weights between nodes in the cluster and nodes outside the cluster.



cohesion



separation

Internal Measures: Silhouette Coefficient

RV College of Engineering®

- Silhouette Coefficient combine ideas of both cohesion and separation, but for individual points, as well as clusters and clusterings
- For an individual point, *i*
  - Calculate ***a*** = average distance of *i* to the points in its cluster
  - Calculate ***b*** = min (average distance of *i* to points in another cluster)
  - The silhouette coefficient for a point is then given by

$$s = \begin{cases} 1 - \frac{a}{b}, & \text{if } a < b \\ \frac{b}{a} - 1, & \text{if } a \geq b \end{cases}$$

    s = 1 – a/b if a < b, (or s = b/a - 1 if a ≥ b, not the usual case)

  - Typically between 0 and 1.
  - The closer to 1 the better.



- Can calculate the Average Silhouette width for a cluster or a clustering

External Measures of Cluster Validity: Entropy and Purity

RV College of Engineering®

Table 5.9. K-means Clustering Results for LA Document Data Set

Cluster	Entertainment	Financial	Foreign	Metro	National	Sports	Entropy	Purity
1	3	5	40	506	96	27	1.2270	0.7474
2	4	7	280	29	39	2	1.1472	0.7756
3	1	1	1	7	4	671	0.1813	0.9796
4	10	162	3	119	73	2	1.7487	0.4390
5	331	22	5	70	13	23	1.3976	0.7134
6	5	358	12	212	48	13	1.5523	0.5525
Total	354	555	341	943	273	738	1.1450	0.7203

entropy For each cluster, the class distribution of the data is calculated first, i.e., for cluster j we compute p_{ij}, the 'probability' that a member of cluster j belongs to class i as follows: $p_{ij} = m_{ij}/m_j$, where m_j is the number of values in cluster j and m_{ij} is the number of values of class i in cluster j. Then using this class distribution, the entropy of each cluster j is calculated using the standard formula $e_j = \sum_{i=1}^{L} p_{ij} \log_2 p_{ij}$, where the L is the number of classes. The total entropy for a set of clusters is calculated as the sum of the entropies of each cluster weighted by the size of each cluster, i.e., $e = \sum_{i=1}^{K} \frac{m_i}{m} e_j$, where m_j is the size of cluster j, K is the number of clusters, and m is the total number of data points.

purity Using the terminology derived for entropy, the purity of cluster j, is given by $purity_j = \max p_{ij}$ and the overall purity of a clustering by $purity = \sum_{i=1}^{K} \frac{m_i}{m} purity_j$.