

Precision Experimental Protocol for Detecting Electromagnetic Stress Asymmetry in Asymmetric Resonant Cavities

Erick S. Sangalang

May 1, 2026

Abstract

We present a detailed experimental protocol for testing the existence of electromagnetic stress asymmetry in asymmetric resonant cavity systems. Building upon prior theoretical, quantitative, and simulation-based studies, this work defines a falsifiable laboratory framework for detecting nanonewton-scale force imbalances potentially arising from spatial energy-density asymmetry under nonequilibrium electromagnetic conditions. The protocol emphasizes systematic error suppression, reproducibility, and clear control experiments to distinguish genuine effects from known electromagnetic, thermal, and mechanical artifacts.

1 Introduction

Recent theoretical and simulation studies have suggested that asymmetric electromagnetic resonator geometries may produce spatial energy-density imbalances characterized by a dimensionless asymmetry parameter A . These imbalances, when coupled to phenomenological vacuum-response models, may give rise to measurable force effects under strong field conditions.

While prior work has established theoretical plausibility and numerical support for nonzero asymmetry factors, experimental validation remains an open challenge. The purpose of this work is to define a precision experimental protocol capable of testing these predictions in a controlled and falsifiable manner.

Null Hypothesis. The null hypothesis for this experiment is that no net force is observed beyond known electromagnetic, thermal, or mechanical effects. Any measured signal must be reproducible, scale with input power, and vanish under symmetric or control conditions to be considered physically significant.

2 Target Signal and Scaling

The proposed effect is characterized by a force scaling relation of the form:

$$F \propto \chi_{\text{eff}} A (E^2 + B^2), \quad (1)$$

where A represents the asymmetry parameter and χ_{eff} is an effective susceptibility.

Based on prior simulation results, typical values are:

$$A \sim 0.1, \quad (2)$$

leading to estimated force magnitudes in the range:

$$F \sim 1 - 100 \text{ nN}, \tag{3}$$

under high-field resonant conditions.

3 Experimental Setup

3.1 Vacuum Environment

Experiments should be conducted in a high-vacuum chamber to eliminate ion wind and convection effects:

- Pressure: $< 10^{-5}$ Torr
- Temperature stabilization recommended

3.2 Resonant Cavity

The cavity should be designed to maximize geometric asymmetry:

- Tapered or dielectric-loaded structure
- High quality factor: $Q \sim 10^3 - 10^5$
- Stable mounting to minimize mechanical coupling

As a representative example, a truncated conical cavity with length $L \sim 10$ cm, small-end radius $r_1 \sim 2$ cm, and large-end radius $r_2 \sim 5$ cm may be used to introduce controlled geometric asymmetry.

3.3 Electromagnetic Drive

- RF or microwave source
- Controlled power sweep
- Frequency tuned to resonance

Typical input power levels in the range of $10 - 100$ W are sufficient to produce measurable field intensities while remaining compatible with laboratory-scale resonator systems.

4 Force Measurement Techniques

4.1 Torsion Balance

A torsion balance provides high sensitivity to small forces:

- Sensitivity: sub-nanonewton achievable
- Optical readout recommended

4.2 Micro-Cantilever

Alternatively, micro-cantilever systems may be used:

- AFM-style detection
- High bandwidth and sensitivity

4.3 Measurement Sensitivity Requirements

To detect forces in the nanonewton regime, the measurement system must achieve a minimum sensitivity of:

$$F_{\min} \lesssim 1 \text{ nN.} \quad (4)$$

For a torsion balance with arm length $L \sim 0.1 \text{ m}$, this corresponds to a torque sensitivity:

$$\tau_{\min} \sim 10^{-10} \text{ N m.} \quad (5)$$

Such sensitivity is achievable using optical lever readout techniques and low-noise suspension systems.

5 Control Experiments

To ensure validity, the following controls are essential:

- **Power-off test:** No force signal
- **Symmetric cavity:** $A \approx 0 \Rightarrow F \approx 0$
- **Orientation reversal:** Sign of force should invert
- **Frequency detuning:** Signal should diminish off-resonance

6 Noise and Systematic Effects

6.1 Error Budget

Systematic Effect	Mitigation	Expected Impact
Thermal drift	Temperature stabilization	Reduced baseline drift
Vibration	Isolation platform	Reduced false displacement
Electrostatic forces	Grounding/shielding	Reduced charge artifacts
EM leakage	RF shielding	Reduced apparatus coupling
Lorentz forces in leads	Symmetric wiring	Reduced spurious force

Key sources of error include:

- Thermal expansion and drift
- Vibrational coupling
- Electromagnetic interference with measurement apparatus

- Electrostatic forces and charge accumulation

Mitigation strategies should include:

- Shielding and grounding
- Active vibration isolation
- Temperature stabilization

7 Expected Signal Characteristics

The expected signal should exhibit:

- Dependence on input power ($\propto E^2$)
- Dependence on cavity asymmetry ($\propto A$)
- Resonance enhancement
- Directional consistency with cavity geometry

8 Discussion

This protocol provides a clear experimental pathway for testing electromagnetic stress asymmetry under nonequilibrium conditions. The emphasis on control experiments and systematic error mitigation ensures that any observed effect can be critically evaluated.

A null result below 1 nN under resonant, high-asymmetry conditions would constrain the effective response parameter for the tested geometry and rule out signal models predicting forces above this threshold. A null result would place meaningful constraints on phenomenological models, while a positive result would motivate deeper theoretical and experimental investigation.

9 Experimental Layout

10 Conclusion

Future work will focus on implementing this protocol in a controlled laboratory environment and comparing measured force limits against predicted scaling behavior.

We have outlined a precision experimental protocol for detecting potential electromagnetic stress asymmetry in asymmetric resonant cavities. This framework enables direct, falsifiable testing of previously proposed theoretical and numerical predictions and provides a foundation for future high-sensitivity investigations.

References

- [1] J. D. Jackson, *Classical Electrodynamics*, 3rd ed., Wiley, 1998.
- [2] A. Taflov and S. C. Hagness, *Computational Electrodynamics: The Finite-Difference Time-Domain Method*, 3rd ed., Artech House, 2005.
- [3] P. W. Milonni, *The Quantum Vacuum*, Academic Press, 1994.




Figure 1: Proposed experimental configuration showing an asymmetric resonant cavity mounted on a torsion balance within a vacuum chamber. The expected force direction is aligned with the cavity axis, and displacement is measured via optical readout.