

Precision Experimental Protocols for Coherent Nonequilibrium Electromagnetic Systems

Erick Sangalang

April 29, 2026

Abstract

This paper proposes a conservative experimental methodology for testing whether strongly driven coherent electromagnetic systems exhibit measurable nonequilibrium ordering behavior beyond conventional dissipative expectations. The work does not claim verified anomalous propulsion, vacuum-energy extraction, or violation of conservation laws. Instead, it develops precision protocols for evaluating resonant electromagnetic systems under controlled laboratory conditions, emphasizing artifact rejection, thermal management, electromagnetic shielding, vibration isolation, vacuum testing, calibration, blind analysis, and null-result interpretation. Candidate systems include high- Q microwave cavities, asymmetric dielectric resonators, superconducting resonators, and metamaterial field-localization structures. The proposed framework is intended to make speculative coherent-field ordering hypotheses experimentally falsifiable while remaining compatible with established thermodynamics and electrodynamics.

1 Introduction

Coherent electromagnetic systems operating far from equilibrium appear in many established areas of physics, including microwave cavity electrodynamics, plasma confinement, superconducting resonators, nonlinear optics, and metamaterials [5, 7, 8, 6]. Such systems may exhibit resonant field localization, metastability, long-lived modes, and nonlinear dissipation pathways.

A recurring challenge in speculative discussions of nonequilibrium electromagnetic systems is the difficulty of distinguishing genuine physical effects from conventional artifacts. Apparent anomalous signals may arise from thermal gradients, electrohydrodynamic forces, Lorentz coupling, electromagnetic leakage, vibration, ground loops, piezoelectric response, cable forces, acoustic effects, or sensor drift.

The purpose of this paper is not to assert that anomalous effects exist. Rather, it proposes a rigorous experimental protocol for testing constrained hypotheses involving coherent nonequilibrium electromagnetic organization. The systems considered here are assumed to be open, externally driven, and fully subject to conservation laws and the second law of thermodynamics.

2 Scope and Scientific Restraint

The present work adopts the following constraints:

- no claim of verified anomalous propulsion is made;
- no claim of unrestricted energy extraction is made;
- no new fundamental force is asserted;

- all proposed effects must be experimentally distinguishable from known electromagnetic, thermal, mechanical, and instrumental artifacts;
- null results are considered scientifically valuable because they constrain the parameter space of coherent nonequilibrium hypotheses.

This framing places the work within experimental methodology rather than speculative confirmation.

3 Candidate Experimental Systems

Candidate systems for controlled investigation include:

- high- Q microwave cavities;
- asymmetric dielectric resonators;
- superconducting microwave resonators;
- metamaterial field-localization structures;
- plasma or gas-discharge resonators under controlled pressure;
- coupled resonant cavity systems with adjustable boundary conditions.

Each candidate platform should be selected based on measurable field confinement, reproducible excitation conditions, thermal controllability, and compatibility with instrumentation shielding.

4 Primary Observables

The most defensible observables are not extraordinary force claims, but conservative measurable quantities such as:

- quality factor variation under controlled boundary changes;
- mode-frequency shifts;
- coherence-dependent dissipation;
- thermal relaxation curves;
- field-localization profiles;
- transient electromagnetic energy retention;
- statistically significant deviations from baseline dissipative models.

Force measurements, if included, should be treated as secondary and only considered after thermal, electromagnetic, and mechanical artifacts are suppressed below the claimed signal scale.

5 Baseline Theoretical Expectation

For a resonant cavity, the stored electromagnetic energy may be written conventionally as

$$U = \frac{1}{2} \int_V (\epsilon |\mathbf{E}|^2 + \mu |\mathbf{H}|^2) dV, \quad (1)$$

where ϵ and μ are the material permittivity and permeability, and $\mathbf{E}$ and $\mathbf{H}$ are the electric and magnetic fields.

The quality factor is conventionally defined as

$$Q = \omega \frac{U}{P_{\text{loss}}}, \quad (2)$$

where ω is angular frequency and P_{loss} is dissipated power.

Any proposed coherent nonequilibrium ordering effect should first be expressed as a deviation from conventional energy-storage, loss, and relaxation behavior rather than as a claim of new energy production.

6 Experimental Protocol




Figure 1: Recommended experimental workflow for testing coherent nonequilibrium electromagnetic systems. The sequence emphasizes baseline characterization, matched controls, environmental isolation, blind testing, artifact rejection, statistical evaluation, and independent replication before any extraordinary interpretation is considered.

6.1 Stage 1: Device Characterization

Before any driven nonequilibrium test, the device should be characterized under low-power baseline conditions:

- measure resonant frequencies;
- measure unloaded and loaded quality factors;
- map field distributions where possible;
- document dielectric, conductor, and thermal properties;
- record environmental conditions.

6.2 Stage 2: Control Configuration

Each experiment should include at least one matched control configuration:

- geometrically symmetric control resonator;
- detuned resonator control;
- nonresonant dummy load;
- reversed-orientation device;
- inactive thermal-equivalent control.

The purpose is to distinguish coherent resonant behavior from ordinary heating, wiring forces, or mechanical coupling.

6.3 Stage 3: Environmental Isolation

Testing should be performed with:

- vibration isolation platform;
- temperature-controlled enclosure;
- shielded cables and feedthroughs;
- Faraday shielding;
- magnetic-field monitoring;
- pressure-controlled chamber when gas effects are relevant.

Vacuum testing is especially important for excluding electrohydrodynamic and ion-wind artifacts in high-voltage or asymmetric-field systems [10, 11].

6.4 Stage 4: Blind and Reversed Tests

To reduce interpretation bias, the following procedures are recommended:

- blind switching between active and control configurations;
- randomized power-on and power-off sequences;
- device reversal tests;
- cable-route reversal tests;
- independent operator verification;
- automated data logging with timestamped environmental channels.

Table 1: Representative artifact sources and corresponding mitigation strategies.

Artifact Source	Primary Mitigation Strategy
Thermal gradients	Multi-point thermal monitoring and matched heating controls
Ion wind / electrohydrodynamics	Vacuum and pressure-dependent testing
Electromagnetic leakage	Faraday shielding, spectrum monitoring, and dummy-load controls
Cable forces	Cable-route reversal and mechanical decoupling
Vibration / acoustic coupling	Isolation platform and accelerometer monitoring
Sensor drift	Baseline logging, calibration checks, and blind switching
Ground loops	Isolated grounding and shield-current monitoring

7 Artifact Rejection

7.1 Thermal Artifacts

Thermal effects can produce apparent forces, frequency shifts, drift, and mechanical deformation. Required controls include:

- thermocouple or infrared monitoring at multiple locations;
- matched resistive heating control;
- thermal time-constant modeling;
- delayed-response analysis after power shutdown;
- isolation from convection where applicable.

7.2 Electromagnetic Coupling

Electromagnetic leakage can couple into sensors, cables, supports, and nearby conductive structures. Controls include:

- spectrum monitoring outside the cavity;
- shield-current monitoring;
- cable-force null tests;
- dummy-load comparison;
- ground-loop isolation;
- sensor operation with RF source disconnected.

7.3 Mechanical and Vibrational Effects

Mechanical artifacts may arise from acoustic excitation, piezoelectric response, fan vibration, pump vibration, and resonant mounting structures. Recommended controls include:

- accelerometer monitoring;
- optical displacement sensing;
- pump-off measurement intervals;
- mechanical dummy masses;
- repeated orientation reversal;
- rigid and flexible mounting comparisons.

8 Vacuum and Pressure Testing

For high-voltage or asymmetric electromagnetic devices, testing should be repeated across pressure regimes:

- atmospheric pressure;
- reduced pressure;
- high vacuum where feasible;
- controlled gas composition.

A genuine non-electrohydrodynamic effect should not scale in the same manner as ion wind, corona discharge, or neutral-gas convection. Pressure dependence should therefore be treated as a primary diagnostic rather than a secondary control.

9 Data Analysis

Data analysis should be performed using pre-registered criteria where possible:

- define the primary observable before data collection;
- define exclusion criteria before data collection;
- report all null results;
- include uncertainty propagation;
- compare against control configurations;
- avoid post-hoc selection of favorable intervals.

Statistical significance should not be interpreted as physical significance unless systematic uncertainties are demonstrated to be below the claimed effect scale.

10 Criteria for a Meaningful Positive Result

A meaningful positive result would require:

1. repeatability across multiple runs;
2. disappearance under appropriate control conditions;
3. scaling with resonant or coherence parameters rather than only with heating;
4. persistence after known artifacts are suppressed;
5. independent replication by another laboratory or operator;
6. compatibility with conservation laws and measured energy inputs.

A single anomalous run should not be considered evidence for new physics.

11 Value of Null Results

Null results are scientifically valuable because they:

- constrain speculative parameter space;
- identify dominant artifacts;
- improve instrumentation practices;
- clarify whether coherent ordering hypotheses reduce to conventional electrodynamics;
- guide future resonator design.

A null result under well-controlled conditions is more valuable than a positive result under poorly constrained conditions.

12 Recommended Reporting Standard

Reports should include:

- complete geometry;
- materials and dielectric properties;
- resonant frequencies and quality factors;
- input power and reflected power;
- environmental temperature and pressure;
- shielding layout;
- cable routing;
- calibration procedures;
- raw and processed data;
- uncertainty budget;
- control results.

Whenever feasible, raw datasets, environmental logs, calibration records, and analysis scripts should be made openly available to facilitate independent verification.

This standard is intended to make future claims independently assessable.

13 Discussion

The protocol proposed here shifts the emphasis from broad theoretical speculation to falsifiable experimental discipline. If coherent nonequilibrium electromagnetic ordering effects exist, they should be detectable through carefully controlled deviations from conventional dissipation, relaxation, or field-localization behavior. If such deviations are absent, the resulting null constraints remain scientifically useful.

The strongest experimental posture is therefore not to seek confirmation of extraordinary claims, but to design tests capable of clearly separating coherent resonant behavior from known artifacts.

14 Conclusion

This paper presented a conservative experimental framework for testing coherent nonequilibrium electromagnetic ordering hypotheses. The proposed protocols emphasize artifact rejection, environmental isolation, matched controls, pressure dependence, blind testing, and rigorous uncertainty analysis.

No claim is made that anomalous energy, propulsion, or new fundamental forces have been observed. Instead, the work provides a methodological pathway for determining whether coherent resonant electromagnetic systems exhibit measurable nonequilibrium behavior beyond conventional dissipative expectations.

A disciplined experimental framework may allow speculative hypotheses to be converted into falsifiable scientific questions. Whether future results are positive or null, such investigations can clarify the limits of coherent electromagnetic organization, boundary-condition physics, and nonequilibrium field behavior.

References

- [1] J. W. Gibbs, *On the Equilibrium of Heterogeneous Substances*, Transactions of the Connecticut Academy, 1876–1878. DOI: 10.5962/bhl.title.5501
- [2] H. B. Callen, *Thermodynamics and an Introduction to Thermostatistics*, 2nd Edition, Wiley, 1985. DOI: 10.1002/9780470117731
- [3] G. Nicolis and I. Prigogine, *Self-Organization in Nonequilibrium Systems*, Wiley, 1977. DOI: 10.1002/9780470142566
- [4] H. Haken, *Synergetics: An Introduction*, Springer, 1983. DOI: 10.1007/978-3-642-88338-5
- [5] J. D. Jackson, *Classical Electrodynamics*, 3rd Edition, Wiley, 1998. DOI: 10.1002/9781119015500
- [6] D. M. Pozar, *Microwave Engineering*, 4th Edition, Wiley, 2011. ISBN: 978-0470631553
- [7] A. Taflov and S. Hagness, *Computational Electrodynamics: The Finite-Difference Time-Domain Method*, Artech House, 2005. DOI: 10.1002/0471654507
- [8] S. Haroche and J.-M. Raimond, *Exploring the Quantum*, Oxford University Press, 2006. DOI: 10.1093/acprof:oso/9780198509146.001.0001
- [9] P. W. Milonni, *The Quantum Vacuum*, Academic Press, 1994. DOI: 10.1016/C2009-0-21276-3
- [10] J. C. Brown and G. W. Walker, “Electric Wind: Forces on Charged Particles and Conductors,” *American Journal of Physics*, 1970. DOI: 10.1119/1.1976263
- [11] T. B. Bahder and C. Fazi, “Force on an Asymmetric Capacitor,” Army Research Laboratory Technical Report, 2003. Available through U.S. Army Research Laboratory archives.
- [12] M. Tajmar and M. Kößling, “Study of the EmDrive Force Measurement with a Torsion Pendulum,” *Acta Astronautica*, 2018. DOI: 10.1016/j.actaastro.2018.07.014
- [13] JCGM, *Evaluation of Measurement Data—Guide to the Expression of Uncertainty in Measurement*, Joint Committee for Guides in Metrology, 2008. Available from the Bureau International des Poids et Mesures.