

Toward Testable Signatures of Emergent Vacuum Response: Quantitative Predictions for Asymmetric Electromagnetic Resonators

Erick S Sangalang

April 30, 2026

Abstract

We present a phenomenological framework for evaluating possible emergent vacuum-response effects in asymmetric electromagnetic resonators. By introducing an effective susceptibility parameter and a measurable asymmetry factor, we derive scaling relations and quantitative force predictions under nonequilibrium electromagnetic conditions. For representative high-field resonator parameters, the model predicts nanonewton-scale signals, with a central estimate of approximately 5–20 nN and a broader illustrative range of 1–100 nN. The framework is intentionally formulated as a falsifiable parameterization: null results at or below the nanonewton level would directly constrain the effective susceptibility and restrict the class of proposed vacuum-response models considered here.

1 Introduction

Precision electromagnetic systems provide a controlled setting for testing small deviations from conventional electromagnetic behavior. Standard classical electrodynamics, when applied to a closed system, predicts no net self-acceleration or reactionless force because momentum conservation requires the internal electromagnetic stresses to cancel. Any proposed anomalous force in a resonant electromagnetic cavity must therefore be treated with substantial caution and must be framed in a way that is experimentally falsifiable.

The purpose of this work is not to claim a verified departure from established physics. Instead, we develop a compact phenomenological model that converts a speculative vacuum-response hypothesis into explicit predictions. The central goal is to define what would be measured, how the signal should scale, and what null results would imply.

2 Theoretical Motivation

The electromagnetic energy density in vacuum is

$$\nu = \frac{1}{2}\epsilon_0 E^2 + \frac{1}{2\mu_0} B^2, \quad (1)$$

where E and B are the local electric and magnetic field amplitudes. In conventional electrodynamics, the distribution of this energy density contributes to stresses and radiation pressure, but the net force on a closed, isolated cavity vanishes after all momentum fluxes and boundary stresses are accounted for.

The present model introduces a small effective correction to the local energy density under nonequilibrium and asymmetric resonator conditions:

$$\nu_{\text{eff}} = \nu (1 + \chi_{\text{eff}} A), \quad (2)$$

where χ_{eff} is an effective vacuum-response susceptibility and A is a dimensionless asymmetry factor. This expression should be interpreted as a test parameterization rather than a microscopic derivation. The model reduces to the standard expectation when $A \rightarrow 0$, $\chi_{\text{eff}} \rightarrow 0$, or the resonator geometry is symmetric.

3 Definition of the Asymmetry Parameter

To avoid treating A as an arbitrary fitting factor, we define it as the normalized imbalance in electromagnetic energy density between opposing regions of the cavity:

$$A = \frac{\int_V (\nu_+ - \nu_-) dV}{\int_V (\nu_+ + \nu_-) dV}, \quad (3)$$

where ν_+ and ν_- denote energy-density contributions associated with opposing regions or directions of the resonator geometry. In an ideal symmetric cavity, $A \approx 0$. In a tapered or dielectric-loaded resonator with a strongly nonuniform field distribution, A may become nonzero.

4 Force Estimate

In classical electrodynamics, the force on material boundaries may be written in terms of the Maxwell stress tensor. In a closed symmetric system, the surface integral of the stress tensor cancels. The phenomenological hypothesis explored here is that a small nonequilibrium vacuum response could appear as an effective imbalance in the stress distribution.

Approximating this imbalance as a gradient in effective electromagnetic energy over a characteristic length L , the estimated force scale is

$$F \sim \frac{\chi_{\text{eff}} A \nu V}{L}, \quad (4)$$

where V is the effective resonator volume. Equation (4) is not a replacement for a full stress-tensor calculation; it is an order-of-magnitude scaling law designed to identify experimentally accessible regimes.

5 Representative Parameters and Prediction

For a tabletop high-field resonator, we take representative values:

$$V \sim 10^{-4} \text{ m}^3, \quad (5)$$

$$L \sim 0.1 \text{ m}, \quad (6)$$

$$A \sim 0.1, \quad (7)$$

$$\chi_{\text{eff}} \sim 10^{-8} - 10^{-6}. \quad (8)$$

For electromagnetic energy densities in the approximate range

$$\nu \sim 10^2 - 10^4 \text{ J/m}^3, \quad (9)$$

the predicted force scale is

$$F \sim 10^{-9} - 10^{-7} \text{ N}, \quad (10)$$

or

Predicted force range: 1–100 nN.

A narrower central estimate for $\chi_{\text{eff}} \sim 10^{-7}$, $A \sim 0.1$, and $U = \nu V \sim 0.05\text{--}0.2 \text{ J}$ is

$$F \approx 5\text{--}20 \text{ nN}.$$

6 Scaling Behavior and Figures

$$F \propto \chi_{\text{eff}} A (E^2 + B^2) \quad (11)$$

For a fixed magnetic-field contribution, the incremental electric-field contribution scales linearly with E^2 , as shown in Fig. 1. This scaling provides a simple experimental discriminator: a genuine signal should track controlled field-amplitude variation, while many mechanical and thermal artifacts will not follow the same dependence.




Figure 1: Predicted incremental force contribution as a function of E^2 , using $V = 10^{-4} \text{ m}^3$, $L = 0.1 \text{ m}$, $A = 0.1$, and $\chi_{\text{eff}} = 10^{-7}$. The plot isolates the electric-field contribution so that the expected linear scaling is visible without a large magnetic-field baseline offset.

Figure 2 illustrates a representative asymmetric energy-density distribution. This figure is not a full electromagnetic simulation; it is a schematic visualization of the type of imbalance captured by A . A future numerical study should compute A directly from finite-element or finite-difference field solutions.




Figure 2: Representative asymmetric field-energy distribution motivating the normalized asymmetry parameter A . The dashed line separates opposing regions used conceptually in Eq. (3).

7 Experimental Implementation

Figure 3 illustrates a representative implementation in which geometric asymmetry produces a controlled imbalance in field-energy distribution.

A feasible test system consists of a high- Q microwave or radiofrequency resonator with geometric tapering or dielectric loading, mounted on a torsion balance or equivalent precision force sensor under high vacuum. Operation below approximately 10^{-5} Torr would reduce electrohydrodynamic and convective artifacts. Thermal gradients, Lorentz forces in leads, vibrational coupling, and electromagnetic leakage must be independently monitored and suppressed.

A conceptual test geometry is shown in Fig. 3. The figure illustrates the desired ingredients: a driven resonant electric-field mode, an applied magnetic field, and a controlled geometric or dielectric asymmetry. The essential experimental test is not simply the observation of a nonzero force, but whether the signal reverses, vanishes, or scales according to the model when A , E , B , phase coherence, or cavity orientation are varied.

8 Relation to Prior Experimental Claims and Null Results

Reports of anomalous forces in asymmetric resonant cavities have historically generated significant debate. Subsequent experimental investigations have emphasized the importance of thermal, electromagnetic, vibrational, and measurement-system artifacts. Null or inconclusive results in related tests do not by themselves rule out every phenomenological model, but they do impose important constraints and raise the evidentiary bar for any proposed effect.

For this reason, the present framework is explicitly falsifiable. If no force above 1 nN is observed under the specified conditions, then the model is constrained approximately by

$$\chi_{\text{eff}} \lesssim 10^{-8} \quad (12)$$




Figure 3: Conceptual asymmetric resonator geometry. A tapered or dielectric-loaded cavity can produce a nonuniform energy-density distribution. In the proposed test, the predicted signal should depend on the asymmetry parameter and vanish in a symmetric control geometry.

for $A \sim 0.1$ and the representative energy-density range considered here. Stronger null results would proportionally tighten this bound.

9 Discussion

Any confirmed signal would require careful reconciliation with conservation of momentum and may imply either overlooked classical effects or the need for extended theoretical description.

The model presented here is intentionally minimal. It does not provide a microscopic derivation of χ_{eff} , nor does it claim that such a vacuum-response susceptibility has been experimentally observed. Its value lies in translating a speculative idea into a quantitative and falsifiable experimental target.

The most important next step is a numerical field study that computes A for specific resonator geometries and evaluates whether realistic field configurations can produce the assumed energy-density imbalance. A subsequent experimental program should then test the predicted scaling with field strength, asymmetry, and cavity orientation.

10 Conclusion

We have presented a quantitative phenomenological framework for possible emergent vacuum-response signatures in asymmetric electromagnetic resonators. The model predicts nanonewton-scale forces under representative high-field conditions and provides explicit scaling and falsification criteria. The framework is not intended as proof of new physics; rather, it defines a measurable target and a clear route for experimental constraint or rejection.

References

- [1] J. D. Jackson, *Classical Electrodynamics*, 3rd ed., Wiley, 1998.
- [2] P. W. Milonni, *The Quantum Vacuum*, Academic Press, 1994.

- [3] A. Taflov and S. C. Hagness, *Computational Electrodynamics: The Finite-Difference Time-Domain Method*, 3rd ed., Artech House, 2005.
- [4] K. Yee, “Numerical solution of initial boundary value problems involving Maxwell’s equations in isotropic media,” *IEEE Transactions on Antennas and Propagation*, vol. 14, no. 3, pp. 302–307, 1966.
- [5] H. White, P. March, J. Lawrence, J. Vera, A. Sylvester, D. Brady, and P. Bailey, “Measurement of impulsive thrust from a closed radio-frequency cavity in vacuum,” *Journal of Propulsion and Power*, vol. 33, no. 4, pp. 830–841, 2017.
- [6] M. Tajmar and M. Kößling, “EmDrive thrust measurements with a torsion balance and using a high power amplifier,” *Acta Astronautica*, vol. 161, pp. 139–144, 2019.