CS684
Embedded Systems (Software)

Models and Tools for Embedded Systems

Kavi Arya

CSE / IIT Bombay

Models and Tools for Embedded Systems

Organization

1. Model-based Development of Embedded Sys.
2. Review of models of concurrency in programming languages
3. Introduction to Lustre/Scade, (Esterel,) Scilab
4. Simple case studies

Development Challenges (Complexity)

- Correct functioning is crucial
- Reactive
- Concurrent
- Realtime
- Stringent resource constraints

Development Challenges

Embedded Systems are complex

1. **Correct functioning is crucial**
   - safety-critical applications
   - damage to life, economy can result
2. **They are Reactive Systems**
   - Once started run forever.
   - Termination is a bad behavior.
   - Compare conventional computing (transformational systems)

Development Challenges

3. **Concurrent systems**
   - System and environment run concurrently
   - Multi-functional

4. **Real-time systems**
   - Not only realtime outputs - but in realtime
   - Imagine delay of minutes in pacemaker system

Development Challenges

5. **Stringent resource constraints**
    - Compact systems
        - simple processors
        - limited memory
    - Quick response
    - Good throughput
    - Low power
    - Time-to-market

System Development

- Process of arriving at final product from reqs
- Requirements
  - Vague ideas, algorithms, of-the shelf components, additional functionality etc.
  - Natural Language statements
  - Informal
- Final Products
  - System Components
  - Precise and Formal

System Components

- **Embedded System Components**
  - Programmable processors (controllers & DSP)
  - Standard and custom hardware
  - Concurrent Software
  - OS Components:
    - Schedulers, Timers, Watchdogs,
    - IPC primitives
  - Interface components
    - External, HW and SW interface

System Development

- Decomposition of functionality
- Architecture Selection:
  Choice of processors, standard hardware
- Mapping of functionality to HW and SW
- Development of Custom HW and software
- Communication protocol between HW and SW
- Prototyping, verification and validation

Functional Design & Mapping



Source:
Ian Phillips, ARM
VSIA 2001

Design Choices

- Choices in Components
  - Processors, DSP chips, Std. Components
- Many different choices in mapping
  - Fully HW solution
    - More speed, cost, TTM (Time to market), less robust
    - Standard HW development
  - Fully SW solution
    - Slow, less TTM, cost, more flexible
    - Standard microcontroller development

Mixed Solution

- **Desired Solution is often mixed**
  - Optimal performance, cost and TTM
  - Design is more involved and takes more time
  - Involves Co-design of HW and SW
  - System Partitioning - difficult step
  - For optimal designs, design exploration and evaluation essential
  - Design practices supporting exploration and evaluation essential
  - Should support correctness analysis as it is crucial to ensure high quality

Classical design methodology



Development Methodology

- **Simplified Picture of SW development**
  - Requirements Analysis
  - Design
  - Implementation (coding)
  - Verification and Validation
  - Bugs lead redesign or re-implementation

Development Methodology

- **All steps (except implementation) are informal**
  - Processes/ objects not well defined and ambiguous
  - Design and requirement artifacts not precisely defined
  - Inconsistencies and incompleteness
  - No clear relationship between different stages
  - Subjective, no universal validity
  - Independent analysis difficult
  - Reuse not possible

Classical Methodology

- **Totally inadequate for complex systems**
  - Thorough reviews required for early bug removal
  - Bugs often revealed late while testing
  - Traceability to Design steps not possible
  - Debugging difficult
  - Heavy redesign cost
- **Not recommended for high integrity systems**
  - i.e. embedded systems

Formal Methodology

- **A methodology using precisely defined artifacts at all stages**
  - Precise statement of requirements
  - Formal design artifacts (Models)
  - Formal: Precisely defined syntax and semantics
  - Translation of Design models to implementation

Model-based Development

- Models: abstract & high level desc. of design objects
- Focus on one aspect at a time
- Less development and redesign time
- Implementation constraints can be placed on models
- Design exploration, evaluation & quick prototyping possible using models

New Paradigm

- Executable models essential
  - Simulation
- Can be rigorously validated
  - Formal Verification
- Models can be debugged and revised
- Automatic generation of final code
  - Traceability
- The paradigm

  Model – Verify – Debug – CodeGenerate

Model-based Methodology



Tools

- Various tools supporting such methodologies
  - **commercial and academic**
- POLIS (Berkeley), Cierto VCC (Cadence)
- SpecCharts (Irvine)
- STATEMATE, Rhapsody (ilogix)
- Rose RT (Rational)
- SCADE, Esterel Studio (Esterel Technologies)
- Stateflow and Simulink (Mathworks)

Modeling Languages

- Models need to be formal
- Languages for describing models - various exist
- High level programming languages (C, C++)
- Finite State Machines, Statecharts, SpecCharts, Esterel, Stateflow
- Data Flow Diagrams, Lustre, Signal, Simulink
- Hardware generation languages (Handel-C)
- Hardware description languages (VHDL, Verilog)
- Unified Modeling Language(UML)

Modeling Languages

- Choice of languages depends on nature of computations modeled
- Seq. programming models for standard data processing computations
- Data flow diagrams for iterative data transformation
- State Machines for controllers
- HDLs for hardware components

Reactive Systems

- Standard Software is a transformational system
- Embedded software is reactive



Reactive Systems



RS features

- Non-termination
- Ongoing continuous relationship with environment
- Concurrency (at least system and   environment)
- Event driven
- Events at unpredictable times
- Environment is the master
- Timely response (hard and soft real time)
- Safety - Critical
- Conventional models inadequate

Finite State Machines

- One of the well-known models
- Intuitive and easy to understand
- Pictorial appeal
- Can be made rigorous
- Standard models for Protocols, Controllers, HW

A Simple Example

- 3 bit counter
- C – count signal for increments
- Resets to 0 when counter reaches maximum value
- Counter can be described by a program with a counter variable (Software Model)
- Or in detail using flip flops, gates and wires (Hardware model)



State Machine Model

- Counter behaviour naturally described by state machine
- States determine the current value of the counter
- Transitions model state changes to the event C.
- Initial state determines initial value of counter
- No final state (why?)

Precise Definition

< Q, q0, S, T>

- Q – A finite no. of state names
- q0 – Initial state
- S – Edge alphabet

  Abstract labels to concrete event, condition and action
- T – edge function or relation

Semantics

- Given syntax, a precise semantics can be defined
- Set of all possible sequences of states & edges
- Each sequence starts with the initial state
- Every state-edge-state triples are adjacent states connected by an edge
- Given FSM, unique set of sequences can be associated
- Language accepted by a FSM

Abstract Models

- Finite State machine model is abstract
- Abstracts out various details
  - How to read inputs?
  - How often to look for inputs?
  - How to represent states and transitions?
  - Focus on specific aspects
- Easy for analysis, debugging
- Redesign cost is reduced
- Different possible implementations
  - Hardware or Software
  - Useful for codesign of systems

Intuitive Models

- FSM models are intuitive
- Visual
  - A picture is worth a thousand words
- Fewer primitives – easy to learn, less scope for mistakes and confusion
- Neutral and hence universal applicability
  - For software, hardware and control engineers

Rigorous Models

- FSM models are precise and unambiguous
- Have rigorous semantics
- Can be executed (or simulated)
- Execution mechanism is simple: An iterative scheme

```
state = initial_state
    loop
        case state:
            state 1:   Action 1
            state 2:   Action 2
                . . .
        end case
    end
```

Code Generation

- FSM models can be refined to different implementation
  - Both HW and SW implementation
  - Exploring alternate implementations
  - For performance and other considerations
- Automatic code generation
- Preferable over hand generated code
- Quality is high and uniform

Another Example

A Traffic Light Controller

- Traffic light at intersection of Highway & Farm road
- Farm road sensors (signal C)
- G, R – setting signals green and red
- S,L - short and long timer signal
- TGR - reset timer, set hway green & farm road red

State Machine



Another Example

A Simple Lift Controller

3-floor lift

- Lift can be in any floor
  - S_i - in floor I
- Request can come from any floor
  - ri - request from floor I
- Lift can be asked to move up or down
  - uj,dj - up/down to jth floor

FSM model



Nondeterminism

- Suppose lift is in floor 2 (State S_2)
- What is the next state when requests r1 and r3 arrive?
  - Go to S_1
  - Or go to S_3
- The model non committal – allows both
- More than one next state for a state and an input
- This is called nondeterminism
- Nondeterminism arises out of abstraction
- Algorithm to decide the floor is not modeled
- Models can be nondeterministic but not real lifts!

Nondeterminism

- Models focus attention on a particular aspect
- The lift model focused on safety aspects
- And so ignored the decision algorithm
  - Modeling languages should be expressive
  - Std. Programming languages are not
- Use another model for capturing decision algorithm
- Multiple models, separation of concerns
  - Independent analysis and debugging
  - Management of complexity
- Of course, there should be a way of combining different models

C-model

```
enum floors {f1, f2, f3};
enum State {first, second, third};
enum bool {ff, tt};
enum floors req, dest;
enum bool up, down = ff;
enum State cur_floor = first;

req = read_req();


while (1)
{ switch (cur_floor)
  { case first: if (req == f2)
                  {up = tt; dest = f2;}
                else if (req == f3)
                  {up = tt; dest = f3;}
                else { up == ff; down = ff;};
                break;
```

C- model

```
case second: if (req == f3)
                    {up = tt; dest = f3;}
                 else if (req == f1)
                       { up = ff; down = tt; dest = f1;}
                     else { up == ff; down = ff;};
                 break;
case third:   if (req == f2)
                   {up = ff; down = tt; dest = f2;}
              else if (req == f1)
                     { up = ff; down = tt; dest = f1;}
                   else { up == ff; down = ff;};
              break; }; /* end of switch */
              req = read_req();   } /* end of while */
```

Suitability of C

- C not natural for such applications
- Various problems
  - Events and states all modeled as variables
  - Not natural for event oriented embedded applications
  - States are implicit (control points decide states)
  - No abstract description possible
  - Commitment to details at an early stage
  - Too much work when design likely to be discarded

Exercise

- Is the C model non-deterministic?
- What happens when two requests to go in different directions arrive at a state?

Yet Another example

- A Simple Thermostat controller



Summary

- Finite number of states
- Initial state
- No final state (reactive system)
- Non determinism (result of abstraction)
- Edges labeled with events
- Behavior defined by sequences of transitions
- Rigorous semantics
- Easy to simulate and debug
- Automatic Code generation

Problems with FSMs

- All is not well with FSMs
- FSMs fine for small systems (10s of states)
- Imagine FSM with 100s and 1000s of states which is a reality
- Such large descriptions difficult to understand
- FSMs are flat and no structure
- Inflexible to add additional functionalities
- Need for structuring and combining different state machines

References

- F. Balarin et al., Hardware – Software Co-design of Embedded Systems: The POLIS approach, Kluwer, 1997
- N. Halbwachs, Synch. Prog. Of Reactive Systems, Kluwer, 1993
- D. Harel et al., STATEMATE: a working environment for the development of complex reactive systems, IEEE Trans. Software Engineering, Vol. 16 (4), 1990.
- J. Buck, et al., Ptolemy: A framework for simulating and prototyping heterogeneous systems, Int. Journal of Software Simulation, Jan. 1990