

GESTIONNAIRE AVANCÉ DE DUPLICATION

Gad — User Guide

Illustrated User Guide

Gestionnaire Avancé de Duplication · Version 0.1.0
Gad, il copie.
US English edition, updated November 6, 2026.

Quick Start · Français · All editions

Project documentation · Offline edition
Version 0.1.0 · November 2026

Contents

Other file managers

Excluding items from transfers

1. What Gad does
2. Installation and startup
3. Understanding the window
4. Using Ctrl+V in Dolphin
5. Starting a copy or move
6. Fast local moves
7. Reading states and progress
8. Organizing the queue
9. Pausing and resuming
10. Limiting bandwidth
11. Resolving conflicts
12. Canceling or undoing transfers
13. Using the context menu
14. Error reporting and targeted retries
15. Checking file contents with MD5
16. Checking file properties
17. Checking available space
18. Waiting for a device to reconnect
19. Resuming after a crash
20. History and cleanup
21. System tray and session startup
22. Phones, FTP, SFTP, and SMB
23. Keyboard reference
24. Troubleshooting
25. Limits and good practices

What Gad does

Gad manages file copies and moves in one KDE Plasma window. Each new request adds work to the queue. The list shows folders and their children, waiting files, active transfers, completed results, and failures. Rows belonging to the same request share a subtle background color and an accent marker.

A **request**, also called a batch, corresponds to one submission: pasting three files creates one request containing those files. Selecting a folder also includes its subfolders and files. The grouping remains useful for destination settings, progress, and undo, even though there are no batch headers above the file rows.

Up to two transfers can run simultaneously when their source and destination disks are independent. A proven local rename can also run alongside a copy on a shared disk when their paths do not overlap. Unknown disk relationships make ordinary copies run alone.

Gad integrates with Dolphin through **Paste with Gad** and its optional Ctrl+V setting. Konqueror integration uses **Konqueror with Gad**. Other managers can send files through Gad's window or a custom command; their native Ctrl+V is not intercepted automatically.

Reading the screenshots

The 13 screenshots show real Gad widgets, sample files, and simulated transfer states. They use the light theme and the interface language of this edition. Personal files and the real desktop are never photographed. External Plasma notifications are not reproduced by these offscreen captures.

Gad provides French, US English, Spanish, Portuguese, German, and Japanese. Choose a language in **Settings → Options…**: it applies immediately without restarting Gad or interrupting transfers. Open dialogs and active notifications update while selection and entered values are preserved. **System** chooses an available variant of the desktop language, falling back to French or English. Uncataloged technical diagnostics and external-service messages may retain their original language.

Installation and startup

Install the Linux build dependencies described in the developer guide and testing guide. From the project directory:

```
python3 scripts/install.py
gad
```


The installer builds the release executable and installs the launcher, icons, and Dolphin actions in your account. It does not require administrator privileges. Close and reopen Dolphin after installation or changes to its actions.

You can start Gad from the application launcher or with `gad`. `gad --background` starts it in the system tray. A second launch contacts the existing instance instead of opening a separate queue.

If the tray is available, closing the main window hides it and leaves transfers running. To quit, use **Quit Gad** in the tray menu. Gad refuses to quit while transfers or preparation tasks are active; a pause alone does not finish them. Without a tray, the window performs the same check before exiting.


For an update, finish or cancel active work and quit Gad normally before reopening it. An already running executable continues to use its old code after a new binary is installed.

Understanding the window



The list shows files directly, with real folders forming the tree. Request colors keep separate submissions recognizable.

Area	Purpose
Source	Add files, add a folder, or paste into the selected destination.
Destination	Enter a local path or a supported remote URL, or browse for a folder.
Settings → Options...	Verification, exclusions, duplication, history, startup, languages, speed limits, and shortcuts.
Progress bar	Combined progress for the listed transfer work.
Filter and controls	Filter rows, pause the queue, cancel, undo, or clear finished history.
File list	Source, destination, state, progress, and detailed messages.
Below the list	Conflict decisions and per-request speed/remaining-time information.
Footer	**About**, **Error report...**, and the combined summary.




Options opens from the Settings block to the right of Destination.

The menu groups verification, hidden items, duplication, history, startup, interrupted transfers, exclusions, language, and the global speed limit. Changes apply immediately and checkboxes leave the menu open. **Limit request speed...** applies to selected rows and is disabled without a selection. The menu scrolls on smaller screens.

Shortcuts enables or disables Ctrl+V with Gad for Dolphin and Konqueror. Dolphin changes use Gad's reversible shortcut helper and require restarting Dolphin; a rejected change restores the checkbox and displays an error. Konqueror picks up changes on the next keypress in **Konqueror with Gad**. Its launch button is available when both the browser and launcher are installed. Text pastes stay native.

About displays the application name, acronym, slogan, icon, version, and build date. The software icon is the curly-haired document image used by the window, launcher, About dialog, and tray.



About identifies the build currently running.

Using Ctrl+V in Dolphin

The right-click **Paste with Gad** action works without replacing Dolphin's native paste shortcut. It receives the destination context you clicked.

To associate Ctrl+V with Gad in Dolphin:

```
gad-dolphin-paste --enable
```

Close and reopen Dolphin. Ctrl+V then targets the currently open Dolphin folder. The integration resolves that folder through Dolphin's session information; it does not require a full path in the window title. In a text field, Ctrl+V remains a text paste.

Shift+Insert remains the standard KDE/Dolphin KIO paste alternative. It is not a new Gad shortcut. To restore the previous Dolphin shortcut configuration:

```
gad-dolphin-paste --disable
```

The change applies to Dolphin, not to every application in Plasma. Existing shortcuts and actions are restored through the integration's saved configuration rather than by resetting unrelated user preferences.

Using Gad with other file managers

Gad can receive files from another manager, such as Nautilus, Nemo, or Thunar. Context-menu and shortcut integration depends on the manager: Gad does not automatically intercept its **Ctrl+V** or infer its active folder.

Copy or cut, then paste in Gad

1. Select files in your manager and use **Ctrl+C**, or **Ctrl+X** to request a move.
2. Open Gad and set the target folder in **Destination**.
3. Click **Paste here**, or press **Ctrl+V inside Gad**.
4. Check the destination and operation type shown in the list.

The manager must publish a file list in a clipboard format understood by Gad. Copying a path as plain text is insufficient. Moving requires a recognized cut marker; if it is unavailable, use the explicit `--move` command below.

Drag files into Gad

Set **Destination** first, then drag files or folders from your manager into Gad's list. **Drag-and-drop always creates a copy**, even if you previously cut those files. To move files, paste with a recognized cut marker or use `--move`.

Create a custom action or button

If your manager can launch a command, menu action, or toolbar button, use the commands below. Replace these example paths; the destination must be an existing folder.

To paste the clipboard into an explicit destination in the background:

```
gad --paste "/home/demo/Documents/Copies"
```

To copy sources without using the clipboard:

```
gad --copy "/home/demo/Images/photo.jpg" "/home/demo/Images/album" --to "/home/demo/Documents/Copies"
```


To explicitly move sources:

```
gad --move "/home/demo/Images/photo.jpg" --to "/home/demo/Documents/Copies"
```

A custom action must pass **the target folder** to `--paste`. For `--copy` and `--move`, pass **the selected source files** before `--to`, followed by the target folder. Substitution variables and quoting depend on the manager: do not assume that a selection argument identifies the open folder or reuse another manager's placeholders. If `gad` is not found, use the full path `~/.local/bin/gad` with your home directory expanded.

Other managers that support KIO service menus may also offer **Paste with Gad**. Its availability is not guaranteed in every manager. The Dolphin and Konqueror options under **Settings → Options…** control only those integrations; `--paste-current` does not discover other applications' active folders.

Starting a copy or move



Choose the destination **before** adding or pasting files. Adding files submits the request immediately; there is no separate Start confirmation.

From Dolphin

1. Use **Ctrl+C** to copy, or **Ctrl+X** to move.
2. Open or right-click the intended destination folder.
3. Choose **Paste with Gad**, or use Ctrl+V if its Gad integration is enabled.
4. Repeat to add more work to the same queue.

An external paste starts in the background and does not force the main window open. If it is hidden, Plasma displays the native progress view. A valid external paste can clear an existing global pause to start the transfer. A pause explicitly requested after submission takes precedence, including during background preparation. A completely duplicate paste does not clear a pause.

From Gad

Use **Add files…** (Add files), **Add folder…** (Add folder), or **Paste here** (Paste here). Ctrl+V inside Gad pastes into the displayed destination. Clipboard content marked as Cut produces a move; ordinary copied content produces a copy.

Dropping files onto Gad always creates a **copy**. A file list pasted while the Destination field has focus still enters the transfer queue. Ordinary text keeps the normal text-field paste behavior.

Duplicate requests

Gad ignores an operation already covered by an active request, including one in pause: the same source, destination, and operation type. The check covers repeated pastes, simultaneous additions, repeated selections, and files already included in another submitted folder.

New files are retained, together with any folders they need. A brief information message reports how many entries were not added. It does not offer an overwrite choice. The first request keeps its verification options.

A different destination or a copy-versus-move change remains a separate request. Different source files sharing a name still use conflict handling. You may intentionally copy a file again after the earlier request finishes.

Preparation

Gad validates all roots and scans the request before copying any of its files. Preparation can take time on a phone or network share. A failure is reported instead of silently starting only the portion that happened to scan successfully.

Special files and paths outside the supported UTF-8 contract are rejected. A source symbolic link is copied as a link, including a broken link; Gad does not traverse it as a source folder.

Excluding items from transfers

Use **Exclusions…** to enter one pattern per line, separately for folders and for files or symbolic links. **Include hidden items** is also available in **Settings → Options…**. It is checked by default, with no name exclusions initially configured.

Type	Example	Effect
Folders	`__*`	Skips folders whose names start with two underscores, including `__pycache__`.
Files	`*.tmp`	Skips files with this extension.
Files	`*.swp` or `*~`	Skips some editor temporary and backup files. Enter each pattern on its own line.

`*` matches zero or more characters and `?` matches one character. Matching is case-sensitive and applies to basenames at every depth, including explicitly selected items. Excluded folders are never traversed. Symbolic links use file patterns and are not followed. Unchecking the hidden-items option excludes names starting with a dot, for both files and folders.

Empty lines are ignored; spaces remain part of patterns. Full paths, regular expressions, and bracket character classes are not interpreted. Limits are 128 patterns per type and 256 UTF-8 bytes per pattern, without slashes or line breaks.

Settings are saved and captured for each new request before remote-access preparation. Existing batches, resumes, and retries keep their original rules. During moves, excluded items remain at the source, so source folders may remain. Whole-folder fast renames are disabled when filtering is active, but eligible individual files can still move quickly.

Fast local moves

For an eligible local move, Gad uses a rename instead of copying the contents and deleting the source. This preserves the file's inode and avoids transferring its data. It can run alongside a copy using the same disk if their paths are independent.

Different bind-mount paths can still refer to one underlying filesystem. For example:

```
/media/library/Music  → /home/you/Music
/media/library/Other  → /home/you/Other
```

Gad can rename between those views when it proves a safe common path and matching identities. The same physical disk alone is insufficient: different partitions, subvolumes, read-only mappings, or kernel rename restrictions can require copy-and-delete instead. A rejected rename is rescheduled with ordinary copy reservations.

For a complete, unchanged folder tree without conflicts or paused/excluded entries, Gad may rename the whole tree at once. The detail reports **dossier renommé en bloc**. Otherwise it processes entries individually. Outside files added to a moved tree are protected during undo rather than silently moved or deleted.

Enabling MD5 uses the ordinary copy path rather than the fast rename shortcut. The concurrency limit remains two operations.

Reading states and progress

Long explanatory tooltips use a line break between sentences. Filenames and paths retain their original punctuation and spacing.

Source rows use Copy icons for copies and Cut icons for moves, including folders and requests being prepared. Folders remain bold and keep their descendants.

The **Order** column is displayed first and automatically fits the minimum width needed by its title, sort arrow, and numbers. It follows the engine queue, including folders, scanning requests, and retained history. Display sorting and filtering never renumber remaining rows, so gaps in a filtered view are normal. Queue priority changes update positions. Hover a number for **Batch #...**. Parallel transfers may finish in a different order.


Column	Meaning
Order	Engine queue position, independent of display sorting; hover for the batch number.
Source	File or folder name; the Copy/Cut icon indicates the operation, and the tooltip provides the full path and optional MD5/rate settings; batch numbers remain in Order tooltips.
Destination	Target path, or the original remote URL reconstructed for display.
Status	Current state, including pause, conflicts, checks, and device waiting.
Progress	Copied bytes and file size, or the MD5/recovery-check progress.
Details	Errors, MD5 results, fast-move information, and verification warnings.

State	Meaning
Scanning...	Validating roots and scanning the request.
Queued	Waiting for its turn, resources, or a resume action.
Running	Transferring data or processing the entry.
Paused	A global, request, or entry pause applies.

State	Meaning
Waiting for device	A known mount is unavailable; partial data is retained.
Checking resume data…	Checking the source and saved partial prefix before writing again.
Verifying MD5…	Independently rereading source and temporary destination.
Decision required	A file conflict needs your decision.
OK	Finished; displayed in green.
Error	A step failed; read the detail or open the error report.
Skipped	Skipped; the source remains.
Canceled	Canceled without automatically undoing completed results.
Restoring…	Undo is running.
Restored	The selected effects were undone.
Restoration incomplete	Undo could not finish safely.

A folder becomes OK only after its relevant children finish. It collapses on that transition. Reopening it manually keeps it open through later progress updates. Selection, hover, and tooltips are preserved while counters change.

Filters



Filtering changes visibility, not transfer behavior.

Filters are available by right-clicking column headers. The former global filter combo above the table has been removed. Ancestor folders remain visible when needed to show a matching child. Selecting a filter opens relevant branches; ordinary progress updates do not reopen branches you collapsed.

Sorting and filtering from headers

Click a column title to toggle ascending and descending display order. **Ctrl+click** adds a column to the existing sort; repeating Ctrl+click reverses that column's direction without changing its priority. Headers show priorities as **(1)**, **(2)**, and so on, with the usual sort arrow on the right of each sorted column. A click without Ctrl restores single-column sorting. Names use natural sorting (`file2` before `file10`). Progress sorts by numeric percentage, independently of file size and displayed units. Sorting is among siblings: folders retain their descendants.

Right-click a header to open its menu. It provides ascending/descending sorting, **Transfer queue order**, and a case-insensitive **Contains…** filter for that column. Source searches also include full paths. Status adds an exact-state selector; Progress adds minimum and maximum percentages. **Remove this column from sorting** removes one sort key while keeping the others. Clear actions remove one column filter or all header filters.

Column filters combine with each other. Matching children retain visible ancestor folders; active filters remain available in column menus. Global counters continue to cover all transfers. Locating a file from a conflict or error report clears filters that could hide it.

Sorting changes only the display, never execution priority. Restore **Transfer queue order** before dragging rows to reorder work. Display settings survive progress updates and language changes.

Counters and estimates

The combined summary counts transfer work. A rename advances logical bytes without representing copied disk traffic. A fully written file can still be undergoing MD5 verification. Hidden/removed rows are excluded from the visible summary. Directories do not contribute file-content bytes.

Below the list, each active request has its own source name, speed, and estimated time remaining. Measurements use the last five seconds of activity. A short warm-up displays **calcul du débit…** until enough time has elapsed.

Copying and MD5 rereads have separate measurements. If MD5 speed is still unknown, the estimate explicitly covers only the copy and says **MD5 à estimer**. When both measurements are available, the estimate includes the remaining copy work and verification reads. It is approximate and does not predict queue waiting time.

A pause suspends estimates; a conflict displays **Decision required**. Individually paused files make the request's total remaining time unknown even while other files advance. Renames do not show artificial disk-copy speeds, and a recognized resumed prefix does not create a speed spike. Without progress, the old speed falls to zero and the estimate becomes unavailable.

Organizing the queue


Drag one or more **waiting** rows before or after another row. The insertion marker shows the intended position; hovering near the edge scrolls the list. Top-level file roots may be interleaved across requests.

A folder moves with its branch. Files within a folder reorder among siblings; they keep their actual parent and destination. Move the parent folder to reposition the whole branch. Dragging never changes the destination.

The context menu provides **Process next** (Process next) and **Reorder queue** (Move in queue). Ctrl and Shift support multiple selection. **Select entire request** selects the other roots belonging to the same submission.

Priorities are saved. Processing next does not interrupt the current file or remove a pause. Disk compatibility and undo dependencies still apply. Unsafe interleaving of requests that replace the same outputs is refused with a reason. A partly published request can therefore keep dependent work waiting during a pause.

Pausing and resuming



Unfinished rows show their pause; completed results remain OK.

Pause all pauses the queue and changes to **Resume queue** (Resume queue). Completed files keep their status. The context menu can pause or resume selected requests or entries. Pausing one request lets other admissible requests advance.

A pause takes effect at a checkpoint rather than forcibly interrupting an active system call. A selected resume removes the global pause so the selection can proceed; pauses belonging to other requests remain in force.

Cancellation is available during a pause. An explicitly requested undo can also run while ordinary copying is globally paused. The pause control in Plasma and the tray menu stays synchronized with the main window.

Limiting bandwidth


Global speed limit in **Settings → Options…** limits the **sum** of simultaneous copy traffic. The interface uses **MiB/s**, equivalent to **MiB/s**: 1 MiB = 1,048,576 bytes. This is not megabits per second. Zero, displayed as **Unlimited**, removes the limit. The setting is remembered and can be changed during transfers.

Right-click a row and choose **Limit request speed…** in the context menu or **Settings → Options…** to limit its entire request. Selecting rows from several requests applies the chosen limit to each of them. Their global budget remains shared. Zero removes only the selected requests' individual limits. Tooltips show an individual limit when one is set.

Both constraints apply: a request limited to 10 MiB/s remains capped at 10 even if the global limit is 50. Two requests without individual limits can use at most 50 MiB/s combined. Equal sharing is not guaranteed.

The cap applies to copied bytes, including mounted remote endpoints. OS and network buffering can produce short variations. MD5 rereads, property checks, and undo are outside this cap. Fast renames remain immediate. Pause and cancellation stay available at low rates.

Resolving conflicts



The source and existing destination are shown side by side beneath the file list.


A conflict panel shows the filename, selectable path, size, and modification time for both sides.

Button	Result
Keep existing file	Keep the existing destination and skip this source. A move does not delete a skipped source.
Keep both	Keep the existing file and choose an available copy name for the new result.
Replace existing file	Replace it, retaining the old destination privately for undo.

The checkbox applies the decision to later conflicts **in that request**. It resets when you change the displayed conflict. With several conflicts, use the selector to choose which one to inspect. A new conflict does not silently switch the item you are deciding about.

Show file in list locates the blocked row, including when a filter hid it. A file occupying a required folder path, or an unsafe symbolic link in that path, can produce an error instead of an automatic folder replacement.

Canceling or undoing transfers



Global actions remain available without a selection.

Stop without undo

Cancel all (Cancel all) stops active and queued work, including outstanding preparation. It leaves completed transfers in place. **Cancel selected operations** limits that stop to the selection. Folder selections include descendants.

Undo completed effects

Cancel all and restore cancels work and undoes recoverable history, newest execution first. **Cancel, delete, and move back** applies undo to the selected entries or branches.

Original operation	Undo behavior
Copy to a new file	Remove the copy created by Gad.
Replace an existing file	Remove the new result and restore the saved destination.
Move	Return the file to its source and remove its destination result.
Create a folder	Remove it only when that can be done without losing other files.

Undo waits for active transfer reservations to be released. Returning a move across filesystems can require copying the contents back. An undo transaction already in progress must finish its safe restoration steps.


Gad checks identities, metadata, and recorded content before altering results. A recreated source, modified destination, missing backup, or absent volume can cause a refusal or an incomplete undo. The detail explains what was retained. A completed copy is not an independent backup, and clearing history removes its undo capability.

Delete and Backspace

Selected row	Delete	Backspace
Finished	Remove the row/history reference; keep the resulting file.	Undo that file or branch when its journal permits it.
Active	Request cancellation.	Request cancellation.
Pending	Remove it from the queue.	Remove it from the queue.

A folder selection extends to its contents. Selecting individual files does not automatically undo their neighbors. Keep history you may need before clearing it.

Using the context menu



Actions adapt to the selection and its current states.


Action	Purpose
Open containing folder	Open a file's parent folder, or open the selected folder itself.
Open file	Open one file with its desktop-associated application.
Select entire request	Select the other entries from the same submission.
Traiter ensuite / Déplacer dans la file	Prioritize waiting entries or branches.
Cancel and keep completed files	Stop selected work and retain completed outputs.
Cancel and restore	Undo the selection when its journal permits it.

Action	Purpose
Limit request speed…	Apply a bandwidth limit to the owning requests.
Mettre en pause / Reprendre	Pause or resume selected work.
Retry failed files only	Retry eligible failures without recopying OK files.
Resume interrupted batches	Validate and resume recoverable work after an interruption.
Reactivate canceled rows	Prepare canceled entries for a new attempt after controlled cleanup.
Remove from list / stop	Apply Delete semantics.

Opening an OK row targets the destination. For pending, active, skipped, canceled, or undone rows, it targets the source. The current state is checked when the action runs. Duplicate folders in a multiple selection open only once. Launching is limited to a single file, not a whole request or a folder.

Reactivation waits for the request to stop and preserves completed neighbors. If the source type changed, add it as a new request rather than reusing the old row.

Error reporting and targeted retries



All six buttons have icons: retry displayed errors, retry the selection, locate, export, refresh, and close.

Open **Error report...** beside About. It groups retained failures by request, operation, source, destination, state, and message. A folder that merely reflects a child's error does not add a duplicate record; a folder's own failure is still shown.

Search filters by request, path, or error message. Selecting a row shows the full detail below it: progress, partial-file location, recoverable bytes, and available MD5 or property information. **Show in list** locates the entry in the main window. **Refresh** refreshes the snapshot explicitly; the report does not continually reshuffle while you inspect it.


Retry failed files only retries eligible errors currently displayed. **Retry selection** targets only selected rows. In this report, selecting a directory error does not silently include filtered-out children. The main list's folder context action retains its normal descendant-selection behavior.

The request must be stopped. Gad validates any partial or published effects, restores only recognized remnants, and queues the failed elements again. The failed file is recopied from the beginning after that cleanup. OK files are not recopied; canceled, skipped, or removed entries are not reactivated. Other entries that were merely waiting in a stopped request remain paused if they were outside the retry. The global pause is respected.

A preparation failure with no listed files can be retried through full root validation and a new scan. If retry preparation fails, repair the cause and refresh the report to try again. A separate incomplete undo remains an undo/recovery task. A modified published result is retained and can make a retry fail safely.

Export… (Export…) is disabled when the loaded report is empty. Filtering all rows out does not disable export because it still covers the complete snapshot. It writes the entire loaded report, including rows hidden by its search filter, as **UTF-8 text** or **JSON**. Text is intended for reading and sharing; JSON retains stable request/file references and diagnostic metadata. Exporting performs no transfer. Errors deliberately removed from history are not reintroduced.

Checking file contents with MD5




Enable **Verify files using MD5** for new submissions. Each regular file is copied and synchronized, then its source and temporary destination are reread and compared. Gad publishes the same verified temporary file under its final name only after successful checks.

The row displays **Verifying MD5…** during rereading and may later show **MD5 OK** and the digest. For an N-byte file, verification adds two N-byte reads. Directories and symbolic links are not checked as file contents.

Read failures, cancellation during verification, source changes, or a digest mismatch prevent publication and preserve the source and any prior destination. A move deletes its source only after successful publication and the required checks. The setting is remembered for future requests; existing requests keep their captured choice.

MD5 verifies consistency of this transfer path. It is not a cryptographic guarantee against deliberately constructed collisions.

Checking file properties



Verify properties compares exposed owner, group, permission bits, POSIX ACLs, and extended attributes. It distinguishes known differences from unavailable checks. Attribute values are not included in saved reports; the report lists differences and unavailable checks. Modification dates are outside this comparison.

Ordinary copies preserve basic permissions and modification time where supported; they do not gain backup-grade owner, ACL, or xattr preservation simply because this box is enabled.

For a copy, a property mismatch can leave the successfully copied result with a warning. For a copy-and-delete move, a failed check before publication preserves the original and prior destination; a failed post-publication check keeps the original and a journal for the created result. A fast rename has already moved the object, so a later warning does not claim the source still exists.

The option is remembered and captured per new request. Reports are available in the detail and folder warning summaries. Remote services can expose only part of these properties.

Checking available space


Check available space estimates the remaining storage required by analyzed requests, including queued and paused copies sharing a volume. Separate volumes are calculated independently.

Old destinations and undo backups already occupy space and are not treated as free capacity during replacement. Recognized allocated resume temporaries are not counted twice. Block allocation rounding is considered. A proven fast rename does not require a second full copy of the data.

Known insufficient space prevents that request from starting. **If capacity cannot be estimated, Gad warns and continues** instead of blocking indefinitely. The warning can remain visible after success. This is an estimate, not a disk-space reservation: another program can consume space afterward, and later additions must be considered separately.

The option is remembered for new requests; existing ones retain their captured choice.

Waiting for a device to reconnect



If a known disk or mount disappears during a transfer, Gad displays **Waiting for device**, retains its partial file, and releases the worker so independent requests can proceed. Plasma also describes the wait.

Reconnect and mount the device **at the same location**. Gad checks the expected mount, source identity/version, and saved prefix before continuing from the last valid durable point. Bytes beyond that point may be recopied. An empty folder left at the mount point, or another volume mounted there, is not sufficient proof. A filesystem UUID can recognize the same volume after Linux assigns a different device number.

Global and targeted pauses remain in force; reconnecting does not override them. A canceled request does not restart. A replaced source, destination, or partial file can make recovery fail rather than overwrite unrelated data. An interrupted publication requires recovery rather than an automatic second copy.

For KDE Connect, FTP, SFTP, and SMB, Gad retries KIO resolution in the background without opening its window or adding another batch. KDE still handles authentication. The mounted path and identities must remain recognizable. If KIO Fuse restarts with a different path, Gad reports it and retains the original journal; restore the original mount or inspect and resubmit the interrupted files.

For KIO Fuse destinations without durable partial recovery, Gad can restart **only the current file from the beginning**, after validating its source and removing its recognized unpublished temporary file. Completed neighbors stay intact. Local reconnect checkpoints are created during the session even if automatic crash recovery is unchecked; that preference still governs restart after a crash.

Detection occurs at transfer checkpoints and connection errors. A system call blocked in the kernel or remote service can delay detection. A deleted file on an otherwise available volume, insufficient space, or permission denial remains an ordinary error.

Resuming after a crash

Resume after interruption is enabled by default for new requests. Compatible local destinations use a durable checkpoint every 64 MiB or after two seconds of progress. After an abrupt stop, Gad can check the source, destination, and partial contents, then resume in the same temporary file.

Completed files stay completed. Global and entry pauses are retained. An explicitly canceled request never resumes automatically. If the global preference is disabled at restart, eligible interrupted requests wait for **Resume interrupted batches** in the context menu. That action concerns the owning request, even if you select one file.

The saved source version and temporary ownership are checked before truncation or writing. Gad compares both prefixes and the recorded digest, then discards only bytes beyond the confirmed point. A changed source or partial file causes a refusal. The row shows **Checking resume data…** and then the resumed byte count. Final MD5 verification still runs if enabled.

This recovery is not available for every intermediate state: ambiguous publication, rename, or undo stages require journal-based recovery. Durable crash recovery is disabled for KIO Fuse destinations. Journals and backups retained for recovery are not removed by uninstalling Gad.

History and cleanup


Keep history retains requests, verification results, and undo information between normal sessions. Without it, current-session records remain visible, but normal shutdown releases their history and backups. Recovery information required after an interruption can remain available even when ordinary history retention is off.

Clear completed operations removes finished history and saved replaced destinations. It does **not** remove the successful final copies, but it removes their undo capability. Undo relies on the original volumes and retained information; it is not an independent backup.

The journal normally resides at `$XDG_DATA_HOME/gad/state.json`, defaulting to `~/.local/share/gad/state.json`. Replaced files are retained in private `.gad-undo-*` directories on their destination volume. These use disk space until the associated recovery history is cleared.

Do not manually delete those private directories while you still need undo. An invalid journal or unrecognized result is retained with an error rather than optimistically discarded.

System tray and session startup



Click the icon to hide a visible window or restore a hidden/minimized one. Its badge counts unfinished requests, including analysis and waiting work. Above 99, it displays `99+`; the tooltip keeps the exact count.

The badge is green during activity, orange for pause or device waiting without an active transfer, and red when a conflict requires a decision. The tooltip summarizes running, waiting, and scanning work. The tray menu provides show, pause/resume, and quit actions.

When the window is hidden or minimized, one combined Plasma job view displays requests, files, bytes, progress, pause, and speed. **Show Gad** opens the main window. Every transfer notification keeps the **Show Gad** link, including completion, cancellation, and error messages. New requests join the same view; there is no second ordinary notification for the same transfer. The native Details area includes speed. Exact external rendering depends on the installed Plasma version and theme.

Enable **Launch at startup** to start Gad in the tray when the desktop session begins. This is per-user autostart, not a system service. Turning it off removes Gad's own startup entry.

Phones, FTP, SFTP, and SMB

Local paths and already mounted folders are supported directly. Raw remote addresses use KIO Fuse on both source and destination sides.

Service	Example
KDE Connect	`kdeconnect://device-id/android/DCIM/Camera/photo.jpg`
FTP	`ftp://files.example/folder/file.txt`
SFTP	`sftp://user@files.example/folder/file.txt`
SMB	`smb://server/share/folder/file.txt`

KDE owns authentication and session handling. Gad does not provide a separate FTP/SSH/SMB password manager. Unsupported schemes, malformed URLs, and ambiguous query/fragment components are rejected.

Both sides are resolved before the request enters the copy engine. Following submissions keep their order. A connection error does not silently submit only part of the source group. The original address is used for display; the mounted path is an implementation detail used for file access and desktop opening.

Permissions, ownership, dates, and server operations vary by service. KIO Fuse destinations use service-defined metadata where chmod/utime are unavailable. Pause remains available, but durable mid-file crash recovery is disabled for these destinations. Undo requires the expected mounted paths and identities; changed mappings are not silently adopted.

Keyboard reference

Key	Gad behavior
Ctrl+C / Ctrl+X in the file manager	Mark files for copying or moving.
Ctrl+V in Gad	Paste into the displayed destination.
Ctrl+V in Dolphin with integration enabled	Submit a background paste to the active folder.
Ctrl / Shift + selection	Select several rows.
Delete	Remove finished rows, stop active entries, or remove pending ones.
Backspace	Undo completed results; otherwise stop/remove the selection.
Shift+Insert in Dolphin	The standard native KIO paste alternative.

These keys do not imply that Gad replaces paste throughout KDE.

Troubleshooting

Symptom	What to check
Clipboard files appear in the clipboard manager but Gad cannot read them	On Wayland, check `wl-paste` availability; ensure the clipboard contains a file list rather than only path text.
A move becomes a copy	Check whether MD5 is enabled, the endpoints really share a supported local filesystem, and the kernel allows a safe rename.
Another request waits despite two workers	Check shared disks, unknown disk topology, conflicts, pauses, and dependencies on partially published results.
A repeated paste adds nothing	An active request may already cover the same source/destination/type; read the brief duplicate message.
Free space cannot be measured	Gad warns and continues; verify capacity through the underlying service if needed.
A device wait does not end	Restore the same mount/path and inspect identity or KIO mapping warnings. A changed file is not automatically accepted.
Retry is unavailable	Wait for the request to stop, select an actual failure, or use the dedicated recovery action for an incomplete undo.
Ctrl+V uses an old destination method	Update the installed integration, close and reopen Dolphin, and restart an idle Gad instance.
Undo is refused	Read the detail for changed files, missing backups, recreated sources, or absent volumes. Keep retained data until resolved.
Tray icon/window behavior differs	Check tray availability and the version of the already running Gad process.

For diagnostics, record the About version, copy versus move, full error text, and whether endpoints are local, mounted, or remote. The error-report export is useful for sharing that information; review personal paths before sharing it.

Limits and good practices

Gad manages transfers and journal-based undo; it does not provide a backup system's complete ownership, ACL, xattr, hard-link, or sparse-file guarantees. Ordinary copies do not preserve hard-link relationships or sparse allocation. A proven rename retains the existing object instead.

MD5 adds independent content checks but is not protection against deliberately constructed collisions. A group of file copies is not an atomic transaction. Concurrent modifications by other programs and filesystem synchronization behavior still matter.

Keep enough space for temporary copies and retained replaced files. Finish recovery before deleting journals or private backups. Test an unfamiliar remote service with noncritical sample data first.

For implementation details and protocol behavior, see the developer guide. For reproducible validation, see Testing Gad.

Adding a language

Languages are discovered at startup from valid `gad_<locale>.qm` catalogs, such as `gad_de_DE.qm`. Qt provides each language's native display name. US English remains available as the source language. Exact locales take priority, followed by an available variant of the same language, then French or English.

To add a language without rebuilding, put its `.qm` in `~/.local/share/gad/translations/` and its `<locale>.png` flag next to it, for example `de_DE.png`, then restart Gad. This directory follows `$XDG_DATA_HOME` when set. Flags may also be in a `flags/` subdirectory or in `~/.local/share/gad/flags/`. Missing flags use a generic icon. Invalid catalogs are ignored. User catalogs override system and embedded catalogs.

For distribution with Gad, place the `.qm` in `translations/` and its PNG in `assets/flags/`. `scripts/resources.py` generates the Qt manifest for Cargo, Qt tests, and documentation captures. No C++ list or source-manifest edit is needed. A compiled `.qm` alone is sufficient; when a `.ts` is supplied, `python3 scripts/translations.py` automatically discovers, validates, and compiles it.

Duplicating in the original folder

Enable **Allow duplication in the same folder**, then copy and paste into the item's containing folder. `photo.jpg` becomes `photo_copied1.jpg`; a `Documents` folder becomes `Documents_copied1`. Gad chooses the first available number, accounting for pending duplications. Symbolic links are copied without following their targets.

This option is disabled by default, saved, and captured for new requests. Moves onto themselves and copies of folders into their own descendants remain rejected. Exclusions still apply. Undo removes the created copy and preserves the original.

Using Gad with Konqueror

Paste with Gad is a KIO service menu shared with Dolphin. Restart Konqueror after installing Gad to load the menu. Copy and cut operations use the same transfer engine and queue.

For **Ctrl+V**, launch **Konqueror with Gad** from the application menu or run `gad-konqueror`. This launcher loads a plugin only in Konqueror. File pastes go to Gad using the active view's folder; pasting text into the address bar and input fields stays native. **Shift+Insert** keeps the usual KIO paste. Supported remote destinations remain available.

The plugin also exposes the active folder to **Paste into the open folder with Gad**, without relying on window titles or stale selections. The standard Konqueror launcher is preserved. Ctrl+V integration is validated with Konqueror 26.08 (Qt 6). If Konqueror is installed after Gad, rerun `python3 scripts/install.py` to build its plugin.

Documentation from About

About links to the **Quick Start**, **User Guide**, and **Developer Guide**, with HTML and PDF access. Links follow the selected Gad language, including when it changes while the dialog is open. Documents are installed locally and remain available without the project folder. If an edition is missing, Gad offers the available English edition; missing documents do not create broken links.