

Models for *Axiomatic Type Theory*

Daniël Otten and Matteo Spadetto

Contents

We explain and motivate Axiomatic Type Theory (ATT).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- comprehension categories: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- path categories (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions only up to isomorphism.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- comprehension categories: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- path categories (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions only up to isomorphism.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- comprehension categories: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- path categories (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions only up to isomorphism.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- **comprehension categories**: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- **path categories** (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions only up to isomorphism.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- **comprehension categories**: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- **path categories** (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions only up to isomorphism.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- **comprehension categories**: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- **path categories** (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions **only up to isomorphism**.
Luckily, we can turn comprehension categories into actual models.

Contents

We explain and motivate Axiomatic Type Theory (**ATT**).
(type theory without reductions)

We compare two semantics for a minimal version of ATT:

- **comprehension categories**: more traditional and well-studied; closely follow the syntax and intricacies of type theory.
- **path categories** (Van den Berg, Moerdijk 2017): more concise; take inspiration from homotopy theory.

However, both specify substitutions **only up to isomorphism**.
Luckily, we can turn comprehension categories into actual **models**.

Our Contributions

Path categories are equivalent to certain comprehension categories.
This allows us to turn path categories into actual models as well.

We introduce a more fine-grained notion: display path categories,
and show a similar equivalence.

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Our Contributions

Path categories are **equivalent** to certain comprehension categories.

This allows us to turn path categories into actual models as well.

We introduce a more fine-grained notion: display path categories, and show a similar equivalence.

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Our Contributions

Path categories are **equivalent** to certain comprehension categories.
 This allows us to turn path categories into actual **models** as well.

We introduce a more fine-grained notion: display path categories,
 and show a similar equivalence.

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 \begin{array}{c} U \uparrow \\ \vdash \\ \downarrow C \end{array} & & \begin{array}{c} F \uparrow \\ \vdash \\ \downarrow U \end{array} \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Our Contributions

Path categories are **equivalent** to certain comprehension categories.
This allows us to turn path categories into actual **models** as well.

We introduce a more fine-grained notion: **display path categories**,
and show a similar equivalence.

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 \begin{array}{c} U \uparrow \\ \vdash \\ \downarrow C \end{array} & & \begin{array}{c} F \uparrow \\ \vdash \\ \downarrow U \end{array} \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Our Contributions

Path categories are **equivalent** to certain comprehension categories.
 This allows us to turn path categories into actual **models** as well.

We introduce a more fine-grained notion: **display path categories**,
 and show a similar equivalence.

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)	type	proofs	undecidable.

Definitional eq is a fragment of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)	type	proofs	undecidable.

Definitional eq is a fragment of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)		judgement	reductions	decidable,
propositional ($=$)		type	proofs	undecidable.

Definitional eq is a fragment of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement reductions	decidable,
propositional ($=$)		type proofs undecidable.

Definitional eq is a fragment of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)		type	proofs

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement reductions	decidable,
propositional ($=$)		type proofs

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)	type	proofs	undecidable.

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement type	reductions	decidable,
propositional ($=$)		proofs	undecidable.

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)	type	proofs	undecidable.

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement reductions	decidable,
propositional ($=$)		type proofs undecidable.

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Equality

Intensional Type Theory (ITT) has two notions of equality:

definitional (\equiv)	judgement	reductions	decidable,
propositional ($=$)	type	proofs	undecidable.

Definitional eq is a **fragment** of propositional eq.

Other fragments:

- larger \rightsquigarrow work in the system,
- smaller \rightsquigarrow find models.

Two extremes:

- Extensional Type Theory (ETT): everything is definitional,
- Axiomatic Type Theory (ATT): nothing is definitional.

Other Fragments

Larger:

- If we define

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

then we can prove

But these proven eq are not definitional.

Agda allows you to make them definitional.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are not definitional.

Agda allows you to make them definitional.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are not definitional.

Agda allows you to make them definitional.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are **not definitional**.

Agda allows you to make them definitional.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are **not definitional**.

Agda allows you to make them **definitional**.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are **not definitional**.

Agda allows you to make them **definitional**.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are **not definitional**.

Agda allows you to make them **definitional**.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Other Fragments

Larger:

- If we define

then we can prove

$$\begin{aligned}0 + n &\equiv n, \\ (S\ m) + n &\equiv S\ (m + n), \\ m + 0 &= m, \\ m + (S\ n) &= S\ (m + n).\end{aligned}$$

But these proven eq are **not definitional**.

Agda allows you to make them **definitional**.

Smaller:

- Cubical Type Theory: only propositional β -rule for $=$ -types.
- Coinductive Types: only propositional β -rule as otherwise definitional eq becomes undecidable.

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? Yes, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? **Yes**, namely:

- binder extensionality (bindext),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? **Yes**, namely:

- binder extensionality (**bindext**),
- uniqueness of identity proofs (uip).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? **Yes**, namely:

- binder extensionality (**bindext**),
- uniqueness of identity proofs (**uip**).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Complexity and Conservativity

The complexity of type checking:

- ETT: undecidable,
- ITT: nonelementary,
- ATT: quadratic.

Does ETT prove more than ATT? **Yes**, namely:

- binder extensionality (**bindext**),
- uniqueness of identity proofs (**uip**).

However, these are the only additional things we can prove.

(Winterhalter 2019)

Minimal ATT

Lets start by considering the normal rules for $=$ -types:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (=F),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (=I),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{\bar{C}, d, p} : C} (=E),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{\bar{C}, d, \text{refl}_x} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Lets start by considering the normal rules for **=-types**:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (=F),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (=I),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{\bar{C}, d, p} : C} (=E),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{\bar{C}, d, \text{refl}_x} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Lets start by considering the normal rules for $=$ -types:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (=F),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (=I),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{\bar{C}, d, p} : C} (=E),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{\bar{C}, d, \text{refl}_x} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Lets start by considering the normal rules for $=$ -types:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (=F),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (=I),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{\bar{C}, d, p} : C} (=E),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{\bar{C}, d, \text{refl}_x} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Lets start by considering the normal rules for **=-types**:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (= \mathcal{F}),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (= \mathcal{I}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{C,d,p}^{\overline{}} : C} (= \mathcal{E}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{C,d,\text{refl}_x}^{\overline{}} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Lets start by considering the normal rules for $=$ -types:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (= \mathcal{F}),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (= \mathcal{I}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x' \vdash \text{ind}_{C,d,p}^{\overline{}} : C} (= \mathcal{E}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x' \vdash C \text{ type} \\ \Gamma, x : A \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A \vdash \text{ind}_{C,d,\text{refl}_x}^{\overline{}} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

Without Π -types, we have to **strengthen** the rules:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (= \mathcal{F}),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (= \mathcal{I}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x', \Delta \vdash C \text{ type} \\ \Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x', \Delta \vdash \text{ind}_{\overline{C}, d, p} : C} (= \mathcal{E}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x', \Delta \vdash C \text{ type} \\ \Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash \text{ind}_{\overline{C}, d, \text{refl}_x} \equiv_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{red}}).$$

Minimal ATT

In ATT, we change the reduction to an **axiom**:

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x, x' : A \vdash x =_A x' \text{ type}} (= \mathcal{F}),$$

$$\frac{\Gamma \vdash A \text{ type}}{\Gamma, x : A \vdash \text{refl}_x : x =_A x} (= \mathcal{I}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x', \Delta \vdash C \text{ type} \\ \Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x, x' : A, p : x =_A x', \Delta \vdash \text{ind}_{\overline{C}, d, p} : C} (= \mathcal{E}),$$

$$\frac{\begin{array}{l} \Gamma, x, x' : A, p : x =_A x', \Delta \vdash C \text{ type} \\ \Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash d : C[x/x', \text{refl}_x/p] \end{array}}{\Gamma, x : A, \Delta[x/x', \text{refl}_x/p] \vdash \beta_{\overline{C}, d, x} : \text{ind}_{\overline{C}, d, \text{refl}_x} =_{C[x/x', \text{refl}_x/p]} d} (= \beta_{\text{ax}}).$$

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an equivalence.

Models

How do we model this minimal ATT?

Two options:

- Follow the syntax and rules. (comprehension category)
 - We require: $=_A$, refl_A , $\text{ind}_{\overline{C},c,p}$, and $\beta_{\overline{C},c,x}$.
- Use intuition from homotopy theory. (path category)
 - We require: $=_A$, refl_A , and that refl_A is an **equivalence**.

Comprehension Categories

In a comprehension category we have:

- a category of contexts with terminal object ϵ ,
- a category of types,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (display map)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (substitution)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- =-types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an =-type.

Comprehension Categories

In a **comprehension category** we have:

- a category of contexts with terminal object ϵ ,
- a category of types,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (display map)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (substitution)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of types,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (display map)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (substitution)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (display map)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (substitution)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (substitution)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The terms of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The **terms** of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The **terms** of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The **terms** of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- $=$ -types: for A a type $=_A$ and terms $\text{refl}_A, \text{ind}_{A,C,d}^=, \beta_{A,C,d}^=$,
- weak stability: for σ we have that $=_A[\sigma]$ is also an $=$ -type.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The **terms** of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- **=-types**: for A a type $=_A$ and terms refl_A , $\text{ind}_{A,C,d}^\perp$, $\beta_{A,C,d}^\perp$,
- **weak stability**: for σ we have that $=_A[\sigma]$ is also an **=-type**.

Comprehension Categories

In a **comprehension category** we have:

- a category of **contexts** with terminal object ϵ ,
- a category of **types**,
- for every type A a context map $p_A : \Gamma.A \rightarrow \Gamma$. (**display map**)
- for every type A in context Γ and context map $\sigma : \Delta \rightarrow \Gamma$,
a type $A[\sigma]$ in context Δ . (**substitution**)
- satisfying some universal properties.

The **terms** of A are the maps $a : \Gamma \rightarrow \Gamma.A$ such that $p_A \circ a = \text{id}_\Gamma$.

Each type former gives additional requirements. For equality:

- **=-types**: for A a type $=_A$ and terms refl_A , $\text{ind}_{A,C,d}^\equiv$, $\beta_{A,C,d}^\equiv$,
- **weak stability**: for σ we have that $=_A[\sigma]$ is also an **=-type**.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned} A[\text{id}_\Gamma] &= A, \\ A[\tau \circ \sigma] &= A[\sigma][\tau]. \end{aligned}$$

And strongly stable:

$$\begin{aligned} \varepsilon_A[\sigma] &= \varepsilon_{A[\sigma]}, \\ \text{refl}_A[\sigma] &= \text{refl}_{A[\sigma]}, \\ \text{ind}_{\overline{A}, C, d}[\sigma] &= \text{ind}_{\overline{A[\sigma]}, C[\sigma], d[\sigma]}, \\ \beta_{\overline{A}, C, d}[\sigma] &= \beta_{\overline{A[\sigma]}, C[\sigma], d[\sigma]}. \end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned} A[\text{id}_\Gamma] &= A, \\ A[\tau \circ \sigma] &= A[\sigma][\tau]. \end{aligned}$$

And strongly stable:

$$\begin{aligned} \text{id}_A[\sigma] &= \text{id}_{A[\sigma]}, \\ \text{refl}_A[\sigma] &= \text{refl}_{A[\sigma]}, \\ \text{ind}_{A,C,d}^\sigma[\sigma] &= \text{ind}_{A[\sigma],C[\sigma],d[\sigma]}^\sigma, \\ \beta_{A,C,d}^\sigma[\sigma] &= \beta_{A[\sigma],C[\sigma],d[\sigma]}^\sigma. \end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned} A[\text{id}_\Gamma] &= A, \\ A[\tau \circ \sigma] &= A[\sigma][\tau]. \end{aligned}$$

And strongly stable:

$$\begin{aligned} \text{=}_A[\sigma] &= \text{=}_{A[\sigma]}, \\ \text{refl}_A[\sigma] &= \text{refl}_{A[\sigma]}, \\ \text{ind}_{\bar{A}, C, d}[\sigma] &= \text{ind}_{\bar{A}[\sigma], C[\sigma], d[\sigma]}, \\ \beta_{\bar{A}, C, d}[\sigma] &= \beta_{\bar{A}[\sigma], C[\sigma], d[\sigma]}. \end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned} A[\text{id}_\Gamma] &= A, \\ A[\tau \circ \sigma] &= A[\sigma][\tau]. \end{aligned}$$

And strongly stable:

$$\begin{aligned} \text{=}_A[\sigma] &= \text{=}_{A[\sigma]}, \\ \text{refl}_A[\sigma] &= \text{refl}_{A[\sigma]}, \\ \text{ind}_{\overline{A}, C, d}[\sigma] &= \text{ind}_{\overline{A}[\sigma], C[\sigma], d[\sigma]}, \\ \beta_{\overline{A}, C, d}[\sigma] &= \beta_{\overline{A}[\sigma], C[\sigma], d[\sigma]}. \end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned}
A[\mathrm{id}_\Gamma] &= A, \\
A[\tau \circ \sigma] &= A[\sigma][\tau].
\end{aligned}$$

And strongly stable:

$$\begin{aligned}
=_{A[\sigma]} &= =_{A[\sigma]}, \\
\mathrm{refl}_{A[\sigma]} &= \mathrm{refl}_{A[\sigma]}, \\
\mathrm{ind}_{\overline{A}, C, d}[\sigma] &= \mathrm{ind}_{\overline{A}[\sigma], C[\sigma], d[\sigma]}, \\
\beta_{\overline{A}, C, d}[\sigma] &= \beta_{\overline{A}[\sigma], C[\sigma], d[\sigma]}.
\end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Strict Models

To model ATT, we need choices that are split:

$$\begin{aligned} A[\text{id}_\Gamma] &= A, \\ A[\tau \circ \sigma] &= A[\sigma][\tau]. \end{aligned}$$

And strongly stable:

$$\begin{aligned} \text{=}_A[\sigma] &= \text{=}_{A[\sigma]}, \\ \text{refl}_A[\sigma] &= \text{refl}_{A[\sigma]}, \\ \text{ind}_{\overline{A}, C, d}[\sigma] &= \text{ind}_{\overline{A}[\sigma], C[\sigma], d[\sigma]}, \\ \beta_{\overline{A}, C, d}[\sigma] &= \beta_{\overline{A}[\sigma], C[\sigma], d[\sigma]}. \end{aligned}$$

We can turn a comprehension category into one that satisfies this:

- (Lumsdaine, Warren 2014): Local Universe Construction.
- (Bocquet 2021): Generic Contexts.

Path Categories

A path category is a category \mathcal{C} with two classes of maps:

- fibrations: closed under pullbacks and compositions,
- (weak) equivalences: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ f$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- fibrations: closed under pullbacks and compositions,
- (weak) equivalences: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ f$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- (weak) equivalences: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- (weak) equivalences: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a trivial fibration. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Categories

A **path category** is a category \mathcal{C} with two classes of maps:

- **fibrations**: closed under pullbacks and compositions,
- **(weak) equivalences**: satisfying 2-out-of-6, so, if we have

$$A \xrightarrow{f} B \xrightarrow{g} C \xrightarrow{h} D$$

where $g \circ f$ and $h \circ g$ are equivalences,
then f , g , h , and $h \circ g \circ h$ are equivalences.

If a map is both then we call it a **trivial fibration**. We require that:

- isomorphisms are trivial fibration,
- trivial fibrations are closed under pullbacks,
- every trivial fibration has a section.

\mathcal{C} has a terminal object 1 and every map $A \rightarrow 1$ is a fibration.

Path Objects

Lastly, a path category has a path object for every object A :

- a factorisation of the diagonal $\delta_A = (\text{id}_A, \text{id}_A)$:

$$\begin{array}{ccc}
 A & \xrightarrow{\delta_A} & A \times A \\
 \searrow r_A & & \nearrow (s_A, t_A) \\
 & PA &
 \end{array}$$

into a weak equivalence r_A followed by a fibration (s_A, t_A) .

Path Objects

Lastly, a path category has a **path object** for every object A :

- a factorisation of the diagonal $\delta_A = (\text{id}_A, \text{id}_A)$:

$$\begin{array}{ccc}
 A & \xrightarrow{\delta_A} & A \times A \\
 \searrow r_A & & \nearrow (s_A, t_A) \\
 & PA &
 \end{array}$$

into a weak equivalence r_A followed by a fibration (s_A, t_A) .

Path Objects

Lastly, a path category has a **path object** for every object A :

- a **factorisation** of the diagonal $\delta_A = (\text{id}_A, \text{id}_A)$:

$$\begin{array}{ccc}
 A & \xrightarrow{\delta_A} & A \times A \\
 \searrow r_A & & \nearrow (s_A, t_A) \\
 & PA &
 \end{array}$$

into a weak equivalence r_A followed by a fibration (s_A, t_A) .

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ homotopic, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an homotopy equivalence, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are precisely the weak equivalences.

In addition, we have a lifting theorem: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are precisely the weak equivalences.

In addition, we have a lifting theorem: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are precisely the weak equivalences.

In addition, we have a lifting theorem: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are **precisely** the weak equivalences.

In addition, we have a lifting theorem: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are **precisely** the weak equivalences.

In addition, we have a **lifting theorem**: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are **precisely** the weak equivalences.

In addition, we have a **lifting theorem**: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Homotopy Theory

We call two maps $f, g : A \rightarrow B$ **homotopic**, written $f \simeq g$, if there exists a map $h : A \rightarrow PB$ such that $s_B \circ h = f$ and $t_B \circ h = g$.

We call $f : A \rightarrow B$ an **homotopy equivalence**, if there exists a map $g : B \rightarrow A$ such that $g \circ f \simeq \text{id}_A$ and $f \circ g \simeq \text{id}_B$.

The homotopy equivalences are **precisely** the weak equivalences.

In addition, we have a **lifting theorem**: for a commutative square

$$\begin{array}{ccc} A & \longrightarrow & C \\ w \downarrow \wr & \nearrow & \downarrow p \\ B & \longrightarrow & D \end{array}$$

where w is an equivalence and p is a fibration, there is a map $d : B \rightarrow C$ unique up to homotopy such that the lower triangle commutes and the upper triangle commutes up to homotopy.

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the contexts are given by \mathcal{C} ,
- the types are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the display map for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the substitution $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the contexts are given by \mathcal{C} ,
- the types are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the display map for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the substitution $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the types are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the display map for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the substitution $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the display map for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the substitution $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the substitution $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the **substitution** $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the **substitution** $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable $=$ -types,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the **substitution** $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable **=-types**,
- weakly stable Σ -types with β and η reductions,
- contextuality (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the **substitution** $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable **=-types**,
- weakly stable **Σ -types** with β and η reductions,
- **contextuality** (contexts are finite).

Path Category \rightsquigarrow Comprehension Category

We can view a path category \mathcal{C} as a comprehension category:

- the **contexts** are given by \mathcal{C} ,
- the **types** are given by the full subcategory $\mathcal{C}^{\text{fib}} \subseteq \mathcal{C}^{\rightarrow}$,
- the **display map** for $p \in \mathcal{C}^{\text{fib}}$ is p itself,
- the **substitution** $p[\sigma]$ is the pullback σ^*p .

We will show that it has additional structure:

- weakly stable **=-types**,
- weakly stable **Σ -types** with β and η reductions,
- **contextuality** (contexts are finite).

Weakly Stable =-Types

For a type A we define:

$$=_A := (s_A, t_A) : P_A \rightrightarrows A \times A, \quad (\text{formation})$$

$$\text{refl}_A := r_A : A \simeq P_A. \quad (\text{introduction})$$

The elimination and β -axiom follow from our lifting theorem and the fact that r_A is an equivalence.

We get weak stability because we can show that path objects are preserved by taking pullbacks.

This uses ideas of (Van den Berg 2018).

Weakly Stable =-Types

For a type A we define:

$$\begin{aligned} =_A &:= (s_A, t_A) : P_A \rightrightarrows A \times A, && \text{(formation)} \\ \text{refl}_A &:= r_A : A \simeq P_A. && \text{(introduction)} \end{aligned}$$

The elimination and β -axiom follow from our lifting theorem and the fact that r_A is an equivalence.

We get weak stability because we can show that path objects are preserved by taking pullbacks.

This uses ideas of (Van den Berg 2018).

Weakly Stable =-Types

For a type A we define:

$$=_A := (s_A, t_A) : P_A \rightarrowtail A \times A, \quad (\text{formation})$$

$$\text{refl}_A := r_A : A \simeq P_A. \quad (\text{introduction})$$

The **elimination** and **β -axiom** follow from our lifting theorem and the fact that r_A is an equivalence.

We get weak stability because we can show that path objects are preserved by taking pullbacks.

This uses ideas of (Van den Berg 2018).

Weakly Stable =-Types

For a type A we define:

$$=_A := (s_A, t_A) : P_A \rightrightarrows A \times A, \quad (\text{formation})$$

$$\text{refl}_A := r_A : A \simeq P_A. \quad (\text{introduction})$$

The **elimination** and **β -axiom** follow from our lifting theorem and the fact that r_A is an equivalence.

We get **weak stability** because we can show that path objects are preserved by taking pullbacks.

This uses ideas of (Van den Berg 2018).

Weakly Stable =-Types

For a type A we define:

$$=_A := (s_A, t_A) : P_A \rightarrowtail A \times A, \quad (\text{formation})$$

$$\text{refl}_A := r_A : A \simeq P_A. \quad (\text{introduction})$$

The **elimination** and **β -axiom** follow from our lifting theorem and the fact that r_A is an equivalence.

We get **weak stability** because we can show that path objects are preserved by taking pullbacks.

This uses ideas of (Van den Berg 2018).

Weakly Stable Σ -Types with β and η

We obtain Σ -types because path categories do not distinguish between a single extension $\Gamma.A$ and $\Gamma.A_0 \dots A_{n-1}$.

The requirements on a comprehension category can be simplified:
for $\Gamma.A.B$ we have a type $\Sigma_A B$ and an iso $\Gamma.A.B \cong \Gamma.\Sigma_A B$
making the square commute:

$$\begin{array}{ccc}
 \Gamma.A.B & \xrightarrow{\sim} & \Gamma.\Sigma_A B \\
 p_B \downarrow & & \downarrow p_{\Sigma_A B} \\
 \Gamma.A & \xrightarrow{p_A} & \Gamma
 \end{array}$$

Holds in path categories: fibrations are closed under composition.

Weakly Stable Σ -Types with β and η

We obtain Σ -types because path categories do **not** distinguish between a single extension $\Gamma.A$ and $\Gamma.A_0 \dots A_{n-1}$.

The requirements on a comprehension category can be simplified:
 for $\Gamma.A.B$ we have a type $\Sigma_A B$ and an iso $\Gamma.A.B \cong \Gamma.\Sigma_A B$
 making the square commute:

$$\begin{array}{ccc}
 \Gamma.A.B & \xrightarrow{\sim} & \Gamma.\Sigma_A B \\
 p_B \downarrow & & \downarrow p_{\Sigma_A B} \\
 \Gamma.A & \xrightarrow{p_A} & \Gamma
 \end{array}$$

Holds in path categories: fibrations are closed under composition.

Weakly Stable Σ -Types with β and η

We obtain Σ -types because path categories do **not** distinguish between a single extension $\Gamma.A$ and $\Gamma.A_0 \dots A_{n-1}$.

The requirements on a comprehension category can be simplified:
 for $\Gamma.A.B$ we have a type $\Sigma_A B$ and an iso $\Gamma.A.B \cong \Gamma.\Sigma_A B$
 making the square commute:

$$\begin{array}{ccc}
 \Gamma.A.B & \xrightarrow{\sim} & \Gamma.\Sigma_A B \\
 p_B \downarrow & & \downarrow p_{\Sigma_A B} \\
 \Gamma.A & \xrightarrow{p_A} & \Gamma
 \end{array}$$

Holds in path categories: fibrations are closed under composition.

Weakly Stable Σ -Types with β and η

We obtain Σ -types because path categories do **not** distinguish between a single extension $\Gamma.A$ and $\Gamma.A_0 \dots A_{n-1}$.

The requirements on a comprehension category can be simplified:
for $\Gamma.A.B$ we have a type $\Sigma_A B$ and an iso $\Gamma.A.B \cong \Gamma.\Sigma_A B$
making the square commute:

$$\begin{array}{ccc}
 \Gamma.A.B & \xrightarrow{\sim} & \Gamma.\Sigma_A B \\
 p_B \downarrow & & \downarrow p_{\Sigma_A B} \\
 \Gamma.A & \xrightarrow{p_A} & \Gamma
 \end{array}$$

Holds in path categories: fibrations are closed under composition.

Weakly Stable Σ -Types with β and η

We obtain Σ -types because path categories do **not** distinguish between a single extension $\Gamma.A$ and $\Gamma.A_0 \dots A_{n-1}$.

The requirements on a comprehension category can be simplified:
for $\Gamma.A.B$ we have a type $\Sigma_A B$ and an iso $\Gamma.A.B \cong \Gamma.\Sigma_A B$
making the square commute:

$$\begin{array}{ccc}
 \Gamma.A.B & \xrightarrow{\sim} & \Gamma.\Sigma_A B \\
 p_B \downarrow & & \downarrow p_{\Sigma_A B} \\
 \Gamma.A & \xrightarrow{p_A} & \Gamma
 \end{array}$$

Holds in path categories: fibrations are closed under composition.

Contextuality

A comprehension category is contextual if for every Γ we have:

- a type A_0 in context ϵ ,
- a type A_1 in context $\epsilon.A_0$,
- a type A_2 in context $\epsilon.A_0.A_1$,
- \vdots
- a type A_{n-1} in context $\epsilon.A_0.....A_{n-2}$,

such that $\Gamma \cong \epsilon.A_0.....A_{n-1}$.

Holds in path categories: every map $\Gamma \rightarrow 1$ is a fibration.

Contextuality

A comprehension category is **contextual** if for every Γ we have:

- a type A_0 in context ϵ ,
- a type A_1 in context $\epsilon.A_0$,
- a type A_2 in context $\epsilon.A_0.A_1$,
- \vdots
- a type A_{n-1} in context $\epsilon.A_0.....A_{n-2}$,

such that $\Gamma \cong \epsilon.A_0.....A_{n-1}$.

Holds in path categories: every map $\Gamma \rightarrow 1$ is a fibration.

Contextuality

A comprehension category is **contextual** if for every Γ we have:

- a type A_0 in context ϵ ,
- a type A_1 in context $\epsilon.A_0$,
- a type A_2 in context $\epsilon.A_0.A_1$,
- \vdots
- a type A_{n-1} in context $\epsilon.A_0.....A_{n-2}$,

such that $\Gamma \cong \epsilon.A_0.....A_{n-1}$.

Holds in path categories: every map $\Gamma \rightarrow 1$ is a fibration.

Comprehension Category \rightsquigarrow Path Category

We can turn a comprehension category \mathcal{C} with weakly stable $=$, $\Sigma_{\beta, \eta}$, and contextuality into a path category by taking:

- the fibrations as the compositions of display maps and isos,
- the weak equivalences as the homotopy equivalences.
- the path objects as the $=$ -types.

Comprehension Category \rightsquigarrow Path Category

We can turn a comprehension category \mathcal{C} with weakly stable $=$, $\Sigma_{\beta,\eta}$, and contextuality into a path category by taking:

- the fibrations as the compositions of display maps and isos,
- the weak equivalences as the homotopy equivalences.
- the path objects as the $=$ -types.

Comprehension Category \rightsquigarrow Path Category

We can turn a comprehension category \mathcal{C} with weakly stable $=$, $\Sigma_{\beta, \eta}$, and contextuality into a path category by taking:

- the **fibrations** as the compositions of display maps and isos,
- the weak equivalences as the homotopy equivalences.
- the path objects as the $=$ -types.

Comprehension Category \rightsquigarrow Path Category

We can turn a comprehension category \mathcal{C} with weakly stable $=$, $\Sigma_{\beta, \eta}$, and contextuality into a path category by taking:

- the **fibrations** as the compositions of display maps and isos,
- the **weak equivalences** as the homotopy equivalences.
- the path objects as the $=$ -types.

Comprehension Category \rightsquigarrow Path Category

We can turn a comprehension category \mathcal{C} with weakly stable $=$, $\Sigma_{\beta,\eta}$, and contextuality into a path category by taking:

- the **fibrations** as the compositions of display maps and isos,
- the **weak equivalences** as the homotopy equivalences.
- the **path objects** as the $=$ -types.

Display Path Categories

In a display path category we distinguish $\Gamma.A$ and $\Gamma.A_0, \dots, A_{n-1}$.

Instead of fibrations we use display maps as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: path objects for display maps $A \rightarrow \Gamma$.

This is sufficient: we can use a lifting theorem and transport to inductively construct path objects for objects.

Display Path Categories

In a **display path category** we distinguish $\Gamma.A$ and $\Gamma.A_0. \dots .A_{n-1}$.

Instead of fibrations we use **display maps** as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: path objects for display maps $A \rightarrow \Gamma$.

This is sufficient: we can use a lifting theorem and transport to inductively construct path objects for objects.

Display Path Categories

In a **display path category** we distinguish $\Gamma.A$ and $\Gamma.A_0.\dots.A_{n-1}$.

Instead of fibrations we use **display maps** as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: path objects for display maps $A \rightarrow \Gamma$.

This is sufficient: we can use a lifting theorem and transport to inductively construct path objects for objects.

Display Path Categories

In a **display path category** we distinguish $\Gamma.A$ and $\Gamma.A_0.\dots.A_{n-1}$.

Instead of fibrations we use **display maps** as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: path objects for display maps $A \rightarrow \Gamma$.

This is sufficient: we can use a lifting theorem and transport to inductively construct path objects for objects.

Display Path Categories

In a **display path category** we distinguish $\Gamma.A$ and $\Gamma.A_0. \dots .A_{n-1}$.

Instead of fibrations we use **display maps** as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: **path objects for display maps** $A \rightarrow \Gamma$.

This is sufficient: we can use a lifting theorem and transport to inductively construct path objects for objects.

Display Path Categories

In a **display path category** we distinguish $\Gamma.A$ and $\Gamma.A_0.\dots.A_{n-1}$.

Instead of fibrations we use **display maps** as a primitive notion.

Fibrations are compositions of display maps and isomorphisms.

In addition, we replace path objects for objects Γ with a seemingly weaker notion: **path objects for display maps** $A \rightarrow \Gamma$.

This is **sufficient**: we can use a lifting theorem and transport to inductively construct path objects for objects.

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are forgetful, F is a free, and C is a cofree.

We end this talk with some open questions:

- Can we simplify other type formers as we did with $=$ -types?
- In particular, are propositional Σ -types and Π -types homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are forgetful, F is a free, and C is a cofree.

We end this talk with some open questions:

- Can we simplify other type formers as we did with $=$ -types?
- In particular, are propositional Σ -types and Π -types homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are **forgetful**, F is a **free**, and C is a **cofree**.

We end this talk with some open questions:

- Can we simplify other type formers as we did with $=$ -types?
- In particular, are propositional Σ -types and Π -types homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are **forgetful**, F is a **free**, and C is a **cofree**.

We end this talk with some open questions:

- Can we simplify other type formers as we did with $=$ -types?
- In particular, are propositional Σ -types and Π -types homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are **forgetful**, F is a **free**, and C is a **cofree**.

We end this talk with some open questions:

- Can we simplify **other type formers** as we did with $=$ -types?
- In particular, are propositional Σ -types and Π -types homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are **forgetful**, F is a **free**, and C is a **cofree**.

We end this talk with some open questions:

- Can we simplify **other type formers** as we did with $=$ -types?
- In particular, are propositional **Σ -types** and **Π -types** homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

Equivalence

We obtain the following diagram of 2-categories:

$$\begin{array}{ccc}
 \text{PathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =, \Sigma_{\beta\eta}} \\
 U \uparrow \dashv \downarrow C & & F \uparrow \dashv \downarrow U \\
 \text{DisplayPathCat} & \xrightarrow{\sim} & \text{ComprehensionCat}_{\text{Contextual}, =}
 \end{array}$$

Here the U 's are **forgetful**, F is a **free**, and C is a **cofree**.

We end this talk with some open questions:

- Can we simplify **other type formers** as we did with $=$ -types?
- In particular, are propositional **Σ -types** and **Π -types** homotopical left and right adjoints of pullback.
- Connect with (Maietti 2005) and (Clairembault, Dybjer 2013).

References

- Benno van den Berg, Ieke Moerdijk (2017): Exact completion of path categories.
- Benno van den Berg (2018): Path categories and propositional identity types.
- Rafaël Bocquet (2020): Coherence of strict equalities in type theories.
- Rafaël Bocquet (2021): Strictification of weakly stable type-theoretic structures using generic contexts.
- Pierre Clairembault, Peter Dybjer (2013): The biequivalence of locally Cartesian closed categories and Martin-Löf type theories.
- Martin Hofmann (1995): On the interpretation of type theory in locally Cartesian closed categories.
- Peter Lumsdaine, Michael Warren (2014): The local universes model, an overlooked coherence construction for dependent type theories.
- Maria Emilia Maietti (2005): Modular correspondence between dependent type theories and categories including pretopoi and topoi.
- Nicolas Oury (2005): Extensionality in the calculus of constructions.
- Matteo Spadetto (2023): A conservativity result for homotopy elementary types in dependent type theory.
- Theo Winterhalter (2019): Formalisation and meta-theory of type theory.