

Quotation 报价单

The seller: JIANGSU KAIGONG MACHINERY CO., LTD.
卖方
Address: NO.1869 WEST ZHONGHUAYUAN ROAD,
地址 KUNSHAN CITY JIANGSU PROVINCE, CHINA.
Tel: 电话 86-512-81639966

Quotation No. :Rev.1-ZJBJ0295
报价单编号
Issuing Date: 2026/5/18
日期

The buyer: Dam San
买方

Address:
地址

TRADE TERMS :CIF Hai Phong

NO. 编号	NAME 名称	MODEL型号	UNIT PRICE 单价	QUANTITY 数量	SUB TOTAL AMOUNT
					(USD)合计 (美金)
1	Cotton Comber	JSFA588A	54,000.00	6	324,000.00
2	Sliver Lap Winder	JSFA3180	66,000.00	1	66,000.00
Total				7	390,000.00

NOTES:备注

1. Payment conditions: 100% irrevocable letter of credit at sight.

付款条件: 100%即期不可撤销信用证。

2. Delivery time: 90 working days after receiving the L/C.

交货期: 在收到买方开立的信用证90个工作日后发货。

3. Production time: Will be started after the buyer issue 100% irrevocable L/C at sight to the seller.

生产时间: 将在卖方收到买方100%即期不可撤销信用证后予以安排。

4. Installation: During the installation period, the buyer should freely provide accommodation(including 3 meal day/person)、provide transportation (include international air tickets and local transportation) and USD100/per day allowance for Kaigong technician.

安装: 设备安调期间, 买方为凯宫安装技师免费提供食宿(含每人一日三餐), 交通费用(含来回机票及当地交通费), 安装人员津贴100美金/人/天。

5. Above price is valid for 2 months from the date of quotation. 以上价格自报价之日起有效期二个月。

6. Appendix 1: Key component configuration. 附件1为设备的主要配置。

7. Appendix 2: Technical specification. 附件2为设备技术参数。

8. Trolleys qty:6pcs, spools qty: 76pcs. 运棉小车数量: 6辆; 筒管数量: 76个。

9. If customer needs partial shipment for above machines, we will quote seperately according to the real situation. 如客户需对如上设备分批出运, 我司将根据分批出运实际情况重新报价。

**Key component configuration****JSFA3180 Sliver Lap Winder**

Key Component	Brand	Place of Origin
Drafting roller	Berkol	Switzerland
Pneumatic cylinder, pneumatic box valve and Manometer	JINQI	Taiwan
Pneumatic Connection	SANG-A	South Korea
Inverter	Schneider	France assembly in China
Touch Screen	KINCO	China
Bearings	INA or NSK or NTN	Germany/Japan
Belt	PLX or Habasit	U.K./Switzerland assembly in China

Key component configuration**JSFA 588A Cotton Comber**

Key Component	Brand	Place of Origin
Top Comb		Germany/Switzerland
Circular comb	130°	Germany/Switzerland
Detaching and drafting roller	Berkol	Switzerland
Pneumatic Box Valve and Manometer	ARK	Korea assembly in China
Pneumatic Connection	SANG-A	South Korea
Inverter	Schneider	France assembly in China
Touch Screen	KINCO	China
Bearings	INA or NSK or NTN	Germany/Japan
Belt	PLX or Habasit	U.K./Switzerland assembly in China
Nipper	Jielong	China
PLC	OMRON / MITSUBISHI	Japan assembly in China

TECHNICAL SPECIFICATION (一)

PARAMETER	JSFA 3180
Design Rate	230 m / min
Batt weight	60-80 g / m
Lap weight Max.	Max. 25 kg
Lap diameter Max.	Max. 580 mm
Lap width	300 mm
No. of feed slivers	18-28
Weight of sliver	3.7-6.0 ktex(18.5-30 g / 5m)
Feeding Can	600mm
Spool specification	300 mm X 200 mm, 2 kg
Batt Weight	80 g / m, Max.590 kg / h
No. of drafting heads	2
Drafting system	3-over-3
Pressure type	Pneumatic weighting
Drafting times	1.395-2.427(Total)1.314-2.285(Main),1.032-1.112(Back zone)
Cotton roll winding	Belt "Ω-type" covered winding controlled by roller
Drafting roller	3 9 mm(Outer diameter) X 300 mm(Length), 85
Machine weight	3.9 T
Rated power	7.5 kW
Running power	4.5 kW
Compressed air consumption	About 14.5 Nm ³ /h(7 bar ISA.)
Suction negative pressure	min. 1000 Pa
Suction air consumption	0.8 m ³ / s
Diameter of suction pipe	300 mm
Foundation bearing capacity	10600 N/m
Electrical control system	PLC (programmable logic control)

JIANGSU KAIGONG MACHINERY CO.,LTD.

TECHNICAL SPECIFICATION (二)

PARAMETER	JSFA 588A
Running speed	400-500 nips / min
No. of combing heads	8
Feeding cotton lap	Width 300 mm、 Weight 60-80 g/m
Suitable cotton fiber length	22-51 mm
Waste cotton percentage	8-25%
Feeding length	4.3、 4.5、 4.7、 5.0、 5.2、 5.6、 5.9
Cylinder comb Dia	125.4 mm
Drafting system type	3-over-3 pressure bar drafting with pneumatic weighting
Drafting times: total drafting	Main drfting 9.12-25.12、 Back zone drafting 1.13-2.00
Air compression	0.6-0.8 mpa
Output sliver	15-30 g / 5 m
Drafting gauge	Front 40.5-60 mm、 Back 44-66 mm
Sliver Can	600 mm
Suction system	Central integral suction
Air Volume	3050 m ³ /h
Machine weight	5T
Total power	5.8 KW
Running power	3.6 KW (50 Hz, 500 nips / min)
Compressed air pressure	0.6 - 0.8 Mpa
Compressed air consumption	0.5 m ³ /h
Main motor (Inverter)	5.5 kw
Brush motor	1.1 kw
Weight	5.25 Tons
Dimension(LxWxH)	7167×2042×1700 mm
Brush motor (installed power)	1.1 kw
Total consumed power	5.1 kw
Weight	5.25 Tons
Dimension(LxWxH)	7167×2042×1700 mm