



TIMTEX TRADING CO.,LTD

9F/8, No.413 LIN SHEN N.RD., TAIPEI, TAIWAN, R.O.C.
Tel: 886-2-25602945,25601676 – Fax:886-2-25310287,25055420
Email: timtex.taipei@msa.hinet.net

The Representative Office in VietNam:

HO CHI MINH OFFICE

NO.30/39 NGUYEN CUU VAN STR, GIA DINH WARD,
HO CHI MINH, VIETNAM.
Tel: +84 - 8 - 3514 6948/ 3514 6949
Email: timtex.saigon@timtextw.com.tw

HA NOI OFFICE

5TH FLOOR-ROOM 12, GOLD TOWER BUILDING NO. 275
NGUYEN TRAI STR, KHUONG DINH WARD, HANOI,
VIETNAM.
Tel:84-4-36643833/ 36644276

PROFORMA INVOICE

Messrs: DONG-IL VIETNAM CO., LTD

Date: 28th Apr, 2026
No. 219202

First of all, Timtex sincerely express our gratitude to DONG-IL VIETNAM CO., LTD, for your trust and cooperation. Regarding your inquiry for Stickiness Tester (model CONTEST-S 3304S) from Mesdan (Italy), we hereby submit the following quotation in response to your inquiry.

Detailed specifications are exhibited from page 03 onwards.

No.	Code	Description	Qty (pcs)	Unit Price (EUR)	Total Price (EUR)
1	3304SLAB	CONTEST-S	1	71.457,00	71.457,00
2	3304 770	CALIBRATION COTTONS FOR CONTEST-S	1	250,00	250,00
3	3304 1300	MONITOR TOUCHSCREEN	1	543,00	543,00
4	3304 1304	BAR CODE SCANNING	1	965,00	965,00
5	165 760	Electronic balance 2200g x 0,01g	1	2.231,00	2.231,00
<i>Optional accessories</i>					
1	199 CC2	Phytosanitary certificate	1		
TOTAL GOODS VALUE					75,446.00
PACKING CHARGES					450.00
HANDLING AND FOB CHARGES					550,00
TRANSPORTATION CHARGES					750,00
INSURANCE CHARGES					585,00
TOTAL VALUE CIF HO CHI MINH PORT					77.781,00

TERMS AND CONDITIONS:

1, Terms of supply: CIF Ho Chi Minh port

2, Shipment by: Sea freight

3, Insurance: Included

4, Shipment date: 6 months from receipt of letter of credit

5, Payment terms: 100% irrevocable L/C at sight

6, Installation and Training: Included

7, Inspection and legalization charge: Not included, If required at customer cost/initiative

8, Technical document: Available in English

9, Guarantee: 12 months from the invoice date in respect of defective materials only

10, Offer Validity: Until 15th May, 2026

TIMTEX TRADING CO., LTD



MR. PETER KO / CHAIRMAN

SPECIFICATIONS

3304SLAB	CONTEST-S
	CONTEST-S 3304S STICKINESS TESTER Cotton stickiness phenomenon (also called "sugar" - honeydew) changes from season to season and from region to region and it is caused by a large and variable source of contaminations. Since "sticky cotton" bales may seriously compromise the spinning process and reduce the quality of the yarn, it is important to grade the sticky cotton with an universal classification, even if each mill has its own typical machinery, knowledge and economical conditions that enable different level of tolerance. There are several testing techniques for determining cotton stickiness: chemical, mechanical and thermo-mechanical methods. Thanks to its highest correlation with processing behaviour and yarn quality, only thermo-mechanical methods are recommended (in both production and trade). In fact, the high variation in stickiness within a sample, as well as within a bale and within a lot, makes the thermo-mechanical method suitably designed for daily massive testing, in a trading context as well as in the spinning mill, thus overcoming the constraints of other methods (chemical and physical). Technical features: fully automatic high volume testing equipment designed to detect, measure, classify and grade cotton stickiness (honeydew/sugar content); unique equipment providing cotton stickiness risk probability on the basis of its grade enabling spinners to anticipate proper actions (how to process & blend different cotton bales); fast testing (30 sec/sample) designed for massive stickiness classification of bales and lots (>500 tests/shift); very repeatable and consistent results; testing method for stickiness grading recognised by ITMF - ICCTM. precious tool for ginning, spinning mills, cotton trader, textiles institutes, R&D labs and other cotton grading, arbitration and classing institutes; Included accessories: - built-in PC. - Sensors to measure the ambient conditions (temperature and relative humidity). - n. 1 compressed air Tool (already installed) equipped with pipe. - n. 1 Toolkit. - n. 1 Calibration cottons for CONTEST-S. 4 packs of 100 g each of calibration cotton with different stickiness levels. Essential accessories: - Contest-S cottons basic set, code 3304.780 - Touch screen monitor, code 3304.1300 - Barcode reader, code 3304.1304 - Electronic balance: 820 g x 0.01 g, code 165.760 Mandatory test ambient conditions (according to ASTM D1776): - Temperature: $21 \pm 1^{\circ}\text{C}$ / $70 \pm 2^{\circ}\text{F}$ - Relative Humidity: $65 \pm 2\%$ Reference test methods: UNI EN 14278-3 Textiles - Determination of cotton fibre stickiness - Part 3: Method using an automatic thermodetection rotating drum device. Size in cm: 151 X 96 X 141 h Origin: IT HS code: 90248000

3304 770	CALIBRATION COTTONS FOR CONTEST-S
	Calibration cottons for CONTEST-S. 4 packs of 100grms each of calibration cotton with different stickiness levels. Origin: US HS code: 52030000
3304 1300	MONITOR TOUCHSCREEN
	Origin: CN HS code: 85285291
3304 1304	BAR CODE SCANNING
	Origin: SK HS code: 84719000
165 760	Electronic balance 2200g x 0,01g
	Laboratory Analytical and Precision Balance; weighing capacity 2.200 g, readability 0,01 g, weighing pan size 182 x 182 mm, enables to start weighing right. Technical features: - High accuracy, the monolithic weigh cell ensures long-term high measurement accuracy. - Easy-to-read digital touchscreen display with graphical user interface. - External calibration. - Integrated below-balance weighing system. - Accurate levelling system. - CE-marked. Optional accessories & consumables: - Calibration report, code 165.CC1 - Calibration weight for laboratory balance: proof line knob weight 2.000 g, OIML class F1, with DAkkS certificate included, code 165.748 Origin: DE HS code: 90160010
	OPTIONAL ACCESSORIES
199 CC2	Phytosanitary certificate
	POWER SUPPLY: 230V 50/60HZ SINGLE PHASE
	PACKING ESTIMATED SPECIFICATIONS
	N.1 crate Dimensions (cm): 170 x 150 x 142 h Volume: 3,621 m3 Net weight: 338,8 kg Gross weight: 540,0 kg