



**Federal Aviation
Administration**

Initial En Route Qualification Training

**Lesson 14
Holding Procedures
End-of-Lesson Test**

Course 50148001



Intentionally left blank

Initial En Route Training

Lesson 14

Holding Procedures

End-of-Lesson Test – Variation 1

Lesson Objectives:

On an End-of-Lesson Test and in accordance with FAA Order JO 7110.65, you will identify:

- Procedures, and phraseology for holding aircraft
-

Directions: Items 1 through 8 are multiple choice. Indicate your selection by circling the appropriate letter.

1. When a delay is expected, holding instructions should be issued at least _____ minutes before the aircraft reaches the clearance limit fix.
 - A. 20
 - B. 15
 - C. 10
 - ☒ D. 5
2. What is the phraseology for issuing holding instructions when the holding pattern is charted?
 - ☒ A. "Cleared to Magnolia VORTAC, hold northwest as published, expect further clearance one one three five."
 - B. "Cleared to Magnolia VORTAC, hold northwest as charted, expect further clearance one one three five."
 - C. "Cleared to Magnolia VORTAC, expect further clearance one one three five."
 - D. "Cleared to Magnolia VORTAC, hold northwest, left turns, expect further clearance one one three five."

HOLDING PROCEDURES
End-of-Lesson Test – Variation 1 *(Continued)*

3. What is the correct sequence for issuing holding instructions for a noncharted holding pattern to an aircraft?
- ☒ A. Holding fix; direction of hold; radial, course, bearing, track, azimuth, airway or route on which to hold; leg length; direction of turns; EFC
 - B. Holding fix; direction of hold; airway or route on which to hold; EFC; leg length; track; azimuth
 - C. Direction of hold; holding fix; EFC; radial; bearing; track; course; airway or route on which to hold
 - D. Holding fix; direction of hold; EFC; direction of turns; leg length; course; bearing; azimuth; airway or route on which to hold
4. Which of the following is an instance when the direction of turns must be included in a holding clearance?
- A. Aircraft is at or below 14,000 feet MSL
 - B. DME or RNAV is to be used
 - C. Aircraft is following a standard pattern
 - ☒ D. Left turns are to be made
5. What action should be taken if you delay or intend to delay aircraft?
- A. Broadcast delay information via ATIS.
 - B. Issue holding instructions.
 - ☒ C. Advise your supervisor or a TMU coordinator.
 - D. Advise all adjacent control facilities.

HOLDING PROCEDURES

End-of-Lesson Test – Variation 1 (Continued)

6. If **NO** delay is expected, when should clearance beyond the fix be issued?
- A. At least three minutes before aircraft arrives at fix
 - B. Before aircraft starts slowing down
 - C. Before aircraft arrives at fix
 - ☒ D. As soon as possible
7. Select the phraseology to clear an aircraft whose route has **NOT** changed beyond a holding fix.
- A. "AS FILED."
 - ☒ B. "VIA LAST ROUTING CLEARED."
 - C. "VIA LAST ROUTING FILED."
 - D. "VIA FILED FLIGHT PLANNED ROUTE."
8. Choose the phraseology to issue the clearance indicated on the strip.

N6835K GLF3/A T420 66 03	GLH 1837	47		130✓	MEI	KLIT GLH V74 MHZ V18 MEI KMEI/1859	H - NW 1857
		18					
		47					
		MHZ					

- A. "Gulfstream Three Five Kilo, hold northwest as published, expect further clearance one eight five seven."
- ☒ B. "Gulfstream Three Five Kilo, cleared to Magnolia VORTAC, hold northwest as published, expect further clearance one eight five seven."
- C. "Gulfstream Three Five Kilo, cleared to Magnolia VORTAC, hold as published, expect further clearance one eight five seven."
- D. "Gulfstream Three Five Kilo, hold northwest as charted, expect further clearance one eight five seven."