



**Federal Aviation
Administration**

Initial En Route Qualification Training

**Lesson 18
Lateral Separation
End-of-Lesson Test**

Course 50148001



Intentionally left blank

Initial En Route Training

Lesson 18

Lateral Separation

End-of-Lesson Test – Variation 1

Lesson Objectives:

On an End-of-Lesson Test and in accordance with FAA Order JO 7110.65, you will identify:

- Airspace to be protected along airways, routes, and holding patterns
 - Minima and procedures for applying lateral separation
-

Directions: Items 1 through 10 are multiple choice. Indicate your selection by circling the appropriate letter. For items 7 through 10, refer to the DME Divergence Distance Minima Table (FAA Order JO 7110.65, paragraph 6-5-2, Table 6-5-2) and the Aero Center Map.

1. When are aircraft established on radials of the same NAVAID that diverge by at least 15 degrees considered to be laterally separated?
 - A. When aircraft are cleared to hold over different fixes at the same altitude.
 - ☒ B. When either aircraft is beyond airspace to be protected for the other.
 - C. When the slant-range is the line-of-sight distance between the aircraft and NAVAID.
 - D. When cleared aircraft on different airways or routes.
2. The size of the protected airspace of a holding pattern varies according to _____ and _____.
 - A. speed; direction of holding
 - B. altitude; wind speed
 - ☒ C. speed; altitude
 - D. altitude; direction of holding

LATERAL SEPARATION
End-of-Lesson Test – Variation 1 (Continued)

3. To determine a distance for lateral separation when the degrees divergence falls between two values listed in the divergence table, ____.
- A. Use the lesser distance
 - B. Take the average of the two distances
 - ☒ C. Use the greater distance
 - D. Take the sum of the two distances
4. The lateral separation provided for an aircraft on an established airway or route and within 51 miles from the NAVAID is _____ miles either side of the centerline.
- A. 10
 - B. 8
 - C. 5
 - ☒ D. 4
5. The protected airspace of a holding pattern must NOT _____ of an airway.
- ☒ A. overlap the protected airspace
 - B. touch the centerline
 - C. overlap the centerline
 - D. touch the protected airspace
6. Aircraft may be cleared to hold over different fixes at the same altitude if the _____.
- A. pilot requests it
 - ☒ B. holding pattern airspaces do NOT overlap
 - C. fixes are on established airways
 - D. controller desires it

LATERAL SEPARATION

End-of-Lesson Test – Variation 1 (Continued)

7. At what point, in miles, southwest of Magnolia VORTAC does lateral separation cease to exist between N76Y and N35Z?

N76Y PA27/A T160	MLU 1135	59	130	MEI	KMLU V18 KMEI /1223	
		11				
		MHZ				

N35Z M20P/A T165	HEZ 1121	01	130	ZAMMA	KHEZ V245 IGB KSTF /1237	
		12				
		MHZ				

TIME: 11:35:00

- A. 5
- ☒ B. 8
- C. 11
- D. 13
-
8. At what point (in miles) from a VOR will two converging aircraft lose separation if their angle of divergence is 15 degrees?
- A. 15 miles
- ☒ B. 17 miles
- C. 19 miles
- D. 21 miles

LATERAL SEPARATION

End-of-Lesson Test – Variation 1 (Continued)

9. At what point, in miles, southeast of SQS VORTAC will lateral separation begin between ASA771 and SWA41?

ASA771 F27/A T230	TXK 0711	35 07	90 ✓	IGB	KTXK V278 IGB KSTF /0800	
		SQS				
SWA41 B733/A T440		↑		MHZ 110	KGWO SQS V555 KMCB /0029	
		KGWO P0735				

- (A) 6
- B. 8
- C. 10
- D. 13
10. The degree of divergence (in miles) between V18 and V417, east of MLU VORTAC is _____ miles.
- (A) 17
- B. 10
- C. 8
- D. 6