

Anwendungstabelle

AcknowledgementDocument

für den Redispatch 2.0

Version:	1.0f
Publikationsdatum:	01.04.2025
Stand Formatbeschreibung:	1.0f
Autor:	BDEW

Disclaimer

Die zusätzlich veröffentlichte Excel-Datei dient als informatorische Lesefassung und entspricht inhaltlich der Anwendungstabelle mit dem identischen Publikationsdatum. Die PDF-Datei ist das gültige Dokument. Diese Excel-Datei wird bis auf Weiteres rein informatorisch und ergänzend veröffentlicht. Der BDEW behält sich vor, in Zukunft eine kostenpflichtige Veröffentlichung der Excel-Datei einzuführen.

AcknowledgementDocument			Übermittlung von initialen Stammdaten mit DP		Übermittlung von angereicherten Stammdaten mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (ANB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>					
0..1	ReceivingDocumentType					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von initialen Stammdaten mit DP		Übermittlung von angereicherten Stammdaten mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (ANB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP

AcknowledgementDocument			Übermittlung Stammdatenänderung vom EIV (verantwortlich) ausgehend mit DP		Übermittlung Stammdatenänderung vom (Anschluss-)NB (verantwortlich) ausgehend mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>					
0..1	ReceivingDocumentType					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Stammdatenänderung vom EIV (verantwortlich) ausgehend mit DP		Übermittlung Stammdatenänderung vom (Anschluss-)NB (verantwortlich) ausgehend mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP

AcknowledgementDocument			Übermittlung von initialen CR-Stammdaten zwischen NB mit DP		Übermittlung von initialen CR-Stammdaten zwischen NB mit DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (clusternder NB)	DP	NB (clusternder NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	A18	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>				
0..1	ReceivingDocumentType				
required	<i>v</i>		Z04	Z04	Z04
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung von initialen CR-Stammdaten zwischen NB mit DP		Übermittlung von initialen CR-Stammdaten zwischen NB mit DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	NB (betroffener NB)
		an	NB (clusternder NB)	DP	NB (clusternder NB)

AcknowledgementDocument			Änderung der CR-Stammdaten zwischen NB mit DP		Änderung der CR-Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	NB (clusternder NB)
			NB (clusternder NB)	DP	NB (betroffener NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f
1..1	xsd:sequence				
1..1	DocumentIdentification				
required	v		x	x	x
1..1	DocumentDateTime				
required	v		x	x	x
1..1	SenderIdentification				
required	v		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	v		A39	A18	A18
1..1	ReceiverIdentification				
required	v		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	v		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	v		x	x	x
0..1	ReceivingDocumentVersion				
required	v				
0..1	ReceivingDocumentType				
required	v		Z04	Z04	Z04
0..1	ReceivingPayloadName				
required	v				
0..1	DateTimeReceivingDocument				
required	v		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	xsd:sequence				
1..1	SendersTimeSeriesIdentification				
required	v				
0..unbounded	TimeIntervalError				
1..1	xsd:sequence				
1..1	QuantityTimeInterval				
required	v				
1..unbounded	Reason				
1..1	xsd:sequence				
1..1	ReasonCode				
required	v				
0..1	ReasonText				
required	v				
0..unbounded	Reason				
1..1	xsd:sequence				
1..1	ReasonCode				
required	v				
0..1	ReasonText				
required	v				
1..unbounded	Reason				
1..1	xsd:sequence				
1..1	ReasonCode				
required	v		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	v		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	xsd:sequence				
1..1	QuantityTimeInterval				
required	v				
1..unbounded	Reason				
1..1	xsd:sequence				
1..1	ReasonCode				
required	v				
0..1	ReasonText				
required	v				

AcknowledgementDocument			Änderung der CR-Stammdaten zwischen NB mit DP		Änderung der CR-Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	NB (clusternder NB)
		an	NB (clusternder NB)	DP	NB (betroffener NB)

AcknowledgementDocument			Übermittlung von Nichtbeanspruchbarkeiten an NB mit DP		Übermittlung von marktbedingten Anpassungen an NB mit DP im Prognosemodell	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	EIV	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A27	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A76 A80	A76 A80	A67	A67
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von Nichtbeanspruchbarkeiten an NB mit DP		Übermittlung von marktbedingten Anpassungen an NB mit DP im Prognosemodell	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	EIV	DP

AcknowledgementDocument			Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	DP NB (anwNB)	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f		1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	SenderIdentification							
required	<i>v</i>		MP-ID DP	MP-ID EIV		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A39	A27		A39	Z01	A08
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID NB	MP-ID DP		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A18	A39		A18	A39	Z01
0..1	ReceivingDocumentIdentification							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentVersion							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	ReceivingPayloadName							
required	<i>v</i>							
0..1	DateTimeReceivingDocument							
required	<i>v</i>		x	x		x	x	x
0..unbounded	TimeSeriesRejection							
1..1	<i>xsd:sequence</i>							
1..1	SendersTimeSeriesIdentification							
required	<i>v</i>							
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
0..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							

AcknowledgementDocument			Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP	EIV	DP -> NB	DP	LF	BKV
			NB (anwNB)	DP	EIV	NB (anwNB)	DP	LF

AcknowledgementDocument			Abruf im Duldungsfall mit Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	BTR EIV	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f		1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	SenderIdentification							
required	<i>v</i>		MP-ID DP A10 NDE	MP-ID EIV A10 NDE		MP-ID BTR A10 NDE	MP-ID LF A10 NDE	MP-ID BKV A10 NDE
1..1	SenderRole							
required	<i>v</i>		A39	A27		A21	Z01	A08
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID NB A10 NDE	MP-ID DP A10 NDE		MP-ID EIV A10 NDE	MP-ID DP A10 NDE	MP-ID LF A10 NDE
required	<i>codingScheme</i>							
1..1	ReceiverRole							
required	<i>v</i>		A18	A39		A27	A39	Z01
0..1	ReceivingDocumentIdentification							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentVersion							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	ReceivingPayloadName							
required	<i>v</i>							
0..1	DateTimeReceivingDocument							
required	<i>v</i>		x	x		x	x	x
0..unbounded	TimeSeriesRejection							
1..1	<i>xsd:sequence</i>							
1..1	SendersTimeSeriesIdentification							
required	<i>v</i>							
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
0..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 16 Z17		A01 A02 Z12 Z 13 Z14 Z15 Z1 6 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z 13 Z14 Z15 Z1 6 Z17
0..1	ReasonText							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							

AcknowledgementDocument			Abruf im Duldungsfall mit Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP	EIV	DP -> NB	BTR	LF	BKV
			NB (anwNB)	DP	EIV	EIV	DP	LF

AcknowledgementDocument			Übermittlung des Abrufs einer SR an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP	NB (anfNB)	DP	NB (anfNB)
			NB (anfNB)	DP	NB (anfNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung des Abrufs einer SR an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP	NB (anwNB)	DP	NB (anfNB)
			NB (anfNB)	DP	NB (anwNB)	DP

AcknowledgementDocument			Übermittlung des Abrufs einer SR an anweisenden NB ohne DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/Attribut	von an	NB (anwNB)	NB (anfNB)
			NB (anfNB)	NB (anwNB)
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>		x	x
1..1	DocumentDateTime			
required	<i>v</i>		x	x
1..1	SenderIdentification			
required	<i>v</i>		MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>		A18	A18
1..1	ReceiverIdentification			
required	<i>v</i>		MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>		A18	A18
0..1	ReceivingDocumentIdentification			
required	<i>v</i>		x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>		x	x
0..1	ReceivingDocumentType			
required	<i>v</i>		A96	A41
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>		x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>		[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			

AcknowledgementDocument			Übermittlung des Abrufs einer SR an anweisenden NB ohne DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	NB (anwNB)	NB (anfNB)
			NB (anfNB)	NB (anwNB)

AcknowledgementDocument			Abruf für eine CR an clusternden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP	NB (cNB)	DP	NB (anfNB)
			NB (anfNB)	DP	NB (cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Abruf für eine CR an clusternden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von	DP	NB (cNB)	DP	NB (anfNB)
		an	NB (anfNB)	DP	NB (cNB)	DP

AcknowledgementDocument			Abruf für eine CR an clusternden NB ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	NB (cNB)	NB (anfNB)	DP	NB (anfB)
			NB (anfNB)	NB (cNB)	NB (cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A41	A42	A42
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Abruf für eine CR an clusternden NB ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von	NB (cNB)	NB (anfNB)	DP	NB (anfB)
		an	NB (anfNB)	NB (cNB)	NB (cNB)	DP

AcknowledgementDocument			Aktualisierung der Abrufrückmeldung für den Abruf einer CR ohne DP
SD Prozess- schritt [2]			1
Häufigkeit	Element/ Attribut	von an	NB (anfNB) NB (cNB)
required	<i>DtdVersion</i>		5
required	<i>DtdRelease</i>		1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f
1..1	<i>xsd:sequence</i>		
1..1	DocumentIdentification		
required	<i>v</i>		x
1..1	DocumentDateTime		
required	<i>v</i>		x
1..1	SenderIdentification		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	SenderRole		
required	<i>v</i>		A18
1..1	ReceiverIdentification		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	ReceiverRole		
required	<i>v</i>		A18
0..1	ReceivingDocumentIdentification		
required	<i>v</i>		x
0..1	ReceivingDocumentVersion		
required	<i>v</i>		x
0..1	ReceivingDocumentType		
required	<i>v</i>		A42
0..1	ReceivingPayloadName		
required	<i>v</i>		
0..1	DateTimeReceivingDocument		
required	<i>v</i>		x
0..unbounded	TimeSeriesRejection		
1..1	<i>xsd:sequence</i>		
1..1	SendersTimeSeriesIdentification		
required	<i>v</i>		
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
0..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText		
required	<i>v</i>		[5]
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		

AcknowledgementDocument		SD Prozessschritt [2]	Aktualisierung der Abrufrückmeldung für den Abruf einer CR ohne DP
			1
Häufigkeit	Element/Attribut	von	NB (anfNB)
		an	NB (cNB)

AcknowledgementDocument			Übermittlung des Abrufs einer SG an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von an	DP NB (anfNB)	NB (anwNB) DP	DP NB (anwNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung des Abrufs einer SG an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von	DP	NB (anwNB)	DP	NB (anfNB)
		an	NB (anfNB)	DP	NB (anwNB)	DP

AcknowledgementDocument			Übermittlung des Abrufs einer SG an anweisenden NB ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	NB (anwNB)	NB (anfNB)	DP	NB (anfNB)
			NB (anfNB)	NB (anwNB)	NB (anwNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A18	A18	A39
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A41	A42	A42
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung des Abrufs einer SG an anweisenden NB ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von	NB (anwNB)	NB (anfNB)	DP	NB (anfNB)
		an	NB (anfNB)	NB (anwNB)	NB (anwNB)	DP

AcknowledgementDocument			Aktualisierung der Abrufrückmeldung für den Abruf einer SR ohne DP	Aktualisierung der Abrufrückmeldung für den Abruf einer SG mit DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SG ohne DP
SD Prozess- schritt [2]			1	1	2	1
Häufigkeit	Element/ Attribut	von an	NB (anfNB) NB (anwNB)	DP NB (anwNB)	NB (anfNB) DP	NB (anfNB) NB (anwNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A42	A42	A42	A42
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Aktualisierung der Abrufrückmeldung für den Abruf einer SR ohne DP	Aktualisierung der Abrufrückmeldung für den Abruf einer SG mit DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SG ohne DP
SD Prozess- schritt [2]			1	1	2	1
Häufigkeit	Element/ Attribut	von an	NB (anfNB)	DP	NB (anfNB)	NB (anfNB)
			NB (anwNB)	NB (anwNB)	DP	NB (anwNB)

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell mit DP		Übermittlung Planungsdaten für SR im Prognosemodell mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A14	A14	A14	A14
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell mit DP		Übermittlung Planungsdaten für SR im Prognosemodell mit DP	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell ohne DP	Übermittlung Planungsdaten für SG mit DP		Übermittlung Planungsdaten für SG ohne DP
SD Prozess- schritt [2]			1	1	2	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (ANB)	NB (ANB)	DP	NB (ANB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A39	A18	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A14	A14	A14	A14
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell ohne DP	Übermittlung Planungsdaten für SG mit DP		Übermittlung Planungsdaten für SG ohne DP
SD Prozess- schritt [2]			1	1	2	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (ANB)	NB (ANB)	DP	NB (ANB)

AcknowledgementDocument			Übermittlung Planungsdaten für CR mit DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)
			NB (cNB)	DP
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>		x	x
1..1	DocumentDateTime			
required	<i>v</i>		x	x
1..1	SenderIdentification			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>		A39	A18
1..1	ReceiverIdentification			
required	<i>v</i>		MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>		A18	A39
0..1	ReceivingDocumentIdentification			
required	<i>v</i>		x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>		x	x
0..1	ReceivingDocumentType			
required	<i>v</i>		A14	A14
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>		x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>		[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			

AcknowledgementDocument			Übermittlung Planungsdaten für CR mit DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)
			NB (cNB)	DP

AcknowledgementDocument			Übermittlung Planungsdaten für CR ohne DP	Übermittlung von Sensitivitäten zu Planungsdaten für SR mit DP		Übermittlung von Sensitivitäten zu Planungsdaten für SR ohne DP
SD Prozess- schritt [2]			1	1 und 3	2 und 4	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP	NB (direkt vorgeleNB ÜNB)	NB (direkt vorgeleNB ÜNB)
			NB (cNB)	NB (ANB vorgeleNB)	DP	NB (ANB vorgeleNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A39	A18	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A14	Z08	Z08	Z08
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Planungsdaten für CR ohne DP	Übermittlung von Sensitivitäten zu Planungsdaten für SR mit DP		Übermittlung von Sensitivitäten zu Planungsdaten für SR ohne DP
SD Prozess- schritt [2]			1	1 und 3	2 und 4	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP	NB (direkt vorge NB ÜNB)	NB (direkt vorge NB ÜNB)
			NB (cNB)	NB (ANB vorge NB)	DP	NB (ANB vorge NB)

AcknowledgementDocument			Übermittlung von Sensitivitäten zu Planungsdaten für SG mit DP		Übermittlung von Sensitivitäten zu Planungsdaten für SG ohne DP	Übermittlung von Planungsdaten
SD Prozessschritt [2]			1 und 3	2 und 4	1	1 und 3
Häufigkeit	Element/Attribut	von an	DP	NB (direkt vorgelNB ÜNB)	NB (direkt vorgelNB ÜNB)	DP
			NB (ANB vorgelNB)	DP	NB (ANB vorgelNB)	NB (cNB vorgelNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A18	A39
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z08	Z08	Z08	Z08
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von Sensitivitäten zu Planungsdaten für SG mit DP		Übermittlung von Sensitivitäten zu Planungsdaten für SG ohne DP	Übermittlung von Planungsdaten
SD Prozessschritt [2]			1 und 3	2 und 4	1	1 und 3
Häufigkeit	Element/Attribut	von	DP	NB (direkt vorgelNB ÜNB)	NB (direkt vorgelNB ÜNB)	DP
		an	NB (ANB vorgelNB)	DP	NB (ANB vorgelNB)	NB (cNB vorgelNB)

AcknowledgementDocument		SD Prozessschritt [2]	Sensitivitäten zu für CR mit DP
Häufigkeit	Element/Attribut	von an	NB (direkt vorgeNB ÜNB) DP
required	<i>DtdVersion</i>		5
required	<i>DtdRelease</i>		1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f
1..1	<i>xsd:sequence</i>		
1..1	DocumentIdentification		
required	<i>v</i>		x
1..1	DocumentDateTime		
required	<i>v</i>		x
1..1	SenderIdentification		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	SenderRole		
required	<i>v</i>		A18
1..1	ReceiverIdentification		
required	<i>v</i>		MP-ID DP
required	<i>codingScheme</i>		A10 NDE
1..1	ReceiverRole		
required	<i>v</i>		A39
0..1	ReceivingDocumentIdentification		
required	<i>v</i>		x
0..1	ReceivingDocumentVersion		
required	<i>v</i>		x
0..1	ReceivingDocumentType		
required	<i>v</i>		Z08
0..1	ReceivingPayloadName		
required	<i>v</i>		
0..1	DateTimeReceivingDocument		
required	<i>v</i>		x
0..unbounded	TimeSeriesRejection		
1..1	<i>xsd:sequence</i>		
1..1	SendersTimeSeriesIdentification		
required	<i>v</i>		
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
0..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText		
required	<i>v</i>		[5]
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		

AcknowledgementDocument			Sensitivitäten zu für CR mit DP
SD Prozess- schritt [2]			2 und 4
Häufigkeit	Element/ Attribut	von	NB (direkt vorge NB ÜNB)
an			DP

AcknowledgementDocument			Übermittlung von Sensitivitäten zu Planungsdaten für CR ohne DP	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP für SR		Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für SR
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/Attribut	von an	NB (direkt vorgeNB ÜNB) NB (cNB vorgeNB)	DP NB (anfNB)	NB (betroffener NB) DP	NB (betroffener NB) NB (anfNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A39	A18	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z08	Z09	Z09	Z09
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von Sensitivitäten zu Planungsdaten für CR ohne DP	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP für SR		Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für SR
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/Attribut	von an	NB (direkt vorgelNB ÜNB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (cNB vorgelNB)	NB (anfNB)	DP	NB (anfNB)

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP für SG		Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für SG	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten
SD Prozessschritt [2]			1	2	1	1
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	NB (betroffener NB)	DP
			NB (anfNB)	DP	NB (anfNB)	NB (anfNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A18	A39
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z09	Z09	Z09	Z09
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP für SG		Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für SG	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP für SG
SD Prozessschritt [2]			1	2	1	1
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	NB (betroffener NB)	DP
		an	NB (anfNB)	DP	NB (anfNB)	NB (anfNB)

AcknowledgementDocument		SD Prozessschritt [2]	notifizierter Abruf, über Abruf über mit DP für CR
Häufigkeit	Element/Attribut	von an	NB (betroffener NB)
			DP
required	<i>DtdVersion</i>		5
required	<i>DtdRelease</i>		1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f
1..1	<i>xsd:sequence</i>		
1..1	DocumentIdentification		
required	<i>v</i>		x
1..1	DocumentDateTime		
required	<i>v</i>		x
1..1	SenderIdentification		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	SenderRole		
required	<i>v</i>		A18
1..1	ReceiverIdentification		
required	<i>v</i>		MP-ID DP
required	<i>codingScheme</i>		A10 NDE
1..1	ReceiverRole		
required	<i>v</i>		A39
0..1	ReceivingDocumentIdentification		
required	<i>v</i>		x
0..1	ReceivingDocumentVersion		
required	<i>v</i>		x
0..1	ReceivingDocumentType		
required	<i>v</i>		Z09
0..1	ReceivingPayloadName		
required	<i>v</i>		
0..1	DateTimeReceivingDocument		
required	<i>v</i>		x
0..unbounded	TimeSeriesRejection		
1..1	<i>xsd:sequence</i>		
1..1	SendersTimeSeriesIdentification		
required	<i>v</i>		
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
0..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText		
required	<i>v</i>		[5]
0..unbounded	TimeIntervalError		
1..1	<i>xsd:sequence</i>		
1..1	QuantityTimeInterval		
required	<i>v</i>		
1..unbounded	Reason		
1..1	<i>xsd:sequence</i>		
1..1	ReasonCode		
required	<i>v</i>		
0..1	ReasonText		
required	<i>v</i>		

AcknowledgementDocument			SD Prozessschritt [2]	notizierter Abruf, über Abruf über mit DP für CR
			2	
Häufigkeit	Element/ Attribut	von	NB (betroffener NB)	
		an	DP	

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für CR	Übermittlung Flex-Beschränkung mit DP		Übermittlung Flex-Beschränkung ohne DP
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (anfNB)	NB [3]	DP	NB [3]
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A39	A18	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z09	B15	B15	B15
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP für CR	Übermittlung Flex-Beschränkung mit DP		Übermittlung Flex-Beschränkung ohne DP
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (anfNB)	NB [3]	DP	NB [3]

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell (mit DP) [4]	
SD Prozess- schritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)
			EIV	DP
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>		x	x
1..1	DocumentDateTime			
required	<i>v</i>		x	x
1..1	SenderIdentification			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>		A39	A18
1..1	ReceiverIdentification			
required	<i>v</i>		MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>		A27	A39
0..1	ReceivingDocumentIdentification			
required	<i>v</i>		x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>		x	x
0..1	ReceivingDocumentType			
required	<i>v</i>		Z05	Z05
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>		x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>		[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell (mit DP) [4]	
SD Prozess- schritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)
			EIV	DP

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell mit DP [4]		Übermittlung Planungsdaten für CR mit DP [4]	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB	DP	NB
			NB (ANB cNB)	DP	NB (ANB cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z05	Z05	Z05	Z05
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell mit DP [4]		Übermittlung Planungsdaten für CR mit DP [4]	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB	DP	NB
			NB (ANB cNB)	DP	NB (ANB cNB)	DP

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell ohne DP [4]	Übermittlung Planungsdaten für CR ohne DP [4]	Übermittlung von P für die Prognose
SD Prozess- schritt [2]			1	1	1
Häufigkeit	Element/ Attribut	von an	NB	NB	DP
			NB (ANB cNB)	NB (ANB cNB)	EIV
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A18	A18	A39
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID EIV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A18	A27
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z05	Z05	Z11
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell ohne DP [4]	Übermittlung Planungsdaten für CR ohne DP [4]	Übermittlung von P für die Prognosegi
SD Prozess- schritt [2]			1	1	1
Häufigkeit	Element/ Attribut	von an	NB	NB	DP
			NB (ANB cNB)	NB (ANB cNB)	EIV

AcknowledgementDocument			Prognoseplanungsdaten Güteprüfung mit DP	Übermittlung der Ergebnisse der Prognosegüteprüfung	Kommunikationstest zwischen Netzbetreibern	Übermittlung von
SD Prozess- schritt [2]			2	3	1	1
Häufigkeit	Element/ Attribut	von an	NB (ANB)	EIV	NB (angefragter)	DP
			DP	NB (ANB)	NB (angefragender)	NB (ANB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID EIV	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A27	A18	A39
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A39	A18	A18	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z11	Z12	A60	Z14
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					

AcknowledgementDocument			Prognoseplanungsdaten Prognosegüteprüfung mit DP	Übermittlung der Ergebnisse der Prognosegüteprüfung	Kommunikationstest zwischen Netzbetreibern	Übermittlung von
SD Prozess- schritt [2]			2	3	1	1
Häufigkeit	Element/ Attribut	von an	NB (ANB)	EIV	NB (angefragter)	DP
			DP	NB (ANB)	NB (anfragender)	NB (ANB)

AcknowledgementDocument		in Stammdaten zu Bilanzkreisen für die Ausgleichsfahrpläne		Übermittlung Stammdatenänderung zu B Ausgleichsfahrpläne vom (Anschluss-)NB (verantwortlich)	
SD Prozessschritt [2]		2	3	1	2
Häufigkeit	Element/ Attribut	von an	LF BKV	DP LF	
		DP	LF	NB (ANB)	DP
required	<i>DtdVersion</i>	5	5	5	5
required	<i>DtdRelease</i>	1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>	1.0f	1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>	x	x	x	x
1..1	DocumentDateTime				
required	<i>v</i>	x	x	x	x
1..1	SenderIdentification				
required	<i>v</i>	MP-ID LF	MP-ID BKV	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>	Z01	A08	A39	Z01
1..1	ReceiverIdentification				
required	<i>v</i>	MP-ID DP	MP-ID LF	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>	A39	Z01	A18	A39
0..1	ReceivingDocumentIdentification				
required	<i>v</i>	x	x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>	x	x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>	Z14	Z14	Z14	Z14
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>	x	x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>	[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung Stammdaten zu Bilanzkreisen für die Ausgleichsfahrpläne		Übermittlung Stammdatenänderung zu B Ausgleichsfahrpläne vom (Anschluss-)NB (verantwortlic	
SD Prozess- schritt [2]			2	3	1	2
Häufigkeit	Element/ Attribut	von an	LF	BKV	DP	LF
			DP	LF	NB (ANB)	DP

AcknowledgementDocument			Finanzkreisen für die (n) ausgehend	Rückmeldung zur Umsetzbarkeit auf den Abruf im Aufforderungsfall mit Delta- /Sollwertanweisung	
SD Prozess- schritt [2]			3	1	2
Häufigkeit	Element/ Attribut	von an	BKV	DP	NB (anwNB)
			LF	EIV	DP
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0f	1.0f	1.0f
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID BKV	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A08	A39	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID LF	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		Z01	A27	A39
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z14	A41	A41
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				

AcknowledgementDocument		ilanzkreisen für die) ausgehend	Rückmeldung zur Umsetzbarkeit auf den Abruf im Aufforderungsfall mit Delta- /Sollwertanweisung	
SD Prozess- schritt [2]		3	1	2
Häufigkeit	Element/ Attribut	von	DP	NB (anwNB)
		an	LF	EIV DP

Fußnoten

Fußnote	Hinweis
[1]	gelöscht
[2]	Der Prozessschritt entspricht dem Prozessschritt des Dokumentes, für den ein ACK als Antwort übermittelt wird.
[3]	Netzbetreiber mit Engpass
[4]	In diesem Prozessschritt werden Kosten übermittelt.
[5]	<p>Wenn im ReasonCode Z12 verwendet wurde: Im Falle eines erkannten Syntaxfehlers ist ein Fehlerbeschreibungstext zu übermitteln der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt.</p> <p>Wenn im ReasonCode Z12 nicht verwendet wurde: Im Falle eines negativen ACKs kann hier optional eine Fehlerbeschreibungstext übermittelt werden, der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt.</p>