

Anwendungstabelle

## **AcknowledgementDocument**

für Redispatch 2.0

Version:	1.0c
Publikationsdatum:	31.03.2023
Stand Formatbeschreibung:	1.0c
Autor:	BDEW

## Disclaimer

Die zusätzlich veröffentlichte Excel-Datei dient als informatorische Lesefassung und entspricht inhaltlich der Anwendungstabelle mit dem identischen Publikationsdatum. Die PDF-Datei ist das gültige Dokument.

Diese Excel-Datei wird bis auf Weiteres rein informatorisch und ergänzend veröffentlicht. Der BDEW behält sich vor, in Zukunft eine kostenpflichtige Veröffentlichung der Excel-Datei einzuführen.

AcknowledgementDocument			Übermittlung von initialen Stammdaten mit DP		Übermittlung von angereicherten Stammdaten mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (ANB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A27	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>					
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Stammdatenänderung vom EIV (verantwortlich) ausgehend mit DP		Übermittlung Stammdatenänderung vom (Anschluss-)NB (verantwortlich) ausgehend mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A27	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>					
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von initialen Cluster-Ressourcen-Stammdaten zwischen NB mit DP		Übermittlung von initialen Cluster-Ressourcen Stammdaten zwischen NB ohne DP
SD			1		1
Prozessschritt [2]			1		1
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	NB (betroffener NB)
		an	NB (clusternder NB)	DP	NB (clusternder NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	A18	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>				
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z04	Z04	Z04
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Änderung der Cluster-Ressourcen-Stammdaten zwischen NB mit DP		Änderung der Cluster-Ressourcen-Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	NB (clusternder NB)
			NB (clusternder NB)	DP	NB (betroffener NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	A18	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>				
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z04	Z04	Z04
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung von Nichtbeanspruchbarkeiten an NB mit DP		Übermittlung von marktbedingten Anpassungen an NB mit DP im Prognosemodell	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	EIV	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A27	A39	A27	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A76 A80	A76 A80	A67	A67
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	DP NB (anwNB)	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>							
1..1	<b>DocumentIdentification</b>							
required	<i>v</i>		x	x		x	x	x
1..1	<b>DocumentDateTime</b>							
required	<i>v</i>		x	x		x	x	x
1..1	<b>SenderIdentification</b>							
required	<i>v</i>		MP-ID DP A10 NDE	MP-ID EIV A10 NDE		MP-ID DP A10 NDE	MP-ID LF A10 NDE	MP-ID BKV A10 NDE
required	<i>codingScheme</i>							
1..1	<b>SenderRole</b>							
required	<i>v</i>		A39	A27		A39	Z01	A08
1..1	<b>ReceiverIdentification</b>							
required	<i>v</i>		MP-ID NB A10 NDE	MP-ID DP A10 NDE		MP-ID NB A10 NDE	MP-ID DP A10 NDE	MP-ID LF A10 NDE
required	<i>codingScheme</i>							
1..1	<b>ReceiverRole</b>							
required	<i>v</i>		A18	A39		A18	A39	Z01
0..1	<b>ReceivingDocumentIdentification</b>							
required	<i>v</i>		x	x		x	x	x
0..1	<b>ReceivingDocumentVersion</b>							
required	<i>v</i>		x	x		x	x	x
0..1	<b>ReceivingDocumentType</b>							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	<b>ReceivingPayloadName</b>							
required	<i>v</i>							
0..1	<b>DateTimeReceivingDocument</b>							
required	<i>v</i>		x	x		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>SendersTimeSeriesIdentification</b>							
required	<i>v</i>							
0..unbounded	<b>TimeIntervalError</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>QuantityTimeInterval</b>							
required	<i>v</i>							
1..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>							
0..1	<b>ReasonText</b>							
required	<i>v</i>							
0..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>QuantityTimeInterval</b>							
required	<i>v</i>							
1..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>							
0..1	<b>ReasonText</b>							
required	<i>v</i>							



AcknowledgementDocument			Abruf im Duldungsfall mit Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	BTR EIV	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>							
1..1	<b>DocumentIdentification</b>							
required	<i>v</i>		x	x		x	x	x
1..1	<b>DocumentDateTime</b>							
required	<i>v</i>		x	x		x	x	x
1..1	<b>SenderIdentification</b>							
required	<i>v</i>		MP-ID DP A10 NDE	MP-ID EIV A10 NDE		MP-ID BTR A10 NDE	MP-ID LF A10 NDE	MP-ID BKV A10 NDE
1..1	<b>SenderRole</b>							
required	<i>v</i>		A39	A27		A21	Z01	A08
1..1	<b>ReceiverIdentification</b>							
required	<i>v</i>		MP-ID NB A10 NDE	MP-ID DP A10 NDE		MP-ID EIV A10 NDE	MP-ID DP A10 NDE	MP-ID LF A10 NDE
required	<i>codingScheme</i>							
1..1	<b>ReceiverRole</b>							
required	<i>v</i>		A18	A39		A27	A39	Z01
0..1	<b>ReceivingDocumentIdentification</b>							
required	<i>v</i>		x	x		x	x	x
0..1	<b>ReceivingDocumentVersion</b>							
required	<i>v</i>		x	x		x	x	x
0..1	<b>ReceivingDocumentType</b>							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	<b>ReceivingPayloadName</b>							
required	<i>v</i>							
0..1	<b>DateTimeReceivingDocument</b>							
required	<i>v</i>		x	x		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>SendersTimeSeriesIdentification</b>							
required	<i>v</i>							
0..unbounded	<b>TimeIntervalError</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>QuantityTimeInterval</b>							
required	<i>v</i>							
1..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>							
0..1	<b>ReasonText</b>							
required	<i>v</i>							
0..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>							
0..1	<b>ReasonText</b>							
required	<i>v</i>							
1..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>QuantityTimeInterval</b>							
required	<i>v</i>							
1..unbounded	<b>Reason</b>							
1..1	<i>xsd:sequence</i>							
1..1	<b>ReasonCode</b>							
required	<i>v</i>							
0..1	<b>ReasonText</b>							
required	<i>v</i>							

AcknowledgementDocument			Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von an	DP	NB (anwNB)	DP	NB (anfNB)
			NB (anfNB)	DP	NB (anwNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A18	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A96	A96	A41	A41
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB ohne DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	NB (anwNB)	NB (anfNB)
			NB (anfNB)	NB (anwNB)
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c
1..1	<i>xsd:sequence</i>			
1..1	<b>DocumentIdentification</b>			
required	<i>v</i>		x	x
1..1	<b>DocumentDateTime</b>			
required	<i>v</i>		x	x
1..1	<b>SenderIdentification</b>			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	<b>SenderRole</b>			
required	<i>v</i>		A18	A18
1..1	<b>ReceiverIdentification</b>			
required	<i>v</i>		MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>			
required	<i>v</i>		A18	A18
0..1	<b>ReceivingDocumentIdentification</b>			
required	<i>v</i>		x	x
0..1	<b>ReceivingDocumentVersion</b>			
required	<i>v</i>		x	x
0..1	<b>ReceivingDocumentType</b>			
required	<i>v</i>		A96	A41
0..1	<b>ReceivingPayloadName</b>			
required	<i>v</i>			
0..1	<b>DateTimeReceivingDocument</b>			
required	<i>v</i>		x	x
0..unbounded	<b>TimeSeriesRejection</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>SendersTimeSeriesIdentification</b>			
required	<i>v</i>			
0..unbounded	<b>TimeIntervalError</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>QuantityTimeInterval</b>			
required	<i>v</i>			
1..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>			
0..1	<b>ReasonText</b>			
required	<i>v</i>			
0..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>			
required	<i>v</i>		[5]	[5]
0..unbounded	<b>TimeIntervalError</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>QuantityTimeInterval</b>			
required	<i>v</i>			
1..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>			
0..1	<b>ReasonText</b>			
required	<i>v</i>			

AcknowledgementDocument			Abruf für eine Cluster-Ressource mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von an	DP NB (anfNB)	NB (cNB) DP	DP NB (cNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A96	A96	A41	A41
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Abruf für eine Cluster-Ressource ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	NB (cNB)	NB (anfNB)	DP	NB (cNB)
			NB (anfNB)	NB (cNB)	NB (cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A18	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A18	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A96	A41	A42	A42
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Aktualisierung der Abrufrückmeldung für den Abruf einer CR ohne DP
SD Prozessschritt [2]			1
Häufigkeit	Element/ Attribut	von an	NB (cNB) NB (anwNB)
required	<i>DtdVersion</i>		5
required	<i>DtdRelease</i>		1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c
1..1	<i>xsd:sequence</i>		
1..1	<b>DocumentIdentification</b>		
required	<i>v</i>		x
1..1	<b>DocumentDateTime</b>		
required	<i>v</i>		x
1..1	<b>SenderIdentification</b>		
required	<i>v</i>		MP-ID DP
required	<i>codingScheme</i>		A10 NDE
1..1	<b>SenderRole</b>		
required	<i>v</i>		A18
1..1	<b>ReceiverIdentification</b>		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	<b>ReceiverRole</b>		
required	<i>v</i>		A18
0..1	<b>ReceivingDocumentIdentification</b>		
required	<i>v</i>		x
0..1	<b>ReceivingDocumentVersion</b>		
required	<i>v</i>		x
0..1	<b>ReceivingDocumentType</b>		
required	<i>v</i>		A42
0..1	<b>ReceivingPayloadName</b>		
required	<i>v</i>		
0..1	<b>DateTimeReceivingDocument</b>		
required	<i>v</i>		x
0..unbounded	<b>TimeSeriesRejection</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>SendersTimeSeriesIdentification</b>		
required	<i>v</i>		
0..unbounded	<b>TimeIntervalError</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>QuantityTimeInterval</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		
0..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		A01 A02 Z12
0..1	<b>ReasonText</b>		
required	<i>v</i>		[5]
0..unbounded	<b>TimeIntervalError</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>QuantityTimeInterval</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		

AcknowledgementDocument			Abruf für eine Steuergruppe mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von an	DP NB (anfNB)	NB (anwNB) DP	DP NB (anwNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A96	A96	A41	A41
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Abruf für eine Steuergruppe ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SR und SG mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	NB (anwNB) NB (anfNB)	NB (anfNB) NB (anwNB)	NB (anwNB) DP	DP NB (anfNB)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP A10 NDE	MP-ID NB A10 NDE	MP-ID NB A10 NDE	MP-ID DP A10 NDE
required	<i>codingScheme</i>					
1..1	<b>SenderRole</b>					
required	<i>v</i>		A18	A18	A18	A39
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB A10 NDE	MP-ID DP A10 NDE	MP-ID DP A10 NDE	MP-ID NB A10 NDE
required	<i>codingScheme</i>					
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A96	A41	A42	A42
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					



AcknowledgementDocument			Aktualisierung der Abrufrückmeldung für den Abruf einer SR und SG ohne DP
SD Prozessschritt [2]			1
Häufigkeit	Element/ Attribut	von an	NB (anwNB) NB (anfNB)
required	<i>DtdVersion</i>		5
required	<i>DtdRelease</i>		1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c
1..1	<i>xsd:sequence</i>		
1..1	<b>DocumentIdentification</b>		
required	<i>v</i>		x
1..1	<b>DocumentDateTime</b>		
required	<i>v</i>		x
1..1	<b>SenderIdentification</b>		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	<b>SenderRole</b>		
required	<i>v</i>		A18
1..1	<b>ReceiverIdentification</b>		
required	<i>v</i>		MP-ID NB
required	<i>codingScheme</i>		A10 NDE
1..1	<b>ReceiverRole</b>		
required	<i>v</i>		A18
0..1	<b>ReceivingDocumentIdentification</b>		
required	<i>v</i>		x
0..1	<b>ReceivingDocumentVersion</b>		
required	<i>v</i>		x
0..1	<b>ReceivingDocumentType</b>		
required	<i>v</i>		A42
0..1	<b>ReceivingPayloadName</b>		
required	<i>v</i>		
0..1	<b>DateTimeReceivingDocument</b>		
required	<i>v</i>		x
0..unbounded	<b>TimeSeriesRejection</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>SendersTimeSeriesIdentification</b>		
required	<i>v</i>		
0..unbounded	<b>TimeIntervalError</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>QuantityTimeInterval</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		
0..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		A01 A02 Z12
0..1	<b>ReasonText</b>		
required	<i>v</i>		[5]
0..unbounded	<b>TimeIntervalError</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>QuantityTimeInterval</b>		
required	<i>v</i>		
1..unbounded	<b>Reason</b>		
1..1	<i>xsd:sequence</i>		
1..1	<b>ReasonCode</b>		
required	<i>v</i>		
0..1	<b>ReasonText</b>		
required	<i>v</i>		

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell mit DP		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB/clustNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A39	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A27	A39	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		A14	A14	A14	A14
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP	Übermittlung von Sensitivitäten (1, 2) und angereicherten Sensitivitäten (3, 4) zu Planungsdaten für SR, SG und CR mit DP	
SD Prozessschritt [2]			1	1 und 3	2 und 4
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB) NB (ANB clustNB)	DP NB (ANB vorgeNB)	NB (direkt vorgeNB ÜNB) DP
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A18	A39	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		A14	Z08	Z08
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung von Sensitivitäten und angereicherten Sensitivitäten zu Planungsdaten für SR, SG und CR ohne DP	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP	
SD Prozessschritt [2]			1	1	2
Häufigkeit	Element/ Attribut	von an	NB (direkt vorgefNB ÜNB) NB (ANB vorgefNB)	DP NB (anfNB)	NB (betroffener NB) DP
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A18	A39	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A18	A39
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z08	Z09	Z09
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP	Übermittlung Flex-Beschränkung mit DP		Übermittlung Flex-Beschränkung ohne DP
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (anfNB)	NB [3]	DP	NB [3]
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A18	A39	A18	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A18	A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		Z09	B15	B15	B15
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung des Beschaffungsvorbehalts mit DP		Übermittlung des Beschaffungsvorbehalts ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/ Attribut	von an	DP	NB	NB
			NB (ÜNB)	DP	NB (ÜNB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	A18	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z06	Z06	Z06
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Beschaffung energetischer Ausgleich bei Beschaffungsvorbehalt	
SD				
Prozessschritt [2]			1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (ÜNB)
			NB	DP
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c
1..1	<i>xsd:sequence</i>			
1..1	<b>DocumentIdentification</b>			
required	<i>v</i>		x	x
1..1	<b>DocumentDateTime</b>			
required	<i>v</i>		x	x
1..1	<b>SenderIdentification</b>			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	<b>SenderRole</b>			
required	<i>v</i>		A39	A18
1..1	<b>ReceiverIdentification</b>			
required	<i>v</i>		MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>			
required	<i>v</i>		A18	A39
0..1	<b>ReceivingDocumentIdentification</b>			
required	<i>v</i>		x	x
0..1	<b>ReceivingDocumentVersion</b>			
required	<i>v</i>		x	x
0..1	<b>ReceivingDocumentType</b>			
required	<i>v</i>		Z07	Z07
0..1	<b>ReceivingPayloadName</b>			
required	<i>v</i>			
0..1	<b>DateTimeReceivingDocument</b>			
required	<i>v</i>		x	x
0..unbounded	<b>TimeSeriesRejection</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>SendersTimeSeriesIdentification</b>			
required	<i>v</i>			
0..unbounded	<b>TimeIntervalError</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>QuantityTimeInterval</b>			
required	<i>v</i>			
1..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>			
0..1	<b>ReasonText</b>			
required	<i>v</i>			
0..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>			
0..1	<b>ReasonText</b>			
required	<i>v</i>			
1..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>			
required	<i>v</i>		[5]	[5]
0..unbounded	<b>TimeIntervalError</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>QuantityTimeInterval</b>			
required	<i>v</i>			
1..unbounded	<b>Reason</b>			
1..1	<i>xsd:sequence</i>			
1..1	<b>ReasonCode</b>			
required	<i>v</i>			
0..1	<b>ReasonText</b>			
required	<i>v</i>			

AcknowledgementDocument			Beschaffung energetischer Ausgleich bei Beschaffungsvorbeh alt ohne DP	Übermittlung von Planungsdaten im Planwertmodell (mit DP) [4]	
SD Prozessschritt [2]			1	1	2
Häufigkeit	Element/ Attribut	von an	NB (ÜNB)	DP	NB (betroffener NB)
			NB	EIV	DP
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A18	A39	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A27	A39
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z07	Z05	Z05
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				



AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP [4]		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP [4]
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/ Attribut	von an	DP	NB	NB
			NB	DP	NB
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	A18	A18
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	A18
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z05	Z05	Z05
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung von Probeplanungsdaten für die Prognosegüteprüfung mit DP		Übermittlung der Ergebnisse der Prognosegüteprüfung	Kommunikationstest zwischen Netzbetreibern
SD Prozessschritt [2]			1	2	3	1
Häufigkeit	Element/ Attribut	von an	DP	ANB	EIV	NB (angefragter)
			EIV	DP	ANB	NB (angfragender)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>					
1..1	<b>DocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>DocumentDateTime</b>					
required	<i>v</i>		x	x	x	x
1..1	<b>SenderIdentification</b>					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID EIV	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>					
required	<i>v</i>		A39	A18	A27	A18
1..1	<b>ReceiverIdentification</b>					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>					
required	<i>v</i>		A27	A39	A18	A18
0..1	<b>ReceivingDocumentIdentification</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentVersion</b>					
required	<i>v</i>		x	x	x	x
0..1	<b>ReceivingDocumentType</b>					
required	<i>v</i>		Z11	Z11	Z12	A60
0..1	<b>ReceivingPayloadName</b>					
required	<i>v</i>					
0..1	<b>DateTimeReceivingDocument</b>					
required	<i>v</i>		x	x	x	x
0..unbounded	<b>TimeSeriesRejection</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>SendersTimeSeriesIdentification</b>					
required	<i>v</i>					
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
0..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>QuantityTimeInterval</b>					
required	<i>v</i>					
1..unbounded	<b>Reason</b>					
1..1	<i>xsd:sequence</i>					
1..1	<b>ReasonCode</b>					
required	<i>v</i>					
0..1	<b>ReasonText</b>					
required	<i>v</i>					

AcknowledgementDocument			Übermittlung von Stammdaten zu Bilanzkreisen für die Ausgleichsfahrpläne		
SD Prozessschritt [2]			1	2	3
Häufigkeit	Element/ Attribut	von an	DP	LF	BKV
			NB (ANB)	DP	LF
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	Z01	A08
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	Z01
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z14	Z14	Z14
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

AcknowledgementDocument			Übermittlung Stammdatenänderung zu Bilanzkreisen für die Ausgleichsfahrpläne vom (Anschluss-)NB (verantwortlich) ausgehend		
SD Prozessschritt [2]			1	2	3
Häufigkeit	Element/ Attribut	von an	DP	LF	BKV
			NB (ANB)	DP	LF
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0c	1.0c	1.0c
1..1	<i>xsd:sequence</i>				
1..1	<b>DocumentIdentification</b>				
required	<i>v</i>		x	x	x
1..1	<b>DocumentDateTime</b>				
required	<i>v</i>		x	x	x
1..1	<b>SenderIdentification</b>				
required	<i>v</i>		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>SenderRole</b>				
required	<i>v</i>		A39	Z01	A08
1..1	<b>ReceiverIdentification</b>				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	<b>ReceiverRole</b>				
required	<i>v</i>		A18	A39	Z01
0..1	<b>ReceivingDocumentIdentification</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentVersion</b>				
required	<i>v</i>		x	x	x
0..1	<b>ReceivingDocumentType</b>				
required	<i>v</i>		Z14	Z14	Z14
0..1	<b>ReceivingPayloadName</b>				
required	<i>v</i>				
0..1	<b>DateTimeReceivingDocument</b>				
required	<i>v</i>		x	x	x
0..unbounded	<b>TimeSeriesRejection</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>SendersTimeSeriesIdentification</b>				
required	<i>v</i>				
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				
0..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>		A01 A02 Z12	A01 A02 Z12	A01 A02 Z12
0..1	<b>ReasonText</b>				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	<b>TimeIntervalError</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>QuantityTimeInterval</b>				
required	<i>v</i>				
1..unbounded	<b>Reason</b>				
1..1	<i>xsd:sequence</i>				
1..1	<b>ReasonCode</b>				
required	<i>v</i>				
0..1	<b>ReasonText</b>				
required	<i>v</i>				

## Fußnoten

Fußnote	Hinweis
[1]	gelöscht
[2]	Der Prozessschritt entspricht dem Prozessschritt des Dokumentes, für den ein ACK als Antwort übermittelt wird.
[3]	Netzbetreiber mit Engpass
[4]	In diesem Prozessschritt werden Kosten übermittelt.
[5]	<p>Wenn im ReasonCode Z12 verwendet wurde: Im Falle eines erkannten Syntaxfehlers ist ein Fehlerbeschreibungstext zu übermitteln der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt.</p> <p>Wenn im ReasonCode Z12 nicht verwendet wurde: Im Falle eines negativen ACKs kann hier optional eine Fehlerbeschreibungstext übermittelt werden, der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt.</p>