

Anwendungstabelle

AcknowledgementDocument

für den Redispatch 2.0

Version:	1.0d
Publikationsdatum:	04.10.2023
Stand Formatbeschreibung:	1.0d
Autor:	BDEW

Disclaimer

Die zusätzlich veröffentlichte Excel-Datei dient als informatorische Lesefassung und entspricht inhaltlich der Anwendungstabelle mit dem identischen Publikationsdatum. Die PDF-Datei ist das gültige Dokument. Diese Excel-Datei wird bis auf Weiteres rein informatorisch und ergänzend veröffentlicht. Der BDEW behält sich vor, in Zukunft eine kostenpflichtige Veröffentlichung der Excel-Datei einzuführen.

AcknowledgementDocument			Übermittlung von initialen Stammdaten mit DP		Übermittlung von angereicherten Stammdaten mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (ANB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>					
0..1	ReceivingDocumentType					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung von initialen Stammdaten mit DP		Übermittlung von angereicherten Stammdaten mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von	DP	NB (ANB)	DP	NB (betroffener NB)
		an	EIV	DP	NB (ANB)	DP
required		v				

AcknowledgementDocument			Übermittlung Stammdatenänderung vom EIV (verantwortlich) ausgehend mit DP		Übermittlung Stammdatenänderung vom (Anschluss-)NB (verantwortlich) ausgehend mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>					
0..1	ReceivingDocumentType					
required	<i>v</i>		Z02	Z02	Z03	Z03
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung Stammdatenänderung vom EIV (verantwortlich) ausgehend mit DP		Übermittlung Stammdatenänderung vom (Anschluss-)NB (verantwortlich) ausgehend mit DP	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von	DP	NB (betroffener NB)	DP	NB (betroffener NB)
		an	EIV	DP	NB (ANB)	DP
required		v				

AcknowledgementDocument			Übermittlung von initialen Cluster-Ressourcen-Stammdaten zwischen NB mit DP		Übermittlung von initialen Cluster-Ressourcen Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (clusternder NB)	DP	NB (clusternder NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	A18	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>				
0..1	ReceivingDocumentType				
required	<i>v</i>		Z04	Z04	Z04
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument		SD Prozess- schritt [2]	Übermittlung von initialen Cluster- Ressourcen-Stammdaten zwischen NB mit DP		Übermittlung von initialen Cluster- Ressourcen Stammdaten zwischen NB ohne DP
Häufigkeit	Element/ Attribut		1	2	1
	von an		DP	NB (betroffener NB)	NB (betroffener NB)
			NB (clusternder NB)	DP	NB (clusternder NB)
required	v				

AcknowledgementDocument			Änderung der Cluster-Ressourcen-Stammdaten zwischen NB mit DP		Änderung der Cluster-Ressourcen-Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	NB (clusternder NB)
			NB (clusternder NB)	DP	NB (betroffener NB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	A18	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>				
0..1	ReceivingDocumentType				
required	<i>v</i>		Z04	Z04	Z04
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument			Änderung der Cluster-Ressourcen-Stammdaten zwischen NB mit DP		Änderung der Cluster-Ressourcen-Stammdaten zwischen NB ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	NB (clusternder NB)
		an	NB (clusternder NB)	DP	NB (betroffener NB)
required	v				

AcknowledgementDocument			Übermittlung von Nichtbeanspruchbarkeiten an NB mit DP		Übermittlung von marktbedingten Anpassungen an NB mit DP im Prognosemodell	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	EIV	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A27	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A76 A80	A76 A80	A67	A67
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung von Nichtbeanspruchbarkeiten an NB mit DP		Übermittlung von marktbedingten Anpassungen an NB mit DP im Prognosemodell	
SD Prozess- schritt [2]			1	2	1	2
Häufigkeit	Element/ Attribut	von	DP	NB (betroffener NB)	DP	NB (betroffener NB)
		an	EIV	DP	EIV	DP
required		v				

AcknowledgementDocument			Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	DP NB (anwNB)	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	SenderIdentification							
required	<i>v</i>		MP-ID DP	MP-ID EIV		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A39	A27		A39	Z01	A08
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID NB	MP-ID DP		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A18	A39		A18	A39	Z01
0..1	ReceivingDocumentIdentification							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentVersion							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	ReceivingPayloadName							
required	<i>v</i>							
0..1	DateTimeReceivingDocument							
required	<i>v</i>		x	x		x	x	x
0..unbounded	TimeSeriesRejection							
1..1	<i>xsd:sequence</i>							
1..1	SendersTimeSeriesIdentification							
required	<i>v</i>							
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
0..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							

AcknowledgementDocument			Abruf im Aufforderungsfall mit Delta-/Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/Attribut	von	DP	EIV	DP -> NB	DP	LF	BKV
		an	NB (anwNB)	DP	EIV	NB (anwNB)	DP	LF
required	v							

AcknowledgementDocument			Abruf im Duldungsfall mit Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/Attribut	von an	DP NB (anwNB)	EIV DP	DP -> NB EIV	BTR EIV	LF DP	BKV LF
required	<i>DtdVersion</i>		5	5		5	5	5
required	<i>DtdRelease</i>		1	1		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>							
1..1	DocumentIdentification							
required	<i>v</i>		x	x		x	x	x
1..1	DocumentDateTime							
required	<i>v</i>		x	x		x	x	x
1..1	SenderIdentification							
required	<i>v</i>		MP-ID DP	MP-ID EIV		MP-ID BTR	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole							
required	<i>v</i>		A39	A27		A21	Z01	A08
1..1	ReceiverIdentification							
required	<i>v</i>		MP-ID NB	MP-ID DP		MP-ID EIV	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole							
required	<i>v</i>		A18	A39		A27	A39	Z01
0..1	ReceivingDocumentIdentification							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentVersion							
required	<i>v</i>		x	x		x	x	x
0..1	ReceivingDocumentType							
required	<i>v</i>		A96	A96		A96	A96	A96
0..1	ReceivingPayloadName							
required	<i>v</i>							
0..1	DateTimeReceivingDocument							
required	<i>v</i>		x	x		x	x	x
0..unbounded	TimeSeriesRejection							
1..1	<i>xsd:sequence</i>							
1..1	SendersTimeSeriesIdentification							
required	<i>v</i>							
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
0..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText							
required	<i>v</i>		[5]	[5]		[5]	[5]	[5]
0..unbounded	TimeIntervalError							
1..1	<i>xsd:sequence</i>							
1..1	QuantityTimeInterval							
required	<i>v</i>							
1..unbounded	Reason							
1..1	<i>xsd:sequence</i>							
1..1	ReasonCode							
required	<i>v</i>							
0..1	ReasonText							

AcknowledgementDocument			Abruf im Duldungsfall mit Sollwertanweisung					
SD Prozessschritt [2]			1	2	3	4	5	6
Häufigkeit	Element/ Attribut	von	DP	EIV	DP -> NB	BTR	LF	BKV
		an	NB (anwNB)	DP	EIV	EIV	DP	LF
required	v							

AcknowledgementDocument			Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP NB (anfNB)	NB (anwNB) DP	DP NB (anwNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von	DP	NB (anwNB)	DP	NB (anfNB)
		an	NB (anfNB)	DP	NB (anwNB)	DP
required	v					

AcknowledgementDocument			Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB ohne DP	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/Attribut	von an	NB (anwNB)	NB (anfNB)
			NB (anfNB)	NB (anwNB)
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>		x	x
1..1	DocumentDateTime			
required	<i>v</i>		x	x
1..1	SenderIdentification			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>		A18	A18
1..1	ReceiverIdentification			
required	<i>v</i>		MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>		A18	A18
0..1	ReceivingDocumentIdentification			
required	<i>v</i>		x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>		x	x
0..1	ReceivingDocumentType			
required	<i>v</i>		A96	A41
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>		x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>		[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			

AcknowledgementDocument		Übermittlung des Abrufs einer steuerbaren Ressource an anweisenden NB ohne DP	
SD Prozessschritt [2]		1	2
Häufigkeit	Element/Attribut	von	NB (anfNB)
		an	NB (anfNB)
required	v		

AcknowledgementDocument			Abruf für eine Cluster-Ressource mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP NB (anfNB)	NB (cNB) DP	DP NB (cNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Abruf für eine Cluster-Ressource mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von	DP	NB (cNB)	DP	NB (anfNB)
		an	NB (anfNB)	DP	NB (cNB)	DP
required		v				

AcknowledgementDocument			Abruf für eine Cluster-Ressource ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	NB (cNB)	NB (anfNB)	DP	NB (anfB)
			NB (anfNB)	NB (cNB)	NB (cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A41	A42	A42
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Abruf für eine Cluster-Ressource ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von	NB (cNB)	NB (anfNB)	DP	NB (anfB)
		an	NB (anfNB)	NB (cNB)	NB (cNB)	DP
required		v				

AcknowledgementDocument		Aktualisierung der Abrufmeldung für den Abruf einer CR ohne DP
SD Prozess- schritt [2]		1
Häufigkeit	Element/ Attribut	von an
		NB (anfNB)
		NB (cNB)
required	<i>DtdVersion</i>	5
required	<i>DtdRelease</i>	1
optional	<i>DtdBDEWNachrichtenVersion</i>	1.0d
1..1	<i>xsd:sequence</i>	
1..1	DocumentIdentification	
required	<i>v</i>	x
1..1	DocumentDateTime	
required	<i>v</i>	x
1..1	SenderIdentification	
required	<i>v</i>	MP-ID DP
required	<i>codingScheme</i>	A10 NDE
1..1	SenderRole	
required	<i>v</i>	A18
1..1	ReceiverIdentification	
required	<i>v</i>	MP-ID NB
required	<i>codingScheme</i>	A10 NDE
1..1	ReceiverRole	
required	<i>v</i>	A18
0..1	ReceivingDocumentIdentification	
required	<i>v</i>	x
0..1	ReceivingDocumentVersion	
required	<i>v</i>	x
0..1	ReceivingDocumentType	
required	<i>v</i>	A42
0..1	ReceivingPayloadName	
required	<i>v</i>	
0..1	DateTimeReceivingDocument	
required	<i>v</i>	x
0..unbounded	TimeSeriesRejection	
1..1	<i>xsd:sequence</i>	
1..1	SendersTimeSeriesIdentification	
required	<i>v</i>	
0..unbounded	TimeIntervalError	
1..1	<i>xsd:sequence</i>	
1..1	QuantityTimeInterval	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	
required	<i>v</i>	
0..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText	
required	<i>v</i>	[5]
0..unbounded	TimeIntervalError	
1..1	<i>xsd:sequence</i>	
1..1	QuantityTimeInterval	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	

AcknowledgementDocument		Aktualisierung der Abrufückmeldung für den Abruf einer CR ohne DP	
		SD Prozess- schritt [2]	1
Häufigkeit	Element/ Attribut	von	NB (anfNB)
		an	NB (cNB)
required	v		

AcknowledgementDocument			Abruf für eine Steuergruppe mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/Attribut	von an	DP NB (anfNB)	NB (anwNB) DP	DP NB (anwNB)	NB (anfNB) DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A96	A41	A41
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Abruf für eine Steuergruppe mit DP			
SD Prozessschritt [2]			1	2	3	4
Häufigkeit	Element/ Attribut	von an	DP	NB (anwNB)	DP	NB (anfNB)
			NB (anfNB)	DP	NB (anwNB)	DP
required		v				

AcknowledgementDocument			Abruf für eine Steuergruppe ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SR und SG mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	NB (anwNB)	NB (anfNB)	DP	NB (anfNB)
			NB (anfNB)	NB (anwNB)	NB (anwNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A18	A18	A39
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A96	A41	A42	A42
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Abruf für eine Steuergruppe ohne DP		Aktualisierung der Abrufrückmeldung für den Abruf einer SR und SG mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von	NB (anwNB)	NB (anfNB)	DP	NB (anfNB)
		an	NB (anfNB)	NB (anwNB)	NB (anwNB)	DP
required		v				

AcknowledgementDocument		Aktualisierung der Abbrückmeldung für den Abruf einer SR und SG ohne DP
SD Prozess- schritt [2]		1
Häufigkeit	Element/ Attribut	von an
		NB (anfNB) NB (anwNB)
required	<i>DtdVersion</i>	5
required	<i>DtdRelease</i>	1
optional	<i>DtdBDEWNachrichtenVersion</i>	1.0d
1..1	<i>xsd:sequence</i>	
1..1	DocumentIdentification	
required	<i>v</i>	x
1..1	DocumentDateTime	
required	<i>v</i>	x
1..1	SenderIdentification	
required	<i>v</i>	MP-ID NB
required	<i>codingScheme</i>	A10 NDE
1..1	SenderRole	
required	<i>v</i>	A18
1..1	ReceiverIdentification	
required	<i>v</i>	MP-ID NB
required	<i>codingScheme</i>	A10 NDE
1..1	ReceiverRole	
required	<i>v</i>	A18
0..1	ReceivingDocumentIdentification	
required	<i>v</i>	x
0..1	ReceivingDocumentVersion	
required	<i>v</i>	x
0..1	ReceivingDocumentType	
required	<i>v</i>	A42
0..1	ReceivingPayloadName	
required	<i>v</i>	
0..1	DateTimeReceivingDocument	
required	<i>v</i>	x
0..unbounded	TimeSeriesRejection	
1..1	<i>xsd:sequence</i>	
1..1	SendersTimeSeriesIdentification	
required	<i>v</i>	
0..unbounded	TimeIntervalError	
1..1	<i>xsd:sequence</i>	
1..1	QuantityTimeInterval	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	
required	<i>v</i>	
0..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText	
required	<i>v</i>	[5]
0..unbounded	TimeIntervalError	
1..1	<i>xsd:sequence</i>	
1..1	QuantityTimeInterval	
required	<i>v</i>	
1..unbounded	Reason	
1..1	<i>xsd:sequence</i>	
1..1	ReasonCode	
required	<i>v</i>	
0..1	ReasonText	

AcknowledgementDocument		Aktualisierung der Abrufrückmeldung für den Abruf einer SR und SG ohne DP	
		SD Prozess- schritt [2]	1
Häufigkeit	Element/ Attribut	von	NB (anfNB)
		an	NB (anwNB)
required	v		

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell mit DP		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von an	DP	NB (betroffener NB)	DP	NB (betroffener NB)
			EIV	DP	NB (ANB/cNB)	DP
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A39	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A39
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		A14	A14	A14	A14
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung von Planungsdaten im Planwertmodell mit DP		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP	
SD Prozessschritt [2]			1	2	1	2
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)	DP	NB (betroffener NB)
		an	EIV	DP	NB (ANB/cNB)	DP
required		v				

AcknowledgementDocument		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP	Übermittlung von Sensitivitäten (1, 2) und angereicherten Sensitivitäten (3, 4) zu Planungsdaten für SR, SG und CR mit DP	
SD Prozessschritt [2]		1	1 und 3	2 und 4
Häufigkeit	Element/Attribut	von NB (betroffener NB)	DP	NB (direkt vorgef. NB) ÜNB
		an NB (ANB cNB)	NB (ANB vorgef. NB)	DP
required	<i>DtdVersion</i>	5	5	5
required	<i>DtdRelease</i>	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>	x	x	x
1..1	DocumentDateTime			
required	<i>v</i>	x	x	x
1..1	SenderIdentification			
required	<i>v</i>	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>	A18	A39	A18
1..1	ReceiverIdentification			
required	<i>v</i>	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>	A18	A18	A39
0..1	ReceivingDocumentIdentification			
required	<i>v</i>	x	x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>	x	x	x
0..1	ReceivingDocumentType			
required	<i>v</i>	A14	Z08	Z08
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>	x	x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>	[5]	[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP	Übermittlung von Sensitivitäten (1, 2) und angereicherten Sensitivitäten (3, 4) zu Planungsdaten für SR, SG und CR mit DP	
SD Prozessschritt [2]			1	1 und 3	2 und 4
Häufigkeit	Element/Attribut	von	NB (betroffener NB)	DP	NB (direkt vorgefNB ÜNB)
		an	NB (ANB cNB)	NB (ANB vorgefNB)	DP
required		v			

AcknowledgementDocument		Übermittlung von Sensitivitäten und angereicherten Sensitivitäten zu Planungsdaten für SR, SG und CR ohne DP	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP	
SD Prozessschritt [2]		1	1	2
Häufigkeit	Element/Attribut	NB (direkt vorgefNB ÜNB) NB (ANB vorgefNB)	DP NB (anfNB)	NB (betroffener NB) DP
required	<i>DtdVersion</i>	5	5	5
required	<i>DtdRelease</i>	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>	x	x	x
1..1	DocumentDateTime			
required	<i>v</i>	x	x	x
1..1	SenderIdentification			
required	<i>v</i>	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>	A18	A39	A18
1..1	ReceiverIdentification			
required	<i>v</i>	MP-ID NB	MP-ID NB	MP-ID DP
required	<i>codingScheme</i>	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>	A18	A18	A39
0..1	ReceivingDocumentIdentification			
required	<i>v</i>	x	x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>	x	x	x
0..1	ReceivingDocumentType			
required	<i>v</i>	Z08	Z09	Z09
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>	x	x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>	[5]	[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			

AcknowledgementDocument		Übermittlung von Sensitivitäten und angereicherten Sensitivitäten zu Planungsdaten für SR, SG und CR ohne DP	Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten mit DP	
SD Prozessschritt [2]		1	1	2
Häufigkeit	Element/Attribut	von	DP	NB (betroffener NB)
		an	NB (ANB vorge!NB)	DP
required	v			

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP	Übermittlung Flex-Beschränkung mit DP		Übermittlung Flex-Beschränkung ohne DP
SD Prozessschritt [2]			1	1	2	1
Häufigkeit	Element/Attribut	von an	NB (betroffener NB)	DP	NB (betroffener NB)	NB (betroffener NB)
			NB (anfNB)	NB [3]	DP	NB [3]
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A18	A39	A18	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID NB	MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A18	A18	A39	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z09	B15	B15	B15
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument			Übermittlung prognostizierter Abruf, Bedarf und Info über Abruf über Planungsdaten ohne DP	Übermittlung Flex-Beschränkung mit DP	Übermittlung Flex- Beschränkung ohne DP
SD Prozess- schritt [2]			1	1 2	1
Häufigkeit	Element/ Attribut	von an	NB (betroffener NB)	DP NB (betroffener NB)	NB (betroffener NB)
			NB (anfNB)	NB [3] DP	NB [3]
required	v				

AcknowledgementDocument			Übermittlung des Beschaffungsvorbehalts mit DP		Übermittlung des Beschaffungsvorbehalts ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB	NB
			NB (ÜNB)	DP	NB (ÜNB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	A18	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z06	Z06	Z06
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument			Übermittlung des Beschaffungsvorbehalts mit DP		Übermittlung des Beschaffungsvorbehalts ohne DP
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von	DP	NB	NB
		an	NB (ÜNB)	DP	NB (ÜNB)
required	v				

AcknowledgementDocument			Beschaffung energetischer Ausgleich bei Beschaffungsvorbehalt	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/Attribut	von an	DP	NB (ÜNB)
			NB	DP
required	<i>DtdVersion</i>		5	5
required	<i>DtdRelease</i>		1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d
1..1	<i>xsd:sequence</i>			
1..1	DocumentIdentification			
required	<i>v</i>		x	x
1..1	DocumentDateTime			
required	<i>v</i>		x	x
1..1	SenderIdentification			
required	<i>v</i>		MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	SenderRole			
required	<i>v</i>		A39	A18
1..1	ReceiverIdentification			
required	<i>v</i>		MP-ID NB	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE
1..1	ReceiverRole			
required	<i>v</i>		A18	A39
0..1	ReceivingDocumentIdentification			
required	<i>v</i>		x	x
0..1	ReceivingDocumentVersion			
required	<i>v</i>		x	x
0..1	ReceivingDocumentType			
required	<i>v</i>		Z07	Z07
0..1	ReceivingPayloadName			
required	<i>v</i>			
0..1	DateTimeReceivingDocument			
required	<i>v</i>		x	x
0..unbounded	TimeSeriesRejection			
1..1	<i>xsd:sequence</i>			
1..1	SendersTimeSeriesIdentification			
required	<i>v</i>			
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
0..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText			
required	<i>v</i>		[5]	[5]
0..unbounded	TimeIntervalError			
1..1	<i>xsd:sequence</i>			
1..1	QuantityTimeInterval			
required	<i>v</i>			
1..unbounded	Reason			
1..1	<i>xsd:sequence</i>			
1..1	ReasonCode			
required	<i>v</i>			
0..1	ReasonText			

AcknowledgementDocument			Beschaffung energetischer Ausgleich bei Beschaffungsvorbehalt	
SD Prozessschritt [2]			1	2
Häufigkeit	Element/Attribut	von an	DP	NB (ÜNB)
			NB	DP
required	v			

AcknowledgementDocument			Beschaffung energetischer Ausgleich bei Beschaffungsvorbeh alt ohne DP	Übermittlung von Planungsdaten im Planwertmodell (mit DP) [4]	
SD Prozess- schritt [2]			1	1	2
Häufigkeit	Element/ Attribut	von an	NB (ÜNB)	DP	NB (betroffener NB)
			NB	EIV	DP
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A18	A39	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID EIV	MP-ID DP
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A27	A39
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z07	Z05	Z05
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument		SD Prozessschritt [2]	Beschaffung energetischer Ausgleich bei Beschaffungsvorbehalt ohne DP	Übermittlung von Planungsdaten im Planwertmodell (mit DP) [4]	
Häufigkeit	Element/Attribut	von	1	1	2
		an	NB (ÜNB)	DP	NB (betroffener NB)
			NB	EIV	DP
required	v				

AcknowledgementDocument			Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP [4]		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP [4]
SD Prozessschritt [2]			1	2	1
Häufigkeit	Element/Attribut	von an	DP	NB	NB
			NB (ANB cNB)	DP	NB (ANB cNB)
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	A18	A18
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	A18
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z05	Z05	Z05
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR mit DP [4]		Übermittlung Planungsdaten für SR im Prognosemodell oder für SG, CR ohne DP [4]
SD Prozess- schritt [2]		1	2	1
Häufigkeit	Element/ Attribut	DP	NB	NB
von	an	NB (ANB cNB) DP		NB (ANB cNB)
required	v			

AcknowledgementDocument			Übermittlung von Probeplanungsdaten für die Prognosegüteprüfung mit DP		Übermittlung der Ergebnisse der Prognosegüteprüfung	Kommunikationstest zwischen Netzbetreibern
SD Prozessschritt [2]			1	2	3	1
Häufigkeit	Element/Attribut	von an	DP	NB (ANB)	EIV	NB (angefragter)
			EIV	DP	NB (ANB)	NB (angefragender)
required	<i>DtdVersion</i>		5	5	5	5
required	<i>DtdRelease</i>		1	1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>					
1..1	DocumentIdentification					
required	<i>v</i>		x	x	x	x
1..1	DocumentDateTime					
required	<i>v</i>		x	x	x	x
1..1	SenderIdentification					
required	<i>v</i>		MP-ID DP	MP-ID NB	MP-ID EIV	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole					
required	<i>v</i>		A39	A18	A27	A18
1..1	ReceiverIdentification					
required	<i>v</i>		MP-ID EIV	MP-ID DP	MP-ID NB	MP-ID NB
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole					
required	<i>v</i>		A27	A39	A18	A18
0..1	ReceivingDocumentIdentification					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentVersion					
required	<i>v</i>		x	x	x	x
0..1	ReceivingDocumentType					
required	<i>v</i>		Z11	Z11	Z12	A60
0..1	ReceivingPayloadName					
required	<i>v</i>					
0..1	DateTimeReceivingDocument					
required	<i>v</i>		x	x	x	x
0..unbounded	TimeSeriesRejection					
1..1	<i>xsd:sequence</i>					
1..1	SendersTimeSeriesIdentification					
required	<i>v</i>					
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
0..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText					
required	<i>v</i>		[5]	[5]	[5]	[5]
0..unbounded	TimeIntervalError					
1..1	<i>xsd:sequence</i>					
1..1	QuantityTimeInterval					
required	<i>v</i>					
1..unbounded	Reason					
1..1	<i>xsd:sequence</i>					
1..1	ReasonCode					
required	<i>v</i>					
0..1	ReasonText					

AcknowledgementDocument		Übermittlung von Probeplanungsdaten für die Prognosegüteprüfung mit DP		Übermittlung der Ergebnisse der Prognosegüteprüfung	Kommunikationstest zwischen Netzbetreibern
SD Prozessschritt [2]		1	2	3	1
Häufigkeit	Element/Attribut	DP	NB (ANB)	EIV	NB (angefragter)
	von an	EIV	DP	NB (ANB)	NB (anfragender)
required	v				

AcknowledgementDocument			Übermittlung von Stammdaten zu Bilanzkreisen für die Ausgleichsfahrpläne		
SD Prozessschritt [2]			1	2	3
Häufigkeit	Element/Attribut	von an	DP	LF	BKV
			NB (ANB)	DP	LF
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	Z01	A08
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	Z01
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z14	Z14	Z14
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument			Übermittlung von Stammdaten zu Bilanzkreisen für die Ausgleichsfahrpläne		
SD Prozess- schritt [2]			1	2	3
Häufigkeit	Element/ Attribut	von an	DP	LF	BKV
			NB (ANB)	DP	LF
required	v				

AcknowledgementDocument			Übermittlung Stammdatenänderung zu Bilanzkreisen für die Ausgleichsfahrpläne vom (Anschluss-)NB (verantwortlich) ausgehend		
SD Prozess- schritt [2]			1	2	3
Häufigkeit	Element/ Attribut	von an	DP	LF	BKV
			NB (ANB)	DP	LF
required	<i>DtdVersion</i>		5	5	5
required	<i>DtdRelease</i>		1	1	1
optional	<i>DtdBDEWNachrichtenVersion</i>		1.0d	1.0d	1.0d
1..1	<i>xsd:sequence</i>				
1..1	DocumentIdentification				
required	<i>v</i>		x	x	x
1..1	DocumentDateTime				
required	<i>v</i>		x	x	x
1..1	SenderIdentification				
required	<i>v</i>		MP-ID DP	MP-ID LF	MP-ID BKV
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	SenderRole				
required	<i>v</i>		A39	Z01	A08
1..1	ReceiverIdentification				
required	<i>v</i>		MP-ID NB	MP-ID DP	MP-ID LF
required	<i>codingScheme</i>		A10 NDE	A10 NDE	A10 NDE
1..1	ReceiverRole				
required	<i>v</i>		A18	A39	Z01
0..1	ReceivingDocumentIdentification				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentVersion				
required	<i>v</i>		x	x	x
0..1	ReceivingDocumentType				
required	<i>v</i>		Z14	Z14	Z14
0..1	ReceivingPayloadName				
required	<i>v</i>				
0..1	DateTimeReceivingDocument				
required	<i>v</i>		x	x	x
0..unbounded	TimeSeriesRejection				
1..1	<i>xsd:sequence</i>				
1..1	SendersTimeSeriesIdentification				
required	<i>v</i>				
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
0..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>		A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17	A01 A02 Z12 Z13 Z 14 Z15 Z16 Z17
0..1	ReasonText				
required	<i>v</i>		[5]	[5]	[5]
0..unbounded	TimeIntervalError				
1..1	<i>xsd:sequence</i>				
1..1	QuantityTimeInterval				
required	<i>v</i>				
1..unbounded	Reason				
1..1	<i>xsd:sequence</i>				
1..1	ReasonCode				
required	<i>v</i>				
0..1	ReasonText				

AcknowledgementDocument			Übermittlung Stammdatenänderung zu Bilanzkreisen für die Ausgleichsfahrpläne vom (Anschluss-)NB (verantwortlich) ausgehend		
SD Prozess- schritt [2]			1	2	3
Häufigkeit	Element/ Attribut	von	DP	LF	BKV
		an	NB (ANB)	DP	LF
required	v				

Fußnoten

Fußnote	Hinweis
[1]	gelöscht
[2]	Der Prozessschritt entspricht dem Prozessschritt des Dokumentes, für den ein ACK als Antwort übermittelt wird.
[3]	Netzbetreiber mit Engpass
[4]	In diesem Prozessschritt werden Kosten übermittelt.
[5]	Wenn im ReasonCode Z12 verwendet wurde: Im Falle eines erkannten Syntaxfehlers ist ein Fehlerbeschreibungstext zu übermitteln der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt. Wenn im ReasonCode Z12 nicht verwendet wurde: Im Falle eines negativen ACKs kann hier optional eine Fehlerbeschreibungstext übermittelt werden, der die Ablehnung begründet und eine schnelle Fehlerbehebung unterstützt.