

# Greedy Algorithms: Grouping Children

Michael Levin

Higher School of Economics

Algorithmic Toolbox  
Data Structures and Algorithms

# Outline

- 1 The Problem
- 2 Naive Algorithm
- 3 Efficient Algorithm



Many children came to a celebration.  
Organize them into the minimum possible  
number of groups such that the age of any  
two children in the same group differ by at  
most one year.

# Outline

- 1 The Problem
- 2 Naive Algorithm
- 3 Efficient Algorithm

## MinGroups( $C$ )

```
 $m \leftarrow \text{len}(C)$   
for each partition into groups  
 $C = G_1 \cup G_2 \cup \dots \cup G_k$ :  
    good  $\leftarrow$  true  
    for  $i$  from 1 to  $k$ :  
        if  $\max(G_i) - \min(G_i) > 1$ :  
            good  $\leftarrow$  false  
    if good:  
         $m \leftarrow \min(m, k)$   
return  $m$ 
```

# Running time

## Lemma

The number of operations in  $\text{MinGroups}(C)$  is at least  $2^n$ , where  $n$  is the number of children in  $C$ .

# Proof

# Proof

- Consider just partitions in two groups



## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$

## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$
- For each  $G_1 \subset C$ ,  $G_2 = C \setminus G_1$

## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$
- For each  $G_1 \subset C$ ,  $G_2 = C \setminus G_1$
- Size of  $C$  is  $n$

## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$
- For each  $G_1 \subset C$ ,  $G_2 = C \setminus G_1$
- Size of  $C$  is  $n$
- Each item can be included or excluded from  $G_1$

## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$
- For each  $G_1 \subset C$ ,  $G_2 = C \setminus G_1$
- Size of  $C$  is  $n$
- Each item can be included or excluded from  $G_1$
- There are  $2^n$  different  $G_1$

## Proof

- Consider just partitions in two groups
- $C = G_1 \cup G_2$
- For each  $G_1 \subset C$ ,  $G_2 = C \setminus G_1$
- Size of  $C$  is  $n$
- Each item can be included or excluded from  $G_1$
- There are  $2^n$  different  $G_1$
- Thus, at least  $2^n$  operations



# Asymptotics

- Naive algorithm works in time  $\Omega(2^n)$

# Asymptotics

- Naive algorithm works in time  $\Omega(2^n)$
- For  $n = 50$  it is at least

$$2^{50} = 1125899906842624$$

operations!



# Asymptotics

- Naive algorithm works in time  $\Omega(2^n)$
- For  $n = 50$  it is at least

$$2^{50} = 1125899906842624$$

operations!

- We will improve this significantly

# Outline

- ① The Problem
- ② Naive Algorithm
- ③ Efficient Algorithm

## Covering points by segments

**Input:** A set of  $n$  points  $x_1, \dots, x_n \in \mathbb{R}$ .

**Output:** The minimum number of segments of unit length needed to cover all the points.


# Example



# Example



# Example



Safe move: cover the leftmost point with a unit segment which starts in this point.



Safe move: cover the leftmost point with a unit segment which starts in this point.






Safe move: cover the leftmost point with a unit segment which starts in this point.



Safe move: cover the leftmost point with a unit segment which starts in this point.



Assume  $x_1 \leq x_2 \leq \dots \leq x_n$

**PointsCoverSorted( $x_1, \dots, x_n$ )**

$R \leftarrow \{\}, i \leftarrow 1$

while  $i \leq n$ :

$[\ell, r] \leftarrow [x_i, x_i + 1]$

$R \leftarrow R \cup \{[\ell, r]\}$

$i \leftarrow i + 1$

    while  $i \leq n$  and  $x_i \leq r$ :

$i \leftarrow i + 1$

return  $R$

## Lemma

The running time of `PointsCoverSorted` is  $O(n)$ .

## Lemma

The running time of `PointsCoverSorted` is  $O(n)$ .

## Proof

- $i$  changes from 1 to  $n$

## Lemma

The running time of `PointsCoverSorted` is  $O(n)$ .

## Proof

- $i$  changes from 1 to  $n$
- For each  $i$ , at most 1 new segment

## Lemma

The running time of `PointsCoverSorted` is  $O(n)$ .

## Proof

- $i$  changes from 1 to  $n$
- For each  $i$ , at most 1 new segment
- Overall, running time is  $O(n)$



# Total Running Time

- `PointsCoverSorted` works in  $O(n)$  time



# Total Running Time

- `PointsCoverSorted` works in  $O(n)$  time
- Sort  $\{x_1, x_2, \dots, x_n\}$ , then call `PointsCoverSorted`

# Total Running Time

- `PointsCoverSorted` works in  $O(n)$  time
- Sort  $\{x_1, x_2, \dots, x_n\}$ , then call `PointsCoverSorted`
- Soon you'll learn to sort in  $O(n \log n)$

# Total Running Time

- `PointsCoverSorted` works in  $O(n)$  time
- Sort  $\{x_1, x_2, \dots, x_n\}$ , then call `PointsCoverSorted`
- Soon you'll learn to sort in  $O(n \log n)$
- Sort + `PointsCoverSorted` is  $O(n \log n)$

# Asymptotics

- Straightforward solution is  $\Omega(2^n)$

# Asymptotics

- Straightforward solution is  $\Omega(2^n)$
- Very long for  $n = 50$

# Asymptotics

- Straightforward solution is  $\Omega(2^n)$
- Very long for  $n = 50$
- Sort + greedy is  $O(n \log n)$

# Asymptotics

- Straightforward solution is  $\Omega(2^n)$
- Very long for  $n = 50$
- Sort + greedy is  $O(n \log n)$
- Fast for  $n = 10\,000\,000$

# Asymptotics

- Straightforward solution is  $\Omega(2^n)$
- Very long for  $n = 50$
- Sort + greedy is  $O(n \log n)$
- Fast for  $n = 10\,000\,000$
- Huge improvement!



# Conclusion

- Straightforward solution is exponential
- Important to reformulate the problem in mathematical terms
- Safe move is to cover leftmost point
- Sort in  $O(n \log n)$  + greedy in  $O(n)$