

AAA Digital Platform — Data Dictionary

Version 3.0 · 11 May 2026 · Confidential — Ambitious about Autism

Database schema reference for every Prisma model used by the Next.js 14 application deployed at `asd-training-app-v2.vercel.app`. Database backend: Neon PostgreSQL accessed via Prisma ORM.

This document is regenerated from markdown via `npm run handover:build` — see `docs/handover/README.md` for the build process.

Changes since v2.0 (4 May 2026): Added Cohort (modelled as `Organisation` rows with `orgType = COHORT`), `CohortMembership`, `CohortEventbriteEvent`, `BrandAsset`, `OAuthSsoConfig`, `LibrarySection`, `SamlAuthnRequest`, toolkit models (`ToolkitRegistrant`, `ToolkitDownload`, `ToolkitAnonymousDocumentEvent`). Flagged `pendingApproval` columns as deprecated (still on schema, no longer read/written).

1. Database Overview

Environment	URL type	Notes
Production	Pooler (port 6543)	<code>pgbouncer=true</code> required — use <code>DATABASE_URL</code>
Production migrations	Direct (port 5432)	Used by Prisma CLI only — use <code>DIRECT_URL</code>
Development	Neon dev branch pooler	Endpoint <code>ep-lucky-cherry-a8toqlw5</code> ; pulled via <code>vercel env pull .env.local</code>

Prisma accessor gotchas:

- Model `ClassSession` → accessor `prisma.classSession` — avoids collision with NextAuth `Session` table.
- `Child` / `Observation` / `AiInsight` / `ObservationAccessLog` were removed in commit `8968cf0` (21 April 2026). Do not reference them.

3. `CV` / `CVWorkExperience` / `CVEducation` / `CVSkill` / `CVReference` / `CareerAdvisorSession` were removed in July 2026 with the CV Builder and Careers Advisor features. Their specifications and AI prompts are preserved in `docs/archive/retired-feature-specs.md` if either is ever rebuilt.
4. `HomePage` is keyed by `id`, not by role. The platform default uses the fixed id `'default'`; a row with an `organisationId` overrides it for that organisation's members.

2. Core Models

User

Field	Type	Nulla ble	Description
id	String (UUID)	No	Primary key
email	String	No	Unique — used for login
name	String	Yes	
password	String	Yes	bcrypt hash (cost 12). Null for SSO-only users.
role	Role enum	No	<code>SUPER_ADMIN</code> / <code>CHARITY_EMPLOYEE</code> / <code>ORG_ADMIN</code> / <code>LEARNER</code>
organisationId	String	Yes	FK → Organisation; SET NULL on org delete
active	Boolean	No	Default true. Deactivated users cannot sign in.
pendingApproval	Boolean	No	Deprecated (May 2026). Column retained; not read or written by current code. Always written as false on new rows.
mustChangePassword	Boolean	No	Forces <code>/change-password</code> redirect via middleware
totpSecret	String	Yes	Encrypted TOTP secret for MFA
totpEnabled	Boolean	No	True once MFA setup is complete
charityPermissions	String[]	No	Scoped permissions for <code>CHARITY_EMPLOYEE</code> role; <code>SUPER_ADMIN</code> has all implicitly

notificationsLastOpenedAt	DateTime	Yes	Unread-badge timestamp on the bell icon
invitedAt / invitedBy	DateTime / String	Yes	Invite audit metadata
createdAt / updatedAt	DateTime	No	Auto-managed

Organisation

Field	Type	Null able	Description
id	String	No	Primary key
name	String	No	
slug	String	No	Unique URL identifier
organisationType	Enum	Yes	SCHOOL / COLLEGE / ACADEMY / UNIVERSITY / EMPLOYER (+ legacy EDUCATION / BUSINESS)
orgType	Enum	No	ORGANISATION or COHORT (cohorts share the same table)
allowedProgramIds	String[]	No	IDs of TrainingProgram records the org can access
allowedRoles	Role[]	No	Roles that can be assigned within this org
active	Boolean	No	
pendingApproval	Boolean	No	Deprecated (May 2026). See User notes.
logoUrl	String	Yes	Vercel Blob URL
parentOrgId / isParentOrg / inheritSettings	String / Boolean / Boolean	mix	Single-level org hierarchy
contactName / contactEmail / contactPhone	String	Yes	Primary contact details
addressLine1 / addressLine2 / city / county / postcode / country	String	Yes	UK postal address fields
createdAt / updatedAt	DateTime	No	Auto-managed

Account (SSO linking)

Field	Type	Nullable	Description
id	String	No	Primary key
userId	String	No	FK → User
provider	String	No	google / azure-ad / credentials
providerAccountId	String	No	ID from the OAuth provider
type	String	No	oauth / credentials
createdAt	DateTime	No	Auto-set

Unique constraint on (provider, providerAccountId) . Account rows are created manually in the NextAuth signIn callback — no PrismaAdapter is used.

CohortMembership

Adds learners to an Organisation row whose orgType is COHORT . Lets the platform manage walk-in / event / public cohorts without polluting the registered-orgs list.

Field	Type	Nullable	Description
id	String	No	Primary key
organisationId	String	No	FK → Organisation (where orgType = COHORT)
userId	String	No	FK → User
status	Enum	No	ACTIVE / INACTIVE
joinedAt	DateTime	No	
sourceEventId	String	Yes	Optional FK → CohortEventbriteEvent if imported from Eventbrite

Unique constraint on (organisationId, userId) .

CohortEventbriteEvent

Records that a cohort was imported (or refreshed) from an Eventbrite event. Used to dedupe imports and surface a "synced from Eventbrite" badge in the admin UI.

Field	Type	Description
id	String	Primary key
organisationId	String	FK → Organisation (cohort row)
eventbriteEventId	String	Eventbrite event id
importedAt	DateTime	When the import ran
importedById	String	FK → User (admin who triggered the import)

OAuthSsoConfig

Single-row config that gates the Google / Microsoft SSO buttons on the login page. Replaced the `ENABLE_OAUTH_SSO` env switch in May 2026.

Field	Type	Default	Description
id	String	—	Primary key
googleEnabled	Boolean	false	Show Google button & accept Google sign-ins
microsoftEnabled	Boolean	false	Show Microsoft button & accept Microsoft sign-ins
updatedAt	DateTime	—	Auto-managed

The `signIn` callback re-checks this row on every OAuth sign-in so direct hits on `/api/auth/signin/google` are rejected when the toggle is off, even though the provider is registered with NextAuth.

3. Training Models

TrainingProgram

Field	Type	Nullable	Description
id	String	No	Primary key

name	String	No	e.g. "ASD Awareness Training"
description	Text	Yes	Rich HTML (sanitised)
order	Int	No	Display sort order
status	Enum	No	DRAFT / UNDER_REVIEW / APPROVED / ARCHIVED
version	String	No	Default "1.0"
audience	Enum	No	ASD_PRACTITIONER / CAREERS
active	Boolean	No	
createdAt / updatedAt	DateTime	No	Auto-managed

Module

Field	Type	Nullable	Description
id	String	No	Primary key
title	String	No	
description	Text	Yes	Rich HTML
order	Int	No	Sort order within program
active	Boolean	No	
programId	String	No	FK → TrainingProgram (CASCADE delete)
createdAt / updatedAt	DateTime	No	Auto-managed

Lesson

Field	Type	Nullable	Description
id	String	No	Primary key
title	String	No	
type	Enum	No	TEXT / VIDEO / SCORM
order	Int	No	Sort order within module

content	Text	Yes	HTML (sanitised via <code>sanitize-html</code>). Used for TEXT lessons
videoUrl	String	Yes	Embed URL for VIDEO lessons
transcript	Text	Yes	Plain-text transcript for TTS fallback
interactiveBlocks	Json	Yes	Hotspot, carousel, video-embed blocks — see <code>lib/interactive-blocks.ts</code>
moduleId	String	No	FK → Module (CASCADE delete)
active	Boolean	No	
scormBlobPrefix	String	Yes	Vercel Blob path prefix for SCORM assets
scormEntryPath	String	Yes	Relative path to the SCORM launch file
scormVersion	String	Yes	<code>"1.2"</code> / <code>"2004"</code>
scormToc	Json	Yes	Parsed <code><organization><item></code> tree for multi-SCO navigation
createdAt / updatedAt	DateTime	No	Auto-managed

QuizQuestion

Field	Type	Nullable	Description
id	String	No	Primary key
question	Text	No	
options	Json	No	Array of answer strings
correctAnswer	String	No	Must match one entry in <code>options</code>
explanation	Text	Yes	Shown after answering
lessonId	String	No	FK → Lesson (CASCADE delete)
order	Int	No	Sort order

TrainingProgress

Field	Type	Nullable	Description
-------	------	----------	-------------

id	String	No	Primary key
userId	String	No	FK → User (CASCADE delete)
moduleId	String	No	Module ID string
lessonId	String	No	Lesson ID string
completed	Boolean	No	
score	Float	Yes	0–100 percentage
interactionData	Json	Yes	SCORM CMI snapshot; <code>navLocation</code> for resume; interactive-block interactions
completedAt	DateTime	Yes	

Unique constraint on `(userId, moduleId, lessonId)` .

LessonAttachment

Field	Type	Description
id	String	Primary key
lessonId	String	FK → Lesson (CASCADE delete)
name	String	Display filename
url	String	Vercel Blob URL
mimeType	String	
sizeBytes	Int?	
createdAt	DateTime	

LessonNote

Field	Type	Description
id	String	Primary key
userId	String	FK → User
lessonId	String	

content	Text	Learner personal notes — plain text
updatedAt	DateTime	

Unique constraint on `(userId, lessonId)`.

4. Sessions, Announcements, Reset Tokens

ClassSession

Always use `prisma.classSession` — NOT `prisma.session` (that's the NextAuth `Session` table).

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
organisationId	String	No	FK → Organisation (the host org or charity)
hostId	String	Yes	FK → User (session host)
dateTime	DateTim e	No	UTC start time
durationMinutes	Int	No	
platform	Enum	No	<code>ZOOM</code> / <code>TEAMS</code> / <code>CUSTOM</code>
meetingUrl	String	Yes	Pasted or auto-generated join link
status	Enum	No	<code>SCHEDULED</code> / <code>IN_PROGRESS</code> / <code>COMPLETED</code> / <code>CANCELLED</code>
recordingUrl	String	Yes	Added after session completes
notes	Text	Yes	
isCharitySession	Boolean	No	True for charity-level workshops
createdAt / updatedAt	DateTim e	No	Auto-managed

SessionAttendee

Field	Type	Description
id	String	Primary key
sessionId	String	FK → ClassSession (CASCADE delete)
userId	String	FK → User
attended	Boolean	Default false; toggled by host
invitedAt	DateTime	Auto-set at record creation

Unique constraint on (sessionId, userId) .

Announcement

Field	Type	Description
id	String	Primary key
title	String	
body	Text	Rich HTML content
organisationId	String?	Null = global announcement visible to all
targetRoles	Role[]	Empty = all roles
expiresAt	DateTime?	Hidden after this date
createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

PasswordResetToken

Used for both password reset (1h expiry) and welcome / magic-link self-registration (24h expiry).

Field	Type	Description
id	String	Primary key
userId	String	FK → User
token	String	Unique SHA-256 hashed at rest (<code>lib/reset-token.ts</code>). Single-use.

expiresAt	DateTime	
usedAt	DateTime?	Set on redemption; second use rejected
createdAt	DateTime	

5. Survey Models

Survey

Field	Type	Description
id	String	Primary key
title	String	
description	Text?	
status	Enum	DRAFT / PUBLISHED / CLOSED
createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

SurveyQuestion

Field	Type	Description
id	String	Primary key
surveyId	String	FK → Survey (CASCADE delete)
type	Enum	MULTIPLE_CHOICE / YES_NO / FREE_TEXT / RATING_SCALE / MULTI_SELECT
text	Text	Question text
options	Json?	Array of option strings; required for MULTIPLE_CHOICE and MULTI_SELECT
order	Int	Sort order

SurveyTarget, SurveyResponse, SurveyAnswer, SurveyInsight

- **SurveyTarget** — { surveyId, targetType (ORG|ROLE), targetValue } . Determines which orgs / roles see a survey.
- **SurveyResponse** — one row per respondent per survey. Respondent identity is pseudonymised with a per-survey key (security-audit hardening, May 2026) so a respondent cannot be cross-referenced across surveys.
- **SurveyAnswer** — one row per question in a response.
- **SurveyInsight** — AI-generated analysis. { surveyId, type (SUMMARY | COMPARATIVE | RECOMMENDATIONS), content } .

All cascade on Survey delete.

6. Document Library

LibraryCollection

Field	Type	Description
id	String	Primary key
title	String	
description	Text?	
targetOrgIds	String[]	Orgs that can see this collection
targetRoles	Role[]	Roles that can see this collection
thumbnailUrl	String?	AI-generated thumbnail on Vercel Blob
createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

LibrarySection

Optional sub-grouping inside a collection. Added April 2026.

Field	Type	Description
id	String	Primary key

collectionId	String	FK → LibraryCollection (CASCADE delete)
title	String	
order	Int	Display order

LibraryDocument

Field	Type	Description
id	String	Primary key
collectionId	String	FK → LibraryCollection (CASCADE delete)
sectionId	String ?	FK → LibrarySection (optional grouping)
name	String	Display filename
url	String	Vercel Blob URL. Served via auth-gated proxy /api/library/documents/[docId]/file — never linked directly.
mimeType	String	
sizeBytes	Int	
order	Int	Sort order within section or collection
createdAt	DateTime	

LibraryDocumentEvent

Field	Type	Description
id	String	Primary key
documentId	String	FK → LibraryDocument (CASCADE delete)
userId	String	FK → User
organisationId	String	Denormalised for reporting
eventType	Enum	VIEW / DOWNLOAD
createdAt	DateTime	

7. Jobs Models

JobOpening

Field	Type	Description
id	String	Primary key
title	String	
employerName	String	
description	Text	Rich HTML
locationType	Enum	ONSITE / HYBRID / REMOTE
employmentType	Enum	INTERNSHIP / APPRENTICESHIP / PART_TIME / FULL_TIME / VOLUNTEER
status	Enum	DRAFT / PUBLISHED / CLOSED / ARCHIVED
closingDate	DateTime?	Auto-closes past this date (lib/jobs.ts)
autismFriendlyNotes	Text?	
skills	String[]	Tag strings
targetOrgIds	String[]	Visibility: restrict to these orgs
targetRoles	Role[]	Visibility: restrict to these roles
logoUrl	String?	Employer logo on Vercel Blob
createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

JobAttachment

Field	Type	Description
id	String	Primary key
jobId	String	FK → JobOpening (CASCADE delete)

name	String	
url	String	Vercel Blob URL — served via auth-gated proxy <code>/api/jobs/[jobId]/attachments/[attachmentId]/file</code>
mimeType	String	
sizeBytes	Int	
createdAt	DateTime	

JobAssignment

Field	Type	Description
id	String	Primary key
jobId	String	FK → JobOpening (CASCADE delete)
userId	String	FK → User (target learner)

Unique constraint on `(jobId, userId)`.

8. AI & Integration

AiPrompt

Field	Type	Description
id	String	Primary key
key	String	Unique string key used by <code>runPrompt(key, values)</code>
name	String	Human-readable name shown in admin UI
purpose / category / tone	Text / String / String	Metadata
requirements	String[]	Bullet-point requirements prepended to prompt
inputVariables	String[]	Expected <code>{{variable}}</code> placeholders

responseFormat	Text	Instructions for the model output format
model	String	Provider/model string e.g. <code>google/gemini-2.5-flash</code>
defaultFields	Json?	Fallback seed values for <code>inputVariables</code>
previousFields	Json?	Undo buffer — last saved values
createdAt / updatedAt	DateTime	Auto-managed

AiPromptContextFile

Field	Type	Description
id	String	Primary key
promptId	String	FK → AiPrompt (CASCADE delete)
filename	String	
url	String	Vercel Blob URL
mimeType	String	<code>application/pdf</code> / <code>application/vnd.openxmlformats...</code> / <code>text/plain</code>
sizeBytes	Int	
parsedText	Text?	Extracted text prepended to the prompt at runtime
createdAt	DateTime	

IntegrationApiKey

Field	Type	Description
id	String	Primary key
name	String	Friendly label
keyHash	String	SHA-256 hash of the raw key — raw key never stored
keyPrefix	String	First chars for display (e.g. <code>"rw_abc12"</code>)
expiresAt	DateTime?	
lastUsedAt	DateTime?	Updated on every successful API call

createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

The raw API key is displayed only once on creation and then discarded. Authentication on `/api/integrations/reports` uses Bearer token; the handler hashes the incoming token and compares against `keyHash`.

BrandAsset

Charity-owned brand assets (logos, banners, illustrations). Used by the AI banner-generation feature and the library/AI Assist tools as context.

Field	Type	Description
id	String	Primary key
type	Enum	<code>BrandAssetType</code> — <code>LOGO</code> / <code>BANNER</code> / <code>ICON</code> / <code>ILLUSTRATION</code> / <code>OTHER</code>
name	String	Display name
url	String	Vercel Blob URL
mimeType	String	
sizeBytes	Int	
description	Text?	
aiTags	String[]	Auto-generated tags for AI context lookups
createdById	String	FK → User
createdAt / updatedAt	DateTime	Auto-managed

SSO & Meeting Config

- **OrgSsoConfig** — per-org SAML 2.0. Fields: `emailDomain`, `ssoUrl`, `entityId`, `certificate` (X.509 PEM), `autoProvision`, `defaultRole`. One row per org.
- **CharitySsoConfig** — charity-level SAML. Same fields plus `enforceForCharityUsers` (forces all charity employees through SSO). Managed at `/super-admin/settings/sso`.

- **OAuthSsoConfig** — see §2. Single-row toggle for Google + Microsoft OAuth.
- **SamlAuthnRequest** — short-lived (5 min) record of an outbound SAML AuthnRequest. Used by the callback to verify InResponseTo and prevent SAML replay attacks.
- **OrgMeetingConfig** — per-org Zoom or Microsoft Teams API credentials for auto-generating meeting links on **ClassSession** creation. Fields: **provider** (ZOOM | TEAMS), **clientId**, **clientSecret**, **accountId** (Zoom), **tenantId** (Teams). Managed at **/admin/settings/meetings**.
- **CharityMeetingConfig** — charity-level equivalent. Used for charity-wide workshops (**isCharitySession = true**).

Public toolkit models (anonymous downloads)

- **ToolkitRegistrant** — captures email + name when a visitor downloads from the public toolkit without an account. Used for follow-up communications.
- **ToolkitDownload** — per-document download event linked to a **ToolkitRegistrant**.
- **ToolkitAnonymousDocumentEvent** — view/download event with no registrant attached (anonymous metric only).

9. Key Relationships

Parent model	Relationship	Child model	Foreign key	On delete
Organisation	1 : many	User	organisationId	SET NULL
Organisation	1 : many	CohortMembership	organisationId	CASCADE
Organisation	1 : many	Organisation (self-ref)	parentOrgId	SET NULL
TrainingProgram	1 : many	Module	programId	CASCADE
Module	1 : many	Lesson	moduleId	CASCADE
Lesson	1 : many	QuizQuestion	lessonId	CASCADE
Lesson	1 : many	LessonAttachment	lessonId	CASCADE
User	1 : many	TrainingProgress	userId	CASCADE
User	1 : many	LessonNote	userId	CASCADE
ClassSession	1 : many	SessionAttendee	sessionId	CASCADE

Survey	1 : many	SurveyQuestion	surveyId	CASCADE
Survey	1 : many	SurveyTarget	surveyId	CASCADE
Survey	1 : many	SurveyResponse	surveyId	CASCADE
LibraryCollection	1 : many	LibrarySection	collectionId	CASCADE
LibraryCollection	1 : many	LibraryDocument	collectionId	CASCADE
LibraryDocument	1 : many	LibraryDocumentEvent	documentId	CASCADE
Organisation	1 : many	JobOpening	organisationId	CASCADE
Organisation	1 : 1	HomePage	organisationId	CASCADE
JobOpening	1 : many	JobAttachment	jobId	CASCADE
JobOpening	1 : many	JobAssignment	jobId	CASCADE
AiPrompt	1 : many	AiPromptContextFile	promptId	CASCADE

10. Sample Prisma Queries

1. Get user with their organisation:

```
const user = await prisma.user.findUnique({
  where: { email },
  include: { organisation: true }
})
```

2. Get training progress for a user:

```
const progress = await prisma.trainingProgress.findMany({
  where: { userId },
  orderBy: { completedAt: 'desc' }
})
```

3. Get sessions for an organisation:

```
const sessions = await prisma.classSession.findMany({
  where: { organisationId },
  include: { attendees: { include: { user: true } } }
})
```

4. Get the job openings visible to a learner (both tiers):

```
// Charity tier: organisationId null, optionally narrowed by
// targetOrgIds.
// Organisation tier: owned by the learner's org, or by its parent.
const jobs = await prisma.jobOpening.findMany({
  where: {
    status: 'PUBLISHED',
    OR: [
      {
        organisationId: null,
        OR: [{ targetOrgIds: { isEmpty: true } }, { targetOrgIds: {
has: organisationId } }]
      },
      { organisationId: { in: [organisationId,
parentOrgId].filter(Boolean) } }
    ]
  },
  include: { attachments: true, assignments: { where: { userId } } }
})
```

5. Resolve cohort members through CohortMembership:

```
const members = await prisma.user.findMany({
  where: {
    cohortMemberships: {
      some: { organisationId: cohortId, status: 'ACTIVE' }
    },
    active: true
  }
})
```

6. Upsert training progress (used by **POST /api/training/progress**):

```
await prisma.trainingProgress.upsert({
  where: { userId_moduleId_lessonId: { userId, moduleId, lessonId } },
  update: { completed: true, completedAt: new Date() },
  create: { userId, moduleId, lessonId, completed: true,
    completedAt: new Date() }
})
```

11. External Integrations

Service	Used for	Auth method	Env var(s)
Neon PostgreSQL	Primary database	Connection string	DATABASE_URL , DIRECT_URL
Vercel Blob	File storage (docs, images, SCORM, TTS, job attachments, brand assets)	Token	BLOB_READ_WRITE_TOKEN
Vercel AI Gateway	AI features routing (multi-provider)	API key	AI_GATEWAY_API_KEY
Eleven Labs	Text-to-speech — Lily voice (pFZP5JQG7iQjIQuC4Bku); MP3s cached at	API key	ELEVENLABS_API_KEY

	<code>tts/<voiceId>/<sha256>.mp3</code>		
Resend	Transactional email (welcome links, password reset, invites, digests)	API key	<code>RESEND_API_KEY</code>
Google OAuth	Optional Google SSO sign-in	Client credentials	<code>GOOGLE_CLIENT_ID</code> , <code>GOOGLE_CLIENT_SECRET</code>
Azure AD	Optional Microsoft SSO sign-in	Client credentials	<code>AZURE_AD_CLIENT_ID</code> , <code>AZURE_AD_CLIENT_SECRET</code> , <code>AZURE_AD_TENANT_ID</code>
Eventbrite	Optional cohort import source	OAuth (org-scoped)	Configured at <code>/super-admin/settings/eventbrite</code>
Stripe	Payments layer (gated by <code>ENABLE_PAYMENTS</code>)	Secret key + webhook	<code>STRIPE_SECRET_KEY</code> , <code>STRIPE_PUBLISHABLE_KEY</code> , <code>STRIPE_WEBHOOK_SECRET</code> , <code>STRIPE_SUBSCRIPTION_PRICE_YEARLY</code>

Available provider/model strings (`lib/ai-models.ts`): `google/gemini-2.5-flash` (default), `google/gemini-2.5-pro` , `anthropic/claude-sonnet-4` , `anthropic/claude-haiku-4` , `openai/gpt-4o-mini` , `openai/gpt-4.1` . Callers use `runPrompt(key, values)` from `lib/ai-runner.ts` . On missing prompt row or upstream error the runner returns the sentinel `AI_FEATURE_UNAVAILABLE` — callers must handle that.