

AAA Digital Platform — Technical Setup Guide

Version 2.0 · 11 May 2026 · Ambitious about Autism

Developer and DevOps reference for setup, deployment, and operation of the AAA Digital Platform.

Changes since v1.0: Added Eventbrite cohort integration env vars, brand-asset upload notes, and an updated CSP table that reflects the May 2026 client-direct Blob upload changes. Removed the `ENABLE_OAUTH_SSO` env variable — OAuth is now toggled in the admin UI (`OAuthSsoConfig` table).

1. Architecture Overview

Layer	Technology	Hosted at
Frontend & API	Next.js 14 App Router, TypeScript	Vercel (<code>asd-training-app-v2</code>)
Database	PostgreSQL, Prisma ORM	Neon (pooler port 6543)
Authentication	NextAuth v4 JWT sessions, TOTP MFA	In-app
File storage	Vercel Blob	Vercel
AI features	Vercel AI Gateway → Gemini / Claude / GPT	Vercel
Text-to-speech	ElevenLabs API (Lily voice, cached to Blob)	ElevenLabs
Email	Resend API (transactional)	Resend
Payments	Stripe (<code>ENABLE_PAYMENTS=false</code> in prod by default)	Stripe
Cohort import (optional)	Eventbrite	Eventbrite

Route groups: `(auth)` → public login / register / reset; `(dashboard)` → leaf roles; `(org-admin)` → `ORG_ADMIN`; `(super-admin)` → `SUPER_ADMIN` / `CHARITY_EMPLOYEE`; `(mfa)` → MFA flow; `(change-password)` → forced change.

Auth flow: credentials / OAuth / SAML → JWT callback extends token (`id` , `role` , `organisationId` , `mustChangePassword` , `totpEnabled` , `mfaPending` , `hasPassword` , `effectivePrograms` , `charityPermissions` , `isParentOrg`) → session callback → middleware checks role / MFA / password.

2. Prerequisites

Tool	Version	Purpose
Node.js	18+ (20 LTS recommended)	Runtime
npm	9+	Package management
Git	Any recent version	Source control
Stripe CLI	Latest	Local webhook forwarding (optional)
Playwright	Installed via npm	E2E testing

External service accounts required: Vercel, Neon, GitHub, Resend, ElevenLabs. **Optional:** Google Cloud (Google SSO), Azure AD (Microsoft SSO), Eventbrite (cohort import), Stripe (payments).

3. Repository Setup

```
git clone https://github.com/Hodgy007/asd-training-app.git
cd asd-training-app
npm install
```

Script	Command	Purpose
<code>dev</code>	<code>npm run dev</code>	Start dev server on <code>localhost:3000</code>
<code>build</code>	<code>npm run build</code>	<code>prisma generate</code> + Vitest + <code>next build</code>
<code>test</code>	<code>npm run test</code>	Run Vitest unit tests
<code>test:e2e</code>	<code>npm run test:e2e</code>	Run Playwright E2E tests
<code>prisma:push</code>	<code>npm run prisma:push</code>	Push schema to database

<code>prisma:studio</code>	<code>npm run prisma:studio</code>	Open Prisma Studio
<code>prisma:seed</code>	<code>npm run prisma:seed</code>	Seed demo users
<code>prisma:generate</code>	<code>npm run prisma:generate</code>	Regenerate Prisma client after schema changes
<code>handover:build</code>	<code>npm run handover:build</code>	Rebuild all handover PDFs from markdown sources

4. Key Directory Structure

Path	Purpose
<code>app/(auth)/</code>	Login, register, forgot-password, reset-password, welcome, sso-complete (all public)
<code>app/(dashboard)/</code>	Leaf-role pages (dashboard, training, cv-builder, careers-advisor, jobs, etc.)
<code>app/(org-admin)/</code>	Org admin pages (<code>/admin/*</code>)
<code>app/(super-admin)/</code>	Super admin pages (<code>/super-admin/*</code>)
<code>app/(mfa)/</code>	MFA setup and verify pages
<code>app/api/</code>	All API route handlers
<code>components/</code>	Shared React components
<code>lib/</code>	Server-side utilities, AI runner, auth helpers, RBAC, rate limit, sanitisers
<code>prisma/</code>	<code>schema.prisma</code> , <code>seed.ts</code>
<code>types/</code>	TypeScript type extensions (session, next-auth)
<code>middleware.ts</code>	Route protection, MFA enforcement, role redirects
<code>public/</code>	Static assets (logo, favicon)
<code>docs/guides/</code>	User-facing markdown guides (source of truth for handover PDFs)
<code>docs/handover/</code>	Handover PDFs + their markdown sources + build tooling
<code>scripts/</code>	Build/maintenance scripts (e.g. <code>build-handover-pdfs.mjs</code>)

5. Environment Variables

Critical: `DATABASE_URL` must use the Neon **pooler** URL (port 6543) in production. Using the direct URL (port 5432) will exhaust connection limits on serverless.

Variable	Required	Description
<code>DATABASE_URL</code>	Yes	Neon pooler — port 6543 with <code>?pgbouncer=true</code>
<code>DIRECT_URL</code>	Yes	Neon direct — port 5432, Prisma migrations only
<code>NEXTAUTH_SECRET</code>	Yes	32+ char random secret: <code>openssl rand -base64 32</code>
<code>NEXTAUTH_URL</code>	Yes	Production URL, no trailing slash
<code>AI_GATEWAY_API_KEY</code>	Yes	Vercel AI Gateway key (multi-provider AI)
<code>RESEND_API_KEY</code>	Yes	Transactional email
<code>BLOB_READ_WRITE_TOKEN</code>	Yes	Vercel Blob file storage
<code>ELEVENLABS_API_KEY</code>	Yes	Text-to-speech (Lily voice)
<code>EMAIL_LOGO_URL</code>	Optional	Override AAA logo URL in transactional emails
<code>GOOGLE_CLIENT_ID</code>	Optional	Google OAuth button hidden if absent
<code>GOOGLE_CLIENT_SECRET</code>	Optional	Google OAuth client secret
<code>AZURE_AD_CLIENT_ID</code>	Optional	Microsoft OAuth button hidden if absent
<code>AZURE_AD_CLIENT_SECRET</code>	Optional	Azure AD OAuth client secret
<code>AZURE_AD_TENANT_ID</code>	Optional	Use <code>common</code> for all account types
<code>DISABLE_MFA</code>	Optional	Set <code>true</code> to skip MFA enforcement (dev only)
<code>ENABLE_PAYMENTS</code>	Optional	Set <code>true</code> to expose <code>/courses</code> and Stripe checkout
<code>STRIPE_SECRET_KEY</code>	Payments	Stripe secret key (<code>sk_test_...</code> / <code>sk_live_...</code>)
<code>STRIPE_PUBLISHABLE_KEY</code>	Payments	Stripe publishable key
<code>STRIPE_WEBHOOK_SECRET</code>	Payments	Stripe webhook signing secret (<code>whsec_...</code>)

Note: The `ENABLE_OAUTH_SSO` env variable was removed in May 2026. OAuth providers are now toggled per-environment by a Charity Admin in `/super-admin/settings/sso` (DB-backed `OAuthSsoConfig`). Setting

`GOOGLE_CLIENT_ID` / `AZURE_AD_CLIENT_ID` makes the providers *available*; flipping the admin toggle makes them *active*.

Eventbrite credentials are configured per-organisation in the admin UI rather than via env vars — see `/super-admin/settings/eventbrite`.

```
# Pull env vars from Vercel (dev branch):
npx vercel env pull .env.local

# Pull production env vars:
npx vercel env pull .env.production --environment production --yes
```

6. Database Setup (Neon)

Two Neon branches are in use: **main** (production, endpoint `ep-blue-thunder-a88kb0cy`) and **dev** (development, endpoint `ep-lucky-cherry-a8toqlw5`). Local dev pulls the dev branch env vars via `npx vercel env pull .env.local`.

```
# Push schema changes to dev database:
npm run prisma:push

# Push schema to PRODUCTION:
npx dotenv-cli -e .env.production -- npx prisma db push

# Seed demo users:
npm run prisma:seed

# Seed training content:
npx tsx prisma/seed-training-content.ts
```

Warn: Always push schema to **BOTH** dev AND production when adding columns that are queried at runtime. Production will crash if it references a missing column.

Prisma accessor gotchas:

- Virtual classroom sessions use `prisma.classSession` (not `prisma.session` — that's the NextAuth Session table).

7. Local Development

```
npm run dev
# Server starts on http://localhost:3000

# Forward Stripe webhooks (separate terminal):
stripe listen --forward-to localhost:3000/api/stripe/webhook
```

Demo credentials (seeded by `npm run prisma:seed`):

Role	Email	Password
SUPER_ADMIN	<code>admin@asdawareness.org.uk</code>	<code>admin123</code>
EMPLOYEE	<code>demo@example.com</code>	<code>demo123</code>

Warn: The dev Neon branch may be paused after inactivity. If login fails with a database connection error, wake the branch up in the Neon console.

8. Testing

```
npm run test           # Vitest unit tests
npm run test:e2e       # Playwright E2E tests
npm run build          # Build (runs tests – failing test blocks
deploy)
```

Test type	Location	What is tested
Vitest unit	<code>lib/__tests__/</code> and <code>app/api/.../__tests__/</code>	RBAC helpers, permission counts, job visibility logic, SCORM progress mapping, AI runner sentinels

Playwright E2E	<code>playwright-report/</code>	Full browser flows — login, training, admin
Build gate	<code>npm run build</code>	Vitest runs before <code>next build</code> — failure blocks deploy

Warn: Do NOT use `isomorphic-dompurify` or `jsdom` at runtime — they break on Vercel serverless. `jsdom` is a `devDependency` only (Vitest env). Use `sanitize-html` for HTML sanitisation.

9. Deployment (Vercel)

Vercel GitHub integration auto-deploys on push to `main`. Preview deployments are created for all branches.

```
# Deploy to production via git (preferred):
git push origin main

# Manual deploy (only if no git push was made):
npx vercel deploy --prod
```

Info: Never run `vercel deploy --prod` after a git push — Vercel auto-deploys from GitHub and a manual deploy creates a duplicate build.

Step	Action
1	Vercel detects push to <code>main</code>
2	Runs build command: <code>prisma generate && cross-env NODE_ENV=test vitest run && next build</code>
3	Deploys to production URL: <code>https://asd-training-app-v2.vercel.app</code>
4	Preview URL available for branch deploys

10. Content Security Policy

CSP is configured in `next.config.js` headers. Key directives that require explicit values:

Directive	Required values	Reason
<code>connect-src</code>	<code>vercel.com</code> , <code>blob.vercel-storage.com</code> , <code>*.public.blob.vercel-storage.com</code>	Client-direct Blob uploads (SCORM packages, brand-asset zips)
<code>media-src</code>	<code>blob:</code>	TTS audio playback
<code>frame-src</code>	<code>blob:</code>	SCORM iframe content
<code>script-src</code>	<code>self</code> , <code>unsafe-eval</code> (dev only)	Next.js HMR
<code>font-src</code>	<code>fonts.gstatic.com</code>	Google Fonts

Warn: SCORM iframe sandbox requires `allow-same-origin` . Removing it causes subresource requests to 401. Do not attempt to harden without a signed-URL scheme. (History: tried it, broke playback, reverted in commit `c317351` .)

11. Key Architectural Decisions

No PrismaAdapter. NextAuth uses JWT sessions (not database sessions) with manual SSO account linking in the `signIn` callback. This avoids `OAuthAccountNotLinked` errors and simplifies the auth flow.

`sanitize-html` , not `DOMPurify`. `isomorphic-dompurify` requires `jsdom` which breaks on Vercel serverless. `sanitize-html` is a pure-Node sanitiser with no browser dependencies.

SCORM buffering. The SCORM asset route (`/api/scorm/[lessonId]/[...path]`) buffers binary bodies before responding. Streaming corrupts media files — same issue as the TTS route.

TTS streaming, not redirect. The `/api/tts` route streams MP3 bytes directly rather than redirecting to Blob. This allows magic-byte validation and prevents browser cache collisions.

Neon over Supabase. Supabase was IPv6-only — incompatible with Vercel Lambda which uses IPv4. Neon supports both. Migration was completed in May 2026.

scorm-again v3. Handles both SCORM 1.2 (**window.API**) and SCORM 2004 (**window.API_1484_11**). Version 3 supports concurrent requests and improved CMI state management.

prisma.classSession , not **prisma.session** . The virtual-classroom model is named **ClassSession** specifically to avoid colliding with the NextAuth **Session** table, so always reach for **prisma.classSession** .

OAuth toggled in DB, not env. **OAuthSsoConfig** lets Charity Admins flip Google / Microsoft on per-environment without a redeploy. Replaces the old **ENABLE_OAUTH_SSO** env flag (removed May 2026).

Auth-gated proxy routes for documents. Library, training, and job document URLs are never linked directly to Vercel Blob — every request goes through **/api/library/documents/[docId]/file** , **/api/scorm/[lessonId]/[...path]** , or **/api/jobs/[jobId]/attachments/[attachmentId]/file** . Lets us enforce per-user entitlement, rate-limit, and audit access.

12. Troubleshooting

Symptom	Likely cause	Fix
All /api/auth/* return 500	Wrong DATABASE_URL (direct, not pooler)	Use Neon pooler URL port 6543
Prisma client not found on Vercel	Client not regenerated before build	Build script must run prisma generate first
Login fails locally	Dev Neon branch paused	Wake branch in Neon console
Google SSO fails	Wrong redirect URI	Check Google Cloud Console → Credentials
Microsoft SSO fails	Wrong redirect URI or tenant	Check Azure Portal → App registrations
OAuth button missing from login page	Provider credentials set but admin toggle off	Sign in as Charity Admin → Settings → SSO → flip toggle

SCORM audio/video corrupted	Streaming not buffering	Ensure route buffers full body before response
TTS returns 200 but no audio	Non-MP3 response from ElevenLabs	Check <code>ELEVENLABS_API_KEY</code> ; inspect magic bytes
Welcome email never arrives	Resend domain not verified, or sender domain mismatch	Verify domain in Resend → Domains; check <code>lib/email-templates/layout.ts</code> From address
Build fails — test error	Vitest runs in build	Fix failing unit test before deploying
MFA redirect loop	TOTP not enrolled	Log in as admin, go to <code>/mfa-setup</code> , complete setup
Brand asset upload 413 / CSP block	CSP missing Blob hosts	Verify <code>connect-src</code> includes <code>vercel.com</code> + <code>*.public.blob.vercel-storage.com</code>
Self-registration form blocked	Rate limit (5 / 15 min / IP)	Wait or use a different IP