

AAA Digital Platform

Data Dictionary

Complete database schema reference for all Prisma models

This document is the authoritative database schema reference for the AAA Digital Platform. It covers every Prisma model, field, relationship, and key query pattern used by the Next.js 14 application deployed at `asd-training-app-v2.vercel.app`. The database backend is Neon PostgreSQL accessed via Prisma ORM.

Version 2.0 | Generated 4 May 2026 | Confidential — Ambitious about Autism

1. Database Overview

Environment	URL type	Notes
Production	Pooler (port 6543)	pgbouncer=true required — use DATABASE_URL
Production migrations	Direct (port 5432)	Used by Prisma CLI only — use DIRECT_URL
Development	Neon dev branch pooler	Endpoint ep-lucky-cherry-a8toqlw5; pulled via vercel env pull .env.local

(1) Model CV uses accessor prisma.cV (capital V) — not prisma.cv. (2) Model ClassSession uses accessor prisma.classSession — avoids collision with the NextAuth Session table. (3) Child/Observation/Ailnsight models were removed in commit 8968cf0 — do not reference them.

2. Core Models — User

Field	Type	Nullabl e	Description
id	String (UUID)	No	Primary key
email	String	No	Unique — used for login
name	String	Yes	
password	String	Yes	bcrypt hash (cost 12). Null for SSO-only users
role	Role enum	No	SUPER_ADMIN CHARITY_EMPLOYEE ORG_ADMIN CAREGIVER CAREER_DEV_OFFICER STUDENT INTERN EMPLOYEE
organisationId	String	Yes	FK → Organisation; SET NULL on org delete
active	Boolean	No	Default true. Deactivated users cannot sign in
pendingApproval	Boolean	No	Awaiting admin activation
mustChangePassword	Boolean	No	Forces /change-password redirect via middleware
totpSecret	String	Yes	Encrypted TOTP secret for MFA
totpEnabled	Boolean	No	True once MFA setup is complete
charityPermissions	String[]	No	Scoped permissions for CHARITY_EMPLOYEE role; SUPER_ADMIN has all implicitly
notificationsLastOpenedAt	DateTime	Yes	Used for unread-badge count on the bell icon
invitedAt	DateTime	Yes	Timestamp of invite email dispatch
invitedBy	String	Yes	userId of the admin who sent the invite
createdAt	DateTime	No	Auto-set
updatedAt	DateTime	No	Auto-updated

2. Core Models — Organisation

Field	Type	Nullable	Description
id	String	No	Primary key
name	String	No	
slug	String	No	Unique URL identifier
organisationType	Enum	Yes	SCHOOL COLLEGE ACADEMY UNIVERSITY EMPLOYER EDUCATION BUSINESS
orgType	Enum	No	ORGANISATION or COHORT
allowedProgramIds	String[]	No	IDs of TrainingProgram records the org can access
allowedRoles	Role[]	No	Roles that can be assigned within this org
cvBuilderEnabled	Boolean	No	Feature flag, default true
careersAdvisorEnabled	Boolean	No	Feature flag, default true
active	Boolean	No	
pendingApproval	Boolean	No	
logoUrl	String	Yes	Vercel Blob URL
parentOrgId	String	Yes	FK → Organisation (self-referencing parent)
isParentOrg	Boolean	No	True if this org manages child schools/cohorts
inheritSettings	Boolean	No	Child org inherits parent allowedProgramIds etc.
contactName	String	Yes	
contactEmail	String	Yes	
contactPhone	String	Yes	
addressLine1	String	Yes	
addressLine2	String	Yes	
city	String	Yes	
county	String	Yes	
postcode	String	Yes	
country	String	Yes	
createdAt	DateTime	No	
updatedAt	DateTime	No	

2. Core Models — Account (SSO linking)

Field	Type	Nullable	Description
id	String	No	Primary key
userId	String	No	FK → User
provider	String	No	google azure-ad credentials
providerAccountId	String	No	ID from the OAuth provider
type	String	No	oauth credentials

createdAt	DateTime	No	Auto-set
-----------	----------	----	----------

Unique constraint on (provider, providerAccountId). Account rows are created manually in the NextAuth signIn callback — no PrismaAdapter is used.

3. Training Models — TrainingProgram

Field	Type	Nullabl e	Description
id	String	No	Primary key
name	String	No	e.g. "ASD Awareness Training"
description	Text	Yes	Rich HTML (sanitised)
order	Int	No	Display sort order
status	Enum	No	DRAFT UNDER_REVIEW APPROVED ARCHIVED
version	String	No	Default "1.0"
active	Boolean	No	
createdAt	DateTime	No	
updatedAt	DateTime	No	

3. Training Models — Module

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
description	Text	Yes	Rich HTML
order	Int	No	Sort order within program
active	Boolean	No	
programId	String	No	FK → TrainingProgram (CASCADE delete)
createdAt	DateTime	No	
updatedAt	DateTime	No	

3. Training Models — Lesson

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
type	Enum	No	TEXT VIDEO SCORM
order	Int	No	Sort order within module
content	Text	Yes	HTML (sanitise-html). Used for TEXT lessons

videoUrl	String	Yes	Embed URL for VIDEO lessons
transcript	Text	Yes	Plain-text transcript for TTS
interactiveBlocks	Json	Yes	Hotspot, carousel, video-embed blocks — see lib/interactive-blocks.ts
moduleId	String	No	FK → Module (CASCADE delete)
active	Boolean	No	
scormBlobPrefix	String	Yes	Vercel Blob path prefix for SCORM assets
scormEntryPath	String	Yes	Relative path to the SCORM launch file
scormVersion	String	Yes	"1.2" "2004"
scormToc	Json	Yes	Parsed tree for multi-SCO navigation
createdAt	DateTime	No	
updatedAt	DateTime	No	

3. Training Models — QuizQuestion

Field	Type	Nullabl e	Description
id	String	No	Primary key
question	Text	No	
options	Json	No	Array of answer strings
correctAnswer	String	No	Must match one entry in options
explanation	Text	Yes	Shown after answering
lessonId	String	No	FK → Lesson (CASCADE delete)
order	Int	No	Sort order

3. Training Models — TrainingProgress

Field	Type	Nullabl e	Description
id	String	No	Primary key
userId	String	No	FK → User (CASCADE delete)
moduleId	String	No	Module ID string
lessonId	String	No	Lesson ID string
completed	Boolean	No	
score	Float	Yes	0-100 percentage
interactionData	Json	Yes	SCORM CMI snapshot; navLocation for resume; interactive-block interactions
completedAt	DateTime	Yes	

Unique constraint on (userId, moduleId, lessonId).

3. Training Models — LessonAttachment

Field	Type	Nullable	Description
id	String	No	Primary key
lessonId	String	No	FK → Lesson (CASCADE delete)
name	String	No	Display filename
url	String	No	Vercel Blob URL
mimeType	String	No	
sizeBytes	Int	Yes	
createdAt	DateTime	No	

3. Training Models — LessonNote

Field	Type	Nullable	Description
id	String	No	Primary key
userId	String	No	FK → User
lessonId	String	No	
content	Text	No	Learner personal notes — plain text
updatedAt	DateTime	No	

Unique constraint on (userId, lessonId).

4. Session & Announcement — ClassSession

Field	Type	Nullable	Description
id	String	No	Primary key
title	String	No	
organisationId	String	No	FK → Organisation
hostId	String	Yes	FK → User (session host)
dateTime	DateTime	No	UTC start time
durationMinutes	Int	No	
platform	Enum	No	ZOOM TEAMS CUSTOM
meetingUrl	String	Yes	Pasted or auto-generated join link
status	Enum	No	SCHEDULED IN_PROGRESS COMPLETED CANCELLED
recordingUrl	String	Yes	Added after session completes
notes	Text	Yes	
isCharitySession	Boolean	No	True for charity-level workshops

createdAt	DateTime	No	
updatedAt	DateTime	No	

Always use `prisma.classSession` — NOT `prisma.session`. The name `ClassSession` avoids collision with the NextAuth Session table.

4. Session & Announcement — SessionAttendee

Field	Type	Nullable	Description
id	String	No	Primary key
sessionId	String	No	FK → ClassSession (CASCADE delete)
userId	String	No	FK → User
attended	Boolean	No	Default false; toggled by host
invitedAt	DateTime	No	Auto-set at record creation

Unique constraint on (sessionId, userId).

4. Session & Announcement — Announcement

Field	Type	Nullable	Description
id	String	No	Primary key
title	String	No	
body	Text	No	Rich HTML content
organisationId	String	Yes	Null = global announcement visible to all
targetRoles	Role[]	No	Empty = all roles
expiresAt	DateTime	Yes	Hidden after this date
createdById	String	No	FK → User
createdAt	DateTime	No	
updatedAt	DateTime	No	

4. Session & Announcement — PasswordResetToken

Field	Type	Nullable	Description
id	String	No	Primary key
userId	String	No	FK → User
token	String	No	Unique SHA-256 hashed token (single-use)
expiresAt	DateTime	No	
usedAt	DateTime	Yes	Set on redemption; second use rejected

createdAt	DateTime	No	
-----------	----------	----	--

5. Survey Models — Survey

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
description	Text	Yes	
status	Enum	No	DRAFT PUBLISHED CLOSED
createdById	String	No	FK → User (super admin)
createdAt	DateTime	No	
updatedAt	DateTime	No	

5. Survey Models — SurveyQuestion

Field	Type	Nullabl e	Description
id	String	No	Primary key
surveyId	String	No	FK → Survey (CASCADE delete)
type	Enum	No	MULTIPLE_CHOICE YES_NO FREE_TEXT RATING_SCALE MULTI_SELECT
text	Text	No	Question text
options	Json	Yes	Array of option strings; required for MULTIPLE_CHOICE and MULTI_SELECT
order	Int	No	Sort order

5. Survey Models — SurveyTarget, SurveyResponse, SurveyAnswer, SurveyInsight

SurveyTarget — determines which orgs / roles see a survey.

Field	Type	Nullabl e	Description
id	String	No	Primary key
surveyId	String	No	FK → Survey (CASCADE delete)
targetType	Enum	No	ORG ROLE
targetValue	String	No	orgId or role enum string

SurveyResponse — one row per user per survey. **SurveyAnswer** — one row per question in that response. **SurveyInsight** — AI-generated analysis stored as type (SUMMARY | COMPARATIVE | RECOMMENDATIONS) + content Text. All cascade on Survey delete.

6. Library Models — Collection, Document, Event

LibraryCollection

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
description	Text	Yes	
targetOrgIds	String[]	No	Orgs that can see this collection
targetRoles	Role[]	No	Roles that can see this collection
thumbnailUrl	String	Yes	AI-generated thumbnail on Vercel Blob
createdById	String	No	FK → User
createdAt	DateTime	No	
updatedAt	DateTime	No	

LibraryDocument

Field	Type	Nullabl e	Description
id	String	No	Primary key
collectionId	String	No	FK → LibraryCollection (CASCADE delete)
name	String	No	Display filename
url	String	No	Vercel Blob URL
mimeType	String	No	
sizeBytes	Int	No	
order	Int	No	Sort order within collection
createdAt	DateTime	No	

LibraryDocumentEvent

Field	Type	Nullabl e	Description
id	String	No	Primary key
documentId	String	No	FK → LibraryDocument (CASCADE delete)
userId	String	No	FK → User
organisationId	String	No	FK → Organisation (denormalised for reporting)
eventType	Enum	No	VIEW DOWNLOAD
createdAt	DateTime	No	

7. CV Builder Models

Prisma accessor is prisma.cV (capital V) — not prisma.cv.

CV

Field	Type	Nullabl e	Description
id	String	No	Primary key
userId	String	No	FK → User
title	String	No	User-facing CV name
status	Enum	No	DRAFT COMPLETE
template	Enum	No	ACCESSIBLE MODERN CLASSIC
currentStep	Int	No	Wizard step, default 1 (1–8)
personalStatement	Text	Yes	
fullName	String	Yes	
email	String	Yes	
phone	String	Yes	
address	String	Yes	
linkedin	String	Yes	
createdAt	DateTime	No	
updatedAt	DateTime	No	

CVWorkExperience — jobTitle, employer, startDate, endDate (nullable), description (nullable), order. FK → CV (CASCADE delete).

CVEducation — qualification, institution, startDate, endDate (nullable), grade (nullable), order. FK → CV (CASCADE delete).

CVSkill — name, level (optional). FK → CV (CASCADE delete).

CVReference — name, jobTitle, company, email, phone (nullable). FK → CV (CASCADE delete).

Dates stored as free-form strings (e.g. "Sept 2022") per UK CV convention. Zod schemas must use `.nullable().optional()` for nullable fields — `z.string().optional()` rejects null.

8. Careers Advisor — CareerAdvisorSession

Prisma accessor is `prisma.careerAdvisorSession`.

Field	Type	Nullabl e	Description
id	String	No	Primary key
userId	String	No	FK → User; indexed
status	Enum	No	IN_PROGRESS COMPLETE
currentStep	Int	No	Wizard step position (1–12)
answers	Json	Yes	Structured questionnaire responses keyed by step
report	Json	Yes	AI report: { strengths, careers, nextSteps, workplaceSupport }
createdAt	DateTime	No	
updatedAt	DateTime	No	

9. Jobs Models — JobOpening, JobAttachment, JobAssignment

JobOpening

Field	Type	Nullabl e	Description
id	String	No	Primary key
title	String	No	
employerName	String	No	
description	Text	No	Rich HTML
locationType	Enum	No	ONSITE HYBRID REMOTE
employmentType	Enum	No	INTERNSHIP APPRENTICESHIP PART_TIME FULL_TIME VOLUNTEER
status	Enum	No	DRAFT PUBLISHED CLOSED ARCHIVED
closingDate	DateTime	Yes	Auto-closes past this date (lib/jobs.ts)
autismFriendlyNotes	Text	Yes	
skills	String[]	No	Tag strings
targetOrgIds	String[]	No	Visibility: restrict to these orgs
targetRoles	Role[]	No	Visibility: restrict to these roles
logoUrl	String	Yes	Employer logo on Vercel Blob
createdById	String	No	FK → User
createdAt	DateTime	No	
updatedAt	DateTime	No	

JobAttachment

Field	Type	Nullabl e	Description
id	String	No	Primary key
jobId	String	No	FK → JobOpening (CASCADE delete)
name	String	No	
url	String	No	Vercel Blob URL
contentType	String	No	
sizeBytes	Int	No	
createdAt	DateTime	No	

JobAssignment

Field	Type	Nullabl e	Description
id	String	No	Primary key
jobId	String	No	FK → JobOpening (CASCADE delete)
userId	String	No	FK → User (target student/learner)

Unique constraint on (jobId, userId).

10. AI & Integration — AiPrompt, AiPromptContextFile

AiPrompt

Field	Type	Nullabl e	Description
id	String	No	Primary key
key	String	No	Unique string key used by runPrompt(key, values)
name	String	No	Human-readable name shown in admin UI
purpose	Text	No	
category	String	No	
tone	String	No	
requirements	String[]	No	Bullet-point requirements prepended to prompt
inputVariables	String[]	No	Expected {{variable}} placeholders
responseFormat	Text	No	Instructions for the model output format
model	String	No	Provider/model string e.g. google/gemini-2.5-flash
defaultFields	Json	Yes	Fallback seed values for inputVariables
previousFields	Json	Yes	Undo buffer — last saved values
createdAt	DateTime	No	
updatedAt	DateTime	No	

AiPromptContextFile

Field	Type	Nullabl e	Description
id	String	No	Primary key
promptId	String	No	FK → AiPrompt (CASCADE delete)
filename	String	No	
url	String	No	Vercel Blob URL
mimeType	String	No	application/pdf application/vnd.openxmlformats... text/plain
sizeBytes	Int	No	
parsedText	Text	Yes	Extracted text prepended to the prompt at runtime
createdAt	DateTime	No	

10. AI & Integration — IntegrationApiKey

Field	Type	Nullabl e	Description
id	String	No	Primary key
name	String	No	Friendly label
keyHash	String	No	SHA-256 hash of the raw key — raw key never stored
keyPrefix	String	No	First 8 chars for display (e.g. "rw_abc12")

expiresAt	DateTime	Yes	
lastUsedAt	DateTime	Yes	Updated on every successful API call
createdByld	String	No	FK → User
createdAt	DateTime	No	
updatedAt	DateTime	No	

The raw API key is displayed only once on creation and then discarded. Authentication on /api/integrations/reports uses Bearer token; the handler hashes the incoming token and compares against keyHash.

10. AI & Integration — SSO & Meeting Config

OrgSsoConfig — per-org SAML 2.0 configuration. Fields: emailDomain, ssoUrl (IdP SSO endpoint), entityld (IdP entity/issuer), certificate (X.509 PEM), autoProvision (Boolean, creates user on first login if true), defaultRole (Role enum used when auto-provisioning). One row per org.

CharitySsoConfig — charity-level SAML configuration. Same fields as OrgSsoConfig plus enforceForCharityUsers (Boolean — forces all charity employees through SSO). Managed at /super-admin/settings/sso.

OrgMeetingConfig — per-org Zoom or Microsoft Teams API credentials for auto-generating meeting links on ClassSession creation. Fields: provider (ZOOM | TEAMS), clientId, clientSecret, accountId (Zoom), tenantId (Teams). Managed at /admin/settings/meetings.

CharityMeetingConfig — charity-level equivalent of OrgMeetingConfig. Used for charity-wide workshops (isCharitySession = true).

11. Key Relationships

Parent model	Relationship	Child model	Foreign key	On delete
Organisation	1 : many	User	organisationId	SET NULL
TrainingProgram	1 : many	Module	programId	CASCADE
Module	1 : many	Lesson	moduleId	CASCADE
Lesson	1 : many	QuizQuestion	lessonId	CASCADE
Lesson	1 : many	LessonAttachment	lessonId	CASCADE
User	1 : many	TrainingProgress	userId	CASCADE
User	1 : many	LessonNote	userId	CASCADE
ClassSession	1 : many	SessionAttendee	sessionId	CASCADE
Survey	1 : many	SurveyQuestion	surveyId	CASCADE
Survey	1 : many	SurveyTarget	surveyId	CASCADE
Survey	1 : many	SurveyResponse	surveyId	CASCADE
LibraryCollection	1 : many	LibraryDocument	collectionId	CASCADE

LibraryDocument	1 : many	LibraryDocumentEvent	documentId	CASCADE
CV	1 : many	CVWorkExperience	cvId	CASCADE
CV	1 : many	CVEducation	cvId	CASCADE
CV	1 : many	CVSkill	cvId	CASCADE
CV	1 : many	CVReference	cvId	CASCADE
JobOpening	1 : many	JobAttachment	jobId	CASCADE
JobOpening	1 : many	JobAssignment	jobId	CASCADE
Organisation	1 : many	Organisation	parentOrgId	SET NULL (self-ref)
AiPrompt	1 : many	AiPromptContextFile	promptId	CASCADE

12. Sample Prisma Queries

1. Get user with their organisation:

```
const user = await prisma.user.findUnique({
  where: { email },
  include: { organisation: true }
})
```

2. Get training progress for a user:

```
const progress = await prisma.trainingProgress.findMany({
  where: { userId },
  orderBy: { completedAt: 'desc' }
})
```

3. Get sessions for an organisation:

```
const sessions = await prisma.classSession.findMany({
  where: { organisationId },
  include: { attendees: { include: { user: true } } }
})
```

4. Get a CV with all sub-items:

```
const cv = await prisma.cv.findFirst({
  where: { userId, id: cvId },
  include: {
    workExperience: true,
    education: true,
    skills: true,
    references: true
  }
})
```

5. Get published jobs visible to a learner (see lib/jobs.ts for full visibility logic):

```
// See lib/jobs.ts:getVisibleJobs() for full visibility logic
const jobs = await prisma.jobOpening.findMany({
  where: { status: 'PUBLISHED' }
})
```

6. Upsert training progress (used by POST /api/training/progress):

```
await prisma.trainingProgress.upsert({
  where: { userId_moduleId_lessonId: { userId, moduleId, lessonId } },
  update: { completed: true, completedAt: new Date() },
  create: { userId, moduleId, lessonId, completed: true, completedAt: new Date() }
})
```

13. External Integrations

Service	Used for	Auth method	Env var(s)
Neon PostgreSQL	Primary database	Connection string	DATABASE_URL, DIRECT_URL
Vercel Blob	File storage (docs, images, SCORM assets, TTS)	Token	BLOB_READ_WRITE_TOKEN
Vercel AI Gateway	AI features routing (multi-provider)	API key	AI_GATEWAY_API_KEY
ElevenLabs	Text-to-speech — Lily voice (pFZP5JQG7iQjIQuC4Bku). MP3s cached at tts//.mp3	API key	ELEVENLABS_API_KEY
Resend	Transactional email (forgot-password, invites)	API key	RESEND_API_KEY
Google OAuth	Google SSO sign-in	Client credentials	GOOGLE_CLIENT_ID, GOOGLE_CLIENT_SECRET
Azure AD	Microsoft SSO sign-in	Client credentials	AZURE_AD_CLIENT_ID, AZURE_AD_CLIENT_SECRET, AZURE_AD_TENANT_ID
Stripe	Payments layer (disabled — ENABLE_PAYMENTS=false until live account)	Secret key + webhook	STRIPE_SECRET_KEY, STRIPE_PUBLISHABLE_KEY, STRIPE_WEBHOOK_SECRET, STRIPE_SUBSCRIPTION_PRICE_YEARLY

Available provider/model strings (lib/ai-models.ts): google/gemini-2.5-flash (default), google/gemini-2.5-pro, anthropic/claude-sonnet-4, anthropic/claude-haiku-4, openai/gpt-4o-mini, openai/gpt-4.1. Callers use runPrompt(key, values) from lib/ai-runner.ts. On missing prompt row or error the runner returns the sentinel AI_FEATURE_UNAVAILABLE.