



Ask

WEBHOOKS



Ask



skills-activity-started

Event triggered when a learner begins a training activity

Event Overview

The `skills-activity-started` event is emitted whenever a learner launches or resumes a training activity in Skills Software. It captures who is taking the activity, which scenario is being attempted, and the learner's progress at the moment the attempt starts. Learners who struggle may re-launch the same activity multiple times, so receiving several start events for the same `activity_id` is expected; `activity_failures` tracks how many times they have previously failed the activity within the session.

Delivery Behavior

- Fires on every launch or resume of an activity attempt, including retries after a failure.
- Delivered independently of the `skills-activity-ended` event. If a learner closes the browser or loses connection, an end event might never arrive for the corresponding attempt.
- `activity_result` is empty at start because no scoring data is available yet.
- `activity_elapsed` carries over any time spent in prior launches of the same attempt, including pause time.

Event Type

skills-activity-started

Webhook Payload

```
{
  "requestId": "548994-0",
  "eventType": "skills-activity-started",
  "timestamp": "2026-01-13T07:55:36.2573248Z",
  "stationId": "696224442a77d0120654fbab",
  "data": {
    "launch_id": "548994-0",
    "event_type": "activity-started",
    "org_id": "10001234",
    "manikin_id": "17700000000",
    "user_email": "user.name@example.com",
    "user_id": "12345",
    "user_name": "User Name",
    "activity_id": "skills-web-adult-compressions",
    "activity_completed": false,
    "activity_score": 0,
    "activity_elapsed": 21063,
    "activity_failures": 0,
    "organization_name": "Distributor A",
    "institution_id": "dfcfb5bc-dd3a-5201-8e17-040e33da9b73",
    "institution_name": "Institution B",
    "time_zone": "Europe/Dublin",
    "activity_result": {},
    "course_id": "manifest/skills_2025_hc_bls_dev",
    "activities": [
      "hc-overview",
      "skills-web-adult-compressions",
      "skills-web-adult-ventilations",
      "skills-web-adult-2CPR-30-2",
      "skills-web-infant-compressions",
      "skills-web-infant-ventilations",
      "skills-web-infant-2CPR-15-2"
    ],
    "course_progress": {
      "hc-overview": {
        "_score": 0,
        "_complete": 1,
        "_elapsed": 20663,
        "_failures": 0
      },
      "skills-web-adult-compressions": {
```

```
{
  {
    {
      "_complete": 0,
      "_score": 0
    }
  }
}
```

Payload Fields

Top-Level Fields

Field	Type	Description
<code>requestId</code>	string	Unique request identifier for idempotency
<code>eventType</code>	string	Always <code>skills-activity-started</code>
<code>timestamp</code>	string	ISO 8601 UTC timestamp when event occurred
<code>stationId</code>	string	Fleet Management station identifier
<code>data</code>	object	Event-specific payload (see below)

Data Object Fields

Field	Type	Description
<code>launch_id</code>	string	Launch identifier for deduplication of delivery
<code>org_id</code>	string	RQI1Stop organization identifier
<code>manikin_id</code>	string	Manikin serial number
<code>user_email</code>	string	Learner's email address
<code>user_id</code>	string	Learner's RQI1Stop user identifier
<code>user_name</code>	string	Learner's full name
<code>activity_id</code>	string	Activity/SCO identifier
<code>activity_completed</code>	boolean	Always false at launch; completion is only reported by the ended event
<code>activity_score</code>	number	Current activity score (0.0 – 1.0)
<code>activity_elapsed</code>	number	Total milliseconds elapsed in the activity attempt so far, pauses included
<code>activity_failures</code>	number	Count of previous failed attempts for this activity within the session
<code>organization_name</code>	string	Organization display name
<code>institution_id</code>	string	Institution identifier
<code>institution_name</code>	string	Institution display name
<code>time_zone</code>	string	Learner's time zone (for example, <code>Europe/Dublin</code>)

<code>activity_result</code>	object	Empty object at launch; populated in the ended event
<code>course_id</code>	string	Course/manifest identifier
<code>activities</code>	array	Ordered list of activity IDs in the course
<code>course_progress</code>	object	Per-activity progress summary for the current course attempt

`course_progress` uses activity IDs as keys. Each entry exposes `_score`, `_complete`, `_elapsed`, and `_failures` values that reflect the learner's history within this course session up to the moment of launch.

Activity Lifecycle Notes

- Learners can abandon an attempt without completing it. Systems integrating with this webhook should not assume that a start event will always be followed by an end event.
- When an activity is retried after a failure, a new start event is emitted with an incremented `activity_failures` count while keeping the same `activity_id`.
- If an activity is paused and resumed, the resumed launch emits another start event with `activity_elapsed` continuing from the prior value, so analytics should treat elapsed time as cumulative.

Use Cases

- Track when learners begin training activities
- Monitor training session starts in real-time
- Trigger notifications when specific activities start

- Log activity start times for analytics
- Initialize progress tracking systems

Example Implementation

```
app.post('/webhooks/fleet-management', async (req, res) => {  
  // Verify signature (see Webhooks Overview)  
  if (!verifySignature(req)) {  
    return res.status(401).send('Invalid signature');  
  }  
  
  const event = req.body;  
  
  if (event.eventType === 'skills-activity-started') {  
    const { user_email, user_name, activity_id, course_id } =  
      event.data;  
  
    // Process activity start  
    await logActivityStart({  
      userEmail: user_email,  
      userName: user_name,  
      activityId: activity_id,  
      courseId: course_id,  
      timestamp: event.timestamp  
    });  
  
    // Respond immediately  
    res.status(200).send('OK');  
  }  
});
```

Related Events

- skills-activity-ended - Triggered when the activity completes or is exited

[Previous
Overview](#)

Next

skills-activity-ended

Last updated 5 months ago