

1 Iterators Warmup

1. If we were to define a class that implements the interface `Iterable<Integer>`, what method(s) would this class need to define? Write the function signature(s) below.

`public Iterator<Integer> iterator();`

2. If we were to define a class that implements the interface `Iterator<Integer>`, what method(s) would this class need to define? Write the function signature(s) below.

`public boolean hasNext();`

`public Integer next();`

3. What's one difference between `Iterator` and `Iterable`?

`Iterator` 是遍历它的对象

`Iterable` 是, 通过 `Iterator` 来遍历内容的对象

2 OHQueue

The goal for this question is to create an iterable Office Hours queue. We'll do so step by step.

The code below for `OHRequest` represents a single request. Like an `IntNode`, it has a reference to the next request. `description` and `name` contain the description of the bug and name of the person on the queue.

```

1 public class OHRequest {
2     public String description;
3     public String name;
4     public OHRequest next;
5
6     public OHRequest(String description, String name, OHRequest next) {
7         this.description = description;
8         this.name = name;
9         this.next = next;
10    }
11 }

```

First, let's define an iterator. Create a class `OHIterator` that implements an iterator over `OHRequest` objects that only returns requests with good descriptions. Our `OHIterator`'s constructor will take in an `OHRequest` object that represents the first `OHRequest` object on the queue. We've provided a function, `isGood`, that accepts a `description` and says if the description is good or not. If we run out of office hour requests, we should throw a `NoSuchElementException` when our iterator tries to get another request.

```
import java.util.Iterator;
```

```
public class OHIterator {
    OHRequest curr;
```

```
    public OHIterator(OHRequest queue) {
        curr = queue;
```

```
    public boolean isGood(String description) {
        return description != null && description.length() > 5;
    }
```

```
    public boolean hasNext() {
        return curr != null && curr.next != null;
    }
```

```
    public OHRequest next() {
```

```
        while (curr != null && !isGood(curr.description))
            curr = curr.next;
```

```
        if (curr == null)
```

```
            throw new NoSuchElementException;
```

```
        String s = curr.description;
        curr = curr.next;
```

```
        return curr;
```

```
    }
```

Handwritten notes:

- implements Iterator<OHRequest>*
- @ override public boolean hasNext() {*
- while (curr != null && !isGood(curr.description))*
- { curr = curr.next;*
- } if (curr == null)*
- return false*
- return true;*
- @ override public OHRequest*
- next() { if (!hasNext())*
- throw new NoSuchElementException;*
- OHRequest t = curr*
- curr = curr.next;*
- curr = curr.next;*
- return t;*
- return t;*

Now, define a class OHQueue. We want our OHQueue to be iterable, so that we can process OHRequest objects with good descriptions. Our constructor will take in an OHRequest object representing the first request on the queue.

```
import java.util.Iterator;
public class OHQueue implements Iterator implements Iterator<OHRequest> {
    OHRequest queue;
    public OHQueue (OHRequest queue) {
        this.queue = queue;
    }

    @override
    public Iterator<OHRequest> iterator() {
        return new RAIterator(queue);
    }
}
```

Fill in the main method below so that you make a new OHQueue object and print the names of people with good descriptions. Note : the main method is part of the OHQueue class.

```
public class OHQueue ... {
    ....

    public static void main(String [] args) {
        OHRequest s5 = new OHRequest("I deleted all of my files", "Allyson", null);
        OHRequest s4 = new OHRequest("conceptual: what is Java", "Omar", s5);
        OHRequest s3 = new OHRequest("git: I never did lab 1", "Connor", s4);
        OHRequest s2 = new OHRequest("help", "Hug", s3);
        OHRequest s1 = new OHRequest("no I haven't tried stepping through", "Itai", s2);

        for (OHRequest i: queue) {
            system.out.println(i.name);
        }
    }
}
```

3 Thank u, next

Now that we have our `OHQueue` from problem 2, we'd like to add some functionality. We've noticed a bug in our office hours system: whenever a ticket's description contains the words "thank u", that ticket is put on the queue twice. To combat this, we'd like to define a new iterator, `TYIterator`.

If the current item's description contains the words "thank u," it should skip the next item on the queue, because we know the next item is an accidental duplicate from our buggy system. As an example, if there were 4 `OHRequest` objects on the queue with descriptions ["thank u", "thank u", "im bored", "help me"], calls to `next()` should return the 0th, 2nd, and 3rd `OHRequest` objects on the queue. Note: we are still enforcing good descriptions on the queue as well!

Hint - To check if a description contains the words "thank u", you can use:

```
curr.description.contains("thank u")
```

```
public class TYIterator extends implements OHIterator {
```

```
    public TYIterator(OHRequest queue) {
        super(queue);
    }
```

```
    @Override
```

```
    public OHRequest next() {
```

```
        OHRequest tmp = super.next();
```

```
        if (tmp != null && tmp.description.contains("thank u"))
```

```
        { tmp = super.next();
```

```
        }
```

```
        return tmp;
```

```
    }
```

4 Senior Class *Extra*

For each line in the main method of our `testPeople` class, if something is printed, write it next to the line. If the line results in an error, write next it whether it is a compile time error or runtime error, and then proceed as if that line were not there.

```

1  public class Person {
2      public String name;
3      public int age;
4
5      public Person(String name, int age) {
6          this.name = name;
7          this.age = age;
8      }
9
10     public void greet(Person other) {System.out.println("Hello, " + other.name);}
11 }
12
13
14 public class Grandma extends Person {
15
16     public Grandma(String name, int age) {
17         super(name, age);
18     }
19
20     @Override
21     public void greet(Person other) {System.out.println("Hello, young whippersnapper");}
22
23     public void greet(Grandma other) {System.out.println("How was bingo, " + other.name + "?");}
24 }
25
26 public class testPeople {
27     public static void main(String[] args) {
28         Person n = new Person("Neil", 12);
29         Person a = new Grandma("Ada", 60);
30         Grandma v = new Grandma("Vidya", 80);
31         Grandma al = new Person("Alex", 70);
32         n.greet(a);
33         n.greet(v);
34         v.greet(a);
35         v.greet((Grandma) a);
36         a.greet(n);
37         a.greet(v);
38         ((Grandma) a).greet(v);
39         ((Grandma) n).greet(v);
40     }
41 }

```

Handwritten notes next to the code:

- Next to line 28: `n`
- Next to line 29: `a p`
- Next to line 30: `v`
- Next to line 31: `al`
- Next to line 32: `11 Hello Neil`
- Next to line 33: `11 Hello vidya`
- Next to line 34: `11 Hello y...`
- Next to line 35: `11 How was bingo. Aida?`
- Next to line 36: `11 Hello, y...`
- Next to line 37: `11 Hello y...`
- Next to line 38: `11 How was bingo, vidya?`
- Next to line 39: `11 R E`