

File permissions in Linux

Project description

The research team at my organization needs to update the file permissions for certain files and directories within the projects directory. The permissions do not currently reflect the level of authorization that should be given. Checking and updating these permissions will help keep their system secure. To complete this task, I performed the following tasks:

Check file and directory details

The following code demonstrates how I used Linux commands to determine the existing permissions set for a specific directory in the file system.

```
researcher2@12f1c39459ac:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 16:09 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 17:39 ..
-rw--w---- 1 researcher2 research_team  46 Dec  9 16:09 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  9 16:09 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec  9 16:09 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  9 16:09 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_t.txt
```

The first line of the screenshot displays the command I entered, and the other lines display the output. The code lists all contents of the projects directory. I used the ls command with the -la option to display a detailed listing of the file contents that also returned hidden files. The output of my command indicates that there is one directory named drafts, one hidden file named .project_x.txt, and five other project files. The 10-character string in the first column represents the permissions set on each file or directory.

In the `/home/researcher2/projects` directory, there are five files with the following names and permissions:

- `project_k.txt`
 - User = read, write,
 - Group = read, write
 - Other = read, write
- `project_m.txt`
 - User = read, write

- Group = read
 - Other = none
- `project_r.txt`
 - User= read, write
 - Group = read, write
 - Other = read
- `project_t.txt`
 - User = read, write
 - Group = read, write
 - Other = read
- `.project_x.txt`
 - User = read, write
 - Group = write
 - Other = none

There is also one subdirectory inside the `projects` directory named `drafts`. The permissions on `drafts` are:

- User = read, write, execute
- Group = execute
- Other = none

There are also two hidden directories without names inside the `projects` directory. The permissions are:

- User = read, write, execute
- Group = execute
- Other = none

Describe the permissions string

The 10-character string can be deconstructed to determine who is authorized to access the file and their specific permissions. The characters and what they represent are as follows:

- ❖ 1st character: This character is either a `d` or hyphen (`-`) and indicates the file type. If it's a `d`, it's a directory. If it's a hyphen (`-`), it's a regular file.
- ❖ 2nd-4th characters: These characters indicate the read (`r`), write (`w`), and execute (`x`) permissions for the user. When one of these characters is a hyphen (`-`) instead, it indicates that this permission is not granted to the user.
- ❖ 5th-7th characters: These characters indicate the read (`r`), write (`w`), and execute (`x`) permissions for the group. When one of these characters is a hyphen (`-`) instead, it indicates that this permission is not granted for the group.

- ❖ 8th-10th characters: These characters indicate the read (r), write (w), and execute (x) permissions for other. This owner type consists of all other users on the system apart from the user and the group. When one of these characters is a hyphen (-) instead, that indicates that this permission is not granted for other.

For example, the file permissions for `project_t.txt` are `-rw-rw-r--`. Since the first character is a hyphen (-), this indicates that `project_t.txt` is a file, not a directory. The second, fifth, and eighth characters are all r, which indicates that user, group, and other all have read permissions. The third and sixth characters are w, which indicates that only the user and group have write permissions. No one has execute permissions for `project_t.txt`.

Change file permissions

The `project_k.txt` has write permission for others and it needs to be removed due to the organization decision.

The following code demonstrates how I used Linux commands to do this:

```
researcher2@12f1c39459ac:~/projects$ chmod o-w project_k.txt
researcher2@12f1c39459ac:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 16:09 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 17:39 ..
-rw--w---- 1 researcher2 research_team  46 Dec  9 16:09 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  9 16:09 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  9 16:09 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_t.txt
researcher2@12f1c39459ac:~/projects$
```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. The `chmod` command changes the permissions on

files and directories. The first argument indicates what permissions should be changed, and the second argument specifies the file or directory. In this example, I removed write

permissions from other for the `project_k.txt` file. After this, I used `ls -la` to review the updates I made.

Change file permissions on a hidden file

The research team at my organization recently archived `project_x.txt`. They do not want

anyone to have write access to this project, but the user and group should have read access. The following code demonstrates how I used Linux commands to change the permissions:

```
researcher2@12f1c39459ac:~/projects$ chmod u-w,g-w .project_x.txt
researcher2@12f1c39459ac:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 16:09 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 17:39 ..
-r----- 1 researcher2 research_team  46 Dec  9 16:09 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  9 16:09 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_k.txt
-rw----- 1 researcher2 research_team  46 Dec  9 16:09 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_t.txt
researcher2@12f1c39459ac:~/projects$ chmod g+r .project_x.txt
researcher2@12f1c39459ac:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 16:09 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  9 17:39 ..
-r--r----- 1 researcher2 research_team  46 Dec  9 16:09 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  9 16:09 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_k.txt
-rw----- 1 researcher2 research_team  46 Dec  9 16:09 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 16:09 project_t.txt
researcher2@12f1c39459ac:~/projects$
```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. I know `.project_x.txt` is a hidden file because it starts with a period (`.`). In this example, I removed write permissions from the user and group, and added read permissions to the group. I removed write permissions from the user with `u-w`. Then, I removed write permissions from the group with `g-w`, and added read permissions to the group with `g+r`.

Change directory permissions

My organization only wants the `researcher2` user to have access to the `drafts` directory and its contents. This means that no one other than `researcher2` should have execute permissions.

The following code demonstrates how I used Linux commands to change the permissions:

```

/home/researcher2
researcher2@4b16f7e3d6e5:~$ ls
projects
researcher2@4b16f7e3d6e5:~$ cd projects
researcher2@4b16f7e3d6e5:~/projects$ ls -l
total 20
drwx--x--- 2 researcher2 research_team 4096 Dec  9 17:53 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec  9 17:53 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  9 17:53 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 17:53 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 17:53 project_t.txt
researcher2@4b16f7e3d6e5:~/projects$ chmod g-x drafts
researcher2@4b16f7e3d6e5:~/projects$ ls -l
total 20
drwx----- 2 researcher2 research_team 4096 Dec  9 17:53 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec  9 17:53 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  9 17:53 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 17:53 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  9 17:53 project_t.txt
researcher2@4b16f7e3d6e5:~/projects$ █

```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. I previously determined that the group had execute permissions, so I used the `chmod` command to remove them. The `researcher2` user already had execute permissions, so they did not need to be added.

Summary

I changed multiple permissions to match the level of authorization my organization wanted for files and directories in the `projects` directory. The first step in this was using `ls -la` to check the permissions for the directory. This informed my decisions in the following steps. I then used the `chmod` command multiple times to change the permissions on files and directories.