### 停车场建表语句

```
CREATE TABLE `parkinglot` (
    `ParkingLotID` int NOT NULL,
    `ParkingName` varchar(255) NOT NULL,
    `Longitude` decimal(9,6) NOT NULL,
    `Latitude` decimal(9,6) NOT NULL,
    `Capacity` int DEFAULT NULL,
    `Rates` decimal(10,2) NOT NULL,
    PRIMARY KEY (`ParkingLotID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
```

## 停车位建表语句

# 用户建表语句

```
CREATE TABLE `users` (
  `UserID` int NOT NULL,
  `Username` varchar(255) CHARACTER SET utf8mb4 COLLATE utf8mb4_0900_ai_ci NOT NULL,
  `Password` varchar(255) CHARACTER SET utf8mb4 COLLATE utf8mb4_0900_ai_ci NOT NULL,
  `Tel` varchar(36) CHARACTER SET utf8mb4 COLLATE utf8mb4_0900_ai_ci DEFAULT NULL,
  PRIMARY KEY (`UserID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
```

### 车辆建表语句

```
CREATE TABLE `vehicle` (
   `VehicleID` int NOT NULL,
   `UserID` int DEFAULT NULL,
   `PlateNumber` varchar(255) DEFAULT NULL,
   `Color` varchar(255) DEFAULT NULL,
   PRIMARY KEY (`VehicleID`),
   KEY `UID` (`UserID`),
   CONSTRAINT `UID` FOREIGN KEY (`UserID`) REFERENCES `users` (`UserID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
```

## 预定建表语句

```
CREATE TABLE `reservation` (
  `ReservationID` int NOT NULL,
  `StartTime` datetime DEFAULT NULL,
  `EndTime` datetime DEFAULT NULL,
  `SpaceID` int DEFAULT NULL,
  `VehicleID` int DEFAULT NULL,
  `LotID` int DEFAULT NULL,
  `Status` enum('Completed','Cancelled','Doing') DEFAULT NULL,
 PRIMARY KEY (`ReservationID`),
 KEY `SID` (`SpaceID`),
 KEY `VID` (`VehicleID`),
 KEY `LID` (`LotID`),
 CONSTRAINT `LID` FOREIGN KEY (`LotID`) REFERENCES `parkinglot` (`ParkingLotID`),
 CONSTRAINT `SID` FOREIGN KEY (`SpaceID`), REFERENCES `parkingspace` (`SpaceID`),
 CONSTRAINT `VID` FOREIGN KEY (`VehicleID`) REFERENCES `vehicle` (`VehicleID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 0900 ai ci;
```

### 支付记录建表语句

```
CREATE TABLE `paymentrecord` (
    `PaymentID` int NOT NULL,
    `ReservationID` int DEFAULT NULL,
    `Amount` double DEFAULT NULL,
    `PaymentTimestamp` datetime DEFAULT NULL,
    `PaymentMethod` varchar(255) DEFAULT NULL,
    PRIMARY KEY (`PaymentID`),
    KEY `RID` (`ReservationID`),
    CONSTRAINT `RID` FOREIGN KEY (`ReservationID`) REFERENCES `reservation` (`ReservationID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
```

#### 停车记录建表语句

```
CREATE TABLE `parkingrecord` (
  `RecordID` int NOT NULL,
  `SpaceID` int DEFAULT NULL,
  `VehicleID` int DEFAULT NULL,
  `LotID` int DEFAULT NULL,
  `StartTime` datetime DEFAULT NULL,
  `EndTime` datetime DEFAULT NULL,
  `Fee` double DEFAULT NULL,
  PRIMARY KEY (`RecordID`),
  KEY `PSID` (`SpaceID`),
  KEY `VEID` (`VehicleID`),
  KEY `PALID` (`LotID`),
  CONSTRAINT `PALID` FOREIGN KEY (`LotID`) REFERENCES `parkinglot` (`ParkingLotID`),
  CONSTRAINT `PSID` FOREIGN KEY (`SpaceID`) REFERENCES `parkingspace` (`SpaceID`),
  CONSTRAINT `VEID` FOREIGN KEY (`VehicleID`) REFERENCES `vehicle` (`VehicleID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 0900 ai ci;
```

### 违规记录建表语句

```
CREATE TABLE `violationrecord` (
   `ViolationID` int NOT NULL,
   `RecordID` int DEFAULT NULL,
   `FineAmount` double DEFAULT NULL,
   `ViolationType` enum('OVERSTAY','NOPAY') CHARACTER SET utf8mb4 COLLATE utf8mb4_0900_ai_ci DEF#
   `Status` enum('PAID','UNPAID','DISPUTED') DEFAULT NULL,
   PRIMARY KEY (`ViolationID`),
   KEY `REID` (`RecordID`),
   CONSTRAINT `REID` FOREIGN KEY (`RecordID`) REFERENCES `parkingrecord` (`RecordID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci;
```