

Product Tests Report

Product name: See3CAM_CU27

Model number: See3CAM_CU27_CHLCC_BX_H02R1

The products mentioned above have been tested in accordance with the tests listed below and were found to comply during the development phase of the product.

1. BS EN 50130-5:2011 Alarm systems Part 5: Environmental test methods

Test specification	Specific Test description Class III weather protected Outdoor, fixed equipment	Comments	Status PASS/FAIL
Dry heat operational IEC 60068-2-2:2007	Temp. +60°C, duration 16 hours.	Tested in operating condition	PASS
Cold operational IEC 60068-2-1:2007	Temp. -30°C, duration 16 hours.	Tested in operating condition	PASS
Damp heat cyclic (operational) IEC 60068-2-30:2005	Temp. 30°C at 95% of RH with non-condensing, 55°C at 93% of RH with non-condensing (2 cycles, 12 hours dwell per cycle).	Tested in operating condition	PASS
Vibration sinusoidal operational IEC 60068-2-6:2008	Frequency range: 10-150Hz Acceleration: 10m/s ² Axis of excitation: X, Y and Z Sweep rate: 1 octave/min Number of sweeps: 20 sweeps/axis.	Tested in operating condition	PASS

2. Additional tests by e-con:

Test specification	Specific test description	Comments	Status PASS/FAIL
HALT (Highly Accelerated Life Test)	Overstress test to Fail. Determination of fail limits for • Low ambient temperature, Step raise +20°C to -40°C • High ambient temperature, Step raise + 20°C to +130°C • Rapid thermal Cycling -40°C to +130°C (5 cycles ,40 minutes dwell per cycle)	Tested in operating condition	PASS
Low storage temperature test	Stress test with 16 hours at specified temperature. • Low temperature -40°C	Tested under non-operating condition	PASS
High storage temperature test	Stress test with 16 hours at specified temperature. • High temperature 85°C	Tested under non-operating condition	PASS
Humidity storage test	Temp. 30°C at 95% of RH with non-condensing, 55°C at 93% of RH with non-condensing (2 cycles,12 hours dwell per cycle)	Tested under non-operating condition	PASS
Retention Period:3 Years	If this is a copy, unless otherwise specified, it is uncontrolled. You must verify the revision before use		Format #: EPQT/F/007 Rev #: 1.2

Product Tests Report

Endurance test	Continuous streaming test for 21 days at 60°C	Tested in operating condition	PASS
	Continuous streaming test for 21 days at room temperature.		
	Continuous streaming test for 21 days at 40°C		

Test conducted by:	P. Thivan Singh	STATUS: Pass/Fail	PASS
Test validated by:	J. Suresh		
Test approved by:	S. Karthikeyan		