

Product Tests Report

Product name: See3CAM_CU27
Model number: See3CAM_CU27_CHL_TC

The products mentioned above have been tested in accordance with the tests listed below and were found to comply during the development phase of the product.

1.BS EN 50130-5:2011 Alarm systems Part 5: Environmental test methods Class III weather protected outdoor, fixed equipment

Test specification	Specific Test description	Comments	Status PASS/FAIL
Dry heat operational IEC 60068-2-2:2007	Temp. +60°C, duration 16 hours.	Tested in operating condition	PASS
Cold operational IEC 60068-2-1:2007	Temp. -30°C, duration 16 hours.	Tested in operating condition	PASS
Damp heat cyclic (operational) IEC 60068-2-30:2005	Temp. 30°C at 95% of RH with non-condensing, 55°C at 93% of RH with non-condensing (2 cycles ,12 hours dwell per cycle)	Tested in operating condition	PASS
Vibration sinusoidal operational IEC 60068-2-6:2008	Frequency range: 10-150Hz Acceleration: 10m/s ² Axis of excitation: X, Y and Z Sweep rate: 1 octave/min. Number of sweeps: 20 sweeps/axis.	Tested in operating condition	PASS

2.Additional tests by e-con

Test specification	Specific Test description	Comments	Status PASS/FAIL
HALT (Highly Accelerated Life Test)	Overstress test to fail. Determination of fail limits for - Low ambient temperature, step raise +20°C to -40°C increased in 10°C per steps - High ambient temperature, step raise + 20°C to +120°C increased in 10°C per steps - Rapid thermal cycling -40°C to +120°C (5cycles ,40minutes dwell per cycle)	Tested in operating condition	PASS
HASA (Highly Accelerated Stress Audit)	Stress test performed within its operating range. -30°C to +60°C (5 cycles,1 hour dwell per cycle).	Tested in operating condition	PASS

Retention Period:3 Years	If this is a copy, unless otherwise specified, it is uncontrolled. You must verify the revision before use	Format #: EPQT/F/007 Rev #: 1.2
--------------------------	---	------------------------------------

Product Tests Report

Thermal power cycling test	Power on/off switching test in combination with thermal cycling. - Thermal cycling range: -30°C to +60°C - Duration: 500 cycles continuously (on/off for every 8 seconds)	Tested in operating condition	PASS
Low storage temperature test	Stress test with 16 hours at specified temperature. Low temperature -40°C	Tested under non-operating condition	PASS
High storage temperature test	Stress test with 16 hours at specified temperature. High temperature +85°C	Tested under non-operating condition	PASS
Humidity storage test	Temp. 30°C at 95% of RH with non-condensing, 55°C at 93% of RH with non-condensing (2 cycles ,12 hours dwell per cycle).	Tested under non-operating condition	PASS
Endurance test	Continuous streaming test for 21 days at 60°C	Tested in operating condition	PASS
	Continuous streaming test for 21 days at room temperature.	Tested in operating condition	

Test conducted by:	Gomathi	STATUS: Pass/Fail	PASS
Test validated by:	J. Suresh		
Test approved by:	S. Karthikeyan		