



QwenPI VLA Training Optimization

NVIDIA DevTech

Results at a Glance

starVLA QwenPI: Qwen3.5-VL 4B + flow-matching action head, ZeRO-2 full fine-tune

3.2×

Faster training step

800 → 249 ms/step (bs 8)

257

Samples / node / s

up from 80 at hand-off

23.1%

**Model FLOPs
utilization**

up from 7.2% (bf16 peak)

340

Samples / node / s


at bs 24 — 1.7× the 200
target

Method: every optimization was profiled with Nsight Systems and validated with a same-node A/B run plus loss-trajectory checks — no stacked guesses, measured deltas only.

Measurement: 8×H200 (NVLink), 60 steps, steady-state p50 of steps 21–44, per-GPU batch 8 unless noted.

Model & Workload


7.5B trainable parameters: Qwen3.5-VL 4B backbone + 3B flow-matching action expert



Training configuration	
Parameters	7.52B, all trainable (bf16)
Parallelism	DeepSpeed ZeRO-2, DP=8, 1 node
ZeRO-2 tuning	bucket 1.5e9, reduce_scatter off
Optimizer	AdamW, fp32 master (sharded)
Batch	8 / GPU → 64 global (up to 24/GPU)
Sequence	text fixed at 192 (left-pad)
Data	LIBERO manipulation, 2 views/sample
Hardware	8×H200 SXM, full NVLink
Software	torch 2.7.1 / NCCL 2.26.2 / HF 5.3 / FA2.8

Baseline Diagnosis: Where Did 800 ms Go?


Five problems visible in one baseline step (nsys, 806.9 ms) — each maps to a fix



1 · fp32 action head	201 ms fp32 GEMMs vs 66 ms bf16 — 2.96B DiT outside autocast	bf16 DiT (−218 ms)
2 · CPU inside forward()	first ~40 ms of every step: compute idle, HF preprocessing on critical path	collate in DataLoader workers
3 · Per-step syncs	loss readback, DS timers, MRoPE position-ids, mm-merge check	sync-free logging + caches (2+3: −117)
4 · Launch-bound eager	13,868 launches/step, median 8 μ s, 79% < 20 μ s — 205 ms pure idle	CUDA Graphs + compile (−126 ms)
5 · Comm configuration	15 small AR buckets; 22 ms redundant flatten; exposed AllGather tail	bucket 1.5e9 + reduce_scatter off (−22)

Optimization Roadmap

Actual step time (ms) after each optimization lands — same node, steady-state p50



Cumulative levels re-measured per step with nsys attached on rank 0 (~5% overhead). The torch 2.7.1 + NCCL 2.26.2 environment upgrade landed between the bf16 and pipeline levels and is folded into the Pipeline bar. Final 249 ms = clean steady-state p50 of merged main.

Fix 1 · bf16 Action Head: -218 ms

800 → 582 ms. One config knob — and numerically a no-op for training

GPU busy by kernel class (baseline step, 543 ms)

201 ms

fp32 GEMM — all from the action head

126 ms

other (fla/GDN, embeddings, misc)

102 ms

elementwise / norm / reduce

66 ms

bf16 GEMM (Qwen3.5)

27 ms

copy / gather / cat


22 ms

attention kernels

37% of all GPU math is fp32 — all of it from the 2.96B DiT outside the bf16 autocast region.

Why was it fp32 at all? Inherited caution for diffusion numerics. Only the timestep embedding and the loss math need fp32 — we kept exactly those in fp32 and moved the transformer body to bf16 (dit_dtype knob, one-line rollback).

Same seed, 200 steps: loss is unchanged




action loss, training steps 1 → 200 · mean per-step $|\Delta| = 0.04$ (run-to-run noise floor) · final: 0.549 vs 0.533


Fix 2+3 · Keep the GPU Fed: -117 ms

545 → 428 ms. 205 ms of every baseline step is GPU idle

Before — everything serialized inside forward()



After — CPU work overlaps the previous step




red = per-step syncs (loss readback, DS timers, mm-merge check): each one drains the launch pipeline and strands the GPU

Preprocess in workers	HF processor (image patches + tokenize) runs in 8 workers, overlapped with the previous step	~40 ms off the critical path
Side-stream H2D	pinned host batch + dedicated copy stream, overlaps the ZeRO-2 optimizer tail	upload hidden
Sync-free logging	DeepSpeed timers unsynchronized; loss .item() only on logging steps	2 device syncs / step removed
MRoPE position-id cache	3D position ids precomputed on CPU, cached by image grid	~13 ms sync eliminated
+ Mixed attention	vision tower FA2 varlen (16 images / kernel); text stays SDPA — full FA2 measured slower at seq 192	-30 ms (428 → 398)

CUDA Graphs & torch.compile: -126 ms

398 → 271 ms. Replay the whole network as six graphs instead of ~14k eager launches



- **Whole-model compile is blocked: the hybrid GDN layers (fla library) graph-break in dynamo**
- So we capture around it: 32 text layers grouped into 4 CUDA Graphs of 8 layers each
- Vision tower captured as a single graph (FA2 kernels inside, host-cached max_seqlen)
- Static shapes make it possible: text fixed at 192, encoder padded to 192
- Sync-free multimodal merge: removed a device-to-host validation readback in the image-token scatter


Kernel launches: 13.9k → 6.4k per step. CPU launch cost leaves the critical path; GPU idle collapses.

ZeRO-2 Comm Tuning & the Final Ledger

271 → 249 ms. Fewer, larger collectives — and an honest ledger of what remains

- `reduce_bucket_size` 5e8 → 1.5e9: 6 gradient AllReduces per step instead of ~20, scoped to this model's config only
- `reduce_scatter=false`: drops DeepSpeed's redundant per-bucket flatten (`CatArrayBatchedCopy`) ahead of each AllReduce
- Verified NOT bandwidth-bound: AllReduce microbenchmark hits 478 GB/s bus bandwidth — the NVLink per-direction ceiling. The remaining exposed comm can only shrink by sending fewer bytes.


Per-step time ledger (same accounting, one steady step from each `nsys` capture)



Gradient AllReduce 15.1 GB/step + optimizer AllGather 15.1 GB/step (bf16). Idle from 254 ms to 43 ms.

Batch Scaling: Sweet Spot at 24 per GPU

Same optimized config, only per-GPU batch changes — peak 340 samples/node/s



- Batching amortizes launch and comm costs: MFU climbs 23% → 30.5%
- bs 32 regresses hard (986 ms/step): not OOM, not the dataloader — memory-pressure effects under investigation
- Larger global batch (192) changes optimization dynamics — needs a convergence run before adoption

What We Ruled Out — and How

Negative results are results: every hypothesis got a same-node experiment

Hypothesis	Experiment	Verdict
FA2 for the text stack	A/B at seq 192	Slower (+10 ms): unpad/repad overhead exceeds kernel gains at short sequences
“NCCL is misconfigured”	Forced protocols, NCCL_DEBUG, microbenchmark	AllReduce already at 478 GB/s busbw = NVLink ceiling; kernel-name suffix was a red herring
masked_scatter nonzero sync	index_copy patch, bitwise-equal unit test	0 ms: the AllReduce tail is gradient-readiness-bound, so hiding the sync moves nothing
MRoPE cache still needed?	Toggle at final config	Neutral at the tip (CUDA Graphs hide it) — kept for CPU headroom, one-knob rollback
Whole-model torch.compile	Compile attempts on torch 2.6 & 2.7	Hybrid GDN layers graph-break in dynamo → group-graph capture instead
FlashQLA GDN kernels	Kernel-time ceiling analysis	Only ~10.5 ms/step of GDN time exists; needs torch $\geq$ 2.8 — deferred, not worth the risk now

Remaining Headroom & Next Steps

Where the next milliseconds live, ranked by ceiling — measured, not guessed



Backward GEMMs at the power wall [fp8 territory]

Sustained GEMM throughput caps at ~622 TFLOPS on this node (power, not occupancy). The only lever left for the math itself is fp8.



Exposed communication (~30-55 ms) [compression]

Bandwidth is at the NVLink ceiling; bytes are the only lever — 1-bit Adam / gradient compression, with convergence sign-off.



Optimizer tail (~25 ms) [compiled autograd]

ZeRO-2 optimizer step + AllGather at step end; compiled autograd / fused optimizer can overlap part of it.



Scale-out readiness [deployment]

On split-topology nodes (4+4 NVLink islands) set NCCL_P2P_LEVEL=NVL — first collective hangs otherwise. bs24 adoption gated on a convergence run.