

Document title
unregister-system HTTP/TLS/URL
Date
2023-03-03
Author
Tamás Bordi
Contact
tbordi@aitia.ai

Document type IDD
Version
4.6.0
Status
RELEASE
Page
1 (7)

unregister-system HTTP/TLS/URL

Interface Design Description

Abstract

This document describes a HTTP protocol with TLS payload security and URL encoding variant of the **unregister-system** service.



Version 4.6.0 Status RELEASE Page 2 (7)

Contents

1	Overview	3
2	Interface Description	4
3	Data Models	5
	3.1 struct QueryParams	5
	3.2 Primitives	5
4	References	6
5	Revision History	7
	5.1 Amendments	7
	5.2 Quality Assurance	7



Version 4.6.0 Status RELEASE Page 3 (7)

1 Overview

This document describes the **unregister-system** service interface, which is enables autonomous system unregistration. It's implemented using protocol, encoding as stated in the following table:

Profile type	Type	Version
Transfer protocol	HTTP	1.1
Data encryption	TLS	1.3
Encoding	URL	-
Compression	N/A	-

Table 1: Communication and semantics details used for the unregister-system service interface

This document provides the Interface Design Description IDD to the *unregister-system – Service Description* document. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the **unregister-system** service HTTP/TLS/URL interface in details.



Version 4.6.0 Status RELEASE Page 4 (7)

2 Interface Description

The service responses with the status code 200 Ok if called successfully. The error codes are, 400 Bad Request if request is malformed, 401 Unauthorized if improper client side certificate is provided, 500 Internal Server Error if Service Registry is unavailable.

DELETE /serviceregistry/unregister-system?system_name={systemName}&address={address}&port={port}}
HTTP/1.1

Listing 1: An unregister-system invocation.

Version 4.6.0 Status RELEASE Page 5 (7)

3 Data Models

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote an Object that must contain certain fields, or names, with values conforming to explicitly named types. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.2, which are used to represent things like hashes, identifiers and texts.

3.1 struct QueryParams

This structure is used to unregister a system from Service Registry.

Field	Type Mandatory		Description		
systemName	Name	yes	Identifier of the system.		
address	Address	no	Network address.		
port	PortNumber	yes	Port of the system.		

3.2 Primitives

Туре	Description
String	An arbitrary UTF-8 string.
Number	Any IEEE 754 binary64 floating point number [1], except for +Inf, -Inf and NaN.

With these primitives now available, we proceed to define all the types specified in the **uregister-system** SD primitives either as *aliases* or *structs*. An *alias* is a renaming of an existing type, but with some further details about how it is intended to be used. Structs are described in the beginning of the parent section. The types are listed by name in alphabetical order.

3.2.1 alias Address = String

A string representation of a network address. An address can be a version 4 IP address (RFC 791), a version 6 IP address (RFC 2460) or a DNS name (RFC 1034).

3.2.2 alias Name = String

A String indentifier that is intended to be both human and machine-readable.

3.2.3 alias PortNumber = Number

Decimal Number in the range of 0-65535.



Version 4.6.0 Status RELEASE Page 6 (7)

4 References

[1]	М.	Cowlishaw,	"IEEE	Standard	d for Flo	ating-Point	t Arithmetic,"	IEEE	Std	754-2019	(Revision	of II	EEE
	754	4-2008), July	/ 2019.	[Online].	Available	: https://do	i.org/10.1109	IEEES	STD.2	019.87662	29		

Version 4.6.0 Status RELEASE Page 7 (7)

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	YYYY-MM-DD	4.6.0		Xxx Yyy

5.2 Quality Assurance

No).	Date	Version	Approved by
1		YYYY-MM-DD	4.6.0	Xxx Yyy