

Database Systems, CSCI 4380-01  
Homework # 2 Answers  
Due Thursday September 19, 2019 at 11:59:59 PM

**Question 1.** Given the following set of functional dependencies, convert it to a minimal basis. Show the main steps, list the changes and explain why the change was made.

$$\mathcal{F} = \{BCF \rightarrow CE, AD \rightarrow EF, BC \rightarrow AF, ACD \rightarrow DF\}$$

**Answer.**

First, convert to a basis:

$$\mathcal{F} = \{BCF \rightarrow C, BCF \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F, ACD \rightarrow D, ACD \rightarrow F\}$$

Remove all trivial functional dependencies:

$$\mathcal{F} = \{BCF \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F, ACD \rightarrow F\}$$

Remove all dependencies implied by others. We will check all one by one, but I will show the successful results:

Can we remove  $ACD \rightarrow F$ ? Given:  $\mathcal{F} = \{BCF \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F\}$

$ACD^+ = \{A, C, D, E, F\}$ . Since it includes  $F$ , then we can remove this functional dependency. (Note that we cannot remove  $AD \rightarrow F$ !)

Next step: Can we simplify any functional dependency by removing attributes from the left hand side? Can we replace  $BCF \rightarrow E$  with  $BC \rightarrow E$ ?

$$\mathcal{F} = \{BCF \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F\}, BC^+ = \{B, C, A, F, E\}$$

$$\mathcal{F}_2 = \{BC \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F\}, BC^+ = \{B, C, A, F, E\}$$

Since, they are equal, we can remove  $F$  in  $BCF \rightarrow E$ .

The final set of functional dependencies:  $\mathcal{F} = \{BC \rightarrow E, AD \rightarrow E, AD \rightarrow F, BC \rightarrow A, BC \rightarrow F\}$   
You can also represent it as:  $\mathcal{F} = \{BC \rightarrow AEF, AD \rightarrow EF\}$

**Question 2.** You are given the relation  $R(A, B, C, D, E, F, G, H)$  with the set  $\mathcal{F}$  of functional dependencies:  $\mathcal{F} = \{AB \rightarrow CD, BD \rightarrow EF, AD \rightarrow G, F \rightarrow B\}$ .

Given the decomposition:  $R_1(A, F, H), R_2(A, B, C, D), R_3(B, D, E, F), R_4(A, D, G)$ , check if the decomposition is lossless or not using the Chase algorithm. Show the crucial steps and discuss whether it is lossy or lossless.

**Answer.**

Let's first draw the canonical database for this:

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i> <sub>1</sub>	<i>c</i> <sub>1</sub>	<i>d</i> <sub>1</sub>	<i>e</i> <sub>1</sub>	<i>f</i>	<i>g</i> <sub>1</sub>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i> <sub>2</sub>	<i>f</i> <sub>2</sub>	<i>g</i> <sub>2</sub>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

Apply  $BD \rightarrow EF$ :

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i> <sub>1</sub>	<i>c</i> <sub>1</sub>	<i>d</i> <sub>1</sub>	<i>e</i> <sub>1</sub>	<i>f</i>	<i>g</i> <sub>1</sub>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>2</sub>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

Apply  $F \rightarrow B$ :

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i>	<i>c</i> <sub>1</sub>	<i>d</i> <sub>1</sub>	<i>e</i> <sub>1</sub>	<i>f</i>	<i>g</i> <sub>1</sub>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>2</sub>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

Apply  $AB \rightarrow CD$ :

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i> <sub>1</sub>	<i>f</i>	<i>g</i> <sub>1</sub>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>2</sub>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

Apply  $AD \rightarrow G$ :

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i> <sub>1</sub>	<i>f</i>	<i>g</i>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

Apply  $BD \rightarrow EF$ :

A	B	C	D	E	F	G	H
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>	<i>h</i>
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>	<i>h</i> <sub>2</sub>
<i>a</i> <sub>3</sub>	<i>b</i>	<i>c</i> <sub>3</sub>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i> <sub>3</sub>	<i>h</i> <sub>3</sub>
<i>a</i>	<i>b</i> <sub>4</sub>	<i>c</i> <sub>4</sub>	<i>d</i>	<i>e</i> <sub>4</sub>	<i>f</i> <sub>4</sub>	<i>g</i>	<i>h</i> <sub>4</sub>

First row has no subscripts, hence this decomposition is lossless.

Note these may not be the most efficient sequence of steps. However, the order in which you apply the actual functional dependencies is not important. Continue applying them and stop when there is no possible changes or a row with no subscript is found.

**Question 3.** You are given the following relations and set of functional dependencies. For each relation, (i) list the keys, (ii) check if relation is in BCNF or not, (iii) check if the relation is in 3NF or not. Explain your reasoning.

- (a)  $R1(A, B, C, D, E)$ ,  $\mathcal{F}_1 = \{AB \rightarrow CD, ABC \rightarrow E\}$

**Answer.** Key: AB. It is both in BCNF and 3NF as both functional dependencies have a superkey on the left.

- (b)  $R2(A, B, C, D, E)$ ,  $\mathcal{F}_2 = \{AB \rightarrow CD, BC \rightarrow E\}$

**Answer.** Key: AB.

It is not in BCNF because  $BC$  is not a superkey but it is on the left hand side of a functional dependency.

It is not in 3NF because  $BC$  is not a superkey and  $E$  is not a prime attribute.

- (c)  $R3(A, B, C, D, E)$ ,  $\mathcal{F}_3 = \{AB \rightarrow CD, ABC \rightarrow E, ED \rightarrow A\}$

**Answer.** Key: AB, BED.

It is not in BCNF because in  $ED \rightarrow A$ ,  $ED$  is not a superkey.

It is in 3NF because in the above functional dependency,  $A$  is a prime attribute.