## Quiz 1, Fall 2018 CSCI 4380 Database Systems Time: 25 minutes

Name 1:	
Name 2:	
Name 3:	<u> </u>

## Rules.

- Open book and notes. Do not use any electronic tools including your computer.
- You can talk to anyone in class. If you know the answer, help someone else in class.
- Each quiz must be by at least two and at most three people. Most quizzes should be by three people, so find someone to talk to. Put your name on one quiz only.

Question (Points: a-8 b-8 c-9). You are given the following data model for elections:

```
Parties(<u>name</u>, url, description, foundedon)
Elections(<u>id</u>, name, etype, state, howoften)
Person(<u>id</u>, fname, lname, bio, birthday)
Candidates(personid, eid, year, partyname, ballotposition, numvotes)
```

Keys are underlined. There are many parties (even though some small) and many elections. Each election has a name and a etype. elections.type is either 'state' or 'federal'. For state elections there is a state listed (e.g. 'NY'. Attribute elections.howoften lists how many years this election occurs regularly.

People run as candidates for different elections, which is stored in the Candidates relation. Each candidate runs for a specific party. If they are independent, candidates.partyname is NULL. Ballotposition is a number (1,2,3) that shows where they appear on the ballot. If they are not on any ballot (write-in candidate), then ballotposition is zero.

Answer the following questions:

(a) For the following, circle one of yes/no based on the relations above and its keys, and write a short one line explanation:

Can a candidate run for tw	o different elections (i.e.	different eid) in the same	YES
year?			

Yes, the primary key has candidate, year and eid, so it is possible to have two tuples with the same year, candidate but different eids.

Can a candidate run for two different ballot positions in the same election NO (same eid) in the same year?

No, for a given candidate, year and eid, there is a single tuple and that has a single ballot position.

Can two different elections have the same name?

YES

Given an eid, the name is fixed. But it is possible to have the same name but different eids.

Can the same person be candidate for different political parties in the same YES year?

It is possible if the candidate is running in two different elections in the same year and the parties for these elections can be different.

(b) Write the following query using relational algebra:

Return the name of all parties that had candidates running only for 'federal' elections, but no candidates in 'state' elections.

## Answer.

$$R1 = \Pi_{partyname}((\sigma_{\text{etype='federal'}}, Elections) \bowtie_{id=eid} Candidates)$$
  
 $R2 = \Pi_{partyname}((\sigma_{\text{etype='state'}}, Elections) \bowtie_{id=eid} Candidates)$   
 $Result = R1 - R2$ 

(c) Write the following query using relational algebra:

Return the name of all people who ran as a candidate for at least two different political parties for the same election in different years.

## Answer.

$$\begin{array}{lcl} R1[p1,eid1,year1,party1] & = & \Pi_{personid,eid,year,partyname} \, Candidates \\ R2[p2,eid2,year2,party2] & = & R1 \\ & R3 & = & R1 \bowtie_{p1=p2 \text{ and } eid1=eid2 \text{ and } party1 <> part2 \text{ and } year1 <> year2 } \, R2 \\ & Result & = & \Pi_{fname,lname} \, (R3 \bowtie_{p1=id} \, Person) \end{array}$$