

New submission for: Lecture Exercise 21

Due: 11/22/2020 @ 11:59 PM EST

Use the following information when answering all the questions below. Assume all indices are 3 levels (root, internal level and leaf).

Relation R(A,B,C,D,E): TUPLES(R)=200,000 - PAGES(R)=5,000

Relation S(F,G): TUPLES(S)=800,000 - PAGES(S)=6,000

Index I1 on R(A,D) with 500 leaf nodes

Index I2 on R(C,D) with 1,250 leaf nodes

Index I3 on R(D,A,B,C) with 4,000 leaf nodes

Condition	Number of matching tuples
R.C='corriedale'	40
'corridale'<= R.C and R.C <='karakul'	2,000
R.D=200	1,000
R.D=200 and R.C='corriedale'	8
R.D=200 and 'corridale'<= R.C and R.C <='karakul'	400

Note that cost of index scan for a query includes the cost scanning the index and the cost of reading matching tuples if necessary. In your computations, always use the worst case assumptions.

1. You are given the following query: SELECT A,B FROM R WHERE R.C='corriedale' and R.D=200

Check all options below that apply are correct for answering this query:

- ☐ Cost of index scan using I3 is 5,002
- ☐ Cost of index scan using I1 is 502
- ☒ Cost of sequential scan is 5,000
- ☐ Cost of index scan using I1 is 1,402
- ☐ Cost of index scan using I3 is 4,002
- ☐ Cost of index scan using I1 is 8
- ☐ Cost of index scan using I1 is 13
- ☒ Cost of index scan using I2 is 12
- ☒ Cost of index scan using I1 is 1,502
- ☐ Cost of index scan using I2 is 10
- ☐ None of these options are correct.
- ☐ Cost of sequential scan is 200,000
- ☐ Cost of index scan using I3 is 4
- ☐ Cost of index scan using I2 is 1003
- ☐ Cost of index scan using I2 is 44
- ☐ Cost of index scan using I1 is 10
- ☐ Cost of index scan using I2 is 1,252
- ☐ Cost of index scan using I2 is 3
- ☐ Cost of index scan using I3 is 4,010

ClearUse Most Recent Submission

2. You are given the following query: SELECT A,B FROM R WHERE R.D=200

Check all options below that apply are correct:

- ☐ Cost of index scan using I3 is 5,002
- ☐ Cost of index scan using I1 is 502
- ☒ Cost of sequential scan is 5,000
- ☐ Cost of index scan using I1 is 1,005
- ☐ Cost of index scan using I3 is 4,002
- ☐ Cost of index scan using I1 is 8
- ☐ Cost of index scan using I1 is 13
- ☐ Cost of index scan using I2 is 12
- ☒ Cost of index scan using I1 is 1,502
- ☐ Cost of index scan using I2 is 10
- ☐ None of these options are correct.
- ☐ Cost of sequential scan is 200,000
- ☐ Cost of index scan using I3 is 4
- ☐ Cost of index scan using I2 is 1003
- ☐ Cost of index scan using I2 is 44
- ☐ Cost of index scan using I1 is 10
- ☐ Cost of index scan using I2 is 1,252
- ☐ Cost of index scan using I2 is 3
- ☐ Cost of index scan using I3 is 4,010

ClearUse Most Recent Submission

3. You are given the following query: SELECT A,B FROM R WHERE 'corridale'<= R.C and R.C <='karakul' and R.D=200

Check all options below that apply are correct:

- ☐ Cost of sequential scan is 200,000
- ☒ Cost of index scan using I2 is 414
- ☐ Cost of index scan using I3 is 4,002
- ☐ Cost of index scan using I1 is 502
- ☐ Cost of index scan using I1 is 10
- ☐ None of these options are correct.
- ☐ Cost of index scan using I3 is 4
- ☐ Cost of index scan using I1 is 8
- ☐ Cost of index scan using I2 is 14
- ☐ Cost of index scan using I3 is 4,402
- ☐ Cost of index scan using I2 is 4
- ☐ Cost of index scan using I2 is 1,252
- ☐ Cost of index scan using I1 is 1,005
- ☐ Cost of index scan using I1 is 13
- ☒ Cost of index scan using I1 is 1,502
- ☐ Cost of index scan using I3 is 6,002
- ☐ Cost of index scan using I2 is 2,014
- ☐ Cost of index scan using I2 is 404
- ☒ Cost of sequential scan is 5,000
- ☐ Cost of index scan using I2 is 2,004

ClearUse Most Recent Submission

4. Suppose you are joining R and S using block nested loop join (BNLJ). Check all options below that are correct. Note: R join S means R is the outer and S is the inner relation (similarly S join S means S is the outer and R is the inner relation).

- ☐ BNLJ Cost with M=1,001 for S join R is: 11,000
- ☒ BNLJ Cost with M=2,001 for R join S is: 23,000
- ☐ BNLJ Cost with M=1,001 for R join S is: 11,000
- ☒ BNLJ Cost with M=1,001 for S join R is: 36,000
- ☐ BNLJ Cost with M=2,001 for R join S is: 11,000
- ☐ BNLJ Cost with M=10,001 for R join S is: 10,000
- ☐ BNLJ Cost with M=10,001 for R join S is: 23,000
- ☐ BNLJ Cost with M=10,001 for R join S is: 35,000
- ☐ BNLJ Cost with M=1,001 for R join S is: 36,000
- ☐ BNLJ Cost with M=2,001 for R join S is: 24,000
- ☐ BNLJ Cost with M=10,001 for R join S is: 36,000
- ☐ BNLJ Cost with M=1,001 for S join R is: 35,000
- ☒ BNLJ Cost with M=1,001 for R join S is: 35,000
- ☐ BNLJ Cost with M=2,001 for R join S is: 17,000
- ☐ BNLJ Cost with M=2,001 for R join S is: 18,000
- ☐ BNLJ Cost with M=10,001 for R join S is: 24,000
- ☒ BNLJ Cost with M=10,001 for R join S is: 11,000

ClearUse Most Recent Submission

By clicking "Submit" you are confirming that you have read, understand, and agree to follow the Academic Integrity Policy.

Submit

Select Submission Version:Version #3Score: 50 / 50GRADE THIS VERSIONDo Not Grade This Assignment

Note: This version of your assignment will be graded by the instructor/TAs and the score recorded in the gradebook.

Submitted Files

I21ex_1.txt (0.10kb)	Download	First access timestamp:	12/20/2020 @ 04:43:05 PM EST
I21ex_2.txt (0.07kb)	Download	Submission timestamp:	11/19/2020 @ 07:57:27 PM EST
I21ex_3.txt (0.10kb)	Download	Days late:	0 (before extensions)
I21ex_4.txt (0.18kb)	Download	Grading time:	5 seconds
		Number of re-autogrades:	2
		Last re-autograde finished:	11/24/2020 @ 11:05:23 AM EST
Download all files:	Download		

50 / 50 Autograding Total	
13 / 13 Test 1 I21ex_1	Show Details
13 / 13 Test 2 I21ex_2	Show Details
13 / 13 Test 3 I21ex_3	Show Details
11 / 11 Test 4 I21ex_4	Show Details