

Write your answers in the box below only. Do not write on the back or outside the box.

Database Systems — CSci 4380
Midterm Exam #1
February 8, 2018

RCS ID: _____ @rpi.edu Name: _____

RIN # : _____

Rules. The exam is 110 minutes for a total of 100 points. Open book and notes. Do not use any electronic tools including your computer, phone or tablet. Work alone. You **cannot** talk to anyone in class, or share notes or thoughts.

Question 1 (10*3=30 points). Write the following queries using relational algebra using the data model below. The model is described in detail in the back of the exam.

Users(username, name, email, password, address)

FriendsWith(username, username2, sincewhen)

Landmarks(landmarkname, landmarktype, state, city, country, zip)

Segments(segmentid, startx, starty, endx, endy, landmarkname)

Events(eventid, username, eventtype, eventdate, starttime, endtime)

DataPoints(pointid, eventid, seqno, starttime, endtime, segmentid)

- (a) Find the **name** and **email** of all users who have started an event at **Monument Square** (name of landmark) in **Troy, NY** (city and state) on **Nov 23, 2018** (event date) at exactly **8 A.M** (event start time). The starting segment for an event is listed in the data point with **seqno** 1 for that event.

Write your answers in the box below only. Do not write on the back or outside the box.

- (b) Return the **username** of users who have **run** (eventtype) in a circle in at least one event (i.e. they passed through the same segment more than once in the same event).

- (c) Find the **username** and **email** of users who have no friends.

Question 2 (14+12=26 points). Suppose you are given the following relations to add to the data model in the appendix. Answer questions regarding each additional relation below.

(a) You are given the following new relation for group events, i.e. events multiple people take part in:

`GroupEvents(gid, eventname, eventdate, starttime, endtime, start_segmentid, username)`

For a given event id (`gid`), there is a single event name, date, starting segment id (`start_segmentid`), start and end times. However, each event can have multiple participating users (`username`). Also, for a given `start_segmentid`, `eventdate`, `starttime`, there is a unique event id (only a single group event on a given date, time and location).

(You can rename the attributes to save time writing as: `GE(gid, en, ed, st, et, ss, user)`)

- (1) Based on the above information, list all applicable functional dependencies.
- (2) What are the key(s)?
- (3) Is this relation in BCNF? 3NF? Explain why or why not.
- (4) If it is not in BCNF, use BCNF decomposition to get events that are in BCNF.

- (b) The following is a new relation for storing user achievements based on specific events:

```
Achievements(aid, username, eventid, atype, aname, priority)
    aid → eventid, atype, priority
    atype → aname, priority
    eventid → username
```

Answer each of the following with yes/no and write a sentence to explain your answer.


- (1) Can an event have two different associated users?
- (2) Is it possible for a user to obtain two different achievements of the same type?
- (3) Is **aid**, **atype** a superkey?
- (4) Is the above set of functional dependencies minimal or can it be simplified?
- (5) Is this relation in 3NF?

Question 3 (12 points). You are given the following relation: $R(A,B,C,D,E,F)$ with the following set of functional dependencies:

$$F = \{ AB \rightarrow D, BC \rightarrow E, E \rightarrow C, BE \rightarrow F \}$$

- List all the keys.
- Convert this relation to 3NF using 3NF decomposition. Show your work.
- For each resulting relation, show the key and state simply whether it is in BCNF or not.

Question 4 (4 points). You are given the two E-R models on the right. Discuss whether model A and model B are the same, i.e. whether you can store the same information in them or not. If this depends on what type of hierarchy model B represents, you can also comment on it. Explain your reasoning.



Write your answers in the box below only. Do not write on the back or outside the box.

Question 5 (12 points). Given the relation: $R(A,B,C,D,E,F,G)$ and

$$F = \{ACD \rightarrow E, BC \rightarrow F, FD \rightarrow AE, C \rightarrow D\}$$

Show whether the following decomposition lossless or not with the Chase algorithm. Show your work.

Decomposition: $R_1(A,B,C,D)$, $R_2(B,C,E)$, $R_3(A,C,F,G)$

Write your answers in the box below only. Do not write on the back or outside the box.

Question 6 (16 points). Create an Entity-Relationship diagram for the following database. Make sure you list all the relevant attributes, underline the keys. For each relationship, mark the participation constraints clearly (one-to-one, one-to-many or many-to-many).

You are creating a database for storing information for a Netflix like service. The database stores movies with id, title, filename and TV shows with id, title. TVShows have episodes. Each episode has a corresponding TV show, a season id, an episode id, title, filename. Some episodes have a next episode (i.e. the episode that will automatically start showing once the user finishes watching the current episode!). The database also stores users, each user has an id, username, password. Users may watch zero or more movies, zero or more TV show episodes. For each movie or episode, the database stores a watch time value for each user, indicating how many minutes the user watched that movie or show. Finally, the database stores which movie appears similar to which other movie for a given user (to be able to make recommendations).

Write your answers in the box below only. Do not write on the back or outside the box.

Use this page for scratch work only.

Data model to be used in Exam #1

This is a data model based on the E-R problem from Homework#3, storing information about where people run or go on bicycle trips. The keys of each relation are underlined.

Users(username, name, email, password, address)

Stores information about the users in the system.

FriendsWith(username, username2, sincewhen)

Both **username** and **username2** refers to **username** in **Users**. Friendship is mutual, but we don't store both pairs (A,B and B,A). The first user (**username**) refers to the user who initiated the friendship request. **sincewhen** is the data the friendship was established.

Landmarks(landmarkname, landmarktype, state, city, country, zip)

Each landmark has a name, type (building, monument, etc.) and address.

Segments(segmentid, startx, starty, endx, endy, landmarkname)

A segment is a road segment where **startx**, **starty**, **endx**, **endy** refer to starting and end longitude and latitude. Each segment may have an associated landmark, referenced with **landmarkname**. If there is no landmark, landmarkname is equal to NULL.

Events(eventid, username, eventtype, eventdate, starttime, endtime)

Each event is created by a user, has a type (such as running and cycling), a specific date (day, month, year) and start and end times given in the 24 hour form, i.e. 16:00.

DataPoints(pointid, eventid, seqno, starttime, endtime, segmentid)

A data point is a point on someone's run or cycling event. Seq no 1 is the starting data point. Each event will have at least one associated data point by default. Each data point has a segment associated with it.

You can connect the segments associated with data points for a specific event based on sequence number (seqno) where the endx,endy of one associated segment should be the startx, starty of the next associated segment. This would show the full route someone took in this event.