

New submission for: Lecture 12 Exercise

Due: 10/18/2020 @ 11:59 PM EDT

You are given the baking database:
bakers(baker,fullName,age,occupation,hometown)
episodes(id,title,firstaired,viewers7day,signature,technical,showstopper)
results(episodeid,baker,result) technicals(episodeid,baker,rank)
signatures(episodeid,baker,make)
showstoppers(episodeid,baker,make) favorites(episodeid,baker)

For each question, enter your SQL query directly in the box. Do not forget to put a semicolon at the end.

1. Return the average viewers (viewers7day) for episodes. Name the returned attribute avgviewers and cast the result as numeric(5,2) using :: for casting.

Press TAB to indent. Press ESC to advance from answer area.

```
SELECT
  AVG (viewers7day)::NUMERIC(5,2) as avgviewers
FROM
  episodes;
```

Clear Use Most Recent Submission

2. Using your query from above, return the id of all episodes with more than average viewers. Order results by id ascending.

Press TAB to indent. Press ESC to advance from answer area.

```
SELECT
  id
FROM
  episodes
WHERE
  viewers7day > (SELECT AVG(viewers7day)::NUMERIC(5,2) FROM episodes)
ORDER BY
  id;
```

Clear Use Most Recent Submission

3. For each baker, return their fullName and the number of times they used 'chocolate' in their showstopper bakes (numtimes). Order results by name and numtimes ascending.

Press TAB to indent. Press ESC to advance from answer area.

```
SELECT
  fullname,
  COALESCE(numtimes, 0) as numtimes
FROM
  bakers b
  LEFT JOIN (SELECT COUNT(*) as numtimes, baker FROM showstoppers st WHERE lower(st.make) LIKE '%chocolate%' GROUP BY baker) AS t
    ON t.baker = b.baker
ORDER BY
  fullname,
  numtimes;
```

Clear Use Most Recent Submission

4. For each baker in the technicals table, return baker and the number of times they were rank 1 (numtimes). Order by baker and numtimes ascending.

Press TAB to indent. Press ESC to advance from answer area.

```
SELECT
  t1.baker,
  t2.numtimes
FROM
  (SELECT DISTINCT baker FROM technicals) as t1
  LEFT JOIN (SELECT COUNT(*) as numtimes, baker FROM technicals t1 WHERE t1.rank = 1 GROUP BY t1.baker) AS t2
    ON t1.baker = t2.baker
WHERE
  t2.numtimes IS NOT NULL
ORDER BY
  baker,
  numtimes;
```

Clear Use Most Recent Submission

5. Using your query from above, find the two largest numtimes values in descending order (i.e. the two highest number of times someone ranked 1 in technicals)!

Press TAB to indent. Press ESC to advance from answer area.

```
SELECT
  numtimes
FROM
  (SELECT
    t1.baker,
    t2.numtimes
  FROM
    (SELECT DISTINCT baker FROM technicals) as t1
    LEFT JOIN (SELECT COUNT(*) as numtimes, baker FROM technicals t1 WHERE t1.rank = 1
  GROUP BY t1.baker) AS t2
    ON t1.baker = t2.baker
  WHERE
    t2.numtimes IS NOT NULL
  ORDER BY
    baker,
    numtimes) AS r
ORDER BY
  numtimes DESC
```

Clear Use Most Recent Submission

By clicking "Submit" you are confirming that you have read, understand, and agree to follow the Academic Integrity Policy.

Submit

Select Submission Version: Version #3 Score: 50 / 50 GRADE THIS VERSION Do Not Grade This Assignment

Note: This version of your assignment will be graded by the instructor/TAs and the score recorded in the gradebook. Submitted Files

l12ex_1.sql (0.07kb)	Download	First access timestamp:	12/20/2020 @ 04:42:56 PM EST
l12ex_2.sql (0.11kb)	Download	Submission timestamp:	10/16/2020 @ 01:25:21 AM EDT
l12ex_3.sql (0.26kb)	Download	Days late:	0 (before extensions)
l12ex_4.sql (0.29kb)	Download	Grading time:	75 seconds
l12ex_5.sql (0.41kb)	Download	Queue wait time:	0 seconds
Download all files:	Download		